Correction to: Methodology to Achieve Pseudo 1-D Combustion System of Polymeric Materials Using Low-Pressured Technique

Tatsuya Migita, Takumi Yamahata, Tsuneyoshi Matsuoka and Yuji Nakamura, Department of Mechanical Engineering, Toyohashi University of Technology, 1-1 Hibarigaoka, Tempaku, Toyohashi 441-8580, Japan*
Patrick Strempl, Technical University of Munich, Arcisstraße 21, 80333 Munich, Germany

Correction to:
Manufactured in The United States
<https://doi.org/10.1007/s10694-019-00877-x>

The original version of this article unfortunately contained an error in Table 1 and text under Sect. 3.3.

In Table 1, the values under the column “Transfer number” are incorrect. Hence, the correct table is presented below:

*Correspondence should be addressed to: Yuji Nakamura, E-mail: yuji@me.tut.ac.jp

Table 1
Summary of averaged length scale measured in the present study

	Pressure (kPa)	d_t/d (–) (measured)	Transfer number, B (–) (estimated from averaged measured d_t/d)	B (–) (**)
Oxygen concentration 20%	20	3.71 ± 0.08	0.44 ± 0.01	1–2
	50	3.28 ± 0.08	0.37 ± 0.02	
	100	3.58 ± 0.07	0.42 ± 0.01	
Oxygen concentration 30%	20	3.89 ± 0.24	0.76 ± 0.06	
	50	3.68 ± 0.17	0.71 ± 0.04	
	100	3.56 ± 0.11	0.68 ± 0.03	

(**)Referred from report in Yang et al. [17, 18]

In Sect. 3.3, the sentence “However, based on the present work...” should read as “However, based on the present work, it is much smaller, maybe due to less soot.