Correction to: Ocular Effects of Exposure to 40, 75, and 95 GHz Millimeter Waves

Masami Kojima^{1,2,3} • Yukihiisa Suzuki⁴ • Kensuke Sasaki⁵ • Masao Taki⁴ •
Kanakko Wake⁵ • Soichi Watanabe⁵ • Maya Mizuno⁵ • Takafumi Tasaki⁶ •
Hiroshi Sasaki^{1,2}

Published online: 26 November 2019

© Springer Science+Business Media, LLC, part of Springer Nature 2019

Correction to: Journal of Infrared, Millimeter, and Terahertz Waves (497)
<https://doi.org/10.1007/s10762-018-0497-z>

Table 4 on page 920 of the above publication contains an error. The corrected table is provided as below:

The online version of the original article can be found at <https://doi.org/10.1007/s10762-018-0497-z>

✉ Masami Kojima
m-kojima@kanazawa-med.ac.jp

¹ Division of Vision Research for Environmental Health, Medical Research Institute, Kanazawa Medical University, Kahoku, Japan

² Department of Ophthalmology, Kanazawa Medical University, Kahoku, Japan

³ School of Nursing, Kanazawa Medical University, 1-1 Daigaku, Uchinada, Kahoku, Ishikawa 920-0293, Japan

⁴ Department of Electrical Engineering and Computer Science, Graduate School of Systems Design, Tokyo Metropolitan University, Tokyo, Japan

⁵ National Institute of Information and Communications Technology, Tokyo, Japan

⁶ Division of Protein Regulation Research, Medical Research Institute, Kanazawa Medical University, Kahoku, Japan

Table 4 Power densities by probability of ocular damage, 10, 50, and 90% probability estimated from MLE results for exposure to 40, 75, and 95 GHz MMW

Frequency	Power density for DD ₁₀ (mW/cm ²)		Power density for DD ₅₀ (mW/cm ²)		Power density for DD ₉₀ (mW/cm ²)	
40 GHz	90.8	+ 73.9 – 40.8	206.0	+ 84.7 – 60.0	467.2	+ 327.9 – 192.7
75 GHz	104.8	+ 26.1 – 20.9	142.8	+ 21.5 – 18.7	194.5	+ 40.2 – 33.4
95 GHz	98.6	+ 52.5 – 34.3	145.6	+ 38.3 – 30.3	215.1	+ 89.0 – 63.0

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.