



Correction to: New concept of electret-based capacitance, as shown for solder and other conductors

D. D. L. Chung^{1,*} and Xiang Xi^{1,2}

¹ Composite Materials Research Laboratory, Department of Mechanical and Aerospace Engineering, University at Buffalo, The State University of New York, Buffalo, NY 14260-4400, USA

² College of Mechanics and Materials, Hohai University, Nanjing 211100, China

Published online:

28 November 2022

© Springer Science+Business Media, LLC, part of Springer Nature 2022

Correction to: J Mater Sci: Mater Electron;
<https://doi.org/10.1007/s10854-022-09366-4>

Unfortunately, in the original version of this article, the below-mentioned corrections were missed to be incorporated during proof correction stage by the typesetting team:

1. In the caption of Fig. 2, the caption of Fig. 2c should read as follows:
(c) Effect of the inter-electrode distance l (up to 200 mm) on the electric field E_1' for the steels [5].
The number 1 should be l .

2. In Table 1, a space to be added after " $|V_2'|$ " in the 4th row of the table title. In addition, in the second entry of the first row of the table, change " $|V_2'|$ " to " $|V_2' |$ ".

This has been corrected by publishing this correction article.

The original article has been updated.

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

The original article can be found online at <https://doi.org/10.1007/s10854-022-09366-4>.

Address correspondence to E-mail: ddlchung@buffalo.edu; http://en.wikipedia.org/wiki/Deborah_Chung