Correction to: PVDF nanofibers obtained by solution blow spinning with use of a commercial airbrush

Gabriel C. Dias¹ · Thelma S. P. Cellet² · Mirian C. Santos³ · Alex O. Sanches¹ · Luiz F. Malmonge¹

Published online: 27 August 2019
© The Polymer Society, Taipei 2019

Correction to: Journal of Polymer Research (2019) 26: 87
<https://doi.org/10.1007/s10965-019-1731-7>

The original version of this article unfortunately contained a mistake. In Table 1 of the published online paper, there are four commas (,) that must be changed to periods (.). The correct Table 1 is now shown here:

Table 1 Flow rate for different solutions employed airbrush at 5 Bar

Solution/solvent	Flow Rate
Álcohol	$5.17 \times 10^{-3} \text{ m}^3/\text{s}$
Water	$7.21 \times 10^{-3} \text{ m}^3/\text{s}$
DMF	$6.73 \times 10^{-3} \text{ m}^3/\text{s}$
Acetone	$13.2 \times 10^{-3} \text{ m}^3/\text{s}$
PVDF/DMF (20%)	$5.92 \times 10^{-4} \text{ m}^3/\text{s}$

Publisher's note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

The online version of the original article can be found at <https://doi.org/10.1007/s10965-019-1731-7>

✉ Gabriel C. Dias
gabriel.fct@gmail.com

¹ Universidade Estadual Paulista (UNESP), Faculdade de Engenharia, Ilha Solteira, Av. Brasil Sul, 56 - Centro, Ilha Solteira, SP 15385-000, Brazil

² Universidade Estadual de Maringá (UEM), Departamento de Química, Maringá, PR, Brazil

³ Universidade Estadual Paulista (UNESP), Instituto de Química, Araraquara, SP, Brazil