Correction to: Characterisation of pyrolysis and combustion parameters of charring materials most frequently found in buildings

Ariza S. Abu-Bakar¹ · Marlene J. Cran³ · Rahul Wadhvani^{2,3} · Khalid A. M. Moinuddin^{2,3}

Published online: 28 November 2019
© Akadémiai Kiadó, Budapest, Hungary 2019

Correction to: Journal of Thermal Analysis and Calorimetry
<https://doi.org/10.1007/s10973-019-08688-6>

In the original publication of the article, Figure 3 was published incorrectly. The corrected Fig. 3 is given in this correction.

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Fig. 3 Heat of reaction (kJ kg⁻¹) for pine

The original article can be found online at <https://doi.org/10.1007/s10973-019-08688-6>.

✉ Khalid A. M. Moinuddin
khalid.moinuddin@vu.edu.au

¹ School of Housing, Building and Planning, Universiti Sains Malaysia, 11800 USM, Penang, Malaysia

² Centre for Environmental Safety and Risk Engineering, Victoria University, PO Box 14428, Melbourne, VIC 8001, Australia

³ Institute for Sustainable Industries and Liveable Cities, Victoria University, PO Box 14428, Melbourne, VIC 8001, Australia