Modelling and dynamic analysis of an anti-stall tool in a drilling system including spatial friction

Roeland Wildemans · Arviandy Aribowo ·
Emmanuel Detournay · Nathan van de Wouw

Received: 1 February 2019 / Accepted: 15 June 2019 / Published online: 27 June 2019
© The Author(s) 2019

Abstract This paper investigates the effects of a down-hole anti-stall tool (AST) in deviated wells on the drilling performance of a rotary drilling system. Deviated wells typically induce frictional contact between the drill-string and the borehole, which affects the drill-string dynamics. In order to study the influence of such frictional effects on the effectiveness of the AST in improving the rate-of-penetration and drilling efficiency, a model-based approach is proposed. A dynamic model with coupled axial and torsional dynamics of a drilling system including the down-hole tool in an inclined well is constructed. Furthermore, the frictional contact between the drill-string and the borehole is modelled by a set-valued spatial Coulomb friction law affecting both the axial and torsional dynamics. These dynamics are described by state-dependent delay differential inclusions. Numerical analysis of this model shows that the rate-of-penetration and drilling efficiency increases by inclusion of the AST, both in the case with and without spatial Coulomb friction. Furthermore, a parametric design study of the AST in different inclined drilling scenarios is performed. This study reveals a design for the AST,

which gives optimal drilling efficiency, robustly over a broad range of inclined drilling scenarios.

Keywords Drill-string dynamics · Set-valued force laws · Spatial Coulomb friction · State-dependent delay differential inclusions

1 Introduction

Drilling is used for the exploration of oil, gas, minerals and increasingly for geothermal energy. Current drilling operations are challenging as often complex, deviated wells need to be drilled, for oil and gas exploration, while, for geothermal applications, drilling into hard rock is required. Improving the efficiency of these drilling operations will significantly reduce the costs. Particularly in geothermal drilling operations, where 30–50% of the total development costs are from drilling [4, 6, 14]. Therefore, the development of new technologies to improve drilling performance is key to increase the economic feasibility of geothermal drilling operations.

Rotary drilling with polycrystalline diamond compact (PDC) bits is widely accepted as most efficient for exploration and production drilling operations. Figure 1 depicts the major components of a rotary drilling system: rig, drill-string, bottom hole assembly (BHA), including stabilizers and down-hole tools, and drill-bit. In a rotary drilling system, a key indicator of its efficiency is the rate-of-penetration (ROP), which is

R. Wildemans (✉) · A. G. Aribowo · N. van de Wouw
Department of Mechanical Engineering, Eindhoven
University of Technology, Eindhoven, The Netherlands
e-mail: r.wildemans@tue.nl

E. Detournay · N. van de Wouw
Department of Civil, Environment and Geo Engineering,
University of Minnesota, Minneapolis, USA

Fig. 1 Schematic overview of a drilling system in an inclined well. (Adapted from Marck [26])

the speed at which the bit is drilling into the sub-surface formation. In order to optimize the ROP, suitable values of the hook-load, which translates into an axial force on the bit referred to as weight-on-bit (WOB), and rotation speed (RPM) imposed at the surface (rig) must be set by drilling operators. For this ROP optimization purpose, the Bourgoyne and Young ROP model is widely used in industry [8,30]. This model takes into account different aspects, such as formation strength, WOB, angular velocity and bit wear, which influence the ROP. Based on the optimal operational parameters, the ROP is then optimized by using various controllers [7]. However, the dynamics of the drill-string, the bit-rock interaction and the (frictional) contact along the drill-string in a deviated well are not taken into account in this modelling approach. A different approach for ROP improvement is the selection of drill-string components, such as drill-bits or down-hole tools located at the BHA of the drill-string [4,5,15]. Down-hole tools can be either active [5,15] or passive [4,31,37]. Active tools typically provide axial excitation during drilling, which can alter the effect of axial friction and consequently improve the drilling efficiency. The current paper aims to model and analyse the effect of a passive

down-hole tool on the drilling efficiency in presence of friction between the drill-string and borehole wall. This work is motivated by field data that show evidence that the AST can increase the drilling efficiency in terms of ROP, also in deviated wells [31,33].

In particular, this paper focuses on the modelling and analysis of the coupling of axial and torsional vibrations in drill-string dynamics, and studies how a down-hole tool, called the anti-stall tool (AST) [31], affects the drilling performance (in terms of ROP) in a deviated borehole. Previous works, e.g., [9,10,32] have shown that a rate-independent bit-rock interaction model [11], including both cutting and frictional contact processes, is essential in the coupling between the axial and torsional dynamics. In the current paper, we also pursue such type of modelling approach, further motivated by the fact that the AST also operates by coupling the axial and torsional dynamics [31,37]. The dynamics of drill-string systems, including such rate-independent bit-rock interaction model, has been described by a variety of dynamical models. In [9,10,17,19,20,23–25,28,29,32] lumped-parameter models for the axial-torsional drill-string dynamics have been proposed, while in [2,3,13,16] both finite-element based and distributed models have been developed. These models have been employed to study instabilities and axial and torsional vibrations of drill-string systems, and recently to investigate the effect of the AST on the ROP [37]. However, the effect of friction between the drill-string and the borehole due to deviated well scenarios has not yet been taken into account.

The modelling of the frictional contact along the drill-string has been considered extensively in the scope of so-called torque and drag models [1,21,34]. The magnitude of the frictional forces mainly depends on the normal force acting between the drill-string and the borehole wall. Hence, in highly deviated wells the effects of this friction indeed becomes more prominent, because the drill-string is resting under its own weight on the borehole wall. However, in these models no vibrational dynamics and down-hole tooling have been taken into account, while it has been shown that the functioning of the AST is intrinsically related to the drill-string dynamics [37].

This work builds on and extends the developments in [37] by modelling and analysis of the (frictional) contact between the BHA and the borehole wall, thereby broadening its applicability to deviated well scenarios. The main contributions of this paper are as follows:

- Firstly, a benchmark model of the drill-string dynamics (without AST) and a drill-string model including AST, both with spatial friction between the borehole and drill-string, are developed. Herein, both unilateral contact and frictional characteristics of the bit–rock interaction and the spatial friction between the borehole and drill-string have been modelled by set-valued force laws. This allows for a unified treatment of these nonlinear model features in a time-stepping-based simulation tool for the resulting delay differential inclusion model;
- Secondly, a model-based analysis of the effect of frictional contact between BHA and borehole wall on the drilling performance (in terms of ROP and drilling efficiency) is performed;
- Finally, a parametric performance study on the AST design is performed leading to an optimal design to maintain a high drilling efficiency, which is robust for a wide range of deviated wells.

The outline of this paper is as follows. In Sect. 2, the dynamic models of a drill-string system without and with AST for drilling in a deviated well are derived. In Sect. 3, a dynamic analysis is performed with a focus on the effect of the spatial frictional contact on drilling performance (ROP and drilling efficiency; for both cases without and with AST). Subsequently, a parametric design study on the AST design is presented in Sect. 4. Finally, conclusions are drawn in Sect. 5.

2 Dynamic modelling

In this section, two models of a drill-string including spatial friction between the BHA and the borehole are presented. In Sect. 2.1, two drill-string models, with and without AST, are introduced, enabling the comparative analysis of systems with and without the AST. In Sect. 2.2, the bit–rock interaction model is discussed. In Sect. 2.3, the model that describes the frictional contact between the borehole and the BHA is presented. Finally, in Sect. 2.4 the two dynamic models, with and without AST, are expressed in dimensionless perturbation coordinates around their nominal solutions in order to identify a minimum set of parameters characterizing the dynamics.

A total overview of a drilling system in a deviated well is depicted in Fig. 1. A typical drilling system is operated from the rig located at the surface, where the top-drive equipment sets the angular speed and

adjusts the weight by regulating the hook-load. These operational conditions are transmitted via slender drill-pipes and a BHA to the drill-bit. The BHA is specifically designed to fulfil a particular drilling objective(s) based on the sub-surface geological conditions and can be composed by several down-hole components, such as stabilizer(s), rotary steerable system (RSS), logging tools, mud motor(s), etc. Due to the larger diameter of the stabilizers compared to the rest of the BHA components, the stabilizers are in contact with the borehole wall, which consequently results in additional friction affecting the drill-string dynamics. The physical aspects to be considered in the modelling are the boundary conditions at the rig, the drill-string dynamics including the AST, the bit–rock interaction as the down-hole boundary conditions and the frictional contact between the stabilizers and the borehole.

2.1 Drill-string dynamics

In this section, the dynamic models of the drill-string systems are presented. First the benchmark model, excluding AST, is discussed. Thereafter, the model including AST is discussed.

2.1.1 Benchmark drill-string dynamics

In Fig. 2, the lumped-parameter benchmark model (i.e., without AST) is schematically depicted. The axial and torsional dynamics are described by this model, which consists of two degrees-of-freedom (DOFs), namely the axial displacement of the bit U_b and the angular displacement of the bit Φ_b .

At the rig, the boundary conditions are given by an imposed constant angular velocity Ω_0 and a constant upward force H_0 , the so-called hook-load. The total mass and inertia of the drill-string including the BHA are lumped in the discrete mass M and inertia I . The torsional stiffness of the drill-pipes is modelled as a torsional spring with stiffness C_p . The viscous friction along the drill-string and BHA in axial and angular directions are characterized by the parameters D and D_ϕ , respectively. The parameters λ_{T_a} and λ_{T_t} are associated with the spatial Coulomb friction between the stabilizers and the borehole in axial and torsional direction, respectively, which is discussed in more detail in Sect. 2.3. The weight acting on the bit is denoted by W and the torque acting on the bit is denoted by T .

Fig. 2 Schematic representation of the benchmark model

The bit–rock interaction model, which is discussed in more detail in Sect. 2.2, relates the weight-on-bit (WOB) W and the torque-on-bit (TOB) T to the axial and angular motion of the bit. This bit–rock law considers two independent processes, namely a pure cutting process and a frictional contact. Hence, the force and torque can be decomposed in a cutting and frictional component, denoted by the superscripts c and f , respectively, i.e., for the total WOB $W = W^c + W^f$, and for the total TOB $T = T^c + T^f$. The force and torque contributions associated with the wearflat will from now on be denoted as follows

$$W^f = -\lambda_{b_a}, \quad T^f = -\lambda_{b_t}. \quad (1)$$

By using a Lagrangian approach, the equations of motion (EOMs) for this model are obtained. In general, these can be written in the following form:

$$\mathbf{M}\ddot{\mathbf{q}} - \mathbf{h}(t, \mathbf{q}, \dot{\mathbf{q}}) = \mathbf{W}\boldsymbol{\lambda}, \quad (2)$$

where $\mathbf{q}$ represent the column with generalized coordinates. $\mathbf{M}$ is the mass matrix and the column $\mathbf{h}(t, \mathbf{q}, \dot{\mathbf{q}})$ contains all generalized forces except the friction forces (both due to frictional contacts at the bit and between the borehole and the stabilizers at the BHA). The vector $\boldsymbol{\lambda}$ contains the generalized forces associated with the set-valued force laws, characterizing both due to frictional contacts at the bit and between the borehole and the stabilizers at the BHA, see Sects. 2.2 and 2.3, and the matrix $\mathbf{W}$ contains the associated generalized force directions. In case of the benchmark model with

Fig. 3 The working principle of the anti-stall tool (AST): an increase in torque (M_2) will cause a contraction (S) to off-load the weight from the cutters (F_2) [4]

the generalized coordinates $\mathbf{q} = [U_b \ \Phi_b]^T$, this results in the following matrices and columns in (2):

$$\mathbf{M} = \begin{bmatrix} M & 0 \\ 0 & I \end{bmatrix} \quad \mathbf{h}(t, \mathbf{q}, \dot{\mathbf{q}}) = \begin{bmatrix} -D\dot{U}_b - H_0 + W_s - W^c \\ -D\Phi_b + C_p(\Omega_0 t - \Phi_b) - T^c \end{bmatrix} \quad (3)$$

$$\mathbf{W} = \begin{bmatrix} 1 & 0 & 1 & 0 \\ 0 & 1 & 0 & R \end{bmatrix}$$

$$\boldsymbol{\lambda} = [\lambda_{b_a} \ \lambda_{b_t} \ \lambda_{T_a} \ \lambda_{T_t}]^T$$

where W^c and T^c satisfying (6), (7) and (8) and $\boldsymbol{\lambda}$ satisfying (9), (12) and (25) and W_s represents the submerged weight of the drill-string. A detailed derivation of the equations of motion can be found in [38].

2.1.2 Drill-string dynamics including AST

The AST is designed to influence the coupling between the axial and torsional displacement. The AST consists of two tool bodies connected by a helical spline and an axial internal spring, as viewed in Fig. 3. According to Selnes et al. [33], the working principle of the tool is

while W^c and T^c satisfy (6), (7) and (8), λ satisfies (9), (12) and (25). The parameters W_s and W_{bs} denote the submerged weights of the drill-string parts above and below the tool, respectively. A detailed derivation of the equations of motion can be found in [38].

2.2 Bit-rock interaction model

In this paper, the rate-independent bit-rock interaction law as introduced in [11, 12] is adopted, which relates the WOB and the TOB to the axial and angular motions of the bit. The bit-rock interaction involves two independent processes: a pure cutting process taking place at the front of the cutters and a frictional contact between the rock and the so-called wearflat underneath the cutters. According to Detournay et al. [11, 12], the cutting contributions for a bit consisting of n identical and symmetrically distributed blades of cutters around the axis of revolution and a bit radius of a , can be written as

$$W^c = na\varepsilon\zeta d_n, \quad T^c = \frac{1}{2}na^2\varepsilon d_n, \quad (6)$$

where ε is the intrinsic specific energy related to the rock strength and ζ is related to the orientation of the cutting face. The cutting force and torque are proportional to the depth-of-cut (DOC) d_n produced by a single blade, which is in general not constant. The DOC depends on the axial position of the bit and the rock surface generated by the previous blade according to

$$d_n = U_b(t) - U_b(t - t_n(t)), \quad (7)$$

where $U_b(t)$ is the axial bit position and t denotes time, see Fig. 5. Furthermore, $t_n(t)$ is the time required for the bit to rotate by an angle of $2\pi/n$, which is the angle between two successive blades. This time-dependent delay $t_n(t)$ (actually state-dependent) is characterized by the implicit equation:

$$\int_{t-t_n(t)}^t \frac{d\Phi_b(s)}{ds} ds = \Phi_b(t) - \Phi_b(t - t_n(t)) = \frac{2\pi}{n}, \quad (8)$$

where $\Phi_b(t)$ denotes the angular position of the bit at time t .

In the contributions associated with the wearflat as introduced in (1), the wearflat reaction force λ_{b_a} is essentially discontinuous in terms of the bit axial velocity. When the bit moves downwards, the contact

Fig. 5 Bottom hole profile between two successive blades [9]

between the wearflat and the rock is fully mobilized. However, when the bit moves upwards, the contact is lost and consequently the reaction force vanishes. Hence, the wearflat reaction force can be described in a set-valued force law by the following inclusion:

$$\lambda_{b_a} \in -na\bar{\sigma}l_n \frac{1 + \text{Sign}(\dot{U}_b)}{2}, \quad (9)$$

where $\bar{\sigma}$ is the maximum contact stress and l_n is the wearflat length per blade. The axial velocity of the bit is denoted by $\dot{U}_b$ and the set-valued sign-function in (9) is defined as

$$\text{Sign}(y) = \begin{cases} 1, & y > 0, \\ [-1, 1], & y = 0, \\ -1, & y < 0. \end{cases} \quad (10)$$

As a consequence of the set-valued nature of the law in (9), the admissible values of the wearflat reaction force form a convex set C_a given by

$$C_a = \{\lambda_{b_a} \mid -na\bar{\sigma}l_n \leq \lambda_{b_a} \leq 0\}. \quad (11)$$

The force acting on the wearflat also induces a frictional torque λ_{b_t} . Since the friction always acts in opposite direction compared to the bit rotational velocity, this frictional torque is discontinuous with respect to the rotational velocity and can be modelled by the following inclusion:

$$\lambda_{b_t} \in \frac{1}{2}a\mu\xi\lambda_{b_a}\text{Sign}(\dot{\Phi}_b). \quad (12)$$

Herein, μ is a rate-independent friction coefficient and ξ characterizes the orientation and spatial distribution

of the frictional contact of the surfaces along the bit blade(s). The angular velocity of the bit is denoted by $\dot{\phi}_b$. The admissible values of the frictional torque forms a convex set C_t , which depends on the wearflat (normal) reaction force λ_{ba} . This set is given by

$$C_t(\lambda_{ba}) = \left\{ \lambda_{bt} \mid \frac{1}{2} a \mu \xi \lambda_{ba} \leq \lambda_{bt} \leq -\frac{1}{2} a \mu \xi \lambda_{ba} \right\}. \quad (13)$$

The set-valued force laws for reaction force λ_{ba} and frictional torque λ_{bt} can be formulated by using normal cones of the convex sets (11) and (13), respectively [18, 22]:

$$-\dot{U}_b \in N_{C_a}(\lambda_{ba}), \quad (14)$$

$$-\dot{\phi}_b \in N_{C_t}(\lambda_{bt}). \quad (15)$$

From convex analysis, these inclusions are equivalent to implicit proximal point formulations [22]. Hence, these formulations transform the associated inclusions into nonlinear implicit equations, which are ultimately used in the (time-stepping-based) numerical solver which is developed in this work. These read as

$$\lambda_{ba} = \text{prox}_{C_a}(\lambda_{ba} - r_1 \dot{U}_b), \quad (16)$$

$$\lambda_{bt} = \text{prox}_{C_t}(\lambda_{bt} - r_2 \dot{\phi}_b), \quad (17)$$

for $r_1, r_2 > 0$ arbitrary, positive constants.

Remark During a torsional slip phase, the cutting edge is in full contact with the rock. However, during torsional stick, this contact is not necessarily fully mobilized, which results in an unknown distribution between torque associated with cutting and friction in this case. To include torsional stick in the model, it is assumed that during torsional stick the contact between the cutting edge of the bit blade and the rock remains fully mobilized. Therefore, this assumption has conditioned that the cutting component of the model in (6) is only valid under the conditions of a nonnegative angular motion of the bit ($\dot{\phi}_b \geq 0$) and with nonnegative DOC ($d_n \geq 0$). Furthermore, a negative DOC is associated with bouncing of the bit, which indicates total loss of contact between the bit and the rock. Hence, bit-bouncing is not analysed in this work.

2.3 Spatial Coulomb friction model

In drilling operations in inclined wells, the drill-string rests on the borehole wall with its own weight, resulting in additional frictional contact between the drill-string and borehole. This contact is mainly generated by a specific BHA component, the stabilizers, due to their larger diameter compared to the rest of the BHA components (see Fig. 6). The frictional contact between the drill-string and borehole has been modelled by torque and drag models [21, 34]. In these models, the frictional contact forces depend on the normal force and the frictional coefficient between contact surfaces. In a drilling operation, the drill-string rotates and translates in axial direction. Hence, the sliding velocity of the contact point has two components, both in axial and tangential direction. Due to this spatial contact, the spatial Coulomb's friction law involves a two-dimensional force $\lambda_T = [\lambda_{T_a} \ \lambda_{T_t}]^T$. In Fig. 6 a schematic representation of the forces acting on the BHA is depicted. Figure 6 also depicts the AST located in between the top and bottom stabilizer of the BHA. In this case, the normal force F_N is distributed over the two stabilizers. In the benchmark model (excluding AST), all friction force acts on a single stabilizer, because in the benchmark model both stabilizers related to the same DOF. Furthermore, homogeneous rock formations are considered in this study, such that the spatial friction law

Fig. 6 The BHA resting on its own weight in an inclined well with the axial (λ_{T_a} , $\lambda_{T_{ba}}$) and tangential (λ_{T_t} , $\lambda_{T_{bt}}$, pointing out the plane) components of the spatial friction acting on the stabilizers and the distributed normal force F_N with distribution Δ

is assumed to be isotropic and its force reservoir is represented by a disc. The admissible values of the spatial Coulomb friction force for a single frictional contact point (i.e., as in the benchmark model) are given by the convex set C_T :

$$C_T = \left\{ \lambda_T \in \mathbb{R}^2 \mid \|\lambda_T\| \leq \mu_w F_N \right\}, \quad (18)$$

where μ_w is the friction coefficient and F_N denotes the normal force between the stabilizer in the BHA and the borehole wall.

Low-order lumped-parameter models for the drill-string dynamics are used in this study, such that only the gravitational effect (represented by the drill-string weight) is considered to contribute to the normal force. Thus, the possible force contributions due to the curvature of the borehole are neglected. Furthermore, it is assumed that the stabilizers are always in contact with the borehole wall. However, when the geometrical structure of the borehole is perfectly vertical ($\Theta = 0^\circ$), the spatial friction force vanishes. As the normal force presumptively depends on the buoyed weight of the BHA and the inclination of the borehole structure Θ , as depicted in Fig. 6, this normal force is defined as

$$F_N = B_F M_{BHA} g \sin \Theta, \quad (19)$$

where M_{BHA} denotes the total mass of the BHA, g the gravitational acceleration and B_F is the buoyancy factor given by

$$B_F = \frac{\rho - \rho_m}{\rho}. \quad (20)$$

Herein, ρ is the density of the BHA and ρ_m is the density of the mud in which the BHA is submerged below the surface. Hence, the magnitude of the normal force increases as the borehole inclination (Θ) increases.

In the benchmark model without the tool, the sliding velocity γ_T at the frictional contact between borehole and BHA is given by

$$\gamma_T = \begin{bmatrix} \dot{U}_b \\ \dot{\phi}_b R \end{bmatrix}, \quad (21)$$

where the first component is associated with the axial and the second with the tangential velocity component. In this definition, R is the outer radius of the stabilizers.

In the drill-string model with the tool, the BHA is separated in two parts, such that the spatial friction can act partly above and partly below the tool as shown in Fig. 6. Essentially, the normal force F_N is distributed between the two locations, namely above and below the AST. As a consequence, the force reservoir C_T can

be segregated into two smaller isotropic reservoirs. In order to enable the analysis of the cases where all the friction acts only above or below the tool, a linear distribution parameter $\Delta \in [0, 1]$ is introduced. The admissible friction force reservoirs associated to the friction forces above and below the tool are, respectively, given by the following convex sets:

$$C_T = \left\{ \lambda_T \in \mathbb{R}^2 \mid \|\lambda_T\| \leq \Delta \mu_w F_N \right\}, \quad (22)$$

$$C_{T_b} = \left\{ \lambda_{T_b} \in \mathbb{R}^2 \mid \|\lambda_{T_b}\| \leq (1 - \Delta) \mu_w F_N \right\}. \quad (23)$$

The index b denotes the contributions, which are lumped at the bit. Note that for a straightforward comparison between the model with and without the tool, the sum of maximal allowable friction forces are equal. When $\Delta = 1$ holds, the spatial friction only acts above the AST; when $\Delta = 0$ holds, all spatial friction acts below the tool. The corresponding sliding velocities are given by

$$\gamma_T = \begin{bmatrix} \dot{U} \\ \dot{\phi} R \end{bmatrix} \quad \text{and} \quad \gamma_{T_b} = \begin{bmatrix} \dot{U}_b \\ \dot{\phi}_b R \end{bmatrix}. \quad (24)$$

The relation between the sliding velocity and the spatial friction force can be expressed by the following inclusion, using the normal cone formulation of the set-valued spatial Coulomb friction law [22]

$$-\gamma_T \in N_{C_T}(\lambda_T). \quad (25)$$

This inclusion can equivalently be written as an implicit proximal point formulation:

$$\lambda_T = \text{prox}_{C_T}(\lambda_T - r \gamma_T), \quad (26)$$

where $r > 0$ is an arbitrary positive constant.

2.4 Dimensionless perturbation models

The EOMs, given by (2), are scaled in order to reduce the number of parameters. Furthermore, the dynamics are expressed around its nominal solution (reflected by a constant angular velocity and ROP) by introducing perturbation coordinates. Following [32], a timescale t_* and a characteristic length L_* are introduced, which are defined by

$$t_* = \sqrt{\frac{I_{tot}}{C_p}} \quad \text{and} \quad L_* = \frac{2C_p}{\varepsilon a^2}, \quad (27)$$

with the total inertia in the benchmark model $I_{tot} = I$ and in the model including AST $I_{tot} = I_a + I_b$. Since

the total inertia is equal in both models, the timescale is the same in both models. By using these scaling parameters, the following dimensionless perturbation coordinates are introduced

$$u(\tau) = \frac{U - U_0}{L_*}, \quad u_b(\tau) = \frac{U_b - U_{b0}}{L_*}, \quad (28)$$

$$\phi_b(\tau) = \Phi_b - \Phi_{b0},$$

which are functions of the dimensionless time

$$\tau = \frac{t}{t_*}. \quad (29)$$

These coordinates represent the dimensionless axial and torsional perturbations with respect to its nominal responses, where the coordinates denoted with subscript b are associated with the bit. Explicit expressions for the nominal displacements U_0 , U_{b0} and Φ_{b0} in both models are given in the subsequent sections.

The generalized forces associated with set-valued force laws are scaled by a characteristic cutting force corresponding to a DOC equal to the characteristic length L_* . This results in the following dimensionless perturbation forces and torque associated to the set-valued force laws introduced in Sects. 2.2 and 2.3:

$$\begin{aligned} \hat{\lambda}_{ba} &= \frac{a}{2\zeta C_p}(\lambda_{ba} - \lambda_{ba0}), \quad \hat{\lambda}_{bt} = \frac{1}{C_p}(\lambda_{bt} - \lambda_{bt0}), \\ \hat{\lambda}_T &= \frac{a}{2\zeta C_p}(\lambda_T - \lambda_{T0}). \end{aligned} \quad (30)$$

Note that $\hat{\lambda}_T$ is a column containing the dimensionless axial and tangential components of the spatial Coulomb friction. Furthermore, in the model including the tool, the spatial Coulomb friction acting above and below the tool both satisfy the same dimensionless perturbed form as above for $\hat{\lambda}_T$. However, the values of each associated friction forces can be different as these are scaled by the parameter Δ in (22) and (23). Furthermore, the nominal values of the frictional contact component in the bit–rock interaction law are $\lambda_{ba0} = -na\bar{\sigma}l_n$ and $\lambda_{bt0} = -\frac{1}{2}na^2\mu\xi\bar{\sigma}l_n$. Expressions for λ_{T0} for both models are given in the subsequent sections.

The dimensionless form of the time delay, depth-of-cut and axial and torsional nominal velocities are given by

$$\begin{aligned} \tau_n &= \frac{t_n}{t_*}, \quad \delta = \frac{d}{L_*}, \\ v_0 &= \frac{V_0 t_*}{L_*}, \quad \omega_0 = \Omega_0 t_*. \end{aligned} \quad (31)$$

The nominal axial velocity V_0 (in original coordinates) in both models is given by

$$V_0 = \frac{1}{D}(-H_0 + M_s g - a\varepsilon\zeta d_0 + \lambda_{ba0} + \lambda_{T_{a0}}). \quad (32)$$

The nominal DOC d_0 and the axial component of the nominal spatial friction $\lambda_{T_{a0}}$ are both functions of the nominal velocity V_0 and given by

$$d_0 = V_0 t_{n0} \quad (33)$$

$$\lambda_{T_{a0}} = -\frac{V_0}{\Omega_0 R} \sqrt{\frac{\mu_w^2 F_N^2}{1 + \left(\frac{V_0}{\Omega_0 R}\right)^2}}, \quad (34)$$

with $t_{n0} = 2\pi/(n\Omega_0)$. Substitution of these expressions results in a fourth-order polynomial in V_0 , which is monotone for positive values of V_0 . Hence, (32) exhibits a unique solution for normal drilling operations (reflected by a positive nominal axial velocity V_0).

Moreover, the dimensionless nominal time delay is defined as $\tau_{n0} = t_{n0}/t_* = 2\pi/(n\omega_0)$. The dimensionless depth-of-cut (δ) can be expressed in terms of a perturbation $\hat{\delta}$ from the nominal depth-of-cut per revolution ($\delta_0 = 2\pi v_0/\omega_0$):

$$\delta = \hat{\delta} + \delta_0. \quad (35)$$

The dimensionless perturbed DOC $\hat{\delta}$ is given by

$$\hat{\delta} = n(u_b(\tau) - u_b(\tau - \tau_n)) + n v_0 \hat{\tau}_n. \quad (36)$$

Herein, τ_n is the dimensionless time delay $\tau_n = \hat{\tau}_n + \tau_{n0}$, where $\hat{\tau}_n$ is its perturbation from the nominal time delay τ_{n0} . This time delay is obtained with the implicit delay equation, given in (8), which reads in a dimensionless formulation:

$$\phi_b(\tau) - \phi_b(\tau - \tau_n) + \omega_0 \hat{\tau}_n = 0. \quad (37)$$

2.4.1 Benchmark drill-string model

The column with the dimensionless perturbation coordinates in the benchmark model is given by $\mathbf{z} = [u_b \ \phi_b]^T$. In the case of a nominal drilling operation, there are no vibrations; thus, the axial and torsional velocities are constant and positive. Due to the constant velocities, the accelerations are equal to zero. By substitution of the constant velocities and zero accelerations in the dynamic models, expressions for the nominal values of the displacements, velocities and forces are obtained. The nominal values of the axial and angular bit displacement, U_{b0} and Φ_{b0} (see (28)), are given by

$$U_{b0} = V_0 t, \quad (38)$$

$$\Phi_{b0} = \Omega_0 t + \frac{1}{C_p} \left(-D_\Phi \Omega_0 - \frac{1}{2} n a^2 \varepsilon d_0 + \lambda_{b_{i0}} + R \lambda_{T_{i0}} \right). \quad (39)$$

The nominal values of the spatial Coulomb friction ($\lambda_{T_0} = [\lambda_{T_{a0}} \lambda_{T_{i0}}]^\top$) are given by

$$\lambda_{T_{a0}} = -\frac{V_0}{\Omega_0 R} \sqrt{\frac{\mu_w^2 F_N^2}{1 + \left(\frac{V_0}{\Omega_0 R}\right)^2}}, \quad (40)$$

$$\lambda_{T_{i0}} = -\sqrt{\frac{\mu_w^2 F_N^2}{1 + \left(\frac{V_0}{\Omega_0 R}\right)^2}}. \quad (41)$$

The scaling and introduction of the perturbation coordinates leads to the dimensionless EOMs in general form:

$$\mathcal{M} \mathbf{z}'' - \mathcal{H}(\tau, \mathbf{z}, \mathbf{z}') = \mathcal{W} \hat{\lambda}. \quad (42)$$

Then, the corresponding matrices and columns in the benchmark are given by

$$\mathcal{M} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \quad \mathcal{H}(\tau, \mathbf{z}, \mathbf{z}') = \begin{bmatrix} -\gamma u'_b - \psi \hat{\delta} \\ -\gamma \phi'_b - \phi_b - \hat{\delta} \end{bmatrix} \quad (43)$$

$$\mathcal{W} = \begin{bmatrix} \psi & 0 & \psi & 0 \\ 0 & 1 & 0 & \chi \end{bmatrix} \quad \hat{\lambda} = [\hat{\lambda}_{ba} \quad \hat{\lambda}_{bi} \quad \hat{\lambda}_{Ta} \quad \hat{\lambda}_{Ti}]^\top$$

2.4.2 Drill-string model including AST

The column with the dimensionless perturbation coordinates in the model including AST is given by $\mathbf{z} = [u \ u_b \ \phi_b]^\top$. The nominal values of the axial and angular displacements, U_0 , U_{b0} and Φ_{b0} , are given by

$$U_0 = V_0 t + \frac{1}{\alpha K_b} \left(\frac{1}{2} n a^2 \varepsilon d_{n0} + \alpha n a \varepsilon \zeta d_{n0} + D_{\Phi_b} \Omega_0 - \alpha M_{bs} g - \alpha \lambda_{b_{a0}} - \lambda_{b_{i0}} - \alpha \lambda_{T_{ba0}} - R \lambda_{T_{bi0}} \right), \quad (44)$$

$$U_{b0} = V_0 t, \quad (45)$$

$$\Phi_{b0} = \frac{1}{\alpha K_b} \left(-n a \varepsilon \zeta d_{n0} + M_{bs} g + \frac{1}{\alpha} D_\Phi \Omega_0 + \lambda_{b_{a0}} + \lambda_{T_{ba0}} \right) + \left(\frac{1}{C_p} + \frac{1}{\alpha^2 K_b} \right) \left(-\frac{1}{2} n a^2 \varepsilon d_{n0} - (D_\Phi + D_{\Phi_b}) \Omega_0 + \lambda_{b_{i0}} + R \lambda_{T_{bi0}} \right) + \frac{R}{C_p} \lambda_{T_{i0}} + \Omega_0 t. \quad (46)$$

The nominal values of the spatial Coulomb friction located above and below the AST ($\lambda_{T_0} = [\lambda_{T_{a0}} \lambda_{T_{i0}} \lambda_{T_{ba0}} \lambda_{T_{bi0}}]^\top$) are given by

$$\lambda_{T_{a0}} = -\frac{V_0}{\Omega_0 R} \sqrt{\frac{\Delta^2 \mu_w^2 F_N^2}{1 + \left(\frac{V_0}{\Omega_0 R}\right)^2}}, \quad (47)$$

$$\lambda_{T_{i0}} = -\sqrt{\frac{\Delta^2 \mu_w^2 F_N^2}{1 + \left(\frac{V_0}{\Omega_0 R}\right)^2}}, \quad (48)$$

$$\lambda_{T_{ba0}} = -\frac{V_0}{\Omega_0 R} \sqrt{\frac{(1 - \Delta)^2 \mu_w^2 F_N^2}{1 + \left(\frac{V_0}{\Omega_0 R}\right)^2}}, \quad (49)$$

$$\lambda_{T_{bi0}} = -\sqrt{\frac{(1 - \Delta)^2 \mu_w^2 F_N^2}{1 + \left(\frac{V_0}{\Omega_0 R}\right)^2}}. \quad (50)$$

Then, the scaled EOMs in dimensionless perturbation coordinates for the model including AST can be written in the general form of (42). The corresponding matrices and columns are given by

$$\mathcal{M} = \begin{bmatrix} m_* + \kappa \iota & -\kappa \iota & \nu \iota \\ -\kappa \iota & -m_* + \kappa \iota + 1 & -\nu \iota \\ \frac{\kappa}{\nu} \iota & -\frac{\kappa}{\nu} \iota & 1 \end{bmatrix}$$

$$\mathcal{H}(\tau, \mathbf{z}, \mathbf{z}') = \begin{bmatrix} -\eta_b^2 (u - u_b) - \gamma u' - \gamma_b (u' - u'_b) - \nu \phi_b \\ \nu \phi_b + \kappa (u - u_b) + \nu \gamma_{\phi_1} \phi'_b + \kappa \gamma_{\phi_1} (u' - u'_b) \\ -\phi_b - \frac{\kappa}{\nu} (u - u_b) - \gamma_{\phi_1} \phi'_b \\ -\kappa (u - u_b) - \nu \gamma_{\phi_1} \phi'_b - \kappa \gamma_{\phi_1} (u' - u'_b) \\ + \eta_b^2 (u - u_b) + \gamma_b (u' - u'_b) - \psi \hat{\delta} \\ -\gamma_{\phi_1} \frac{\kappa}{\nu} (u' - u'_b) - \gamma_{\phi_2} \phi'_b - \hat{\delta} \end{bmatrix} \quad (51)$$

$$\mathcal{W} = \begin{bmatrix} 0 & 0 & \psi & \nu \chi & 0 & 0 \\ \psi & 0 & 0 & -\nu \chi & \psi & 0 \\ 0 & 1 & 0 & \chi & 0 & \chi \end{bmatrix}$$

$$\hat{\lambda} = [\hat{\lambda}_{ba} \quad \hat{\lambda}_{bi} \quad \hat{\lambda}_{Ta} \quad \hat{\lambda}_{Ti} \quad \hat{\lambda}_{T_{ba}} \quad \hat{\lambda}_{T_{bi}}]^\top.$$

The definitions of the characterizing dimensionless parameters in (43) and (51) are given in Table 1, along with their values used in Sect. 3. The models presented in this section will now be used to analyse their dynamics, in particular to study the effect of the AST and spatial frictional on the drilling performance.

3 Drilling performance analysis

In this section, the effect of spatial Coulomb friction on the drilling performance is investigated. The drilling

Table 1 Characteristic system parameters

Parameter	Symbol	Value
Characteristic length	$L_* = \frac{2C_p}{\varepsilon a^2}$	7.13×10^{-4}
Characteristic time	$t_* = \sqrt{\frac{I_{tot}}{C_p}}$	0.45
Mass ratio	$m_* = \frac{M_a}{M_{tot}}$	0.92
Inertia ratio	$\iota = \frac{I_a}{I_{tot}}$	0.86
Scaled axial damping	$\gamma = \frac{D}{M_{tot}} \sqrt{\frac{I_{tot}}{C_p}}$	6.43×10^{-3}
Torsional damping above tool	$\gamma_{\phi_1} = \frac{D_{\phi}}{\sqrt{I_{tot} C_p}}$	2.05×10^{-4}
Torsional damping below tool	$\gamma_{\phi_2} = \frac{D_{\phi_b}}{\sqrt{I_{tot} C_p}}$	7.39×10^{-6}
Drill-string design	$\psi = \frac{I_{tot} a \varepsilon \zeta}{M_{tot} C_p}$	37.5
Arm Coulomb friction force	$\chi = \frac{2\xi R}{a}$	0.96
Wearflat friction	$\lambda = \frac{a^2 \bar{\sigma} l}{2\xi C_p}$	16.15
Drill-bit design	$\beta = \mu \xi \zeta$	0.81
Inertia mass ratio	$\kappa = \frac{I_{tot}}{\alpha^2 M_{tot}}$	0.56
Scaled lead of tool	$\nu = \frac{\alpha \kappa}{L_*}$	50.64
Scaled axial stiffness of tool	$\eta_b = \sqrt{\frac{K_b I_{tot}}{M_{tot} C_p}}$	2.06
Scaled axial damping of tool	$\gamma_b = \frac{D_b}{M_{tot}} \sqrt{\frac{I_{tot}}{C_p}}$	0.45

performance is characterized by the drilling efficiency and ROP. This paper focuses on the effect of friction on the drilling performance under different operational conditions, namely the prescribed angular speed and the hook-load at the surface. The characterizing parameters are introduced in Sect. 3.1. Next, in Sect. 3.2 the drilling performance of the benchmark model is investigated. In Sect. 3.3, the drilling performance of the model including AST is investigated and these results are compared to the benchmark model in order to investigate the effectiveness of the AST.

3.1 Drilling performance variables

From stability analyses of the benchmark model in the absence of spatial Coulomb friction, it is observed that the nominal solution is typically unstable for realistic operating conditions [10, 32, 36]. As a consequence, solutions diverge away from the unstable nominal response and result in a time-varying steady-state response from the nonlinear dynamics, where the nonlinearities are related to the set-valued nonlinearities in the bit–rock interaction law, the set-valued spatial fric-

tion law and the state-dependent delay effect. The drill-string system exhibits both axial and torsional vibrations, where the torsional vibrations typically evolve over a significantly slower timescale compared to the axial vibrations. Since the torsional vibrations typically converge to a steady-state torsional limit cycle, in this section, the performance characterization variables are averaged over a torsional limit cycle.

The performance of a drilling operation is mainly characterized by the drilling efficiency [27]. The drilling efficiency reflects how much of the total torque provided to the bit is used for cutting.

Remark Note that the torque provided at the bit is in general not equal to the torque applied at the surface due to frictional losses along the drill-string.

In line with previous studies [32, 37], this efficiency is defined as the ratio between the energy devoted to the cutting process and the total energy dissipated at the bit (i.e., by cutting and frictional forces). The average drilling efficiency η is given by

$$\eta = \frac{\langle T^c \rangle}{\langle T^c \rangle + \langle T^f \rangle}. \quad (52)$$

Herein T^c represents the cutting torque and T^f denotes the frictional torque at the bit. The brackets $\langle \cdot \rangle$ denote the average over a torsional limit cycle. However, the averaged frictional torque at the bit, $\langle T^f \rangle$, is not directly obtained from the numerical simulation, since the frictional torque at the wearflat, T^f , acts on the same DOF as the tangential component of the set-valued Coulomb friction force below the AST, $\lambda_{T_{bf}}$ (see (3) and Fig. 2 for the benchmark model and (5) and Fig. 4 for the model including AST). Besides, both torques are governed by a similar set-valued force law, see (15) and (25). As a consequence, it is not possible to distinguish between the wearflat torque and the set-valued frictional torque below the AST in numerical simulations with the model.

Let us now explain how we obtain an accurate measure for the frictional losses acting at the bit in order to assess the efficiency in (52). According to (12), the frictional torque at the bit is proportional to the wearflat reaction force W^f with a factor $1/2a\mu\xi$. From the model including the tool, as depicted in Fig. 4, the average of the sum of the wearflat force and the axial set-valued friction force below the AST, $\langle W^f + \lambda_{T_{ba}} \rangle$, can directly be computed. Since the averaged axial velocity is much smaller compared to the averaged tangential velocity (i.e., $\langle \dot{U}_b \rangle / \langle R\dot{\Phi}_b \rangle = \mathcal{O}(10^{-4} - 10^{-2})$), the frictional contact basically only produces a frictional torque and thus the axial component $\lambda_{T_{ba}}$ is negligible. Hence, the average wearflat force $\langle W^f \rangle$ is approximated by $\langle W^f + \lambda_{T_{ba}} \rangle$ and can be used to calculate the average frictional torque at the bit $\langle T^f \rangle$.

A higher drilling efficiency will result in more efficient drilling and consequently in saving drilling costs. Moreover, a higher drilling efficiency, as defined in (52), implies less frictional dissipation at the bit, which is generally favourable from a bit wear perspective (i.e., longer bit life-time or maintaining bit sharpness).

A control parameter in both models is the hook-load H_0 at the surface (an upward force). It can be deduced that an increase in the hook-load is causing a decrease in the total weight applied to the bit, and this consequently will decrease the ROP. However, the total weight applied on the bit is not only defined by the hook-load, but also by the gravitational forces acting on the submerged drill-string. Therefore, instead of varying the hook-load, the total nominal weight applied on the bit W_0 is varied as a control parameter in the simulations. The total weight applied on the bit is defined as

$$W_0 = W_s - H_0, \quad (53)$$

with W_s the submerged weight of the drill-string.

Remark In general, the WOB depends on the inclination of the well, since the submerged weight of a drill-string decreases when the inclination increases. However, it is beyond the scope of this paper to study how all individual force components vary with the inclination. Therefore, it is assumed that the hook-load is adjusted when the inclination changes such that the WOB remains constant.

3.2 Drilling performance of the benchmark model

The performance analysis pursued in this section focuses on the axial bit velocity, because this ultimately determines the ROP. The dynamic models as presented in Sect. 2 are simulated with a time-stepping-based numerical simulator. The structure of the numerical simulator is based on [35].

Time-domain responses of the axial bit velocity of the benchmark model with and without spatial friction between the BHA and the borehole wall are depicted in Fig. 7. In both simulations, the same boundary conditions are applied (the total weight applied on the bit $W_0 = 171$ kN and the angular velocity at the top-drive $\Omega_0 = 80$ RPM). The initial conditions in both simulations are chosen close to the desired nominal operating conditions ($u_b(0) = \phi_b(0) = 1 \times 10^{-4}$ and $\dot{u}_b(0) = \dot{\phi}_b(0) = 0$), such that the initial perturbations are small with respect to the nominal solution. Figure 7a, b shows the axial bit velocity without and with spatial friction, respectively. Both cases show unstable transient behaviour where the oscillations grow until the bit experiences an axial (and a torsional) stick-slip limit cycle. Furthermore, the transient phase in the case with friction is longer, i.e., it requires more time to reach the axial (and torsional) limit cycle. This implies that the friction has a stabilizing effect on the drill-string dynamics, which reduces the growth rate of the axial (and torsional) vibrations. The spatial Coulomb friction does not qualitatively change the drill-string system response of the benchmark model for this specific set of operation conditions.

Next, the effect of the spatial friction is investigated for a broad range of operation conditions. The range of the nominal WOB (W_0) corresponds with the range of hook-load forces of $H_0 = 370 - 440$ kN.

Fig. 7 **a** The axial bit velocity for the benchmark model without friction between the BHA and borehole wall ($\Theta = 0$) and **b** with Coulomb friction ($\Theta = 90^\circ$) ($W_0 = 171$ kN and $\Omega_0 = 80$ RPM)

This range is chosen such that lower values result in bit-bouncing and higher values in a negative nominal axial velocity (see (32) for the relation between H_0 and V_0). The range of angular velocities corresponds with $\Omega_0 = 30 - 150$ RPM. The drilling efficiency η and averaged ROP for this range of operation conditions are depicted in Figs. 8, 9 and 10 for different inclined scenarios with $\Theta = 0^\circ$, $\Theta = 45^\circ$ and $\Theta = 90^\circ$, respectively.

In Figs. 8a, b, 9a, b and 10a, b, it can be observed that the ROP increases with increasing nominal WOB and prescribed angular velocity. An increase in W_0 , under a prescribed constant angular velocity, results in an increased ratio between the cutting and frictional forces. Also with faster rotation (higher values of Ω_0) more volume of rock is cut in a given time window. Furthermore, the spatial Coulomb friction has a small effect on the ROP, implying that the portion of the total force used for the cutting process is not affected significantly by the spatial friction between the BHA and borehole.

The drilling efficiency for different operation conditions is shown in Figs. 8c, d, 9c, d and 10c, d. An increase in the nominal WOB results in a higher drilling efficiency. This indicates that for a higher W_0 more energy is used for the cutting process, which is in line with the results in Figs. 8a, 9a and 10a. However, an increasing prescribed angular velocity results in a decreasing drilling efficiency, which indicates that less energy is used for cutting. This implies a decrease in DOC. Even with the decrease in DOC, an increased ROP is still maintained. This consequently happens since with a higher angular velocity more volume of rock is removed by cutting in a given amount of time. From these results, it can be concluded that the spatial Coulomb friction mainly acts in tangential direction.

This is a direct consequence of the large angular velocity compared to the axial velocity of the drill-string, which results in a sliding velocity (between stabilizer and borehole) with a relative small axial component compared to the tangential component. Consequently, this is reflected by the ratio between the axial and tangential components of the spatial Coulomb friction ($\lambda_T = \lambda_{T_a}/\lambda_{T_t}$), which is of $\mathcal{O}(10^{-4} - 10^{-2})$. This observation indicates that the spatial Coulomb friction basically only produces a torsional friction and consequently hardly influences the axial motion of the bit, as reflected in the ROP observations.

3.3 Drilling performance of the model including AST

In this section, we analyse the drilling performance of the system with AST in the presence of spatial friction between borehole and stabilizers.

Steady-state time-domain responses of the axial bit velocity for the drill-string model including the AST with and without spatial friction are depicted in Fig. 11. These responses are obtained with the same boundary conditions as used in benchmark model ($W_0 = 171$ kN and $\Omega_0 = 80$ RPM). The initial conditions are chosen close to the nominal operating conditions ($u(0) = u_b(0) = \phi_b(0) = 1 \times 10^{-4}$ and $\dot{u}(0) = \dot{u}_b(0) = \dot{\phi}_b(0) = 0$). In the absence of spatial Coulomb friction, the axial vibrations have a larger amplitude compared to the cases with spatial Coulomb friction. Furthermore, the axial bit velocity exhibits stick-slip transitions in case with and without spatial friction. Comparing the response of the model including AST with response of the benchmark shows a significant difference between the axial responses. In particular, the amplitude of the axial bit velocity ($\dot{U}_b$) increases by including the AST

Fig. 8 Drilling performance without and with AST in a vertical well with inclination angle $\Theta = 0^\circ$. The rate-of-penetration as function of **a** applied WOB W_0 and **b** rotational velocity Ω_0 and drilling efficiency as a function of **c** applied WOB W_0 and **d** rotational velocity Ω_0 ($W_0 = 184$ kN and $\Omega_0 = 80$ RPM, unless parameter is varied)

up to two times the amplitude of the axial bit velocity obtained with the benchmark model.

The drilling performance for a range of operational conditions is depicted in Figs. 8, 9 and 10 for different inclined scenarios with $\Theta = 0^\circ$, $\Theta = 45^\circ$ and $\Theta = 90^\circ$, respectively. The trends are comparable with the benchmark model, since the increase of the nominal WOB and prescribed angular velocity result in an increasing ROP, while the drilling efficiency increases with W_0 and decreases with increasing Ω_0 . These figures also indicate that the spatial friction hardly affects the ROP. However, Fig. 10 shows that it makes a difference if the spatial Coulomb friction fully acts below ($\Delta = 0$) or above ($\Delta = 1$) the AST. In the simulations, it is observed that the axial vibrations above the tool ($\dot{U}$) decreases when the spatial friction acts fully above the tool ($\Delta = 1$). This indicates that smaller vibrations above the AST have a positive effect on the effectiveness of the tool, since it results in a slight improvement of ROP. When the friction fully acts below the tool ($\Delta = 0$), the ROP is slightly lower compared to the case without spatial friction. Furthermore, the influ-

ence of the location where the spatial friction acts is also observed in the drilling efficiency, which is lower in the case when all spatial friction acts below the tool. Hence, it can be concluded that the effect of the spatial friction on the axial vibrations, which are related to the improved drilling performance, depends on the location where the spatial friction acts. For various operational conditions (W_0 and Ω_0), the drilling performance is higher for the case where all the additional friction acts above the tool. This insight reveals that it is more beneficial in practice to place the AST closer to the bit, such that the friction acts mainly above the tool.

A comparison between the ROP and drilling efficiency obtained with the benchmark model and with the model including AST shows that incorporating the AST significantly improves the ROP and the drilling efficiency for a broad range of spatial friction levels. For example, in the case of a prescribed angular velocity $\Omega_0 = 80$ RPM and a nominal WOB of $W_0 = 192$ kN, the benchmark model results in the absence of spatial friction in a ROP of $\langle \dot{U}_b \rangle = 3.94 \times 10^{-3}$ m/s and a

Fig. 9 Drilling performance without and with AST in an inclined well with inclination angle $\Theta = 45^\circ$. The rate-of-penetration as function of **a** applied WOB W_0 and **b** rotational velocity Ω_0 and drilling efficiency as a function of **c** applied WOB W_0 and **d** rotational velocity Ω_0 ($W_0 = 184 \text{ kN}$ and $\Omega_0 = 80 \text{ RPM}$, unless parameter is varied)

drilling efficiency $\eta = 0.28$, see Fig. 8. Under the same operational condition, a ROP of $\langle \dot{U}_b \rangle = 6.08 \times 10^{-3} \text{ m/s}$ and a drilling efficiency $\eta = 0.37$ is obtained with the model including AST. In this specific case, an increase of more than 50% in ROP and more than 30% in drilling efficiency is achieved by incorporating the AST. In the presence of spatial friction, the increase in ROP and drilling efficiency are comparable.

3.4 Discussion

From the performance analysis, it is concluded that the spatial friction hardly affects the ROP, since the axial component of the friction is relatively small compared to the tangential component. Furthermore, simulation results have revealed that incorporating the AST in the drill-string results in an improved drilling efficiency and ROP for a broad range of deviated wells. In case when the spatial friction acts fully above the AST, a slight improvement of drilling performance is observed compared to the case without spatial friction and when all friction acts below the tool.

4 Parametric design study AST

Based on the analysis performed in the previous section, incorporating the AST can provide a solution to improve the drilling efficiency, also in inclined drilling scenarios with increased frictional contact. From this point of view, the question arises how to find the optimal tool settings that provide the highest drilling efficiency. A parametric design study is performed in order to investigate the optimal tool design and to understand whether the optimality of this design is influenced by the frictional contacts between the BHA and the bore-hole wall (i.e., whether optimal tool settings can be found that robustly optimize performance for a broad range of deviated wells).

In practical field cases, the tool is placed in the bottom part of the BHA [33], which results in more mass of the BHA above the tool than below the tool. Since the largest contribution to the spatial friction comes from the heaviest part of the BHA, all simulations in this section are performed under the assumption that all spatial Coulomb friction forces fully act above the tool ($\Delta = 1$).

Fig. 10 Drilling performance without and with AST in an inclined well with inclination angle $\Theta = 90^\circ$. The rate-of-penetration as function of **a** applied WOB W_0 and **b** rotational velocity Ω_0 and drilling efficiency as a function of **c** applied WOB W_0 and **d** rotational velocity Ω_0 ($W_0 = 184$ kN and $\Omega_0 = 80$ RPM, unless parameter is varied)

Fig. 11 **a** The steady-state axial bit velocity for the model including AST without friction between the BHA and borehole wall ($\Theta = 0$), **b** with Coulomb friction ($\Theta = 90^\circ$) acting fully above the tool $\Delta = 1$ and **c** with Coulomb friction ($\Theta = 90^\circ$) acting fully below the tool $\Delta = 0$ ($W_0 = 171$ kN and $\Omega_0 = 80$ RPM)

The tool design is mainly reflected by two parameters, namely the lead of the helical spline β and the spring stiffness K_b . In the current design of the AST, a lead angle of $\beta = 45^\circ$ and a spring stiffness $K_b = 1522.5$ kN/m are used. The investigated range of the lead angle is in between $\beta = 10 - 70^\circ$ and the spring stiffness range is in between $50 - 11133$ kN/m. Higher values of spring stiffness results in bit-bouncing

in absence of spatial friction. Two different operational scenarios are investigated, namely with a low angular velocity, where $\Omega_0 = 50$ RPM, and a high angular velocity, where $\Omega_0 = 120$ RPM. By considering these two operation scenarios, it can be investigated if the tool design is robust for different operational conditions. In all simulations $W_0 = 171$ kN.

Fig. 12 Drilling efficiency for different tool settings at **a** $\Theta = 0^\circ$, **b** $\Theta = 45^\circ$ and **c** $\Theta = 90^\circ$ with $\Omega_0 = 50$ RPM and $W_0 = 201$ kN. The highest drilling efficiency is denoted by the red dots. (Color figure online)

Fig. 13 Drilling efficiency for different tool settings at **a** $\Theta = 0^\circ$, **b** $\Theta = 45^\circ$ and **c** $\Theta = 90^\circ$ with $\Omega_0 = 120$ RPM and $W_0 = 201$ kN. The highest drilling efficiency is denoted by the red dots. (Color figure online)

From the resulting parametric study, it is observed that a higher spring stiffness results in a higher frequency of the vibrations induced by the tool contraction. Furthermore, a smaller value of the lead will result in less contraction at a certain torsional displacement.

In Fig. 12, the drilling efficiency is plotted against the lead angle and the spring stiffness for different well inclination angles, and for the low angular velocity case ($\Omega_0 = 50$ RPM). The shape of the surfaces characterizing the drilling efficiency have similar trends for different values of Θ , indicating that the influence of the spring stiffness and the lead on the drilling efficiency is comparable under various levels of spatial Coulomb friction. Figure 12 shows that for various spatial Coulomb frictions, the optimal value for the lead angle is around 30° . Since in the current designs a lead angle of 45° is used, between 2 and 7% in drilling efficiency can be gained by changing the lead angle to 30° in this specific case with the above-mentioned operational conditions. Furthermore, it is observed that for lower values of the spring stiffness, the tool provides a higher drilling efficiency. However, the influence of

the spring stiffness is relatively small compared to the influence of the lead angle.

In Fig. 13, the drilling efficiency for the high angular velocity case ($\Omega_0 = 120$ RPM) is depicted for various values of the lead angle and spring stiffness and for different values of Θ . The shapes in these figures are slightly different compared to the low angular velocity case. The dependency of the drilling efficiency η on the spring stiffness K_b reveals a less clear trend compared to the low angular velocity case. The optimal lead angle in this case is also around $\beta = 30^\circ$, which is equal to the low angular velocity case. However, it is observed that in the high angular velocity case the drilling efficiency is less sensitive for an increase in lead angle compared to the low angular velocity case.

Based on these results, the general conclusion is that the optimal values of the tool design are robust for different friction levels and a range of angular velocities imposed at the surface (rig). Hence, an optimal design for the AST that gives optimal drilling efficiency over a broad range of inclined scenarios is feasible.

5 Conclusions

In this paper, the effect of a passive down-hole anti-stall tool on the drilling performance of rotary drilling systems has been investigated for deviated well scenarios. A model including the coupled axial-torsional drill-string dynamics, the bit-rock interaction, the tool and the frictional effects of the stabilizers, due to borehole inclination, has been developed. A set-valued modelling approach for all contact and frictional effects has been pursued leading to a model in terms of a delay differential inclusion for which a time-stepping method is employed for simulation purposes. Numerical analysis results revealed that the down-hole tool significantly improves drilling efficiency and ROP for a broad range of deviated wells. Moreover, based on a parametric design study it is concluded that an optimal tool design, in terms of drilling efficiency, can be found that is robust for a large range of borehole inclinations and operational conditions.

Acknowledgements This study is supported by the Indonesian Endowment Fund for Education (LPDP) of the Republic of Indonesia (Grant No. PRJ-4653/LPDP.3/2016).

Compliance with ethical standards

Conflict of interest The authors declare that they have no conflict of interest.

Open Access This article is distributed under the terms of the Creative Commons Attribution 4.0 International License (<http://creativecommons.org/licenses/by/4.0/>), which permits unrestricted use, distribution, and reproduction in any medium, provided you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made.

A Coordinate transformation

The drill-string dynamics including AST are expressed in a set of dependent coordinates $\mathbf{q}^c = [U, \Phi, U_b, \Phi_b]^T$ combined with the following holonomic constraint:

$$h_{AST} = \alpha(\Phi - \Phi_b) - (U - U_b) = 0. \quad (54)$$

The dynamics of the constrained system can also be given in variational form:

$$(\delta \mathbf{q}^c)^T (\mathbf{M}^c \dot{\mathbf{q}}^c - \mathbf{h}^c(t, \mathbf{q}^c, \dot{\mathbf{q}}^c) - \mathbf{W}^c \boldsymbol{\lambda}) = 0, \quad (55)$$

which holds for all the virtual displacements $\delta \mathbf{q}^c$ that satisfy the variational holonomic constraint given by

$$\mathbf{W}_c^T \delta \mathbf{q}^c = 0, \quad (56)$$

where $\mathbf{W}_c^T$ is the constraint Jacobian:

$$\mathbf{W}_c^T = \frac{\partial h_{AST}}{\partial \mathbf{q}^c} = \begin{bmatrix} -1 \\ \alpha \\ 1 \\ -\alpha \end{bmatrix}. \quad (57)$$

Expressions for $\mathbf{M}^c$ and $\mathbf{h}^c(t, \mathbf{q}^c, \dot{\mathbf{q}}^c)$ can be found in [38]. The set of independent coordinates $\mathbf{q} = [U \ U_b \ \Phi_b]^T$ is introduced, such that it uniquely determines $\mathbf{q}^c = \mathbf{q}^c(\mathbf{q})$. The relation between the set of dependent and independent coordinates is explicitly given by a constant transformation matrix $\mathbf{T}$. Hence, the following relations hold:

$$\mathbf{q}^c = \mathbf{T} \mathbf{q}, \quad \dot{\mathbf{q}}^c = \mathbf{T} \dot{\mathbf{q}}, \quad \ddot{\mathbf{q}}^c = \mathbf{T} \ddot{\mathbf{q}}, \quad (58)$$

with

$$\mathbf{T} = \begin{bmatrix} 1 & 0 & 0 \\ \frac{1}{\alpha} & -\frac{1}{\alpha} & 1 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}. \quad (59)$$

Moreover, the virtual displacement in terms of the independent coordinates can be written as follows:

$$\delta \mathbf{q}^c = \mathbf{T} \delta \mathbf{q}. \quad (60)$$

Substitution of Eqs. (58) and (60) into (55) results in the following equation

$$\delta \mathbf{q}^T \left(\mathbf{T}^T \mathbf{M}^c \mathbf{T} \ddot{\mathbf{q}} - \mathbf{T}^T \mathbf{h}^c(t, \mathbf{T} \mathbf{q}, \mathbf{T} \dot{\mathbf{q}}) - \mathbf{T}^T \mathbf{W}^c \boldsymbol{\lambda} \right) = 0, \quad \forall \delta \mathbf{q}. \quad (61)$$

Since the generalized coordinates $\mathbf{q}$ are independent, all virtual displacements $\delta \mathbf{q}$ are admissible and therefore the dynamics in independent coordinates can be written as follows:

$$\mathbf{T}^T \mathbf{M}^c \mathbf{T} \ddot{\mathbf{q}} - \mathbf{T}^T \mathbf{h}^c(t, \mathbf{T} \mathbf{q}, \mathbf{T} \dot{\mathbf{q}}) = \mathbf{T}^T \mathbf{W}^c \boldsymbol{\lambda}. \quad (62)$$

The new system matrices, explicitly given in (5), are now given by

$$\mathbf{M} := \mathbf{T}^T \mathbf{M}^c \mathbf{T}, \quad \mathbf{h}(t, \mathbf{q}, \dot{\mathbf{q}}) := \mathbf{T}^T \mathbf{h}^c(t, \mathbf{T} \mathbf{q}, \mathbf{T} \dot{\mathbf{q}}), \quad \mathbf{W} := \mathbf{T}^T \mathbf{W}^c. \quad (63)$$

References

- Aadnoy, B.S., Andersen, K.: Design of oil wells using analytical friction models. *J. Pet. Sci. Eng.* **32**(1), 53–71 (2001)
- Aarsnes, U., Aamo, O.: Linear stability analysis of self-excited vibrations in drilling using an infinite dimensional model. *J. Sound Vib.* **360**, 239–259 (2016)
- Aarsnes, U., van de Wouw, N.: Dynamics of a distributed drill string system: characteristic parameters and stability maps. *J. Sound Vib.* **417**, 376–412 (2018)
- Akutsu, E., Rødsjø, M., Gjertsen, J., Andersen, M., Reimers, N.: Faster ROP in hard chalk: proving a new hypothesis for drilling dynamics. In: *SPE/IADC Drilling Conference and Exhibition* (2015)
- Alali, A., Akubue, V.A., Barton, S.P., Gee, R., Burnett, T.G.: Agitation tools enables significant reduction in mechanical specific energy. In: *SPE Asia Pacific Oil and Gas Conference and Exhibition*. Society of Petroleum Engineers (2012)
- Angelone, M., Labini, S.: Overcoming research challenges for geothermal energy. In: *Technical Report* (2014)
- Astrid, P., Singh, A.K., Huhman, J.E., Stoeve, M.A., Dykstra, M.W., Grauwmans, R.H.G.M., Blangé, J.J.: Optimizing performance of a drilling assembly (2014)
- Bahari, M.H., Bahari, A., Nejati, F., Rajaei, R., Vosoughi-V, B.: Drilling rate prediction using Bourgoyne and Young model associated with genetic algorithm. In: *4th ACM International Conference on Intelligent Computing and Information Systems (ACM-ICICIS)* (2009)
- Besselink, B., van de Wouw, N., Nijmeijer, H.: A semi-analytical study of stick-slip oscillations in drilling systems. *J. Comput. Nonlinear Dyn.* **6**(2), 021006-1–021006-9 (2011)
- Depouhon, A., Detournay, E.: Instability regimes and self-excited vibrations in deep drilling systems. *J. Sound Vib.* **333**(7), 2019–2039 (2014)
- Detournay, E., Defourny, P.: A phenomenological model for the drilling action of drag bits. *Int. J. Rock Mech. Min. Sci. Geomech. Abs.* **29**(1), 13–23 (1992)
- Detournay, E., Richard, T., Shepherd, M.: Drilling response of drag bits: theory and experiment. *Int. J. Rock Mech. Min. Sci.* **45**(8), 1347–1360 (2008)
- Di Meglio, F., Aarsnes, U.: A distributed parameter systems view of control problems in drilling. In: *2nd IFAC Workshop on Automatic Control in Offshore Oil and Gas Production OOGP 2015*, vol. 48, pp. 272–278 (2015)
- Finger, J., Blankenship, D.: *Handbook of Best Practices for Geothermal Drilling* (2010)
- Forster, I.: Axial excitation as a means of stick slip mitigation: small scale rig testing and full scale field testing. In: *SPE/IADC Drilling Conference and Exhibition*, pp. 1–28. *SPE/IADC 139830* (2011)
- Germay, C., Denoël, V., Detournay, E.: Multiple mode analysis of the self-excited vibrations of rotary drilling systems. *J. Sound Vib.* **325**(1–2), 362–381 (2009)
- Germay, C., Van de Wouw, N., Nijmeijer, H., Sepulchre, R.: Nonlinear drillstring dynamics analysis. *SIAM J. Appl. Dyn. Syst.* **8**(2), 527–553 (2009)
- Glocker, C.: *Set-Valued Force Laws*, vol. 1. Springer, Heidelberg (2001)
- Gupta, S., Wahi, P.: Global axial-torsional dynamics during rotary drilling. *J. Sound Vib.* **375**, 332–352 (2016)
- Gupta, S., Wahi, P.: Tuned dynamics stabilizes an idealized regenerative axial-torsional model of rotary drilling. *J. Sound Vib.* **412**, 457–473 (2018)
- Johancsik, C., Friesen, D., Dawson, R.: Torque and drag in directional wells-prediction and measurement. *J. Pet. Technol.* **36**(6), 987–992 (1984)
- Leine, R.I., van de Wouw, N.: *Stability and Convergence of Mechanical Systems with Unilateral Constraints*, vol. 36. Springer, Heidelberg (2008)
- Liu, X., Vljajic, N., Long, X., Meng, G., Balachandran, B.: Nonlinear motions of a flexible rotor with a drill bit: stick-slip and delay effects. *Nonlinear Dyn.* **72**(1–2), 61–77 (2013)
- Liu, X., Vljajic, N., Long, X., Meng, G., Balachandran, B.: Coupled axial-torsional dynamics in rotary drilling with state-dependent delay: stability and control. *Nonlinear Dyn.* **78**(3), 1891–1906 (2014)
- Liu, X., Vljajic, N., Long, X., Meng, G., Balachandran, B.: State-dependent delay influenced drill-string oscillations and stability analysis. *ASME. J. Vib. Acoust.* **136**(5), 051008-1–051008-9 (2014)
- Marck, J.: A nonlinear dynamical model of borehole spiraling. In: *Ph.d. Thesis*, University of Minnesota, Minneapolis (2015)
- Mensa-Wilmot, G., Harjadi, Y., Langdon, S., Gagneaux, J., Corp, C.: Drilling efficiency and rate of penetration: definitions, influencing factors, relationships and value. In: *IADC/SPE Drilling Conference and Exhibition* (2010)
- Nandakumar, K., Wiercigroch, M.: Stability analysis of a state dependent delayed, coupled two DOF model of drill-string vibration. *J. Sound Vib.* **332**(10), 2575–2592 (2013)
- Nandakumar, K., Wiercigroch, M., Pearson, C.: Bit-bounce and stick-slip in drill-string dynamics. In: *Symposium on Nonlinear Dynamics for Advanced Technologies and Engineering Design*, vol. 32, pp. 323–335 (2013)
- Nascimento, A., Kutas, D.T., Elmgerbi, A., Thonhauser, G., Mathias, M.H.: Mathematical modeling applied to drilling engineering: an application of Bourgoyne and Young ROP model to a Presalt case study. In: *Mathematical Problems in Engineering* (2015)
- Reimers, N.: Antistall tool reduces risk in drilling difficult formations. *J. Pet. Technol.* **64**(1), 26–29 (2012)
- Richard, T., Germay, C., Detournay, E.: A simplified model to explore the root cause of stick-slip vibrations in drilling systems with drag bits. *J. Sound Vib.* **305**(3), 432–456 (2007)
- Selnes, K.S., Clemmensen, C., Reimers, N.: Drilling difficult formations efficiently with the use of an antistall tool. *Proc. IADC/SPE Drill. Conf.* **24**, 531–536 (2008)
- Sheppard, M., Wick, C., Burgess, T.: Designing well paths to reduce drag and torque. *SPE Drill. Eng.* **2**(04), 344–350 (1987)
- Studer, C., Leine, R., Glocker, C.: Step size adjustment and extrapolation for time-stepping schemes in non-smooth dynamics. *Int. J. Numer. Methods Eng.* **76**(11), 1747–1781 (2008)
- Vromen, T.G.M.: Control of stick-slip vibrations in drilling systems. In: *Ph.d Thesis*, Eindhoven University of Technology, Eindhoven (2015)

37. Vromen, T.G.M., Detournay, E., Nijmeijer, H., van de Wouw, N.: Modelling and dynamic analysis of drilling systems with a down-hole tool for rate-of-penetration increase. *SPE J.* (2018)
38. Wildemans, R.: Modelling and dynamic analysis of an anti-stall tool in a drilling system including spatial friction. In: Master's Thesis, Eindhoven University of Technology, Eindhoven (2018). <https://research.tue.nl/en/studentTheses/modelling-and-dynamic-analysis-of-an-anti-stall-tool-in-a-drillin>. Accessed 11 June 2019

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.