



## Correction: Shielding effectiveness performance of polyaniline-NiFe<sub>2</sub>O<sub>4</sub>:Cu composites for sub-8 GHz applications

Ethem İlhan Şahin<sup>1</sup> · Mehriban Emek<sup>2</sup> · Jamal Eldin F. M. Ibrahim<sup>3,4</sup> · Görkem Yumuşak<sup>5</sup> · Mesut Kartal<sup>6</sup>

Published online: 5 July 2023  
© The Author(s) 2023

**Correction to:** *Optical and Quantum Electronics* (2023) 55:500  
<https://doi.org/10.1007/s11082-023-04791-z>

In the original publication of the article, Table 3 was published with a typo and the reference and the citation for “Başaran (2021)” was incorrect. The citation (Basaran 2020) should be cited as (Şahin and Emek 2021). The corrected Table 3 and the reference has been provided with this Correction.

**Open Access** This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article’s Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article’s Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by/4.0/>.

---

The original article can be found online at <https://doi.org/10.1007/s11082-023-04791-z>.

---

✉ Jamal Eldin F. M. Ibrahim  
[jamalfadoul@gmail.com](mailto:jamalfadoul@gmail.com)

<sup>1</sup> Advanced Technology Research and Application Center, Adana Alparslan Türkeş Science and Technology University, 01250 Adana, Turkey

<sup>2</sup> Department of Physics, Computer Technologies, Golbasi Vocational School, Adiyaman University, 02040 Gölbaşı, Adiyaman, Turkey

<sup>3</sup> Present Address: Department of Materials Technology, University of Bahri, Khartoum, Sudan

<sup>4</sup> Institute of Ceramic and Polymer Engineering, University of Miskolc, Egyetemvaros, Miskolc 3515, Hungary

<sup>5</sup> Department of Metallurgical and Materials Engineering, Marmara University, 34722 Göztepe, Istanbul, Turkey

<sup>6</sup> Department of Electronics and Communication Engineering, İstanbul Technical University, 34469 Maslak, Istanbul, Turkey

**Table 3** The microwave absorption properties of synthesized powders compared with other results in the literature

Sample	RL	Frequency GHz	References
PANI/Cu-added NiFe <sub>2</sub> O <sub>4</sub>	−29.74 dB	6.82	This work
PANI/BaFe <sub>12</sub> O <sub>19</sub>	−12.5 dB	7.8	Yang et al. (2010)
PANI/MnFe <sub>2</sub> O <sub>4</sub>	−15.3 dB	10.4	Thirumalairajan et al. (2013)
PANI/ZnO	−41 dB	14.1	ur Rehman et al. (2019)
NiFe <sub>2</sub> O <sub>4</sub> -graphene oxide	−46.8 dB	6.8	Zhao et al. (2016a)
NiFe <sub>2</sub> O <sub>4</sub> nanosheets	−47.1	7.67	Zhao et al. (2016b)

## Reference

Şahin, E.İ, Emek, M.: Electromagnetic shielding effectiveness of wollastonite/PANI/Colemanite composites. *Eur. J. Sci. Technol.* **21**, 83–89 (2021). <https://doi.org/10.31590/ejosat.816145>

**Publisher's Note** Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.