

RKCL5470

ERRATA

RKCL5253

**EFFECT OF NICKEL LOADING ON THE ACTIVITY OF Ni/ZrO₂ FOR
METHANE STEAM REFORMING AT LOW TEMPERATURE**

**Long Q. Nguyen, Leonila C. Abella, Susan M. Gallardo
and Hirofumi Hinode**

React.Kinet.Catal.Lett.
Vol. 93, No. 2, 227-232 (2008)
10.1007/s11144-008-5253-2

The correct form of Figs 1-3 is the following:




Fig. 1. Effect of Ni loading on the methane conversion
10%Ni/ZrO₂ (a), 15%Ni/ZrO₂ (b), 20%Ni/ZrO₂ (c), 25%Ni/ZrO₂ (d) and
30%Ni/ZrO₂ (e). At T = 600°C, CH₄:H₂O:He = 1:3:4, and GHSV = 24,000 h⁻¹




Fig. 2. The hydrogen yield over various Ni loaded catalysts: 10%Ni/ZrO₂ (a), 15%Ni/ZrO₂ (b), 20%Ni/ZrO₂ (c), 25%Ni/ZrO₂ (d) and 30%Ni/ZrO₂ (e). At T = 600°C, CH₄:H₂O:He = 1:3:4, and GHSV = 24,000 h⁻¹




Fig. 3. The selectivity of carbon monoxide over various Ni loading catalysts: 10%Ni/ZrO₂ (a), 15%Ni/ZrO₂ (b), 20%Ni/ZrO₂ (c), 25%Ni/ZrO₂ (d) and 30%Ni/ZrO₂ (e). At T = 600°C, CH₄:H₂O:He = 1:3:4, and GHSV = 24,000 h⁻¹