ERRATUM

The following correction should be made to the list of references in the article entitled “Comparative Analysis of Processing Techniques’ Effect on the Strength of Carbon Black (N220)-Filled Poly(Lactic Acid) Composites” by A. V. Rane, K. Kanny, A. Mathew, T. P. Mohan, and S. Thomas in Vol. 51, No. 3, 476–489 (2019), <https://doi.org/10.1007/s11223-019-00093-6>.

We apologize to the authors and readers for these technical lapses made by the journal staff.

The references should read as follows:

30. J. S. Dick, *Basic Rubber Testing: Selecting Methods for a Rubber Test Program*, ASTM (2003).
31. N. X. Ding and M. S. Zhan, “Magnetostrictive properties of carbon black filled polypropylene composites,” *Polym. Test.*, **23**, 523–526 (2004).
32. A. Kaynak, A. Polat, and U. Yilmazer, “Some microwave and mechanical properties of carbon fiber-polypropylene and carbon black-polypropylene composites,” *Mater. Res. Bull.*, **31**, No. 10, 1195–1206 (1996).
33. S. Zhao, W. Zhai, N. Li, et al., “Liquid sensing properties of carbon black/polypropylene composite with a segregated conductive network,” *Sensor. Actuat. A-Phys.*, **217**, 13–0 (2014).
34. M. Kurzböck, G. M. Wallner, and R. W. Lang, “Black pigmented polypropylene materials for solar absorbers,” *Energy Proced.*, **30**, 438–445 (2012).
35. F. Beck, G. T. Suden, U. Tormin, and T. Boinowitz, “Thin inert bipolar electrodes fabricated from carbon black filled polypropylene,” *Electrochim. Acta*, **41**, No. 6, 933–935 (1996).
36. S. Mondal, S. Ganguly, P. Das, et al., “Effect of thermal-air ageing treatment on mechanical properties and electromagnetic interference shielding effectiveness of low-cost nano-structured carbon filled chlorinated polyethylene,” *Mater. Sci. Eng. B*, **225**, 140–149 (2017).
37. Y. Luo, Y. Liu, and L. Wang, “Influence of plasma discharge on vapor sensitivity of polyethylene/carbon black conductive films,” *Sensor. Actuat. B-Chem.*, **119**, No. 2, 516–523 (2006).
38. L. Ma, J. Zhao, X. Wang, et al., “Effects of carbon black nanoparticles on two-way reversible shape memory in cross-linked polyethylene,” *Polymer*, **56**, 490–497 (2015).
39. R. Auras, T. L. Lim, S. E. M. Sekle, and H. Tsuji, *Poly(lactic acid): Synthesis, Structures, Properties, Processing and Application*, Wiley (2010).
40. B. P. Grady, *Carbon Nanotube-Polymer Composites Manufacture, Properties, and Applications*, Wiley, Hoboken, NJ (2011).
41. *ASTM D792-13. Standard Test Methods for Density and Specific Gravity (Relative Density) of Plastics by Displacement*, ASTM International, West Conshohocken, PA (2013).
42. G. Wypych, *Handbook of Fillers*, 2nd edn, ChemTec Publishing, Toronto–New York (2000).
43. P. S. Theocaris, *The Mesophase Concept in Composites*, Springer-Verlag, Berlin–Heidelberg (1987).
44. J. Roesler, H. Harders, and M. Baeker, *Mechanical Behaviour of Engineering Materials: Metals, Ceramics, Polymers, and Composites*, Springer-Verlag Berlin–Heidelberg (2007).
45. V. Shah, *Handbook of Plastics Testing and Technology*, Wiley, New York (1998).
46. S. Qian, H. Zhang, W. Yao, and K. Sheng, “Effects of bamboo cellulose nanowhisker content on the morphology, crystallization, mechanical, and thermal properties of PLA matrix biocomposites,” *Compos. Part B-Eng.*, **133**, 203–209 (2018).
47. G. Wypych, *Atlas of Material Damage*, ChemTec Publishing, Toronto (2012).
48. J. Wang, H. Li, R. Liu, et al., “Thermoelectric and mechanical properties of PLA/Bi_{0.5}Sb_{1.5}Te₃ composite wires used for 3D printing,” *Compos. Sci. Technol.*, **157**, 1–9 (2018).
49. *ASTM D648-18. Standard Test Method for Deflection Temperature of Plastics Under Flexural Load in the Edgewise Position*, ASTM International, West Conshohocken, PA (2018).
50. J. E. Mark, *Physical Properties of Polymers Handbook*, Springer, New York (2007).