Numerical Modeling of Momentum Dispersion in Porous Media Based on the Pore Scale Prevalence Hypothesis

Feixiong Rao¹ · Andrey V. Kuznetsov² · Yan Jin¹

Received: 16 February 2020 / Accepted: 15 May 2020 / Published online: 30 May 2020
© The Author(s) 2020

Abstract

A macroscopic model that accounts for the effect of momentum dispersion on flows in porous media is proposed. The model is based on the pore scale prevalence hypothesis (PSPH). The effects of macroscopic velocity gradient on momentum transport are approximated using a Laplacian term. A local Reynolds number Re_d , which characterizes the strength of momentum dispersion, is introduced to calculate the effective viscosity. The characteristic length used in defining Re_d is the pore size, while the characteristic velocity is the mixing velocity. A Taylor expansion is made for the effective viscosity with respect to Re_d . The two leading-order terms of the Taylor series are adopted in the present PSPH momentum-dispersion model. The model constants are determined from the direct numerical simulation results of a flow in the same porous medium bounded by two walls. The effective viscosity approaches the molecular viscosity when the porosity is increased to 1. It approaches infinity when the porosity approaches 0. The benchmark studies show that the effects of the macroscopic velocity gradient can be approximated by the Laplacian term. The proposed PSPH momentum-dispersion model is highly accurate in a wide range of Reynolds and Darcy numbers as well as porosities.

Keywords Macroscopic modeling · Momentum dispersion · Pore scale prevalence hypothesis · Turbulence

1 Introduction

A porous medium consists of a solid matrix with interconnected voids (Nield and Bejan 2017). Many industrial processes can be approximated as convection in porous media (Bruant et al. 2002; Taheri 2014; de Lemos 2012a; Kim et al. 2000). Turbulence is welcome in many processes (Bruant et al. 2002; Taheri 2014) since it might significantly enhance the heat and mass transfer. Turbulent convection in a porous medium can be

✉ Yan Jin
yan.jin@zarm.uni-bremen.de

¹ Center of Applied Space Technology and Microgravity (ZARM), University of Bremen, 28359 Bremen, Germany

² Department of Mechanical and Aerospace Engineering, North Carolina State University, Raleigh, NC 27695-7910, USA

calculated using direct numerical simulation (DNS), in which all geometrical details of the porous matrix are taken into account. However, DNS is often too computationally expensive and provides too much information to be practical in engineering applications. Therefore, convection in porous media is more often studied by solving macroscopic equations.

Macroscopic equations for simulating flow in a porous medium can be derived by time- and volume-averaging the Navier–Stokes equations (Pope 2000; de Lemos 2005). The effect of the porous matrix on the losses of mechanical energy is often approximated by the Darcy term when the flow velocity is low. The Forchheimer term is used to correct the Darcy equation when the velocity is high. In a recent study, Lasseux et al. (2019) proposed a more accurate and complicated model that involves two effective coefficients for accounting for the time-decaying influence of the flow initial condition. However, the Darcy–Forchheimer equation is still the most widely used model for solving engineering problems.

Another alternative to the Darcy equation is known as the Brinkman equation. A Laplacian term is introduced in the macroscopic momentum equation to model the effects of the velocity gradient, including the effects of momentum dispersion and molecular diffusion. In early papers, the effective viscosity $\tilde{\mu}$ in the Brinkman equation was assumed to have the same value as the molecular viscosity μ , see Brinkman (1947). However, the experiments by Givler and Altobelli (1994) show that $\tilde{\mu}$ may be different from μ , and the effects of this difference were investigated in Kuznetsov (1997). Later, Valdes-Parada et al. (2007) argued the effective viscosity is different from the fluid viscosity only for high porosity cases. By performing a series of numerical simulations, Vafai (2005) concluded that whether $\tilde{\mu}/\mu$ is larger or smaller than unity depends on the type of a porous medium. Ochoa-Tapia and Whitaker (1995) suggested that a value of $\tilde{\mu}/\mu$ can be approximated as $1/\phi$, where ϕ is the porosity of the porous medium. Thus, $\tilde{\mu}/\mu$ is larger than unity. Bear and Bachmat (1990) suggested $\tilde{\mu}/\mu$ to be equal to $1/(\phi\tau^*)$, where τ^* is the tortuosity of the porous medium and depends on the geometry of a porous matrix. Saez et al. (1991) also suggested that $\tilde{\mu}/\mu$ is close to the tortuosity which is thought to be less than unity. Based on the earlier work by Vafai and Tien (1981, 1982) and without strict validation, Hsu and Cheng (1990) proposed a momentum equation that models the momentum dispersion by the Brinkman term, in which $\tilde{\mu}/\mu$ is set to 1.

Some studies examined the validity of the Brinkman equation. Using the Green's function approach, Durlofsky and Brady (1987) suggested that the Brinkman equation is valid for $\phi > 0.95$. Rubinstein (1986) showed that the Brinkman equation can be used when ϕ is as small as 0.8. Nield and Bejan (2017) argued that the Brinkman model is breaking down when a large value of $\tilde{\mu}/\mu$ is needed to match theory and experiment. Gerritsen et al. (2005) suggested that the Brinkman equation is not uniformly valid as the porosity tends to unity. Auriaut (2009) stated that the Brinkman equation appears to be valid for flows through fixed beds of particles or fibers at very low porosity. It cannot be physically justified for classical porous media with connected porous matrices. However, in another recent study Kuznetsov and Kuznetsov (2017) showed that the Brinkman model can fit experimental data when $\tilde{\mu}/\mu$ is as large as 8 and reported the confidence intervals for the effective viscosity. It is still not clear whether a Laplacian term, such as one used in the Brinkman model, can be used as a reasonable approximation of momentum dispersion, especially when the porosity is small.

Some other studies suggested that the Brinkman term does not need to be taken into account in many applications since its effect is significant only in a thin boundary layer, see Nield and Bejan (2017), Tam (1969), and Levy (1981). However, in a recent

DNS study, Jin and Kuznetsov (2017) showed that the Brinkman term may have an important effect near a wall when the flow is turbulent.

Jin et al. (2015) and Uth et al. (2016) studied turbulent flows in porous media using DNS and proposed the pore scale prevalence hypothesis (PSPH). The PSPH states that the size of turbulent eddies is restricted by the pore size. Jin and Kuznetsov (2017) further indicated that both turbulent motions and momentum dispersion are characterized by the pore size. Chu et al. (2018) confirmed the PSPH if the porous matrix is not sparsely packed. However, the effect of the pore size on momentum dispersion is not explicitly accounted for in previous models (Brinkman 1947; Ochoa-Tapia and Whitaker 1995; Hsu and Cheng 1990).

The purpose of this paper is to develop a momentum-dispersion model based on the PSPH. Results of the PSPH momentum-dispersion model will be validated by the DNS results in which the detailed pore-scale geometry is accounted for. Through this study, we will also try to answer whether the effects of the velocity gradient on momentum transport can be reasonably well approximated by using the Laplacian term.

The structure of this paper is as follows. The governing equations and numerical methods in this study are introduced in Sect. 2. Equations for the model coefficients are discussed in Sect. 3. In Sect. 4, the developed macroscopic model is applied to simulating flows in two types of porous media to demonstrate its utility. Finally, the conclusions are given in Sect. 5.

2 Governing Equations and Numerical Methods

2.1 Governing Equations for Microscopic DNS

The governing equations for microscopic DNS of incompressible flows in porous media are the transient Navier–Stokes equations. They are

$$\frac{\partial u_i}{\partial x_i} = 0, \quad (2.1)$$

$$\frac{\partial u_i}{\partial t} + \frac{\partial u_i u_j}{\partial x_j} = -\frac{1}{\rho} \frac{\partial p}{\partial x_i} + \nu \frac{\partial^2 u_i}{\partial x_j^2} + g_i, \quad (2.2)$$

The dimensions of the velocity u_i , distance x_i , time t , density ρ , pressure p , kinematic viscosity of the fluid ν , and negative of the applied pressure gradient g_i (assumed to be a constant value) in Eqs. (2.1) and (2.2) are [LT], [L], [T], [ML⁻³], [ML⁻¹T⁻²], [L²T⁻¹], and [LT⁻²], respectively, where L, T and M can be any units of length, time, and mass. These units are not specified so that the numerical results can be applied in any system of units.

The detailed geometry of the porous matrix is accounted for in microscopic DNS. The Navier–Stokes equations are solved directly without introducing any additional model. The purpose of performing microscopic DNS is to determine the model coefficients and to obtain the data for model validation.

2.2 Governing Equations for Macroscopic Simulation

Macroscopic equations for flows in porous media are derived by volume averaging the Navier–Stokes equations. The approach of derivation is similar to that used by de Lemos (2012a, b), who averaged the governing Eqs. (2.1)–(2.2) over volume and time. By contrast, only volume averaging was used in our derivation. The macroscopic equations are expressed as

$$\frac{\partial(\phi\langle u_i \rangle^i)}{\partial x_i} = 0, \quad (2.3)$$

$$\frac{\partial(\phi\langle u_i \rangle^i)}{\partial t} + \frac{\partial(\phi\langle u_i \rangle^i \langle u_j \rangle^j)}{\partial x_j} = -\frac{1}{\rho} \frac{\partial(\phi\langle p \rangle^i)}{\partial x_i} + \phi g_i - \phi R_i + \nu \frac{\partial^2(\phi\langle u_i \rangle^i)}{\partial x_j^2} - \frac{\partial(\phi\langle u_i u_j \rangle^i)}{\partial x_j}. \quad (2.4)$$

The operator $\langle \cdot \rangle^i$ denotes volume averaging over the fluid region of a representative elementary volume (REV). The porosity ϕ is defined as $\phi = \frac{V_f}{V_s + V_f}$, where V_s and V_f are the solid and fluid volumes in a REV, respectively. R_i denotes the total drag caused by the effect of the porous matrix.

It should be noted that an undetermined tensor $\phi\langle u_i u_j \rangle^i$, which corresponds to momentum dispersion, appears in Eq. (2.4). The spatial deviation ${}^i\varphi$, where φ could be any variable under consideration, is the difference between the real value and its intrinsic average, calculated as

$${}^i\varphi = \varphi - \langle \varphi^i \rangle \quad (2.5)$$

$\phi\langle u_i u_j \rangle^i$ needs to be closed before the macroscopic Eqs. (2.3)–(2.4) can be solved.

2.3 Total Drag

The total drag R_i is usually approximated by the Forchheimer extension of the Darcy equation (Lage and Antohe 2000), calculated as

$$R_i = R_{Di} + R_{Fi} = \frac{\nu}{K} u_{Di} + \frac{c_F}{\sqrt{K}} |\mathbf{u}_D| u_{Di} \quad (2.6)$$

u_{Di} denotes the seepage velocity $\phi\langle u_i \rangle$, $\mathbf{u}_D$ is the superficial velocity vector. c_F is a dimensionless coefficient which accounts for the nonlinear increase of the form-drag with the velocity. Masuka and Takatsu (1996) and Wood et al. (2020) stated that the Darcy–Forchheimer law appears to be valid for both laminar and turbulent flows. The permeability K is a measure of the ability of a porous medium to allow fluids to pass through it. For a homogeneous porous medium, K is traditionally determined by the ratio of νu_{D1} and $g_1 - \frac{1}{\rho} \frac{\Delta p}{\Delta x}$ as the flow velocity is small (approaches 0), where Δp is the increase of pressure over the length Δx .

Some studies show that c_F is not a constant but is related to the superficial (filtration) flow velocity, see Lage et al. (1997). Here, we make a Taylor expansion for R_i with respect to a local Reynolds number, Re_K , calculated as

$$R_i = \frac{\nu}{K} u_{Di} (1 + c_{F1} \text{Re}_K + c_{F2} \text{Re}_K^2 + \dots + c_{Fn} \text{Re}_K^n + O(\text{Re}_K^{n+1})) \quad (2.7)$$

$c_{F1}, c_{F2}, \dots, c_{Fn}$ are the coefficients of the Taylor series. Re_K is the local Reynolds number based on the permeability, calculated as

$$\text{Re}_K = \frac{\sqrt{K} |\mathbf{u}_D|}{\nu} \quad (2.8)$$

Comparing Eqs. (2.6) and (2.7), it is evident that c_F is calculated as

$$c_F = c_{F1} + c_{F2} \text{Re}_K + \dots + c_{Fn} \text{Re}_K^{n-1} + O(\text{Re}_K^n) \quad (2.9)$$

In this study, R_i is approximated with the three leading-order terms of Eq. (2.7), as

$$R_i \approx \frac{\nu}{K} u_{Di} (1 + c_{F1} \text{Re}_K + c_{F2} \text{Re}_K^2) \quad (2.10)$$

The dependence of c_F on the velocity is taken into account in Eq. (2.9).

2.4 PSPH Model for Momentum Dispersion

The gradient of macroscopic velocity might affect the momentum dispersion $\phi \langle u_i^i u_j^i \rangle^i$, molecular diffusion $2\nu s_{Dij}$, and total drag R_i . A symmetric tensor $D_{ij} = 2\tilde{\nu} s_{Dij}$ is introduced to account for its effects, where s_{Dij} is the strain rate of the superficial velocity $\mathbf{u}_D$, $\tilde{\nu}$ is an effective viscosity. The macroscopic Eq. (2.4) becomes

$$\frac{\partial u_{Di}}{\partial t} + \frac{\partial (u_{Di} u_{Di} / \phi)}{\partial x_j} = -\frac{1}{\rho} \frac{\partial (\phi \langle p \rangle^i)}{\partial x_i} + \phi g_i - \phi R_i + \frac{\partial D_{ij}}{\partial x_j} \quad (2.11)$$

$\tilde{\nu}/\nu$ is often treated as a constant or a function of the porosity (Brinkman 1947; Ochoa-Tapia and Whitaker 1995). However, the DNS results by Jin and Kuznetsov (2017) showed that the magnitude of $\tilde{\nu}$ increases with an increase in the local Reynolds number, as the momentum dispersion becomes more important.

We propose a new Reynolds number that characterizes the strength of the local momentum dispersion. According to the PSPH, the characteristic length scale of the flow in a porous medium is the pore size s . In a review paper, Wood et al. (2020) suggested that the pore size can be characterized by the mean particle diameter for a generic porous matrix (GPM). In this study, we use $\sqrt{K}$ to characterize the pore size s , because $\sqrt{K}$ has a linear relationship with s when the shape of the porous matrix is fixed. $\sqrt{K}$ is also used as the length scale because it is easy to determine K for a porous matrix.

Jin and Kuznetsov (2017) suggested that the characteristic velocity for flows in porous media close to the wall is the product of $\sqrt{K}$ and the magnitude of the strain rate $|s_{Dij}|$, calculated as

$$|s_{Dij}| = (2s_{Dij}s_{Dij})^{1/2} \quad (2.12)$$

This is similar to the mixing length model of Prandtl (1925) in which the fluid is assumed to mix within the mixing length due to turbulent fluctuations.

Using $\sqrt{K}$ and $|s_{Dij}|\sqrt{K}$ as the characteristic length and velocity, respectively, Re_d is defined as

$$Re_d = \frac{K|s_{Dij}|}{\nu} \quad (2.13)$$

For a one-dimensional wall bounded flow, Re_d represents the ratio between the inertial force $u|du/dy|$ and the resisting force according to the Darcy law, $\frac{\nu}{K}u$, where u is the macroscopic streamwise velocity and y is the distance from the wall.

The ratio $\tilde{\nu}/\nu$ approaches a constant value c_{B1} when the Reynolds number Re_d approaches 0. A Taylor expansion with respect to Re_d can be made for $\tilde{\nu}/\nu$, as follows

$$\tilde{\nu}/\nu = c_{B1} + c_{B2}Re_d + \dots + c_{Bn}Re_d^{n-1} + O(Re_d^n) \quad (2.14)$$

where $c_{B1}, c_{B2}, \dots, c_{Bn}$ are the coefficients of the Taylor series. In this study, we take the two leading-order terms of Eq. (2.14), i.e.,

$$\tilde{\nu}/\nu \approx c_{B1} + c_{B2}Re_d \quad (2.15)$$

The effective viscosity $\tilde{\nu}$ in Eq. (2.11) can be determined using Eq. (2.15).

2.5 Numerical Methods

Two methods are used in the simulation. They are

- A finite volume method (FVM) which directly solves the Navier–Stokes equations.
- A Lattice–Boltzmann method (LBM) which determines the particle distribution; this method indirectly corresponds to solving the Navier–Stokes equations.

The FVM is used for solving the macroscopic Eqs. (2.3)–(2.4). The solver is developed based on the open source computational fluid dynamics (CFD) code OpenFoam 18.12. To compute the derivatives of the velocity, the variables at the interfaces of the grid cells are obtained with linear interpolation. This leads to a second-order central difference scheme for spatial discretization. The pressure at the new time level is determined by the Poisson equation. The velocity is corrected by the Pressure–Implicit scheme with Splitting of Operators (PISO) pressure–velocity coupling.

The LBM is used for solving the microscopic Eqs. (2.1)–(2.2) to determine the model coefficients and obtain the validation data. The basic equation of the present LBM is a discretized version of the Boltzmann equation (Aidun and Clausen 2009) with the collision operator being treated by the Bhatnagar–Gross–Krook (BGK) model (Bhatnagar et al. 1954), i.e.

$$f_i(\mathbf{x} + \xi_i \Delta t, t + \Delta t) - f_i(\mathbf{x}, t) = -\frac{1}{\hat{\tau}}(f_i(\mathbf{x}, t) - f_i^{\text{eq}}(\mathbf{x}, t)) \quad (2.16)$$

where ξ_i is a discrete particle velocity, $f_i(\mathbf{x}, t)$ is the probability to find a particle with a velocity ξ_i at a position $\mathbf{x}$ at a time t , $f_i^{\text{eq}}(\mathbf{x}, t)$ is the equilibrium form of $f_i(\mathbf{x}, t)$, and $\hat{\tau}$ is the relaxation time, which is related to the viscosity of the fluid [see Chen and Doolen (1998)].

With the help of the Chapman–Enskog expansion (Chen and Doolen 1998), the compressible Navier–Stokes equations can be derived from the Lattice Boltzmann equation.

Equation (2.16) is equivalent to the incompressible Navier–Stokes Eqs. (2.1)–(2.2) for small Mach numbers, i.e. for negligible compressibility of the fluid (Chen and Doolen 1998).

The bounce back model is used to account for the no-slip boundary condition at the solid walls. In this model the particles are bounced back to the flow domain without any loss of mechanical energy when the particles collide with a wall. This model ensures conservation of mass and momentum at the boundary. More details can be found in Mohamad (2011).

Both the FVM and LBM solvers have received intensive validations and verifications in our previous studies (Jin and Kuznetsov 2017; Jin et al. 2015; Uth et al. 2016). Therefore, these numerical methods are directly used in this study. The DNS solutions can be used to validate the model results. Typical DNS cases are calculated using different meshes to estimate the uncertainty of the DNS solutions due to mesh-dependence. It will be introduced below when the numerical results are discussed.

3 Model Coefficients

The model coefficients K , c_{F1} , c_{F2} , c_{B1} , and c_{B2} are geometric parameters which are independent of the flow condition. They need to be determined before the macroscopic Eqs. (2.3)–(2.4) can be solved. Various empirical and half-empirical correlations exist for calculating these coefficients.

In the case of beds of particles or fibers, the permeability K can be approximated by the Carman–Kozeny equation (Kozeny 1927; Carman 1956)

$$K = \frac{D_{p2}^2 \phi^3}{180(1 - \phi)^2} \quad (3.1)$$

where D_{p2} is an effective average particle or fiber diameter.

c_F is often set to a constant in previous studies, so c_F is identical to c_{F1} and c_{F2} is 0. Ward (1964) suggested that c_F is a universal constant, with a value of approximately 0.55. In a later study, Beavers et al. (1973) showed that c_F can be better expressed as

$$c_F = 0.55 \left(1 - 5.5 \frac{d}{D_e} \right) \quad (3.2)$$

where d is the sphere diameter and D_e is the size of the bed. Nield and Bejan (2017) suggested that c_F depends on the nature of the porous medium, and can be as small as 0.1. Irmay (1958) suggested an alternate equation for calculating the total drag R_i , i.e.,

$$R_i = \frac{\beta(1 - \phi)^2}{D_{p2}^2 \phi^3} u_{Di} + \frac{\alpha(1 - \phi)}{D_{p2} \phi^3} |\mathbf{u}_D| u_{Di}, \quad (3.3)$$

which is known as Ergun's equation. The model coefficients α and β are set to 1.75 and 150, respectively. K and c_F in Eq. (3.3) are calculated as

$$K = \frac{D_{p2}^2 \phi^3}{\beta(1 - \phi)^2}, \quad c_F = \alpha \beta^{-1/2} \phi^{-3/2} \quad (3.4)$$

c_{B2} has never been accounted for in the previous studies. Brinkman (1947) set c_{B1} to 1. Thus, D_{ij} in Eq. (2.11) is calculated as

$$D_{ij} = \nu \frac{\partial u_{Di}}{\partial x_j}, \quad (3.5)$$

which neglects momentum dispersion. The same assumption is also used in the macroscopic equations proposed by Hsu and Cheng (1990).

The results of Ochoa-Tapia and Whitaker (1995) suggest that $c_{B1} = \frac{1}{\phi}$. D_{ij} is then calculated as

$$D_{ij} = \frac{\nu}{\phi} \frac{\partial u_{Di}}{\partial x_j} \quad (3.6)$$

In practice, we find that the correlations above may produce considerable errors since these model coefficients are related to the geometry of the porous matrix. The concept of tortuosity was introduced in some studies to account for the variation of pore-scale geometries. However, it is hard to determine the tortuosity. Also, we have not found a clear relationship between the model coefficients and the tortuosity. Therefore, the concept of tortuosity is not used in this study.

With the fast development of high-performance computers, it is possible to determine the model coefficients directly from the CFD results. To determine the model coefficients, we use DNS to compute the flow in the porous medium that is bounded by two walls. Periodic boundary conditions are used in the streamwise and transverse directions. The number of REV in the wall-normal direction should be large enough so that the flow near the central region is not affected by the walls.

Two types of porous matrices are utilized in this study; they are composed of arrays of spheres or cubes. A schematic geometry of the porous matrix is shown in Fig. 1. The porous matrix is composed of 96 ($4 \times 8 \times 4$) REV. The domain size is $4s \times 8s \times 4s$, where the pore size s is defined as the distance between two adjacent solid elements. The viscosity ν is set to $0.002 \text{ L}^2\text{T}^{-1}$. g_1 is varied to obtain different Reynolds numbers. The simulations are performed using the LBM. The grid points are uniformly distributed. $(41s/d)^3$ grid points are used in each REV for laminar flows. d is the size of the

Fig. 1 Schematic geometry of the porous matrix

porous element. $(81s/d)^3$ grid points are used in each REV for turbulent flows. Up to 161 million grid points are used in the study.

Since a wall only affects the flow in a few REV's next to it, the macroscopic equation in the central region of the channel can be simplified to

$$g_1 - R_1 = g_1 - \frac{\nu}{K} u_{D1} (1 + c_{F1} \text{Re}_K + c_{F2} \text{Re}_K^2) = 0 \quad (3.7)$$

In order to determine the value of K , we first specify g_1 and then calculate the seepage velocity u_{D1} . We then calculate the approximate value of K by fitting the DNS results with $g_1 = \frac{\nu}{K} u_{D1}$ for $1 \leq \text{Re}_s \leq 20$, where Re_s is the Reynolds number based on the pore size s . The corresponding values of Re_K are in the range 0.04–0.8. Ward (1964) suggested that the transition from the Darcy regime to the Forchheimer regime occurs in the Re_K range 1–10, so the flow is still in the Darcy regime. We did not determine K for very small values of Re_s because it leads to a considerable error for flows with large Re_K values. We then set c_{F2} in Eq. (3.7) to 0, and adjusted the values of K and c_{F1} by fitting the microscopic DNS results with Eq. (3.7) for $\text{Re}_K \leq 3$. After K and c_{F1} are determined, the value of c_{F2} is obtained by fitting the microscopic DNS results for $\text{Re}_K > 3$. The solution of Eq. (3.7) and the microscopic DNS results for the porous matrix composed of spheres are compared in Fig. 2. Typical turbulent cases are recalculated using a different resolution (71^3 grid points for each REV) to estimate the uncertainty due to the mesh resolution. It can be seen that our DNS solutions are generally mesh-independent. It is evident that c_{F2} has significant effects at large Re_K values.

The values of K for different geometries of porous elements are shown in Fig. 3. It can be seen that the geometry of the porous matrix has significant effects on the model coefficients. The correlations proposed in the previous studies produce considerable errors, particularly for large values of ϕ . Therefore, instead of using the correlations in

Fig. 2 Applied pressure gradient g_1 versus Reynolds number Re_K . The porous matrix is made of arrays of spheres. $\phi = 0.48$ ($s/d = 1$), $K = 0.0026$, $c_{F1} = 0.049$, and $c_{F2} = 0.003$. The DNS solutions from a high-resolution mesh (81^3 grid points for each REV) and from a low-resolution mesh (71^3 grid points for each REV) are compared to indicate the numerical error

Fig. 3 Permeability K versus porosity ϕ for porous matrices composed of spheres and cubes. The K values obtained from DNS results are compared with the results from the Carman–Kozeny (Eq. 3.1) and Ergun (Eq. 3.4) equations

the references, the values of K are determined by fitting with the DNS results obtained in this study.

The values of $c_F = c_{F1} + c_{F2}\text{Re}_K$ for the porous matrices composed of spheres and cubes are shown in Fig. 4. Values of c_{F1} and c_{F2} are also obtained directly by fitting the DNS results. It can be seen that the values of c_F for a porous matrix composed of spheres are close to the lower limit of the values suggested by Nield and Bejan (2017). The values of c_F for a porous matrix composed of cubes are even lower.

The macroscopic equation near the wall can be simplified as

$$\phi g_1 - \phi R_1 + \frac{d}{dx_1}(\bar{\nu} D_{12}) = 0 \quad (3.8)$$

The coefficients for calculating R_1 have already been determined above. c_{B1} and c_{B2} are determined by fitting the solution of Eq. (3.8) near the wall to the DNS results. The error of R_1 in the central region may affect the accuracy of c_{B1} and c_{B2} . To avoid this uncertainty, the value of c_{F2} is adjusted so that the calculated velocity at the center line u_{cl} is identical to the DNS results.

We first set c_{B2} to 0. c_{B1} is adjusted until the solution of Eq. (3.8) averaged in the first REV close to wall is identical to the DNS results. The DNS results for $\text{Re}_K \leq 1$ are used to determine c_{B1} . The values of c_{B1} for different geometries of porous elements are shown in Fig. 5. It can be seen that c_{B1} approaches 1 as ϕ increases asymptotically to 1, while it approaches infinity as ϕ decreases asymptotically to 0. This agrees with physical expectations. c_{B1} does not change significantly when the geometry of the porous matrix is changed. It can be reasonably approximated as

Fig. 4 The Forchheimer coefficient c_F versus Re_K . The porous matrix is composed of spheres ($\phi = 0.48$) or cubes ($\phi = 0.42$). The values of c_F in this study are calculated using $c_F = c_{F1} + c_{F2}Re_K$. c_{F1} and c_{F2} are determined from the DNS results. They are compared with the range 0.1–0.55 suggested by Nield and Bejan (2017) and the predictions of the Ergun equation (Eq. 3.4)

Fig. 5 c_{B1} versus porosity ϕ for different geometries of porous elements

$$c_{B1} = 49.63 \times \frac{(1 - \phi)^2}{\phi^{0.5}} + 1 \quad (3.9)$$

c_{B2} is determined by fitting the model results to the DNS results for $\text{Re}_K > 1$, see Fig. 6. c_{B2} for porous matrices composed of cubes or spheres can be approximated by the following correlation

$$c_{B2} = 0.79 \times \frac{(1 - \phi)^2}{\phi^3} \quad (3.10)$$

c_{B2} approaches 0 as ϕ increases asymptotically to 1, while it approaches infinity as ϕ decreases asymptotically to 0. Only two geometries of the porous elements are considered in this study. Our numerical results show that values of c_{B1} and c_{B2} are not affected significantly when the pore-scale geometry is changed.

4 Test Cases

The developed macroscopic equations are used to solve the flows in two types of porous media to demonstrate the utility of the developed macroscopic model. The first case deals with a flow in a channel occupied by a homogeneous and isotropic porous medium. The second case deals with a flow in a porous medium with two porosity scales.

4.1 Flow in a Channel Occupied by a Homogeneous and Isotropic Porous Medium

Microscopic DNS results for the flow rate in the same porous media have been used to determine the model coefficients. The purpose of this test case is to show that the PSPH momentum-dispersion model can be used for wide ranges of Darcy numbers (Da) and Reynolds numbers (Re_{cl}). The Reynolds number Re_{cl} is based on the half channel height H and the centerline velocity in the channel u_{cl} , and is defined as

Fig. 6 c_{B2} versus porosity ϕ for different geometries of porous elements

$$\text{Re}_{cl} = \frac{u_{cl}H}{\nu} \quad (4.1)$$

The Darcy number is defined as

$$\text{Da} = \frac{K}{H^2} \quad (4.2)$$

The instantaneous velocity magnitudes for representative Reynolds numbers are shown in Fig. 7. It may also be observed that the wall mainly affects the first REV next to it.

We fix the Reynolds number Re_{cl} (or u_{cl}) and reduce the pore size s , which results in three different scale ratios (H/s): 20, 30, and 40. The corresponding Darcy numbers are 8.5×10^{-6} , 3.8×10^{-6} , and 2.1×10^{-6} , respectively. Figure 8 shows that the distribution of u_{D1} is steeper near the wall when Da is smaller. The results of u_{D1} from the PSPH model and DNS are averaged in each REV, so they can be compared quantitatively. The symbol $\langle \dots \rangle^v$ in Fig. 8 denotes the whole REV-averaged velocity $\langle u_{D1} \rangle^v$ obtained from DNS and PSPH model results. It can be seen that the results from the PSPH model are in good agreement with the DNS results.

The numerical results in Fig. 8 are shown again in Fig. 9, but the distance from the wall x_2 is normalized with the pore size s instead of H . The DNS results from two mesh resolutions are almost identical, indicating the mesh-independence of the DNS solution. The profiles of u_{D1} collapse to a single curve, suggesting that the characteristic length of the flow is s ; this is in accordance with the PSPH. Figure 9 also shows that the PSPH momentum-dispersion model is more accurate than the macroscopic model using Brinkman's expression (Brinkman 1947) or Ochoa-Tapia and Whitaker's expression (Ochoa-Tapia and Whitaker 1995).

Different Reynolds numbers Re_{cl} can be obtained by changing the applied pressure gradient g_1 . Figure 10 shows the results for different values of Re_{cl} , which are in the turbulent regime. There are some perturbations of the velocity for the porous medium composed of spheres; this is also observed in Jin and Kuznetsov (2017). These perturbations are not found for the porous medium composed of cubes. The profiles of u_{D1} for different values of Re_{cl} collapse to a single curve when they are normalized with u_{cl} . The DNS results are mesh-independent, see Fig. 10b. The model results for both porous matrices are in good agreement with the DNS results.

It can be also seen in Fig. 10 that, for the porous matrix under consideration, the wall only affects the flow in the first REV next to it. Therefore, in Fig. 11, we only compare the macroscopic and microscopic results for volume-averaged value of u_{D1} in the first REV next to the wall. c_{B2} has non-negligible effects when the flow is characterized by a large Reynolds number, particularly when the flow is turbulent, see Fig. 11b. The value of u_{D1} next to the wall may be over-predicted by 10% if c_{B2} is neglected.

4.2 Flows in Porous Media with Two Porosities

To further investigate the generality of the proposed PSPH momentum-dispersion model, the flows in porous media with two porosities are simulated. The geometry of the porous matrix is shown in Fig. 12. A constant applied pressure gradient g_1 forces the fluid to flow with two characteristic velocities. The zone with a higher porosity has a higher velocity. Therefore, this type of flow has two characteristic Reynolds numbers based on the pore size s , calculated as

Fig. 7 Instantaneous velocity magnitude. In **a**, **b** the porous matrix is composed of spheres, $\phi = 0.48$. **a** $Re_{cl} = 98$, laminar; **b** $Re_{cl} = 1730$, turbulent. In **c**, **d** the porous matrix is composed of cubes, $\phi = 0.49$. **c** $Re_{cl} = 127$, laminar; **d** $Re_{cl} = 2339$, turbulent

$$Re_1 = \frac{u_a s}{\nu}; \quad Re_2 = \frac{u_b s}{\nu} \quad (4.2)$$

where u_a and u_b are the macroscopic velocities in the two porous medium zones far away from the interface. The computational domain is composed of 128 ($4 \times 8 \times 4$) REV's. The two porous medium zones have the same pore size s but different sizes of porous elements

Fig. 8 u_{D1}/u_{cl} and $\langle u_{D1} \rangle^v/u_{cl}$ versus the normalized distance from the wall x_2/H . The porous matrix is composed of cubes, $\phi = 0.49$, $Re_{cl} = 127$. Lines: u_{D1}/u_{cl} obtained from continuous PSPH model results; hollow symbols: $\langle u_{D1} \rangle^v/u_{cl}$ from REV-averaged PSPH model results; solid symbols: $\langle u_{D1} \rangle^v/u_{cl}$ from REV-averaged DNS results

Fig. 9 u_{D1}/u_{cl} and $\langle u_{D1} \rangle^v/u_{cl}$ versus the normalized distance from the wall x_2/s . The porous matrix is composed of cubes, $\phi = 0.49$, $Re_{cl} = 127$

(d_1 and d_2), leading to two different porosities ϕ_1 and ϕ_2 . Up to 661 million grid points are used for turbulent flows (each REV has 151^3 points).

Typical laminar and turbulent flows in this porous medium are shown in Fig. 13. The porosities of the two porous medium zones are $\phi_1 = 0.42$ and $\phi_2 = 0.49$, respectively. It

Fig. 10 Streamwise velocity $\langle u_{D1} \rangle^v$ versus the normalized distance from the wall x_2/s for different values of Re_{cl} . The porous matrix is composed of spheres **(a)** and cubes **(b)**. Hollow symbols: PSPH model results; solid symbols: DNS results. Mesh 1: 101^3 grid points for each REV; mesh 2: 76^3 grid points for each REV

can be seen that the effects of the interface are limited to the two REV's in the vicinity of the interface.

Figure 14 shows the velocity profiles in the wall normal direction for $g_1 = 0.07$ and $g_1 = 1.1$. Both laminar and turbulent cases are calculated using a lower-resolution mesh (each REV has 91^3 points). It can be seen that the results for the laminar flow are mesh-independent. The results for the turbulent flow are slightly mesh-dependent. The

Fig. 11 $\langle u_{D1} \rangle^v$ in the first REV next to the wall versus the applied pressure gradient g_1 . The porous matrix is composed of cubes. **a** Whole range of values of the applied pressure gradient; **b** zoomed results in the turbulent regime

macroscopic model results are compared with the microscopic DNS results. It can be seen that the PSPH momentum-dispersion model is more accurate than the macroscopic model with Brinkman's expression (Brinkman 1947) or Ochoa-Tapia and Whitaker's expression (Ochoa-Tapia and Whitaker 1995). When the mesh resolution is improved, the DNS results become closer to the PSPH-model results.

Fig. 12 Schematic geometry of a porous matrix with two porosities

Fig. 13 Instantaneous velocity magnitude. The porous matrix is composed of cubes, $\phi_1 = 0.42$, $\phi_2 = 0.49$. **a** $Re_1 = 30$ and $Re_2 = 60$ (laminar flow); **b** $Re_1 = 454$ and $Re_2 = 860$ (turbulent flow)

The results for more values of g_1 and ϕ are shown in Fig. 15. This figure depicts the values of u_{D1}^v in two REV's adjacent to the interface. It can be seen that the PSPH model can be used in a wide range of the flow conditions, including both laminar and turbulent flows. In general, the errors in velocity distributions predicted by the model for all conditions simulated here are small. The deviation of model predictions from DNS results may increase when the difference between the two porosities increases. The deviation may be related to the errors of both the momentum-dispersion model and Darcy–Forchheimer model.

Fig. 14 REV-averaged streamwise velocity $\langle u_{D1} \rangle^v$ versus the normalized distance from the wall x_2/s . The porous matrix is composed of cubes, $\phi_1 = 0.42$, $\phi_2 = 0.49$. **a** $Re_1 = 30$, $Re_2 = 60$ (laminar flow); **b** $Re_1 = 454$, $Re_2 = 860$ (turbulent flow). Mesh 1: 151^3 grid points for each REV; mesh 2: 91^3 grid points for each REV

5 Conclusions

A momentum-dispersion model for flows in porous media is proposed based on the PSPH, which states that the characteristic length scale for flows in porous media is the pore size. The effects of macroscopic velocity gradient are modeled by using a Laplacian term in the macroscopic momentum equation. The local Reynolds number $Re_d = \frac{K|s_{Dij}|}{\nu}$, which describes the strength of the local momentum dispersion, is introduced using the pore size

Fig. 15 $\langle u_{D1} \rangle^v$ in the first REV next to the wall versus applied pressure gradient g_1 . **a** Cubes, $\phi_1 = 0.42$ and $\phi_2 = 0.49$; **b** cubes, $\phi_1 = 0.42$ and $\phi_2 = 0.54$

(identified by $\sqrt{K}$) as the characteristic length and the mixing velocity, $\sqrt{K}|s_{Dij}|$, as the characteristic velocity. The effective viscosity is expanded as a Taylor series with respect to Re_d . The model coefficients are expected to be only related to the geometry of the REV. They can be determined from the DNS results for flows in a wall-bounded porous medium made of the REV's under consideration.

The proposed macroscopic equations are used to simulate the flows in two types of porous media: a porous medium bounded by two walls and a porous medium with two porosities. The model results are in good agreement with the DNS results in wide ranges of the Reynolds number, Darcy number, and porosity. The study shows that the effects of macroscopic velocity gradient on momentum transport in porous media can be reasonably well approximated using a Laplacian term.

Acknowledgements Open Access funding provided by Projekt DEAL. The authors gratefully acknowledged the support of this study by China Scholarship Council and Deutsche Forschungsgemeinschaft (DFG) (Grant No. 408356608). All parallel computations are performed using the cluster of the Center of Applied Space Technology and Microgravity (ZARM), University of Bremen.

Open Access This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by/4.0/>.

References

- Aidun, C.K., Clausen, J.R.: Lattice-Boltzmann method for complex flows. *Annu. Rev. Fluid Mech.* **41**, 439–472 (2009)
- Auriault, J.L.: On the domain of validity of Brinkman's equation. *Transp. Porous Med.* **79**, 215–223 (2009)
- Bear, J., Bachmat, Y.: Introduction to modeling of Transport Phenomena in Porous media. Kluwer Academic, Dordrecht (1990)

- Beavers, G.S., Sparrow, E.M., Rodenz, D.E.: Influence of bed size on the flow characteristics and porosity of randomly packed beds of spheres. *J. Appl. Mech.* **40**(3), 655–660 (1973)
- Bhatnagar, P.L., Gross, E.P., Krook, M.: A model for collision processes in gases. I. Small amplitude processes in charged and neutral one-component systems. *Phys. Rev.* **94**, 511–525 (1954)
- Brinkman, H.C.: A calculation of the viscous force exerted by a flowing fluid on a dense swarm of particles. *Appl. Sci. Res. A* **1**, 27–34 (1947)
- Bruant Jr., R.G.J., Celia, M.A., Guswa, A.J., Peters, C.A.: Peer reviewed: safe storage of CO₂ in deep saline aquifers. *Environ. Sci. Technol.* **36**(11), 240A–245A (2002)
- Carman, P.C.: *Flow of Gases Through Porous Media*. Butterworths, London (1956)
- Chen, S., Doolen, G.D.: Lattice Boltzmann method for fluid flows. *Annu. Rev. Fluid Mech.* **30**, 329–364 (1998)
- Chu, X., Weigand, B., Vaikuntanathan, V.: Flow turbulence topology in regular porous media: from macroscopic to microscopic scale with direct numerical simulation. *Phys. Fluids* **30**, 065102 (2018)
- de Lemos, M.J.S.: The double-decomposition concept for turbulent transport in porous media. In: Ingham, D.B., Pop, I. (eds.) *Transport Phenomena in Porous Media III*, pp. 1–33. Elsevier, Oxford (2005)
- de Lemos, M.J.S.: *Turbulence in Porous Media: Modeling and Applications*, 2nd edn. Elsevier, Oxford (2012a)
- de Lemos, M.J.S.: *Turbulent Impinging Jets into Porous Media*. Springer, New York (2012b)
- Durlofsky, L., Brady, J.F.: Analysis of the Brinkman equation as a model for flow in porous media. *Phys. Fluids* **30**, 3329–3341 (1987)
- Gerritsen, M.G., Chen, T., Chen, Q.: personal Communication. Stanford University, California (2005)
- Givler, R.C., Altobelli, S.: A determination of the effective viscosity for the Brinkman–Forchheimer flow model. *J. Fluid Mech.* **258**, 355–370 (1994)
- Hsu, C.T., Cheng, P.: Thermal dispersion in a porous medium. *Int. J. Heat Mass Transf.* **33**, 1587–1597 (1990)
- Irmay, S.: On the theoretical derivation of Darcy and Forchheimer formulas. *Trans. Am. Geophys. Union* **39**(4), 702–707 (1958)
- Jin, Y., Kuznetsov, A.V.: Turbulence modeling for flows in wall bounded porous media: an analysis based on direct numerical simulations. *Phys. Fluids* **29**, 045102 (2017)
- Jin, Y., Uth, M.-F., Kuznetsov, A.V., Herwig, H.: Numerical investigation of the possibility of macroscopic turbulence in porous media: a direct numerical simulation study. *J. Fluid Mech.* **766**, 76–103 (2015)
- Kim, W.S., Kim, D.S., Kuznetsov, A.V.: Simulation of coupled turbulent flow and heat transfer in the wedge-shaped pool of a twin-roll strip casting process. *Int. J. Heat Mass Transf.* **43**, 3811–3822 (2000)
- Kozeny, J.: Ueber kapillare Leitung des Wassers im Boden. *Sitzb. Akad. Wiss. Wien. Math. naturw. Klasse.* **136**(2a), 271–306 (1927)
- Kuznetsov, A.V.: Influence of the stress jump condition at the porous-medium/clear-fluid interface on a flow at a porous wall. *Int. Commun. Heat Mass Transf.* **24**, 401–410 (1997)
- Kuznetsov, I.A., Kuznetsov, A.V.: Using resampling residuals for estimating confidence intervals of the effective viscosity and Forchheimer coefficient. *Transp. Porous Med.* **119**, 451–459 (2017)
- Lage, J.L., Antohe, B.V.: Darcy's experiments and the deviation to nonlinear flow regime. *J. Fluids Eng.* **122**(3), 619–625 (2000)
- Lage, J.L., Antohe, B.V., Nield, D.A.: Two types of nonlinear pressure drop versus flow-rate relation observed for saturated porous media. *J. Fluids Eng.* **119**(3), 701–706 (1997)
- Lasseux, D., Valdés-Parada, F.J., Bellet, F.: Macroscopic model for unsteady flow in porous media. *J. Fluid Mech.* **862**, 283–311 (2019)
- Levy, T.: Loi de Darcy ou loi de Brinkman? *C. R. Acad. Sci. Paris, Sér. II* **292**, 872–874 (1981)
- Masuoka, T., Takatsu, Y.: Turbulence model for flow through porous media. *Int. J. Heat Mass Transf.* **39**, 2803–2809 (1996)
- Mohamad, A.A.: *Lattice Boltzmann Method*. Springer, London (2011)
- Nield, D.A., Bejan, A.: *Convection in Porous Media*, 5th edn. Springer, Switzerland (2017)
- Ochoa-Tapia, J.A., Whitaker, S.: Momentum transfer at the boundary between a porous media and a homogeneous fluid—I. Theoretical development. *Int. J. Heat Mass Transf.* **38**, 2635–2646 (1995)
- Pope, S.B.: *Turbulent Flows*. Cambridge University Press, Cambridge (2000)
- Prandtl, L.: Bericht über untersuchungen zur ausgebildeten turbulenz. *Z. Angew. Math. Mech.* **5**(1), 136–139 (1925)
- Rubinstein, J.: Effective equations for flow in random porous media with a large number of scales. *J. Fluid Mech.* **170**, 379–383 (1986)
- Saez, A.E., Perfetti, J.C., Rusinek, I.: Prediction of effective diffusivities in porous media using spatially periodic models. *Transp. Porous Med.* **6**, 143–157 (1991)

- Taheri, H.: Numerical investigation of stratified thermal storage tank applied in adsorption heat pump cycle. PhD dissertation at Karlsruhe University of Technology (2014)
- Tam, C.K.W.: The drag on a cloud of spherical particles in low Reynolds number flow. *J. Fluid Mech.* **38**(3), 537–546 (1969)
- Uth, M.-F., Jin, Y., Kuznetsov, A.V., Herwig, H.: A direct numerical simulation study on the possibility of macroscopic turbulence in porous media: effects of different solid matrix geometries, solid boundaries, and two porosity scales. *Phys. Fluids* **28**, 065101 (2016)
- Vafai, K.: *Handbook of Porous media*, 2nd edn. Taylor & Francis Group, Boca Raton (2005)
- Vafai, K., Tien, C.L.: Boundary and inertial effects on flow and heat transfer in porous media. *Int. J. Heat Mass Transf.* **24**, 195–203 (1981)
- Vafai, K., Tien, C.L.: Boundary and inertial effects on convective mass transfer in porous media. *Int. J. Heat Mass Transf.* **25**, 1183–1190 (1982)
- Valdes-Parada, F.J., Ochoa-Tapia, J.A., Alvarez-Ramirez, J.: On the effective viscosity for the Darcy–Brinkman equation. *Phys. A Stat. Mech. Appl.* **385**, 69–79 (2007)
- Ward, J.C.: Turbulent flow in porous media. *J. Hydraul. Div.* **90**, 1–12 (1964)
- Wood, B.D., He, X.L., Apte, S.V.: Modeling turbulent flows in porous media. *Annu. Rev. Fluid Mech.* **52**, 171–203 (2020)

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.