Correction to: Friction and Wear Characteristics of Single Crystal Ni-Based Superalloys at Elevated Temperatures

Pantcho Stoyanov¹ · Lesley Dawag¹ · Daniel G. Goberman² · Dilip Shah¹

Published online: 21 March 2018

© Springer Science+Business Media, LLC, part of Springer Nature 2018

Correction to: Tribology Letters (2018) 66:47
<https://doi.org/10.1007/s11249-018-0994-1>

The original version of this article unfortunately contained an error in Figs. 3 and 6 captions.

The corrected figure captions are given below:

Fig. 3 Cross-sectional SEM images produced by FIB of **a** the unworn Waspaloy[®], **b** the unworn single crystal

PWA1484 CHT {100}, **c** the worn single crystal PWA1484 {100} parallel to the sliding direction and **d** the worn Waspaloy[®] parallel to the sliding direction.

Fig. 6 XPS depth profile of the single crystal PWA1484 counterface used on **a** the Waspaloy[®], and **b** the single crystal PWA1484 CHT {100}.

The original article can be found online at <https://doi.org/10.1007/s11249-018-0994-1>.

✉ Pantcho Stoyanov
pantcho.stoyanov@pw.utc.com

¹ Pratt & Whitney, United Technologies Corporation, East Hartford, CT, USA

² United Technology Research Center, United Technologies Corporation, East Hartford, CT, USA