



## Correction to: Hydrogel as a Medium for Fluid-Driven Fracture Study

N.J. O’Keeffe<sup>1</sup> · P.F. Linden<sup>1</sup>

Published online: 5 July 2018  
© Society for Experimental Mechanics 2018

**Experimental Mechanics (2017) 57:1483–1493**

<https://doi.org/10.1007/s11340-017-0314-y>

In the above article, due to a systematic error in analysing the thickness of the fracture, property values were calculated using half the actual value of  $w$ . Thus, the y-axis values in Fig. 4b will be twice as large. Consequently, in Table 1 and Fig. 6, the values for the stress intensity  $K_I$  will be doubled and the fracture energy values  $\gamma_s$  are four times larger due to the relation with  $K_I$ . This does not change the qualitative behaviour of these results described in the paper or the overall conclusions of the paper.

---

The online version of the original article can be found at <https://doi.org/10.1007/s11340-017-0314-y>

---

✉ N. J. O’Keeffe  
okeeffen@damtp.cam.ac.uk

P. F. Linden  
p.f.linden@damtp.cam.ac.uk

<sup>1</sup> Department of Applied Mathematics and Theoretical Physics,  
University of Cambridge, Wilberforce Road, Cambridge CB3 0WA,  
UK

