CORRECTION

Correction to: Process Parameter Impact on Suspension-HVOF-Sprayed Cr₂O₃ Coatings

Jarkko Kiilakoski¹ · Richard Trache² · Stefan Björklund³ · Shrikant Joshi³ · Petri Vuoristo¹

Published online: 18 November 2019
© ASM International 2019

Correction to:
J Therm Spray Tech
<https://doi.org/10.1007/s11666-019-00940-7>

In the references section there is a correction to reference number 41. It should read as follows:

V. Matikainen, S. Rubio Peregrina, N. Ojala, H. Koivuluoto, J. Schubert, S. Houdková, and P. Vuoristo,

Erosion Wear Performance of WC-10Co4Cr and Cr₃C₂-25NiCr Coatings Sprayed with High-Velocity Thermal Spray Processes, *Surf. Coat. Technol.*, 2019, **370**, p 196-212.

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

The original article can be found online at <https://doi.org/10.1007/s11666-019-00940-7>.

✉ Jarkko Kiilakoski
jarkko.kiilakoski@saint-gobain.com

¹ Materials Science and Environmental Engineering, Tampere University, Korkeakoulunkatu 6, 33720 Tampere, Finland

² Treibacher Industrie AG, Althofen, Austria

³ Production Technology, University West, Trollhättan, Sweden