CORRECTION

Correction to: Dynamic Response Analysis of Large Arch-Roof Oil Tank Subjected to the Coupling Impact of Two-Source Blast Waves Based on Finite Element Method

Guohua Chen · Fan Wang · Chilou Zhou · Kun Hu

Published online: 7 February 2020
 © ASM International 2020

Correction to: J Fail. Anal. and Preven.

<https://doi.org/10.1007/s11668-020-00833-w>

The original article has been corrected.

In the original version of the article, some of the entries in Table 12 were misaligned. Following is the corrected table:

Table 12 Dynamic response state of the tank wall in 0°, 30° direction

Off-ground height (m)	0° direction			Response state	30° direction			Response state
	Maximum stress (MPa)	Dynamic yield strength (MPa)	Difference		Maximum stress (MPa)	Dynamic yield strength (MPa)	Difference	
0.242	332	391.9	– 59.9	Elastic deformation	325	391.9	– 66.9	Elastic deformation
2.098	360		– 31.9		334		– 57.9	
4.419	330		– 61.9		320		– 71.9	
6.739	326		– 65.9		322		– 69.9	
9.060	357		– 34.9		328		– 63.9	
11.38	498		106.1	Yield failure	474		82.1	Yield failure
13.70	631		239.1		545		153.1	
16.02	499		107.1		531		139.1	

The original article can be found online at <https://doi.org/10.1007/s11668-020-00833-w>.

G. Chen · F. Wang · C. Zhou (✉) · K. Hu
 School of Mechanical and Automotive Engineering, South China University of Technology, Guangzhou 510641, Guangdong, People's Republic of China
 e-mail: mezc1@scut.edu.cn; Chilou.Zhou@warwick.ac.uk

G. Chen · F. Wang · C. Zhou · K. Hu
 Guangdong Provincial Science and Technology Collaborative Innovation Center for Work Safety, Guangzhou 510641, Guangdong, People's Republic of China

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

C. Zhou
 School of Engineering, University of Warwick, Coventry CV4 7AL, UK