

## Erratum to: Overview of Materials Qualification Needs for Metal Additive Manufacturing

MOHSEN SEIFI $_{\rm D},^{1,5}$  AYMAN SALEM,  $^2$  JACK BEUTH,  $^3$  OLA HARRYSSON,  $^4$  and JOHN J. LEWANDOWSKI  $^1$ 

1.—Department of Materials Science and Engineering, Case Western Reserve University, Cleveland, USA. 2.—Materials Resources LLC, Dayton, OH, USA. 3.—Department of Mechanical Engineering, Carnegie Mellon University, Pittsburgh, USA. 4.—Department of Industrial and Systems Engineering, North Carolina State University, Raleigh, USA. 5.—e-mail: mohsen.seif@case.edu

## Erratum to: JOM, Vol. 68, No. 3, 2016 DOI: 10.1007/s11837-015-1810-0

• There was an error in the caption to Fig. 4. The correct caption appears below.

**Fig. 4** Examples of parts/components made by Powder Bed Fusion AM technologies. (a) Inlet temperature sensor housing for jet turbine engine, roughly 7.5 cm tall; (b) Ti-6Al-4V acetabular cup produced by electron beam melting, EBM (i.e., Arcam); (c) Bracket produced via laser-based powder bed (i.e., EOS); (d) GE LEAP engine Co-Cr fuel nozzle produced via direct metal laser melting, DMLM (i.e., EOS).

- Some unit measures were incorrect in Fig. 5b. The corrected Fig. 5 appears below.
- Also, the callout to Fig. 9a on page 757 should refer to Fig. 9a (left).




Fig. 5. (a) P–V map for electron beam processed Ti-6Al-4V showing regimes of good quality beads as well as size of beta grains.<sup>35</sup> (b) Inset shows different scales of surface roughness of multi-layer beads produced via laser-based techniques at different P–V combinations.

The online version of the original article can be found under doi:10.1007/s11837-015-1810-0.