

Erratum to: Measurement of peak fluence of neutron beams using Bi-fission detectors

R K JAIN¹, ASHOK KUMAR^{2,*}, N L SINGH³, L TOMMASINO⁴
and B K SINGH⁵

¹Department of Physics, School of Basic & Applied Sciences, Shobhit University, Meerut 250 110, India

²Department of Applied Science (Physics), Vidya College of Engineering, Meerut 250 010, India

³Physics Department, M.S. University of Baroda, Vadodara 390 002, India

⁴National Agency for Environment Protection and Technical Services, APAT, via V. Brancati-48, 00144, Rome, Italy

⁵High Energy Physics Laboratory, Department of Physics, Banaras Hindu University, Varanasi 221 005, India

*Corresponding author. E-mail: ashokblp@gmail.com

(*Pramana – J. Phys.* **78**, 493–498 (2012))

The original publication of this article (10.1007/s12043-011-0236-7), unfortunately bears incorrect information in table 1. The corrected table 1 is shown below.

Table 1. Measured and calculated neutron fluence.

Energy (MeV)	(Sparks/neutrons)* 10^{-7}	Sparks/cm ²	Measured neutron peak fluence	Calculated neutron peak fluence
100	2.2 ± 0.2	16 ± 2	$(7.7 \pm 0.4) \cdot 10^7$	$(7.3 \pm 0.8) \cdot 10^7$