Correction to: Microstructural and Wear Behaviour of Al 6063–W Nanocomposites Developed Using Friction Stir Processing

L. Feroz Ali¹ · N. Kuppuswamy² · R. Soundararajan³ · K. R. Ramkumar⁴ · S. Sivasankaran⁵

Published online: 10 August 2021

© The Korean Institute of Metals and Materials 2021

Correction to: Metals and Materials International

<https://doi.org/10.1007/s12540-021-01029-z>

Unfortunately, the original publication of the article contained the errors in third author's affiliation and figure 5. The correct affiliation and Fig. 5 are given in this correction. The original article has been corrected.

The original article can be found online at <https://doi.org/10.1007/s12540-021-01029-z>.

✉ L. Feroz Ali
ferozmts@gmail.com

N. Kuppuswamy
kuppuswamynts@gmail.com

R. Soundararajan
soundararajan.mtech@gmail.com

K. R. Ramkumar
get2raam@gmail.com

S. Sivasankaran
s.udayar@qu.edu.sa; sivasankarangs1979@gmail.com

¹ Department of Mechatronics Engineering, Sri Krishna College of Engineering and Technology, Coimbatore, Tamilnadu 641008, India

² Department of Mechanical Engineering, KIT–Kalaingar Karunanidhi Institute of Technology, Coimbatore, Tamilnadu 641402, India

³ Department of Mechanical Engineering, Sri Krishna College of Engineering and Technology, Coimbatore 641008, Tamilnadu, India

⁴ Department of Metallurgical and Materials Engineering, Indian Institute of Technology Madras, Chennai 600036, India

⁵ Department of Mechanical Engineering, College of Engineering, Qassim University, Buraidah 51452, Saudi Arabia

Fig. 5 FESEM micrographs of: **a** unreinforced Al 6063 matrix, **b** Al 6063–6 vol% W, and **c** Al 6063–12 vol% W nanocomposites

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.