J Opt (April 2024) 53(2):980
https://doi.org/10.1007/s12596-023-01424-2

CORRECTION

Correction to: Suitability of commercially available array spectroradiometer for sphere spectroradiometric applications

Vijeta[1,2] · Naval Manchalwar[1] · Shibu Saha[1] · V. K. Jaiswal[1] · Parag Sharma[1,2]

Received: 21 September 2023 / Accepted: 21 September 2023 / Published online: 11 October 2023

Correction to: J Opt
https://doi.org/10.1007/s12596-023-01299-3

In this article references 18 and 24 were incorrectly given as

18. D. Vijeta, R.K. Kapri, S. Saha, V.K. Jaiswal, P. Sharma, Theoretical simulation for evaluating error in irradiance measurement using optical detectors having different cosine responses. Mapan **36**(3), 473–480 (2021). https://doi.org/10.1007/s12647-021-00486-6

24. D. Vijeta, P. Sharma, V.K. Jaiswal, S. Saha, R. Mehrotra, Study of Array Detector Based Spectrophotometer for Sphere Photometry, in *ICOL-2019*. ed. by K. Singh, A.K. Gupta, S. Khare, N. Dixit, K. Pant (Springer), pp. 565–569 (2021). https://doi.org/10.1007/978-981-15-9259-1_130

and should have been as

18. Vijeta, R.K. Kapri, S. Saha, V.K. Jaiswal, P. Sharma, Theoretical simulation for evaluating error in irradiance measurement using optical detectors having different cosine responses. Mapan **36**(3), 473–480 (2021). https://doi.org/10.1007/s12647-021-00486-6

24. Vijeta, P. Sharma, V.K. Jaiswal, S. Saha, R. Mehrotra, Study of Array Detector Based Spectrophotometer for Sphere Photometry, in *ICOL-2019*. ed. by K. Singh, A.K. Gupta, S. Khare, N. Dixit, K. Pant (Springer), pp. 565–569 (2021). https://doi.org/10.1007/978-981-15-9259-1_130

In the acknowledgement section, the last line,"This work has also been supported by the Academy of Scientific and Innovative Research (AcSIR), Ghaziabad, India", should be removed and the correct acknowledgement section should read as below:

Acknowledgements The authors thank Director, CSIR–National Physical Laboratory for encouragement and support. Technical support from the members of the Optical Radiation Metrology group is acknowledged. Financial support from the Bureau of Energy Efficiency (BEE), the Ministry of Power, Government of India, for the LED testing and calibration facility is acknowledged. One of the authors, Vijeta is thankful to University Grant Commission (UGC) for providing the fellowship under the UGC-SRF scheme.

The original article can be found online at https://doi.org/10.1007/s12596-023-01299-3.

✉ Parag Sharma
sharmap2@nplindia.org

[1] CSIR-National Physical Laboratory, Dr. K.S Krishnan Marg, New Delhi 110012, India

[2] Academy of Scientific and Innovative Research (AcSIR), Ghaziabad 201002, India