Correction to: Realizing simultaneously enhanced energy and power density full-cell construction using mixed hard carbon/ $\text{Li}_4\text{Ti}_5\text{O}_{12}$ electrode

Shi-Fei Huang, Yao Lv, Da Tie, Yang Yu, Yu-Feng Zhao*

© The Nonferrous Metals Society of China and Springer-Verlag GmbH Germany, part of Springer Nature 2019

Correction to: Rare Met.

<https://doi.org/10.1007/s12598-019-01312-4>

In the original publication, in Figure 3, part d has been mistakenly published same as part c. The correct version of Fig. 3 is given in this Correction.

The original article can be found online at <https://doi.org/10.1007/s12598-019-01312-4>.

S.-F. Huang, Y. Lv, D. Tie, Y. Yu, Y.-F. Zhao*
State Key Laboratory of Metastable Materials Science and
Technology, Key Laboratory of Applied Chemistry, Yanshan
University, Qinhuangdao 066004, China
e-mail: yufengzhao@ysu.edu.cn

Y.-F. Zhao
Institute of Sustainable Energy, Shanghai University, Shanghai
200444, China

Fig. 3 **a** Maximum energy density ($P_{\max}$) and **b** maximum power density ($E_{\max}$) of NCM111/LTO + HC system; **c** discharge curves of NCM111/LTO + HC at current density of $0.1 \text{ A} \cdot \text{g}^{-1}$ with operate potential of 1.5–3.0 V; **d** rate performance of NCM111/LTO + HC system