CORRECTION

Correction to: Influence of Multiple Earthquakes on Single-Layer Reticulated Dome and Its Shaking-Table Test

Ying-Nan Zhang^{1,2,3} · Xu-Dong Zhi^{1,2,3} · Feng Fan^{1,2,3}

Published online: 1 February 2020
© Korean Society of Steel Construction 2020

Correction to: International Journal of Steel Structures
<https://doi.org/10.1007/s13296-019-00272-w>

In the original publication of the article, data of maximum nodal displacement were published incorrectly in few places. The correct data are provided below.

Under the section 5.6 Verification of Four Aftershock-Influence Levels, data of maximum nodal displacement in the following sentence were published incorrectly as, “...stiffness still remains good, with only $L/456$ as the maximum nodal displacement. Under condition 16, the...” The correct sentence should read as “...stiffness still remains good, with only $L/1368$ as the maximum nodal displacement. Under condition 16, the...”

In addition, data of maximum nodal displacement in the following sentence were published incorrectly as “...The structural stiffness reduces a lot, with many visibly bent tubes, and the maximum nodal displacement reaches $L/199$. Under condition 20, the model topples.” The correct sentence should read as “...The structural stiffness reduces a lot, with many visibly bent tubes, and the maximum nodal displacement reaches $L/597$. Under condition 20, the model topples.”

Finally, data of maximum nodal displacement of Table 7 were published incorrectly. The correct version of Table 7 is provided below.

The original article can be found online at <https://doi.org/10.1007/s13296-019-00272-w>.

✉ Xu-Dong Zhi
zhixudong@hit.edu.cn

- ¹ Key Laboratory of Structural Engineering Disaster Control of Education Ministry (Harbin Institute of Technology), Harbin 150090, China
- ² Key Laboratory of Civil Engineering Intelligent Disaster Prevention and Mitigation Control of Ministry of Industry and Information (Harbin Institute of Technology), Harbin 150090, China
- ³ School of Civil Engineering, Harbin Institute of Technology, Harbin 150090, China

Table 7 Structural state from condition 8 to condition 20

Condition	Maximum nodal displacement of VD1 (L : span)	Existing deformed tubes or not	Ratio of yield members (%)	Structural state
8	1/2469	No	0	Elastic
10	1/3429	No	0	Elastic
12	1/1848	No	0	Elastic
14	1/1368	No	8.33	Slightly plastic
16	1/774	Yes	22.22	Slightly plastic
18	1/597	Yes	59.72	Significantly plastic
20	–	–	–	Collapse

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.