Critical challenges in biohydrogen production processes from the organic feedstocks

Ahmed I. Osman^{1,2} · Tanmay J. Deka¹ · Debendra C. Baruah³ · David W. Rooney¹

Received: 28 May 2020 / Revised: 12 August 2020 / Accepted: 14 August 2020
© The Author(s) 2020

Abstract

The ever-increasing world energy demand drives the need for new and sustainable renewable fuel to mitigate problems associated with greenhouse gas emissions such as climate change. This helps in the development toward decarbonisation. Thus, in recent years, hydrogen has been seen as a promising candidate in global renewable energy agendas, where the production of biohydrogen gains more attention compared with fossil-based hydrogen. In this review, biohydrogen production using organic waste materials through fermentation, biophotolysis, microbial electrolysis cell and gasification are discussed and analysed from a technological perspective. The main focus herein is to summarise and criticise through bibliometric analysis and put forward the guidelines for the potential future routes of biohydrogen production from biomass and especially organic waste materials. This research review claims that substantial efforts currently and, in the future, should focus on biohydrogen production from integrated technology of processes of (i) dark and photofermentation, (ii) microbial electrolysis cell (MEC) and (iii) gasification of combined different biowastes. Furthermore, bibliometric mapping shows that hydrogen production from biomethanol and the modelling process are growing areas in the biohydrogen research that lead to zero-carbon energy soon.

Keywords Biohydrogen · Fermentation · Bio-photolysis · Biowaste · Waste to energy · Microbial electrolysis cell · Gasification · Climate change

Nomenclature

ATP	Adenosine triphosphate
BOD	Biological oxygen demand
Chl	Chlorophyll <i>a+b</i>
CCWP	Concentrated cheese whey permeate
COD	Chemical oxygen demand
DF	Dark fermentation
GHG	Greenhouse gas
HRT	Hydraulic retention time
HPR	Hydrogen production rate
HC	Hydrocarbon
H ₂ SO ₄	Sulphuric acid

LCA	Life cycle assessment
MEC	Microbial electrolysis cell
NG	Natural gas
OLR	Organic loading rate
PNSB	Purple non-sulphur bacteria
PF	Photofermentation
SCW	Second cheese whey
SRT	Solid retention time
TS	Total solid
VSS	Volatile suspended solids
VS	Volatile solid
WGSR	Water gas shift reaction
WoS	Web of Science

✉ Ahmed I. Osman
aosmanahmed01@qub.ac.uk

¹ School of Chemistry and Chemical Engineering, Queen's University Belfast, Belfast, Northern Ireland BT9 5AG, UK

² Chemistry Department, Faculty of Science-Qena, South Valley University, Qena 83523, Egypt

³ Energy Conservation Laboratory, Department of Energy, Tezpur University, Sonitpur 784028, India

1 Introduction

The depletion of fossil-based fuel sources along with their increasing use day by day has created big concerns related to greenhouse gas (GHG) emissions and global warming. Increasing levels of CO₂, which is a patent GHG emission and associated with burning fossil fuel sources, were found

to exceed 409 ppm [1–3], which is aiding to the global temperature increase [4, 5]. Moreover, growing industrial and economic development of the modern world is also demanding more sources of clean energy for the near future. The increasing gap between the growing energy demand and necessary energy supply due to at the rising human population has sparked a huge interest in new biofuel research as well as production in recent times [6]. Therefore, from the perspective of alternative energy sources, renewable energy sectors like solar, hydro, wind and biofuels like biodiesel, bioethanol and biohydrogen are finding its use in current development agendas across the world. Recently, hydrogen production by water electrolysis has gained global attention as one of the most promising and eco-friendly energy alternatives. H_2 is found to have a high energy content of around 122 kJ/g, about 2.75 times higher than other HC fuels [7, 8]. It also possesses wide versatility in its production as well as its applications ranging from fuel-cells to biofertilisers and biofuels. H_2 produced from biological sources is known as bio- H_2 . Hydrogen produces no harmful greenhouse gases upon combustion but only water. Therefore, it is considered one of the energy sources to have the potential to replace part of the conventional fossil-based fuels shortly [9].

As far the production is concerned, fossil fuel is responsible for the majority of hydrogen production, out of which 60% is produced from dedicated primary hydrogen-producing facilities. It is also reported that around 71.27% of hydrogen is produced from natural gas (NG), 27.27% from coal, 0.7% from petroleum and the remaining 0.7% from water electrolysis [10–12]. Notably, the hydrogen production from fossil reformation is neither renewable nor carbon neutral as the production process involves high numbers of GHG footprints [4]. H_2 production is also achieved with water gas shift reaction (WGSR), thermal decomposition, catalytic oxidation, steam gasification, pyrolysis and autothermal reforming [13, 14]. The recent popularity of waste-to-energy studies also creates an impact on research related to hydrogen production utilising waste materials effectively. Biohydrogen is produced from different organic wastes, thereby solving the issue of waste disposal and energy generation at the same time. Organic waste can be defined as the waste materials that are biodegradable and originates from plants or animals which can be broken into CO_2 , methane or simple organic molecules [15]. Organic wastes like industrial waste, municipal sewage sludge, solid waste, agricultural residues and poultry waste, manure, have the potential to be used for bioenergy production [16].

However, recent publications suggested further investigations are required on the production of H_2 using organic waste materials. The concept of using waste materials from different biological sources to produce environment-friendly biohydrogen can be potentially helpful to tackle the ongoing environmental challenges, while for all H_2 production

processes (NG reforming, biomass and coal gasification, water electrolysis and others), there are requirements for better reliability and operating flexibility, a reduction in the capital costs and a significant enhancement in the plant efficiencies [17]. Herein, we assessed the routes of biohydrogen production derived from different organic waste materials and highlighted the key factors affecting the yield of biohydrogen. Furthermore, through bibliometric mapping, we suggest steps and future guidelines from the gaps in the literature for the optimisation of hydrogen production from organic waste streams. Overall, this critical review is aimed at helping the academics working in the biohydrogen production research area along with the industrial application and roll-out of a zero-carbon economy. It will also focus on themes that face the development and potential transformation of the biohydrogen market and its future.

2 Review methodology

Web of Science (WoS) was utilised herein to obtain the data within the core collection database and then the exported data files; some Boolean operator logic was implemented in the search to find suitable publications and identify evidence gaps in the knowledge and research concerning the biohydrogen topic. A broad timespan of biohydrogen research covering all available year option in the time frame of 1970–2020 is shown in Fig. 1. The bibliometric mapping generated from the WoS core collection is shown in Fig. 1. The overall number of data which was 1539 was exported to the VOSviewer software. Herein, we used the co-occurrence as the type of analysis and all keywords included and the fractional counting method employed. We have direct clusters in Fig. 1 linking specific keywords to general areas such as biohydrogen production. This approach enabled us to visualise the most distinguished keywords in publications in the last 50 years for biohydrogen production. For example, keywords like dark fermentation, water and ethanol production along with lignocellulosic biomass were the most frequently occurring keywords. Other common related keywords to the biohydrogen production are hydrolysis, pyrolysis, gasification, enzymatic hydrolysis, biodiesel production, sludge, microalgae, wastewater, anaerobic digestion, photo-fermentation, glucose, supercritical water and saccharification. Furthermore, the WoS search showed other keywords associated with the production conditions such as pre-treatment, pH, light and temperature. On the other hand, new keywords have been introduced to biohydrogen production recently such as methanol, modeling, storage, fuel-cells, energy recovery, organic waste, bioreactors, light intensity, methanogenesis along with the techno-economic and life cycle assessment (LCA) studies. This implies that areas such as hydrogen production from

3 Production of biohydrogen from organic waste through biological methods

biohydrogen production processes along with their energy conversion efficiencies. Energy conversion efficiency can be defined as the ratio between the useful output of an energy conversion machine/process and energy input [25]. In this section, these processes of biohydrogen production are discussed. Figure 2 shows the different biological processes involved in biohydrogen production. Biohydrogen production with dark fermentation, MEC and biomass gasification possesses high process efficiency, and biomass is the common feedstock in all of the aforementioned processes. Again, photofermentation and biophotolysis can be seen dependant on solar energy for the production of biohydrogen. Different process parameters are associated with all these processes, which have their own importance. Every process has its certain specification and operating conditions along with advantages and disadvantages which are discussed below.

Table 1 Status of available biohydrogen production technologies

Production process	Feedstock	Maturity	Energy conversion efficiency (%)	[Ref.]
Dark fermentation	Biomass	Long term	4.3	[21]
Photo fermentation	Biomass + sunlight	Long term	5.1	[21]
Bio photolysis	Sunlight + water	Long term	2.7–4.0	[22]
Microbial electrolysis cells	Biomass + electricity	Long term	11.3	[23]
Biomass gasification	Biomass	Commercial	88.1	[24]

3.1 Fermentation

Fermentation can be defined as the process of energy generation involving an endogenous electron acceptor from the oxidation of organic waste materials using a number of different microorganisms. The results of fermentation depend on the applied catalyst (isolated enzyme or microorganism producer) and used organic substrate (mostly carbohydrate or protein), along with the process parameters. The character of the fermentation process can be either aerobic or anaerobic [26]. Fermentation of organic waste materials using microorganisms under anaerobic conditions is a good way to produce H_2 along with other organic alcohols/acids as by-products. Depending on the necessity of light for the microorganisms, the biofermentation can be divided into two types: (a) dark fermentation and (b) photo fermentation. Dark fermentation is the process of fermentation carried out in dark anaerobic conditions, where breakdown of cellulosic organic feedstock results in the production of biological hydrogen along with organic acids and alcohols [27].

Unlike dark fermentation, photofermentation uses photosynthetic bacteria that use sunlight to produce CO_2 and H_2 from organic molecules under anaerobic conditions [28]. For improving the yield of biohydrogen, studies related to the integration of both the two fermentation processes can also be found. Figure 3 shows the two types of biofermentation processes used for H_2 production.

3.1.1 Dark fermentation

Dark fermentation has become one of the well-known technologies for biohydrogen production, which enables the microorganisms to produce H_2 in a dark anaerobic condition [29]. However, with the formation of many by-products, the low H_2 yield on substrates is a major disadvantage. Equations 1 and 2 show the main reactions that are involved in the dark fermentation process of hydrogen production. Equation 1 shows the reaction for H_2 production as a result of the proton reduction by generated electrons from C-source degradation. [NiFe]-hydrogenase and [FeFe]-hydrogenase are generally involved in such process of H_2 formation [30]. A maximum H_2

Fig. 2 Overview of the biological biohydrogen production processes

Fig. 3 **a** Dark fermentation and **b** photofermentation processes during the hydrogen production from organic waste or wastewater

yield of 4 mol H₂/mol glucose can be seen to be achievable in the dark fermentation process practically, though Eq. 2 shows a theoretical yield of 12 mol H₂/mol glucose [31]. Higher yields can be achieved in thermophilic fermentations. This low yield in dark fermentation is mainly happening due to the production of other by-products such as acetic acid, propionic acid and butyric acid. Equation 3 shows the acetic acid pathway, where the reaction of glucose and two water molecules produce acetic acid (CH₃COOH). Similarly, propionic acid can be found to be produced along with acetic acid from glucose, as shown in Eq. 4. Again, Eq. 5 shows the production of butyric acid from glucose reacting with six water molecules [32]. In all the three pathways, CO₂ and H₂ are seen to be produced in different quantities.

(Acetic acid pathway)

(Propionic acid pathway)

(Butyric acid pathway)

Several types of waste with different chemical compositions are seen used as a substrate to produce H₂ in the dark fermentation process. Among those, the most widely used waste includes agricultural wastes (viz. rice/wheat/corn straw, animal manure), various wastewater types (viz. distillery wastewater, cheese whey effluent, palm oil mill effluent), food waste, municipal sewage waste and sewage sludge [33]. The sugar or carbohydrate-rich waste substrates tend to produce more H₂ compared with lipid or protein-rich substrates. A linear correlation between H₂ production and the proportion of carbohydrate-rich waste substrate was also found [34]. Waste like sewage sludge and palm oil mill effluent

usually have a low H₂ yield compared with other waste due to the high presence of protein or lipid [33].

The pre-treatment is a crucial step in biohydrogen research. Table 2 shows various studies related to pre-treatment methods, like physical (high temperature, ultrasonication and microwave), mechanical (milling and grinding), enzymatic, radiation and hydrothermal pre-treatment for the improvement of H₂ yield [49–51]. Different types of substrates need different pre-treatment methods, which can enhance the production efficiency of hydrogen. Pre-treatment of dairy manure can be done mainly with three different methods: (a) acid (0.2% w/w HCl solution) treatment, (b) alkali (0.2% w/w NaOH solution) treatment and (c) 2 h infrared oven treatment [33, 35]. In the case of sewage sludge, 15-min boiling at around 100 °C completes the pre-treatment [36]. Pre-treatment of rice straw for hydrogen production was found with boiling at 80–100 °C [37], and in another case, treatment with alkali solution (1% w/w) was found with cellulose hydrolysis after cutting and grinding (2 mm size) [41]. Distillery wastewater was also found to be pre-treated with pH neutralisation, centrifugation and sterilisation [39]. Food waste was found to be pre-treated in many ways. Sieving and 6 h boiling at around 100 °C of food waste hydrolysate for hydrogen production were reported by Han et al. [42]. Kim et al. [43] mentioned pre-treatment of food waste and sludge mixture with 30-min heating (at 120 °C), alkalinisation (3 M NaOH) and acidification (3 M HCl). Kitchen mill shredding was also applied as a pre-treatment method to food waste combined with 5% glycerol [44].

The H₂ yield of 1130 mmol/g COD was reported for plain palm oil, while an improvement of 2760 and 1880 mmol/g COD was found for surfactant (Tween 80) and enzyme (Optimase BG) pre-treatment, respectively [52]. Efficient H₂ production with lignocellulosic materials like sugarcane bagasse rice/corn/wheat straw and corn stalk from agricultural waste needs pre-treatment as mentioned in several different studies [53, 54]. An increase in 47.3% of biohydrogen production was seen for pre-treatment of rice husk with a commercial enzyme (Celluclast 1.5 L) compared with that of rice husk without pre-treatment (321 mL H₂/g rice husk) [54]. Similarly, 35% high H₂ yield (155 mL H₂/g VS) was seen in

Table 2 Comparison of biohydrogen production from wastes with the dark fermentation process

Substrate	Pre-treatment process	Microorganism	pH	Temperature (°C)	H ₂ yield (mL/g VS)	[Ref.]
Dairy manure	HCl (0.2%) treatment, boiling/infrared radiation	Mixed culture	5.0	36.0 ± 1	31.5	[35]
Sewage sludge	100 °C boiling (for 15 min)	Mixed culture	7.0	37.0	11.2	[36]
Sewage sludge + poplar leaves					20.8	
Sewage sludge + flower waste					32.0	
Sewage sludge + ryegrass					51.0	
Rice straw	80–100 °C boiling	Activated sewage sludge	4.0–5.5	35.0	14.5 ± 0.3	[37]
Food waste+ sewage sludge +3% crude glycerol	100 °C heat shock (for 30 min)	Mixed culture	5.5	35.0	179.3	[38]
Distillery wastewater	Neutralisation (to pH 6.7 with KOH), 5000 rpm centrifugation, sterilisation	Mixed culture	5.0	37.0	1.6 ± 0.3*	[39]
Cassava wastewater	Sieving, 95 °C boiling (for 15 mins)	Mixed culture	5.5	37.0	39.8**	[40]
Rice straw	Cutting and grinding (2 mm size), 1.0% alkali pre-treatment, cellulose hydrolysis	<i>Clostridium pasteurianum</i>	7.5	37.0 ± 2	2.6*** (47.6 mL/g released sugar)	[41]
Food waste hydrolysate	Sieving, 100 °C boiling (for 6 h)	<i>A. awamori</i> , <i>A. oryzae</i>	4.0–4.6	37.0	219.9 (39.1 mL/g food waste)	[42]
Food waste + sludge	120 °C heating (for 30 mins), alkalisalation (3 M NaOH), acidification (3 M HCl) -		5.5 ± 0.1	37.0	13.8	[43]
Food waste +5% crude glycerol	Kitchen mill shredding	Mixed culture	5.0–5.5	35.0 ± 1	180.0	[44]
Sugarcane bagasse	H ₂ SO ₄ (2%) in solid-to-liquid and mass ratio 1:15, 121 °C sterilisation (for 1 h)	<i>Enterobacter aerogenes</i>	6.8	30.0	1000.0****	[45]
Brewery wastewater	Dilution with distilled water, pH adjustment with HCL and NaOH	<i>Klebsiella pneumoniae</i>	5.5	35.0 ± 1	1.7*****	[46]
Glucose	–	<i>Thermotoga neapolitana</i>	6.5	70.0	1.7*****	[47]
Wheat straw	Overnight soaking in acetic acid, steam explosion at 190 °C (for 10 min), enzymatic hydrolysis for 72 h	<i>Caldicellulosiruptor saccharolyticus</i>	6.5 ± 0.1	70.0	134.0*****	[48]

*mL/mL wastewater; **mL/g- COD; ***L/L hydrolysate

****mL/L hydrolysate; *****mol H₂ mol⁻¹ glucose; *****mmol H₂/L

the case of cornstalk pre-treated with lime compared with that of the untreated stalk (115 mL H₂/g VS) [55]. Song et al. [56] studied biohydrogen production from an aquatic weed, *Alternanthera philoxeroides*, pre-treated with 1% H₂SO₄ at 135 °C for 15 min, using *Enterobacter aerogenes* ZJU1. The optimum H₂ production was found to increase by 59.9% to reach production of 62.2 mL/g with pre-treatment compared with 38.9 mL/g VS for the raw material, without pre-treatment. That low hydrogen yield may be due to the utilisation of different feedstocks (115 mL H₂/g VS). Shao et al. [57] used dilute acid (1% H₂SO₄)-pre-treated duckweed biomass for H₂ production using dark fermentation. They found a maximum H₂ yield of 169.30 mL/g dry weight under a temperature condition of 35 °C and an initial pH value of 7.0. Acid pre-treatment (0.2% HCl) of dairy manure was also seen improving the H₂ yield by 36%; further 6.8 and 4.5% improvement in H₂ production from dairy manure was reported for base pre-treatment (0.2% NaOH) solution and infrared oven pre-treatment, respectively [35]. Thus, it can be seen that pre-treatment of substrates is highly recommended for good yield of biohydrogen in dark fermentation.

Another important parameter for the dark fermentation biohydrogen yield is the pH environment value. pH level in the dark fermentation process is found to influence the metabolic pathway and microorganism activity of the microorganisms and thereby affect the substrate degradation and production efficiency. The pH levels at the start of operation and during the process were seen carefully maintained in many dark fermentation studies [58–60]. Using dark fermentation of cheese whey wastewater, the highest biohydrogen production was found at pH 5.5 and pH 6.5 for thermophilic and mesophilic conditions, respectively [59]. Xing et al. [35] studied a wide variation in pH between 4.0 and 12.0 for fermentation of dairy manure. At pH 5.0, they found the highest biohydrogen yield of 31.5 mL/g VS. A pH below 4.0 and above 12.0 showed no biohydrogen production.

Hydrogenotrophic methanogens act as one of the major H₂-consuming microorganisms which reduced the H₂ yield by consuming H₂ to produce methane. Therefore, inhibiting the production of hydrogenotrophic methanogens, which acts as an H₂-consuming microorganism, is one of the major steps for dark fermentation. Pre-treatment of inoculum is considered for enriching H₂-producing bacteria and suppressing H₂-consuming methanogens. Since methanogens are strictly anaerobic microorganisms, aeration around the reactor can inhibit the methanogen production and thereby increase the H₂ yield [61]. The impact of pH in the growth of methanogen is another important aspect of biohydrogen yield. It has been reported that methanogens are capable of producing methane by consuming H₂ under an optimal pH range of 7–8 and optimal hydraulic retention time (HRT) of 15–20 days [62]. Kumar et al. [63] attained a hydrogen yield of 29.5 mL/g VS with

pH 5.5 and methanogenic inhibitor from mixed microalgae biomass (*Scenedesmus* and *Chlorella*).

Production of biohydrogen by dark fermentation is accomplished by various microorganisms that are capable of converting a wide range of organic waste substrates. Based on different living temperatures, these microorganisms are classified as thermophiles (45–65 °C), mesophiles (25–45 °C) and psychrophiles (0–25 °C). The commonly used mesophilic cultures for H₂ production are *Clostridium* and *Enterobacter* (*Clostridium beijerinckii*, *Clostridium butyricum*, *Enterobacter aerogenes* and *Enterobacter asburiae*); while the most reported thermophilic one is *Thermoanaerobium* (*Thermoanaerobacterium thermosaccharolyticum*) [35]. Again, depending on their growth of metabolism in the presence of oxygen, they are divided as facultative (e.g. *E. cloacae*, *Enterobacter aerogenes*, *Citrobacter intermedius* and *Escherichia coli*) or obligate bacteria (e.g. *C. paraputrificum*, *Ruminococcus albus* and *Clostridium beijerinckii*) [13, 64]. Facultative bacteria are the organisms that make ATP by aerobic respiration (in the presence of oxygen) and are also capable of anaerobic respiration or fermentation (in the absence of oxygen). On the contrary, obligate bacteria are unable to produce ATP (in the absence of oxygen) and cannot live in the presence of oxygen. *Enterobacter* and *Clostridium* are two species of gram-positive bacteria for large-scale production of hydrogen for their ability of fast-growing and forming endospores. Lactic bacteria like *Klebsiella pneumoniae*, *Cellulomonas* and some thermophilic archaea like *Thermotoga neapolitana* and *Caldicellulosiruptor saccharolyticus* were also found showing good results for H₂ production through dark fermentation [65].

HRT (hydraulic retention time) acts as one of the important parameters for proper fermentation of substrate and efficient H₂ production. The stability of the reactor and utilisation efficiency of the feedstock depends on HRT. Santiago et al. [66] found that HRT and solid retention time (SRT) have a great impact on the biohydrogen production and associated sub-products from organic solid waste (OSW) using a dark fermentation process. A 16 h of HRT and 55 h of SRT were found to be the optimum conditions to maximise the biohydrogen production. HRT was found as the main influencing parameter in the whole process. The substrate hydrolysis rate increased with decreasing HRT time. Moreover, substrate hydrolysis-ssolubilisation process time got reduced with an increase in SRT and a decrease in HRT. Fatty acid production was found maximum with long SRT and HRT of 60 h and 48 h, respectively. Lu et al. [67] studied the effects of HRT and concentration of substrate on the HPR (hydrogen production rate) from glucose in a pilot-scale bioreactor of 3 m³ with three sequential chambers of 1 m³ each. A HRT of 24 h and substrate concentration of 30 g/L with a maximum HPR of 100.2 mol/m³-d were found optimal for the reactor.

The production of biohydrogen using dark fermentation of two different cheese deproteinisation dairy waste streams SCW (second cheese whey) and CCWP (concentrated cheese whey permeate) was studied by Colombo et al. [68]. With an increasing OLR (organic loading rate), H₂ production was seen increasing to 3.47 NL H₂/d and 5.07 NL H₂/d for SCW and CCWP, respectively. Similarly, organic acid yield was also found higher with increasing OLR (14.6 g/L/d and 12.6 g/L /d for SCW and CCWP, respectively). Table 2 describes different studies of biohydrogen production from wastes using a dark fermentation pathway. It can be seen that combined fermentation of different substrates leads to an increased biohydrogen yield. Moreover, pre-treatment processes such as acid treatment, base treatment, heat treatment and pH neutralisation have shown a significant impact on the yield of biohydrogen. Most of the studies were found to utilise a mixed culture process for good results.

3.1.2 Photofermentation

The production of H₂ with photofermentation involves decomposition of organic acids with the aid of light-dependant, sulphur and non-sulphur purple bacteria. A group of bacteria having the ability to do photosynthesis is known as purple sulphur bacteria. Again, purple non-sulphur bacteria (PNSB), commonly known as photobacteria, are a group of photoheterotrophic bacteria capable of degrading several carbon substrates like carbohydrate, organic matter, biowastes and organic acids for the production of H₂ [69]. Equations 6 and 7 show the reaction involved with the production of H₂ by photofermentive process from glucose and acetic acid, respectively. Oxidation of organic acids, like acetic acid, propionic acid, butyric acid, lactic acid and malic acid, by photofermentive bacteria, produces H₂ and CO₂. Therefore, to obtain a higher H₂ yield, the two-stage dark fermentation process is often followed by a photofermentation process [70]. The energy needed for the growth of microorganisms is gathered from the production of adenosine triphosphate (ATP) using light through photophosphorylation [4]. Batch or continuous photofermentation process can be obtained using an artificial source of light or solar illumination as shown in Fig. 3b.

The photofermentation process offers the possibility of high H₂ production from a wide variety of substrates including wastewaters (such as olive mill wastewater, dairy wastewater, brewery wastewater) and wastes rich in organic acids (such as dark fermentation effluent, agricultural waste after hydrolysis) [33, 71]. The best H₂-producing microorganism for the photofermentation is PNS (purple non-sulphur bacteria),

which include the *Rhodobacter* species (*Rhodobacter capsulatus*, *Rhodobacter sphaeroides*, *Rhodovulum palustris* and *Rhodopseudomonas sulfidophilum*) [72]. Some other bacteria used in H₂ production using nitrogenase and ATP production are *Chlorobium vibrioforme*, *Allochrodatum vinosum*, *Desulfuromonas acetoxidans*, *Thiocapsa roseopersicina* and *Chloroflexus aurantiacus* [13]. Hydrogenase and nitrogenase are two different enzymes that help these bacteria to produce H₂ from organic acids using solar energy [73]. Nitrogenase are found to be the main enzymes responsible for H₂ production in limited-O₂ conditions. NH₃ is generally produced from N₂ by nitrogenase (in large-scale production), but in absence of N₂, ATP is used along with redundancy by nitrogenase to generate H₂ [13], as shown in Eq. 8.

Several studies can be found regarding photofermentive H₂ production in recent years. Mirza et al. [74] found a wide range of 148–513 mL H₂/L photofermentive biohydrogen production using raw sugarcane bagasse with the help of PNSB (purple non-sulphur bacteria) isolated from the paddy rice field *Rhodobacter capsulatus*-PK. A maximum yield of 96 mol H₂/mol sugar was achieved with initial pH 7.0 ± 0.2 and 10% (v/v) inoculum size, at a temperature of 30 ± 2.0 °C along with a light intensity of 120–150 W/m². The production of 671 mL/L of H₂ from glucose was also found with this process. For cost reduction of temperature control during summer, *Rhodobacter capsulatus*-PK was found as a good candidate for photofermentive bio-H₂ production. García-Sánchez et al. [75] used *Rhodopseudomonas pseudopalustris* to produce H₂ by tequila vinasses (VT) photofermentation. Compared with synthetic medium, they found a double H₂ yield with VT. With the replacement of H₂ by N₂ compared with unchanged headspace, three-time growth was seen in *R. pseudopalustris* up to 4.5 g/L, and the H₂ yield also increased to 860 mL H₂/L. Laurinavichene et al. [39] used PNS bacteria and anaerobic saccharolytic consortium to perform sequential dark photofermentation, which resulted in 17.6 L/L of distillery waste of maximum H₂ yield. Machado et al. [76] investigated the influence of milk whey permeate and glucose on the H₂ yield using PNS bacteria *Rhodobacter capsulatus* and *Rhodopseudomonas palustris* through co-culture. The maximum H₂ yield was found to be 287.39 ± 5.75 mmol of H₂/L day. Keskin and Hallenbeck [77] used beet two major sugar mill waste—black strap and beet molasses for biohydrogen production using photofermentation. The H₂ yield found from pure beet sucrose, black strap and beet molasses are 14 H₂/mol sucrose, 8 H₂/mol sucrose and 10.5 mol H₂/mol sucrose, respectively. A comparative study of different parameters involved in photofermentive biohydrogen production process is shown in Table 3. The

Table 3 Comparison of biohydrogen production with photofermentation

Substrate	Pre-treatment process	Microorganism	pH	Temperature (°C)	Light (W/m ²)	H ₂ yield	[Ref.]
DF effluent of distillery wastewater	-	<i>R. capsulatus</i> B10, <i>R. sphaeroides</i> B-3059	7.0	30.0	30.0	3.2 mL/mL wastewater	[39]
Rotten apple batch	Crushing, sieve screening	Mixed culture	7.1	30.5	24.0	112.0 mL/g TS	[78]
Palm oil mill effluent	-	<i>Rhodopseudomonas palustris</i>	5.5	30.0 ± 1	55.3	2.3 mL H ₂ /mL POME	[79]
DF effluent of sugarcane bagasse	Centrifugation, Vacuum filtration	<i>Rhodopseudomonas</i> BHU 01	6.8	34.0	8.5	755.0 mL/L hydrolysate	[45]
DF effluent of corn stover	-	Mixed culture	7.0 ± 0.08	30.0	23.7	4.7 m ³ /m ³ -d	[80]
Sugar beet molasses	Addition of buffer, pH adjustment, sterilisation	<i>R. sphaeroides</i> O.U.001 <i>R. capsulatus</i> YO3	7.5	30.0	114.0	9.4 mol/mol sucrose 10.6 mol/mol sucrose	[81]
		<i>R. capsulatus</i> DSM 1710				12.7 mol/mol sucrose	
		<i>Rhodopseudomonas palustris</i> DSM 127				19.0 mol/mol sucrose	
Cornstalk pith	Enzyme cellulase hydrolysis (at 50 °C)	Mixed culture	7.0	30.0	15.8	2.6 mol/mol sugar consumed	[82]
<i>Chlorella pyrenoidosa</i> + cassava starch	Acid (1% H ₂ SO ₄) treatment, heating at 135 °C (for 15 min)	<i>Clostridium butyricum</i>	7.0 ± 0.1	30.0 ± 1	47.4	388.0 ± 42.1 mL/g VS	[83]
Cellulose	-	<i>Cellulomonas fimi</i> ATCC 484, <i>Rhodopseudomonas palustris</i> CGA009	-	30.0	40.0	3.8 mol H ₂ /mol glucose	[84]
Brewery wastewater	Pre-treated with banana peel	<i>Rhodobacter sphaeroides</i> 158 DSM	7.4	30.0 ± 2	126.0	408.3 mL H ₂ L ⁻¹	[85]
Cornstalk pith	-	<i>Rhodospirillum rubrum</i> , <i>Rhodopseudomonas capsulata</i> , <i>Rhodopseudomonas pulastris</i> , <i>Rhodobacter sphaeroides</i> and <i>Rhodobacter capsulatus</i>	7.3 ± 0.5	30.0	15.8	211.9 mL/L-medium	[86]
Agar embedded molasses	-	Heat-treated hot-spring sludge	7.4	37.0	39.5	226.2 mL H ₂ /g TS	[87]
Corn stover powder	-	<i>Rhodobacter sphaeroides</i> , <i>Rhodospirillum rubrum</i> , <i>Rhodobacter capsulatus</i> and <i>Rhodopseudomonas palustris</i>	6.5	30.0	47.4–55.3	62.3 ± 0.8 mL/g VS	[88]

Table 4 Comparison of biohydrogen production by microalgae and cyanobacteria

Microalgae/cyanobacteria	Production conditions	pH	T (°C)	Light (W/m ²)	H ₂ yield	[Ref.]
<i>C. reinhardtii</i> cbn 1–48 (spectral selective activation of PSI)	Tris-acetate-phosphate medium, 5% CO ₂ , dark anaerobic adaptation	7.2	25.0 ± 2	426.6	40.2 mL/kg DCW	[92]
<i>C. reinhardtii</i> Dang 137 ⁺ (magnesium deprived)	TAP medium	7.7	25.0	34.1	6.0 mmol/L	[93]
<i>Chlorella</i> sp. IOAC707S (phosphorous deprived)	TAP-seawater medium	7.2	28.0	10.7	38.0 mL/L	[94]
<i>Lyngbya</i> sp. (benzoate as a carbon source)	Basal medium, 600 mg/l benzoate at late exponential phase	7.4	32.0	31.6	17.1 μmol H ₂ /g Chl a/h	[95]
<i>Nostoc</i> PCC 7120 Δ <i>hupW</i>	BG110 medium, supplied with a mixture of red and white light, altering 100% Ar and Ar/N ₂ (20/80)	8.0	30.0	18.8	6.2 mL/L/h	[22]
<i>C. reinhardtii</i> (CC124)	Sulphur-free TAP medium	7.7	-	64.0	1.3 ± 0.1 mL/L/h	[96]
<i>C. reinhardtii</i> CC-425 strain (phosphorus and sulphur deprived)	TAP medium, TAP-sulphur	-	-	121.6	0.8 μmol/mg Chl /h	[97]

temperature variation clearly shows that the optimum operating temperature range of photofermentation lies between 28 and 32 °C. Further, the highest H₂ yield with photofermentation can be seen with a neutral pH value (around 7) in most of the cases [89]. Moreover, the light intensity and HRT play a very important role in the H₂ yield in photofermentation. Because of the slow metabolic activity of PNSB in photofermentation, usually longer HRT can be seen compared with dark fermentation [33]. Moreover, light source plays a very important role in the growth of microorganisms as well as the H₂ yield in photofermentation, which can be easily seen in Table 3.

3.2 Biophotolysis

Biophotolysis or water-splitting photosynthesis is the process in which by using oxygenic photosynthetic microorganisms like cyanobacteria and green microalgae, H₂ can be produced with only sunlight and water. For this process, FeFe-hydrogenase is needed for the green microalgae application and heterocystous cyanobacteria nitrogenase finds its use [13]. Biophotolysis H₂ production can be divided into two ways: (a) direct biophotolysis and (b) indirect biophotolysis.

3.2.1 Direct biophotolysis

In the direct biophotolysis, photosynthetic microorganisms like green algae and cyanobacteria absorb 400–700 nm solar radiation for their cell growth [90]. After accepting solar radiation, the microorganisms can evolve hydrogen through nitrogenase or hydrogenase. In direct biophotolysis, water splitting occurs with a light energy of 680 nm wavelength to produce protons, electrons and oxygen as shown in Eq. 9. The

electrons derived from Eq. 9 are transferred through PS II and PS I to a potentially sufficient amount for ferredoxin (Fd) reduction. The reduced Fd then is used for the reduction of hydrogenase enzyme NADP⁺ to NADPH, which is responsible for the production of H₂, as shown in Eq. 10 [13].

3.2.2 Indirect biophotolysis

Indirect biophotolysis involves a two-step photosynthetic conversion of light energy to carbohydrates as a form of chemical energy. As shown in Eq. 11, in the first step, using light energy O₂ and carbohydrate (starch and glycogen in green algae and cyanobacteria, respectively) are produced [91]. By limiting N₂ during Eq. 10, an increase in carbohydrate yield and reduction in O₂ amount can be achieved, which subsequently is advantageous for high H₂ yield. The second step involves the conversion of carbohydrate to CO₂ and H₂ with light energy under an anaerobic condition with less O₂, as shown in Eq. 12 and Eq. 13. [73].

Many recent research studies can be found producing biohydrogen from green algae and cyanobacteria as shown in Table 4. Kossalbayev et al. [98] studied the biohydrogen yield using four different cyanobacteria strains: (a) *Desertifilum* sp. IPPAS B-1220, (b) *Synechocystis* sp. PCC 6803, (c) *Phormidium corium* B-26 and (d) *Synechococcus*

Fig. 4 Schematic diagram of two-chamber and single-chamber MEC (microbial electrolysis cells)

sp. I12. Within 120 dark hours, *Synechocystis* sp. PCC 6803 was seen to have a high H_2 accumulation of $0.037 \mu\text{mol } H_2/\text{mg Chl/h}$. Again, at 166 h of light incubation, *Desertifilum* sp. IPPAS B-1220 was seen to produce $0.229 \mu\text{mol } H_2/\text{mg Chl/h}$. Hoshino et al. [92] investigated the H_2 and O_2 yield through the implementation of PS I light in *Chlamydomonas reinhardtii* mutant strains. In a continuous 18 h PS I light supply, H_2 production was seen at $220 \text{ dm}^3/\text{kg}$ and $176 \text{ dm}^3/\text{kg}$ for cbn 1–48 (a mutant with a chlorophyll-b deficiency) and VHL^R-S4 (a mutant with high light tolerance), respectively. The highest H_2 production of $366 \text{ dm}^3/\text{kg}$ was seen in cbn 1–48 under 1.5 h light and dark iteration with PS I-light. Esquivel et al. [99] also studied the H_2 yield with biophotolysis by *Chlamydomonas reinhardtii* wild and mutant strains. Kosourov et al. [100] found a maximum of $9.4 \mu\text{mol}/\text{mg}$ chlorophyll/h H_2 yield with a 7.7 pH by using *C. reinhardtii*. Huesemann et al. [101] studied H_2 production using *Plectonema boryanum* (nonheterocystous nitrogen-fixing cyanobacterium) under continuous illumination, where the maximum H_2 production rate was found as $0.18 \text{ mL}/\text{mg day}$ with a 1 mM initial nitrate concentration under $100 \mu\text{mol}/\text{m}^2$ light intensity.

3.3 Bioelectrochemical system

Bioelectrochemical system of H_2 production from a wide variety of substrates using microbial electrolysis cells (MEC) is a new technology getting popularity in recent years. MEC technology is also known as biocatalysed electrolysis cells or electrofermentation [13]. As shown in Fig. 4, the MEC system has two electrodes, cathode and anode, which can either be placed in the same single chamber (single-chamber MEC) or be separately placed in two individual chambers (two-chamber MEC). In the two-chamber MEC, to separate the two

chambers, commonly a proton exchange membrane is used. Other recently developed membranes include a charge-mosaic membrane, cation/anion exchange membrane and bipolar membrane [102]. In the two-chamber MEC, the anode chamber is filled with the organic wastewater, while the cathode chamber can be filled with different solutions (like moderate acidified water, phosphate-buffered solution, bicarbonate buffers and salt solutions) [103, 104]. The main working process in both the MEC types is the same. Electrons get generated by the oxidation of organic matter in the anode, which are transported to the anode. Then, they are transported to the cathode where upon combining with protons, H_2 gets generated [33].

The initial MEC systems comprised of two chambers avoiding interference of electrodes, which produced high-purity H_2 [105]. MEC acts as an anaerobic system sensitive to oxygen. Equations 14–16 show the production of H_2 using MEC for acetate. In addition to a potential generated by microorganisms (-0.300 V), MEC needs a small external potential of more than 0.110 V for the production of H_2 [106]. The external power source use of the battery is generally considered, but the use of renewable power generated from solar, wind, MFCs and waste heat can be seen [19, 107].

Many different substrates were found in use for MEC to produce H_2 . Some common pure chemical substrates used are butyrate, glucose, acetate and glycol. However, different waste streams like poultry farming wastewater [108, 109], domestic wastewater [105, 110, 111], waste activated sludge [112–114] and industrial wastewater [115, 116] are used in

Table 5 A comparison study of working parameters of MEC

Type of waste	Type of MEC reactor	Temperature (°C)	pH	External voltage (V)	H ₂ yield (L/L/d)	[Ref.]
Domestic wastewater	6 two-chamber cassettes (Pilot-scale) MEC	13.5 ± 1.2–21.0 ± 1.2	7.0 ± 0.4 (influent), 6.7 ± 0.2 (effluent)	1.1	0.02 L/L/d	[105]
Swine manure wastewater	Two-chamber MEC	25.0 ± 2	7.0	1.2	5.1*	[108]
Waste activated sludge	Single-chamber MEC	20.0	7.0 ± 0.2	0.6	90.6**	[113]
Effluent from DF sugar beet juice wastewater	Two-chamber MEC	25.0	7.2	0.4	306.0***	[115]
Food processing wastewater (FP)	Single-chamber MEC	30.0	7.3	0.7	0.4	[116]
Chemical industrial wastewater (IN)			6.4		0.6	
Cornstalk wastewater	Two-chamber MEC	25.0 ± 2	7.0	1.0	3.9****	[119]

*mmol/g COD; **mL/g VSS; ***mL/g COD; ****mL/L/d

MEC. Tenca et al. [116] found a higher H₂ yield for methanol-rich industrial wastewater compared with food processing wastewater, but the food processing wastewater was found to have high H₂ selectivity of around 86% compared with that of industrial chemical wastewater. Improvement in the H₂ yield can be seen in many studies with MEC coupled with anaerobic digestion and/or dark fermentation [114, 115, 117, 118]. Huang et al. [117] studied the H₂ production from food waste from anaerobic digestion coupled with the single-chamber MEC. They found 511.02 mL H₂/g VS of the H₂ yield from the continuous AD-MEC process which was much higher than the AD H₂ yield (49.39 mL H₂/g VS). Dhar et al. [115] studied the H₂ yield from sugar beet juice using an integrated MEC dark fermentation process. Overall H₂ yield with the integrated process was found to be 25% of initial chemical oxygen demand (COD) (6 mol H₂/mol hexose_{added}) which is much higher than that of dark fermentation alone (13% of initial COD). Li et al. [118] also found a maximum H₂ yield of 387.1 mL H₂/g corn stalk with the integrated dark fermentation MEC process, which was around thrice that from dark fermentation alone with 20 g/L of corn stalk input and 7.0 initial pH value. Lu et al. [114] also found twice H₂ yield with waste activated sludge coupled with MEC (Table 5).

Raw materials, temperature, pH and operating voltage play an important role in determining the H₂ yield in MEC. However, with MEC, it has been noticed that operating temperatures from 0 can be used in producing biohydrogen from wastewater without having significant effects on the yield. An H₂ yield of 0.015 L/L/d was found with domestic wastewater within an operating temperature range of 13 to 21 °C [105]. Heidrich et al. [120] found improvement in exoelectrogen activities with temperature while studying MEC with domestic wastewater within 1–22 °C. Patil et al. [121] also demonstrated operating MEC with wastewater within 0 to 45 °C. Better performance was seen within 10 °C to 20 °C, thereby showing the advantages of MEC over other fermentative

biohydrogen production processes. Again, an increasing H₂ yield with increasing external applied voltage was reported in the literature [108, 113].

In MEC, certain microorganisms which are capable of transferring electrons from the chamber to anode are used, known as electrogens. *Shewanella* spp. and *Geobacter* spp. are two popular electrogenic groups, out of which *Shewanella oneidensis* and *Geobacter sulfurreducens* are the most discussed species [122]. *Acetobacterium woodii*, *Ochrobactrum anthropic*, *Sphingomonas strain DJ*, *Rhodopseudomonas palustris* and *Rhodospirillum rubrum* are some other exoelectrogenic species reported in recent studies [33, 122–124]. Rago et al. [125] found a high H₂ yield (2.6 L H₂/L_{REACTOR}/d) with alkaline MEC, using *Alkalibacter* sp. as exoelectrogen.

4 Biohydrogen production through gasification

Gasification of biowaste is another way of producing bio-H₂. In gasification, syngas (a mixture of CO, CO₂, H₂ and CH₄) and several by-products (tar, char, light HCs) are produced by partial oxidation of organic materials at high temperature and pressure [126]. Even though gasification is not a biological process, it is effective for organic waste conversion to hydrogen. The concentration of H₂ produced during gasification can be improved by optimisation of operating parameters. Equations 17–23 show the main reactions involved during gasification.

Gasification of different types of waste materials like sewage sludge, municipal solid waste, agricultural and forest biomass, animal manure and food waste has been seen as a popular technology to produce hydrogen [33]. Prasertcharoensuk et al. [127] studied the effect of parameters on hydrogen production through lignocellulosic biomass waste gasification. H_2 content in the syngas was found increasing up to 67 mol% with pyrolysis temperature higher than 800 °C and 0.5–1 cm³ particle size. Su et al. [128] studied the effects of temperature (400–450 °C), food additive (NaHCO_3 , NaCl and NaOH) and reaction time (20–60 min) on the supercritical water gasification of food waste. They found a maximum H_2 yield of 12.73 mol/kg with NaOH as a catalytic agent. Zhang et al. [129] found 28.9% H_2 content from food waste with an anaerobic digestion and gasification integrated process. Chang et al. [130] found a maximum of 29.72 g H_2 /kg substrate and 19.78 g H_2 /kg substrate H_2 yield with bagasse gasification and waste mushroom gasification, respectively. Shie et al. [131] studied plasma gasification of lignocellulosic municipal solid waste for H_2 production. The effect of different factors like biomass type, reaction temperature, feed size, catalyst type and SB (steam-to-biomass) ratio on the H_2 production in a steam gasification process is discussed by Parthasarathy and Narayanan [132]. Nanda et al. [133] studied supercritical water gasification of different agro-food residues and fruit wastes like a banana peel, *Aloe vera* rind, lemon peel, coconut shell, sugarcane bagasse, pineapple peel and orange peel. During the production of biodiesel, glycerol is produced in large quantities as a by-product. Recently, Osman et al. used glycerol along with the alumina foil waste using photocatalysis to produce a steady state of 4.2 millimole H_2 g/ TiO_2 hr., which is a promising result of multifunctional cheap photocatalytic materials for the production of green biohydrogen [134].

5 Challenges with biohydrogen production through biological methods

Several studies have been made so far for enhancing the economic feasibility of the H_2 production process via biological methods. Although these processes have different advantages, there are many key challenges also which need to be addressed in future studies [4, 13, 33]. Table 6 describes the different advantages and challenges associated with these processes. As shown in Table 6, the biohydrogen production processes vary from process to process. The maximum yield of H_2 production was found

Table 6 Advantages and challenges with biohydrogen production with biological methods

H_2 production processes	Advantages	Challenges
Dark fermentation	<ul style="list-style-type: none"> > The utilisation of a diverse, wide variety of different wastes. > H_2 production rate is high. > Reactor configuration is simple. 	<ul style="list-style-type: none"> > Separation of H_2 needed from $\text{CO}_2 + \text{H}_2$ mixture after production. > BOD level in the effluent is high. > Pre-treatment is necessary for lignocellulosic waste.
Photofermentation	<ul style="list-style-type: none"> > High COD removal rate. > High H_2 yield. 	<ul style="list-style-type: none"> > An external source of light is required > H_2 production rate is low. > The need for low light conversion efficiency. > Not suitable for other wastes except VFA-rich waste.
Biophotolysis	<ul style="list-style-type: none"> > Use of renewable energy. > High light H_2 conversion efficiency (microalgae with FeFe hydrogenase). 	<ul style="list-style-type: none"> > A customized photobioreactor is required. > H_2 yield is low > External light source is required.
MEC	<ul style="list-style-type: none"> > H_2 yield is high. > High COD removal rate. > Suitable working under room temperature. 	<ul style="list-style-type: none"> > H_2 production rate is low. > The need for external voltage. > A catalyst is needed for the electrode.

to be 14.2 ± 0.2 mL/g VSS, and H_2 production rate was 0.13 mL/g VSS h [135]. It was found that for photofermentation, the maximum H_2 yield was 642 ± 22 mL, and the maximum H_2 production rate 77.78 mL/L/h, with an initial pH of 7 [136]. In another case, the effect of adding corn stalk enzymatic hydrolysate H_2 yield was found to increase up to 1287.06 mL H_2 /g TOC, and the maximum H_2 production rate was found to be 10.23 mL/h [137]. Kossalbayev et al. [98] found a maximum H_2 yield of 0.348 $\mu\text{mol H}_2/\text{mg Chl/h}$ with *Desertifilum* sp. IPPAS B-1220. Moreover, energy conversion efficiency with biophotolysis was found to be around 2.4–4% [22]. Jayabalan et al. [138] found a maximum H_2 production rate of 4.38 ± 0.11 mmol/L/D from the sugar industry wastewater using MEC. A H_2 production rate of 3.48 L/L/d and an H_2 yield of 511.02 mL H_2 g⁻¹ VS was reported from food waste anaerobic digestion coupled with MEC [117].

Water electrolysis is another way of producing hydrogen from water using electricity. To produce 1 kg H_2 , around 9 L

of water is needed and 8 kg of O_2 occurs as a by-product in this process. The hydrogen produced with water electrolysis has a purity of 99.99 vol% (strongly depending on the type of electrolysis (AEL, PEM, etc.)) [139]. Yuzer et al. [140] found a maximum hydrogen production rate of 11.4 mmol/h with the use of a bipolar membrane. They found the highest energy efficiency of 82% and an exergy efficiency of 68% with the anion exchange membrane. Chakik et al. [141] found a maximum efficiency of 99.13% with a production rate of 2.34 mL/min using a $Zn_{95}\%Cr_5\%$ electrode in 20 g/L NaOH solution at 0.45 A, 5 V. Kovač et al. [142] studied H_2 production with a rate of 1.138 g/h from the electrolysis of alkaline water using solar energy.

Bio- H_2 production through the biological methods, for instance, dark fermentation, can produce H_2 without light along with in photofermentation, and photosynthetic bacteria can use a wide range of spectral energy. However, the energy conversion efficiency, in general, is low with 4.3 and 5.11% for dark and photofermentation processes, respectively [21]. The major challenges herein are the low bio- H_2 production rate and yield and the high cost of the raw feedstocks; thus, using organic waste materials helps to address this issue.

Overall, hydrogen can be produced from various sources, with potential supply from renewable electricity, nuclear power and lignocellulosic biomass. However, it is currently dominated by using fossil-based fuels. From biomass sources, H_2 production comes mainly from anaerobic digestion, fermentation or gasification routes. While the former route is mature, it only processes specific feedstocks (food waste, sewage sludge and crops waste). While fermentation can utilise and process the non-edible cellulosic part of lignocellulosic biomass, gasification can process the whole portion of the biomass, but the technology is still not fully mature worldwide. H_2 production mostly comes from natural gas and coal, while during its production globally, a greenhouse gas in the form of CO_2 is released which is equivalent to the combined generated annual CO_2 emissions of the UK and Indonesia with an energy consumption of 275 million tonnes of oil equivalent (2% of total worldwide energy demand) [10]. Thus, carbon capture and storage (CCS) is crucial when producing H_2 from fossil-based fuels along with maximising our way of producing H_2 from clean electricity. Currently, the International Energy Agency (IEA) reported that the technical potential of producing hydrogen from renewable electricity is expensive. However, it is expected to decrease by 30% by 2030 due to the scaling up of H_2 production along with progress in renewables technology that comes with a reduction in the costing. Three major technologies could benefit from that: electrolyzers (splitting water using electricity to produce H_2), fuel cells and refuelling equipment. With the progress in solar photovoltaic and wind renewable energy technologies along with batteries, renewable electricity could provide both low-

carbon electricity and low-carbon H_2 , as well as using electrolysis, which accounts for only 2% of the global hydrogen production now. Economically, H_2 production from natural gas is the cheapest method in most of the countries around the world, such as in the Middle East which costs (1\$/kg H_2). On the other hand, electrolysis cost is 10–40\$/MWh along with full load hours of 3000–6000, so it can compete with natural gas coupled with CCSU (carbon capture storage and utilisation). Interestingly, countries that import natural gas and have available sources of renewables or nuclear power could easily find electrolysis as an attractive option. However, the production of H_2 -based fuel using hydrogen as a feedstock is not economically feasible at the moment.

Overall, electrolysis is a promising route where the efficiency of the electrolyser ranges from 60 to 80%, while for other green hydrogen routes such as dark fermentation, photofermentation, biophotolysis and microbial electrolysis cells, their energy conversion efficiencies are low which are 4.3, 5.11, 4.0 and 11.3%, respectively [21–23]. This is as a result of the complex structure of the biomass that requires complicated processing procedures during the production of green bio- H_2 . Also, finding the cheap feedstock of biomass is crucial herein. For instance, to meet the theoretical H_2 production demand in the USA, which is 60 Mt H_2 , this would require nearly 100% of its biomass resources. However, by employing PV or wind power, only 1% or 6% will be required [143]. The factors that affect the costing of H_2 production from electrolysis are the cost for the electricity, capital expenditure requirements, conversion efficiency and annual operating hours.

6 Conclusion

For the future of the zero-carbon economy, biohydrogen is considered a promising candidate for fossil fuel replacement due to its zero-carbon emission. This review study provides a brief critical technological discussion and analysis of the processes that are used in biohydrogen production from organic biowastes along with the factors responsible for the efficient H_2 yield. Herein, raw materials, processing and production techniques and environmental influences of biohydrogen production have been reviewed. Wide varieties of biowaste materials, such as wastewaters, forest and agricultural residues, food wastes and municipal and sewage wastes, have been utilised in biohydrogen production. Regarding the high H_2 yield and feedstock availability, dark fermentation, photofermentation and gasification showed clear promising results. The combined fermentation processes also have shown promising results in different studies. Pre-treatment of the substrate, pH, temperature and hydraulic retention time (HRT) are crucial factors in regulating the optimum biohydrogen production route. The MEC method showed promising results with a good yield of biohydrogen using

waste feedstock under low-temperature conditions. However, a large-scale production with these processes is still challenging. The need for future studies addressing more variants of microorganisms and waste varieties is highly observed. It is the authors' thought that the integration of more than one production process along with different biomass waste streams is required along with modelling to allow better processing for biohydrogen production. This would help alleviate issues concerned with fossil-based fuel, while also promoting environmental benefit as in the production of biohydrogen from sustainable waste materials and consequently working toward the zero-carbon economy.

Acknowledgements The authors would like to acknowledge the support given by the EPSRC project “Advancing Creative Circular Economies for Plastics via Technological-Social Transitions” (ACCEPT Transitions, EP/S025545/1). The authors also wish to acknowledge the support of The Bryden Centre project (Project ID VA5048) which was awarded by The European Union's INTERREG VA Programme. The authors would like to thank Charlie Farrell and Patrick McNicholl who assisted in the proof-reading of the manuscript.

Open Access This article is licensed under a Creative Commons Attribution 4.0 International License, which permits use, sharing, adaptation, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if changes were made. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by/4.0/>.

References

1. Tausz-Posch S, De Kok LJ (2020) Plant functioning in a changing global atmosphere. *Plant Biol* 22:3–4
2. Fawzy S, Osman AI, Doran J, Rooney DW (2020) Strategies for mitigation of climate change: a review. *Environ Chem Lett*
3. Zhang Q, Dai W, Wang X, Li J (2020) Elevated CO₂ concentration affects the defense of tobacco and melon against lepidopteran larvae through the jasmonic acid signaling pathway. *Sci Rep* 10: 4060
4. Mishra P, Krishnan S, Rana S, Singh L, Sakinah M, Ab Wahid Z (2019) Outlook of fermentative hydrogen production techniques: an overview of dark, photo and integrated dark-photo fermentative approach to biomass. *Energy Strategy Reviews* 24:27–37
5. <https://www.co2.earth/monthly-co2>, Accessed on: 5th July, 2020
6. Martins F, Felgueiras C, Smitková M (2018) Fossil fuel energy consumption in European countries. *Energy Procedia* 153:107–111
7. Argun H, Kargi F (2010) Bio-hydrogen production from ground wheat starch by continuous combined fermentation using annular-hybrid bioreactor. *Int J Hydrog Energy* 35:6170–6178
8. Lubitz W, Tumas W (2007) Hydrogen: an Overview. *Chem Rev* 107:3900–3903
9. Christopher K, Dimitrios R (2012) A review on exergy comparison of hydrogen production methods from renewable energy sources. *Energy Environ Sci* 5:6640–6651
10. The future of hydrogen, Report prepared by the IEA for the G20, Japan
11. Schoots K, Ferioli F, Kramer GJ, van der Zwaan BCC (2008) Learning curves for hydrogen production technology: an assessment of observed cost reductions. *Int J Hydrog Energy* 33:2630–2645
12. A.I. Osman, Catalytic hydrogen production from methane partial oxidation: mechanism and kinetic study, *Chemical Engineering & Technology*, n/a
13. Chandrasekhar K, Lee YJ, Lee DW (2015) Biohydrogen production: strategies to improve process efficiency through microbial routes. *Int J Mol Sci* 16:8266–8293
14. Osman AI, Abu-Dahrieh JK, Cherkasov N, Fernandez-Garcia J, Walker D, Walton RI, Rooney DW, Rebrov E (2018) A highly active and synergistic Pt/Mo₂C/Al₂O₃ catalyst for water-gas shift reaction. *Molecular Catalysis* 455:38–47
15. Abdul Kadir K, Wahidah N, Jamaludin S (2016) An overview of organic waste in composting. *MATEC Web of Conferences* 47: 05025
16. Dhanya BS, Mishra A, Chandel AK, Verma ML (2020) Development of sustainable approaches for converting the organic waste to bioenergy. *Sci Total Environ* 723:138109
17. Riis T, Hagen EF, Vie PJS, Ulleberg Ø, Hydrogen production R&D - gaps and priorities - IEA HIA, <https://webstore.iea.org/download/direct/992>, accessed 12-08-2020
18. Dincer I, Acar C (2015) Review and evaluation of hydrogen production methods for better sustainability. *Int J Hydrog Energy* 40: 11094–11111
19. Zhang Y, Angelidaki I (2014) Microbial electrolysis cells turning to be versatile technology: recent advances and future challenges. *Water Res* 56:11–25
20. Lin C-Y, Nguyen TM-L, Chu C-Y, Leu H-J, Lay C-H (2018) Fermentative biohydrogen production and its byproducts: a mini review of current technology developments. *Renew Sust Energy Rev* 82:4215–4220
21. Zhang Z, Li Y, Zhang H, He C, Zhang Q (2017) Potential use and the energy conversion efficiency analysis of fermentation effluents from photo and dark fermentative bio-hydrogen production. *Bioresour Technol* 245:884–889
22. Nyberg M, Heidorn T, Lindblad P (2015) Hydrogen production by the engineered cyanobacterial strain *Nostoc PCC 7120* ΔhupW examined in a flat panel photobioreactor system. *J Biotechnol* 215:35–43
23. Zhang L, Wang Y-Z, Zhao T, Xu T (2019) Hydrogen production from simultaneous saccharification and fermentation of lignocellulosic materials in a dual-chamber microbial electrolysis cell. *Int J Hydrog Energy* 44:30024–30030
24. Detchusanat T, Im-orb K, Ponpesh P, Arpornwicheanop A (2018) Biomass gasification integrated with CO₂ capture processes for high-purity hydrogen production: process performance and energy analysis. *Energy Convers Manag* 171:1560–1572
25. Mitsushima S, Gollas B, Hacker V (2018) Chapter 1 - introduction, in: V. Hacker, S. Mitsushima (Eds.) *Fuel cells and hydrogen*, Elsevier, pp. 1–13
26. Tomasik P, Horton D (2012) Chapter 2 - enzymatic conversions of starch, in: D. Horton (Ed.) *Advances in carbohydrate chemistry and biochemistry*, Academic Press, pp. 59–436
27. Rizwan M, Shah SH, Mujtaba G, Mahmood Q, Rashid N, Shah FA (2019) Chapter 1 - ecofuel feedstocks and their prospect, in: A.K. Azad, M. Rasul (Eds.) *Advanced biofuels*, Woodhead Publishing, pp. 3–16
28. Mona S, Kumar SS, Kumar V, Parveen K, Saini N, Deepak B, Pugazhendhi A (2020) Green technology for sustainable

- biohydrogen production (waste to energy): a review. *Sci Total Environ* 138481
29. Ghimire A, Frunzo L, Pirozzi F, Trably E, Escudie R, Lens PNL, Esposito G (2015) A review on dark fermentative biohydrogen production from organic biomass: process parameters and use of by-products. *Appl Energy* 144:73–95
 30. Hallenbeck PC (2009) Fermentative hydrogen production: principles, progress, and prognosis. *Int J Hydrog Energy* 34:7379–7389
 31. Sarangi PK, Nanda S (2020) Biohydrogen production through dark fermentation. *Chem Eng Technol* 43:601–612
 32. Zhou S, Pu Y, Zhang Q, Shi R, Guo X, Wang W, Ji J, Wei T, Ouyang T (2019) Microstructure and dielectric properties of high entropy Ba (Zr_{0.2}Ti_{0.2}Sn_{0.2}Hf_{0.2}Me_{0.2})O₃ perovskite oxides. *Ceram Int*
 33. Tian H, Li J, Yan M, Tong YW, Wang C-H, Wang X (2019) Organic waste to biohydrogen: a critical review from technological development and environmental impact analysis perspective. *Appl Energy* 256:113961
 34. Alibardi L, Cossu R (2016) Effects of carbohydrate, protein and lipid content of organic waste on hydrogen production and fermentation products. *Waste Manag* 47:69–77
 35. Xing Y, Li Z, Fan Y, Hou H (2010) Biohydrogen production from dairy manures with acidification pretreatment by anaerobic fermentation. *Environ Sci Pollut Res* 17:392–399
 36. Yang G, Wang J (2017) Enhanced hydrogen production from sewage sludge by co-fermentation with forestry wastes. *Energy Fuel* 31:9633–9641
 37. Alemahdi N, Che Man H, Abd Rahman NA, Nasirian N, Yang Y (2015) Enhanced mesophilic bio-hydrogen production of raw rice straw and activated sewage sludge by co-digestion. *Int J Hydrog Energy* 40:16033–16044
 38. Silva FMS, Mahler CF, Oliveira LB, Bassin JP (2018) Hydrogen and methane production in a two-stage anaerobic digestion system by co-digestion of food waste, sewage sludge and glycerol. *Waste Manag* 76:339–349
 39. Laurinavichene T, Tekucheva D, Laurinavichius K, Tsygankov A (2018) Utilization of distillery wastewater for hydrogen production in one-stage and two-stage processes involving photofermentation. *Enzym Microb Technol* 110:1–7
 40. Intanoo P, Chaimongkol P, Chavadej S (2016) Hydrogen and methane production from cassava wastewater using two-stage upflow anaerobic sludge blanket reactors (UASB) with an emphasis on maximum hydrogen production. *Int J Hydrog Energy* 41:6107–6114
 41. Srivastava N, Srivastava M, Kushwaha D, Gupta VK, Manikanta A, Ramteke PW, Mishra PK (2017) Efficient dark fermentative hydrogen production from enzyme hydrolyzed rice straw by *Clostridium pasteurianum* (MTCC116). *Bioresour Technol* 238:552–558
 42. Han W, Ye M, Zhu AJ, Zhao HT, Li YF (2015) Batch dark fermentation through enzymatic hydrolyzed food waste for hydrogen production. *Bioresour Technol* 191:24–29
 43. Kim S, Choi K, Kim JO, Chung J (2013) Biological hydrogen production by anaerobic digestion of food waste and sewage sludge treated using various pretreatment technologies. *Biodegradation* 24:753–764
 44. Silva FMS, Oliveira LB, Mahler CF, Bassin JP (2017) Hydrogen production through anaerobic co-digestion of food waste and crude glycerol at mesophilic conditions. *Int J Hydrog Energy* 42:22720–22729
 45. Rai PK, Singh SP, Asthana RK, Singh S (2014) Biohydrogen production from sugarcane bagasse by integrating dark- and photo-fermentation. *Bioresour Technol* 152:140–146
 46. Estevam A, Arantes MK, Andrigheto C, Fiorini A, da Silva EA, Alves HJ (2018) Production of biohydrogen from brewery wastewater using *Klebsiella pneumoniae* isolated from the environment. *Int J Hydrog Energy* 43:4276–4283
 47. Okonkwo O, Papirio S, Trably E, Escudie R, Lakaniemi A-M, Esposito G (2020) Enhancing thermophilic dark fermentative hydrogen production at high glucose concentrations via bioaugmentation with *Thermotoga neapolitana*. *Int J Hydrog Energy* 45:17241–17249
 48. Soto LR, Byrne E, van Niel EWJ, Sayed M, Villanueva CC, Hatti-Kaul R (2019) Hydrogen and polyhydroxybutyrate production from wheat straw hydrolysate using *Caldicellulosiruptor* species and *Ralstonia eutropha* in a coupled process. *Bioresour Technol* 272:259–266
 49. Łukajtis R, Hołowacz I, Kucharska K, Glinka M, Rybarczyk P, Przyjazny A, Kamiński M (2018) Hydrogen production from biomass using dark fermentation. *Renew Sust Energ Rev* 91:665–694
 50. Eskicioglu C, Monlau F, Barakat A, Ferrer I, Kaparaju P, Trably E, Carrère H (2017) Assessment of hydrothermal pretreatment of various lignocellulosic biomass with CO₂ catalyst for enhanced methane and hydrogen production. *Water Res* 120:32–42
 51. Yin Y, Wang J (2015) Biohydrogen production using waste activated sludge disintegrated by gamma irradiation. *Appl Energy* 155:434–439
 52. Leão EP, Babel S (2012) The influence of enzyme and surfactant on biohydrogen production and electricity generation using palm oil mill effluent. *J Clean Prod* 31:91–99
 53. Guo P, Mochizuki K, Cheng W, Zhou M, Gao H, Zheng D, Wang X, Cui Z (2011) Effects of different pretreatment strategies on corn stalk acidogenic fermentation using a microbial consortium. *Bioresour Technol* 102:7526–7531
 54. Gonzales RR, Kim S-H (2017) Dark fermentative hydrogen production following the sequential dilute acid pretreatment and enzymatic saccharification of rice husk. *Int J Hydrog Energy* 42:27577–27583
 55. Cao G-L, Guo W-Q, Wang A-J, Zhao L, Xu C-J, Zhao Q-I, Ren N-Q (2012) Enhanced cellulosic hydrogen production from lime-treated cornstalk wastes using thermophilic anaerobic microflora. *Int J Hydrog Energy* 37:13161–13166
 56. Song W, Ding L, Liu M, Cheng J, Zhou J, Li Y-Y (2020) Improving biohydrogen production through dark fermentation of steam-heated acid pretreated *Alternanthera philoxeroides* by mutant *Enterobacter aerogenes* ZJU1. *Sci Total Environ* 716:134695
 57. Shao W, Wang Q, Rupani PF, Krishnan S, Ahmad F, Rezaia S, Rashid MA, Sha C, Md Din MF (2020) Biohydrogen production via thermophilic fermentation: a prospective application of *Thermotoga* species. *Energy* 197:117199
 58. Li C, Fang HHP (2007) Fermentative hydrogen production from wastewater and solid wastes by mixed cultures. *Crit Rev Environ Sci Technol* 37:1–39
 59. Azbar N, Dokgöz FT, Keskin T, Eltem R, Korkmaz KS, Gezgin Y, Akbal Z, Öncel S, Dalay MC, Gönen Ç, Tutuk F (2009) Comparative evaluation of bio-hydrogen production from cheese whey wastewater under thermophilic and mesophilic anaerobic conditions. *Int J Green Energy* 6:192–200
 60. Guo XM, Trably E, Latrille E, Carrère H, Steyer J-P (2010) Hydrogen production from agricultural waste by dark fermentation: a review. *Int J Hydrog Energy* 35:10660–10673
 61. Rafieenia R, Lavagnolo MC, Pivato A (2018) Pre-treatment technologies for dark fermentative hydrogen production: current advances and future directions. *Waste Manag* 71:734–748
 62. Mamimin C, Singkhala A, Kongjan P, Suraraksa B, Prasertsan P, Imai T, O-Thong S (2015) Two-stage thermophilic fermentation and mesophilic methanogen process for biohythane production from palm oil mill effluent. *Int J Hydrog Energy* 40:6319–6328
 63. Kumar G, Zhen G, Sivagurunathan P, Bakonyi P, Nemestóth N, Béla-Bakó K, Kobayashi T, Xu KQ (2016) Biogenic H₂ production from mixed microalgae biomass: impact of pH control and methanogenic inhibitor (BESA) addition. *Biofuel Res J* 11:470–474

64. Chandrasekhar K, Venkata Mohan S (2014) Bio-electrohydrolysis as a pretreatment strategy to catabolize complex food waste in closed circuitry: function of electron flux to enhance acidogenic biohydrogen production. *Int J Hydrog Energy* 39:11411–11422
65. Tsygankov DNTAA (2011) Integration of biological H₂ producing processes, State of the art and progress in production of bio hydrogen, Bentham Science Publishers Ltd, USA; Chapter 5:pp. 78–93
66. Santiago SG, Morgan-Sagastume JM, Monroy O, Moreno-Andrade I (2019) Biohydrogen production from organic solid waste in a sequencing batch reactor: an optimization of the hydraulic and solids retention time. *Int J Hydrog Energy*
67. Lu C, Wang Y, Lee D-J, Zhang Q, Zhang H, Tahir N, Jing Y, Liu H, Zhang K (2019) Biohydrogen production in pilot-scale fermenter: effects of hydraulic retention time and substrate concentration. *J Clean Prod* 229:751–760
68. Colombo B, Villegas Calvo M, Pepè Sciarria T, Scaglia B, Savio Kizito S, D'Imporzano G, Adani F (2019) Biohydrogen and polyhydroxyalkanoates (PHA) as products of a two-steps bioprocess from deproteinized dairy wastes. *Waste Manag* 95:22–31
69. Monroy I, Buitrón G (2020) Production of polyhydroxybutyrate by pure and mixed cultures of purple non-sulfur bacteria: a review. *J Biotechnol* 317:39–47
70. Das D (2009) Advances in biohydrogen production processes: an approach towards commercialization. *Int J Hydrog Energy* 34: 7349–7357
71. Ni M, Leung DY, Leung MKH, Sumathy K (2006) An overview of hydrogen production from biomass. *Fuel Process Technol* 87: 461–472
72. Cai J, Zhao Y, Fan J, Li F, Feng C, Guan Y, Wang R, Tang N (2019) Photosynthetic bacteria improved hydrogen yield of combined dark- and photo-fermentation. *J Biotechnol* 302:18–25
73. Azwar MY, Hussain MA, Abdul-Wahab AK (2014) Development of biohydrogen production by photobiological, fermentation and electrochemical processes: a review. *Renew Sust Energy Rev* 31:158–173
74. Mirza SS, Qazi JI, Liang Y, Chen S (2019) Growth characteristics and photofermentative biohydrogen production potential of purple non sulfur bacteria from sugar cane bagasse. *Fuel* 255:115805
75. García-Sánchez R, Ramos-Ibarra R, Guatemala-Morales G, Arriola-Guevara E, Toriz-González G, Corona-González RI (2018) Photofermentation of tequila vinasses by *Rhodospseudomonas pseudopalustris* to produce hydrogen. *Int J Hydrog Energy* 43:15857–15869
76. Machado RG, Moreira FS, Batista FRX, Ferreira JS, Cardoso VL (2018) Repeated batch cycles as an alternative for hydrogen production by co-culture photofermentation. *Energy* 153:861–869
77. Keskin T, Hallenbeck PC (2012) Hydrogen production from sugar industry wastes using single-stage photofermentation. *Bioresour Technol* 112:131–136
78. Lu C, Zhang Z, Ge X, Wang Y, Zhou X, You X, Liu H, Zhang Q (2016) Bio-hydrogen production from apple waste by photosynthetic bacteria HAU-M1. *Int J Hydrog Energy* 41:13399–13407
79. Mishra P, Thakur S, Singh L, Ab Wahid Z, Sakinah M (2016) Enhanced hydrogen production from palm oil mill effluent using two stage sequential dark and photo fermentation. *Int J Hydrog Energy* 41:18431–18440
80. Zhang Q, Zhang Z, Wang Y, Lee D-J, Li G, Zhou X, Jiang D, Xu B, Lu C, Li Y, Ge X (2018) Sequential dark and photo fermentation hydrogen production from hydrolyzed corn stover: a pilot test using 11 m³ reactor. *Bioresour Technol* 253:382–386
81. Sagir E, Ozgur E, Gunduz U, Eroglu I, Yucel M (2017) Single-stage photofermentative biohydrogen production from sugar beet molasses by different purple non-sulfur bacteria. *Bioprocess Biosyst Eng* 40:1589–1601
82. Jiang D, Ge X, Zhang T, Liu H, Zhang Q (2016) Photo-fermentative hydrogen production from enzymatic hydrolysate of corn stalk pith with a photosynthetic consortium. *Int J Hydrog Energy* 41:16778–16785
83. Xia A, Cheng J, Ding L, Lin R, Song W, Zhou J, Cen K (2014) Enhancement of energy production efficiency from mixed biomass of *Chlorella pyrenoidosa* and cassava starch through combined hydrogen fermentation and methanogenesis. *Appl Energy* 120:23–30
84. Hitit ZY, Lazaro CZ, Hallenbeck PC (2017) Single stage hydrogen production from cellulose through photo-fermentation by a co-culture of *Cellulomonas fimi* and *Rhodospseudomonas palustris*. *Int J Hydrog Energy* 42:6556–6566
85. Al-Mohammedawi HH, Znad H, Eroglu E (2019) Improvement of photofermentative biohydrogen production using pre-treated brewery wastewater with banana peels waste. *Int J Hydrog Energy* 44:2560–2568
86. Jiang D, Ge X, Lin L, Zhang T, Liu H, Hu J, Zhang Q (2020) Continuous photo-fermentative hydrogen production in a tubular photobioreactor using corn stalk pith hydrolysate with a consortium. *Int J Hydrog Energy* 45:3776–3784
87. Mıynat ME, Ören İ, Özkan E, Argun H (2020) Sequential dark and photo-fermentative hydrogen gas production from agar embedded molasses. *Int J Hydrog Energy*
88. Zhu S, Zhang Z, Li Y, Tahir N, Liu H, Zhang Q (2018) Analysis of shaking effect on photo-fermentative hydrogen production under different concentrations of corn stover powder. *Int J Hydrog Energy* 43:20465–20473
89. Ghosh S, Dairkee UK, Chowdhury R, Bhattacharya P (2017) Hydrogen from food processing wastes via photofermentation using purple non-sulfur bacteria (PNSB) – a review. *Energy Convers Manag* 141:299–314
90. Nagakawa H, Takeuchi A, Takekuma Y, Noji T, Kawakami K, Kamiya N, Nango M, Furukawa R, Nagata M (2019) Efficient hydrogen production using photosystem I enhanced by artificial light harvesting dye. *Photochem Photobiol Sci* 18:309–313
91. Fakhimi N, Tavakoli O (2019) Improving hydrogen production using co-cultivation of bacteria with *Chlamydomonas reinhardtii* microalga. *Mater Sci Energy Technol* 2:1–7
92. Hoshino T, Johnson DJ, Scholz M, Cuello JL (2013) Effects of implementing PSI-light on hydrogen production via biophotolysis in *Chlamydomonas reinhardtii* mutant strains. *Biomass Bioenergy* 59:243–252
93. Volgusheva A, Kukarsikh G, Krendeleva T, Rubin A, Mamedov F (2015) Hydrogen photoproduction in green algae *Chlamydomonas reinhardtii* under magnesium deprivation. *RSC Adv* 5:5633–5637
94. Batyrova K, Gavrishcheva A, Ivanova E, Liu J, Tsygankov A (2015) Sustainable hydrogen photoproduction by phosphorus-deprived marine green microalgae *Chlorella* sp. *Int J Mol Sci* 16:2705–2716
95. Shi X-Y, Yu H-Q (2016) Simultaneous metabolism of benzoate and photobiological hydrogen production by *Lyngbya* sp. *Renew Energy* 95:474–477
96. Oncel S, Kose A (2014) Comparison of tubular and panel type photobioreactors for biohydrogen production utilizing *Chlamydomonas reinhardtii* considering mixing time and light intensity. *Bioresour Technol* 151:265–270
97. Kosourov SN, Ghirardi ML, Seibert M (2011) A truncated antenna mutant of *Chlamydomonas reinhardtii* can produce more hydrogen than the parental strain. *Int J Hydrog Energy* 36:2044–2048
98. Kossalbayev BD, Tomo T, Zayadan BK, Sadvakasova AK, Bolatkhan K, Alwasel S, Allakhverdiev SI (2020) Determination of the potential of cyanobacterial strains for hydrogen production. *Int J Hydrog Energy* 45:2627–2639
99. Esquivel MG, Amaro HM, Pinto TS, Fevereço PS, Malcata FX (2011) Efficient H₂ production via *Chlamydomonas reinhardtii*. *Trends Biotechnol* 29:595–600
100. Kosourov S, Seibert M, Ghirardi ML (2003) Effects of extracellular pH on the metabolic pathways in sulfur-deprived, H₂-

- producing *Chlamydomonas reinhardtii* cultures. *Plant Cell Physiol* 44:146–155
101. Huesemann MH, Hausmann TS, Carter BM, Gerschler JJ, Benemann JR (2010) Hydrogen generation through indirect biophotolysis in batch cultures of the nonheterocystous nitrogen-fixing cyanobacterium *Plectonema boryanum*. *Appl Biochem Biotechnol* 162:208–220
 102. Kadier A, Simayi Y, Abdesahian P, Azman NF, Chandrasekhar K, Kalil MS (2016) A comprehensive review of microbial electrolysis cells (MEC) reactor designs and configurations for sustainable hydrogen gas production. *Alex Eng J* 55:427–443
 103. Yossan S, Xiao L, Prasertsan P, He Z (2013) Hydrogen production in microbial electrolysis cells: choice of catholyte. *Int J Hydrog Energy* 38:9619–9624
 104. Luo S, Jain A, Aguilera A, He Z (2017) Effective control of biolythane composition through operational strategies in an innovative microbial electrolysis cell. *Appl Energy* 206:879–886
 105. Heidrich ES, Dolfing J, Scott K, Edwards SR, Jones C, Curtis TP (2013) Production of hydrogen from domestic wastewater in a pilot-scale microbial electrolysis cell. *Appl Microbiol Biotechnol* 97:6979–6989
 106. Cheng S, Logan BE (2007) Sustainable and efficient biohydrogen production via electrohydrogenesis. *Proc Natl Acad Sci* 104:18871–18873
 107. Wang A, Sun D, Cao G, Wang H, Ren N, Wu W-M, Logan BE (2011) Integrated hydrogen production process from cellulose by combining dark fermentation, microbial fuel cells, and a microbial electrolysis cell. *Bioresour Technol* 102:4137–4143
 108. Shen R, Jiang Y, Ge Z, Lu J, Zhang Y, Liu Z, Ren ZJ (2018) Microbial electrolysis treatment of post-hydrothermal liquefaction wastewater with hydrogen generation. *Appl Energy* 212:509–515
 109. Wagner RC, Regan JM, Oh S-E, Zuo Y, Logan BE (2009) Hydrogen and methane production from swine wastewater using microbial electrolysis cells. *Water Res* 43:1480–1488
 110. Escapa A, Gil-Carrera L, García V, Morán A (2012) Performance of a continuous flow microbial electrolysis cell (MEC) fed with domestic wastewater. *Bioresour Technol* 117:55–62
 111. Cusick RD, Kiely PD, Logan BE (2010) A monetary comparison of energy recovered from microbial fuel cells and microbial electrolysis cells fed winery or domestic wastewaters. *Int J Hydrog Energy* 35:8855–8861
 112. Liu W, Huang S, Zhou A, Zhou G, Ren N, Wang A, Zhuang G (2012) Hydrogen generation in microbial electrolysis cell feeding with fermentation liquid of waste activated sludge. *Int J Hydrog Energy* 37:13859–13864
 113. Feng Y, Liu Y, Zhang Y (2015) Enhancement of sludge decomposition and hydrogen production from waste activated sludge in a microbial electrolysis cell with cheap electrodes. *Environ Sci Water Res Technol* 1:761–768
 114. Lu L, Xing D, Liu B, Ren N (2012) Enhanced hydrogen production from waste activated sludge by cascade utilization of organic matter in microbial electrolysis cells. *Water Res* 46:1015–1026
 115. Dhar BR, Elbeshbishy E, Hafez H, Lee H-S (2015) Hydrogen production from sugar beet juice using an integrated biohydrogen process of dark fermentation and microbial electrolysis cell. *Bioresour Technol* 198:223–230
 116. Tenca A, Cusick RD, Schievano A, Oberti R, Logan BE (2013) Evaluation of low cost cathode materials for treatment of industrial and food processing wastewater using microbial electrolysis cells. *Int J Hydrog Energy* 38:1859–1865
 117. Huang J, Feng H, Huang L, Ying X, Shen D, Chen T, Shen X, Zhou Y, Xu Y (2020) Continuous hydrogen production from food waste by anaerobic digestion (AD) coupled single-chamber microbial electrolysis cell (MEC) under negative pressure. *Waste Manag* 103:61–66
 118. Li X-H, Liang D-W, Bai Y-X, Fan Y-T, Hou H-W (2014) Enhanced H₂ production from corn stalk by integrating dark fermentation and single chamber microbial electrolysis cells with double anode arrangement. *Int J Hydrog Energy* 39:8977–8982
 119. Shen R, Liu Z, He Y, Zhang Y, Lu J, Zhu Z, Si B, Zhang C, Xing X-H (2016) Microbial electrolysis cell to treat hydrothermal liquefied wastewater from cornstalk and recover hydrogen: degradation of organic compounds and characterization of microbial community. *Int J Hydrog Energy* 41:4132–4142
 120. Heidrich ES, Edwards SR, Dolfing J, Cotterill SE, Curtis TP (2014) Performance of a pilot scale microbial electrolysis cell fed on domestic wastewater at ambient temperatures for a 12month period. *Bioresour Technol* 173:87–95
 121. Patil SA, Harnisch F, Kapadnis B, Schröder U (2010) Electroactive mixed culture biofilms in microbial bioelectrochemical systems: the role of temperature for biofilm formation and performance. *Biosens Bioelectron* 26:803–808
 122. Kumar R, Singh L, Zularisam AW (2016) Exoelectrogens: recent advances in molecular drivers involved in extracellular electron transfer and strategies used to improve it for microbial fuel cell applications. *Renew Sust Energy Rev* 56:1322–1336
 123. Zhen G, Lu X, Kumar G, Bakonyi P, Xu K, Zhao Y (2017) Microbial electrolysis cell platform for simultaneous waste biorefinery and clean electrofuels generation: current situation, challenges and future perspectives. *Prog Energy Combust Sci* 63:119–145
 124. Karthikeyan R, Cheng KY, Selvam A, Bose A, Wong JWC (2017) Bioelectrohydrogenesis and inhibition of methanogenic activity in microbial electrolysis cells - a review. *Biotechnol Adv* 35:758–771
 125. Rago L, Baeza JA, Guisasola A (2016) Increased performance of hydrogen production in microbial electrolysis cells under alkaline conditions. *Bioelectrochemistry* 109:57–62
 126. Abdoulmoumine N, Adhikari S, Kulkarni A, Chattanathan S (2015) A review on biomass gasification syngas cleanup. *Appl Energy* 155:294–307
 127. Prasertcharoensuk P, Bull SJ, Phan AN (2019) Gasification of waste biomass for hydrogen production: effects of pyrolysis parameters. *Renew Energy* 143:112–120
 128. Su W, Cai C, Liu P, Lin W, Liang B, Zhang H, Ma Z, Ma H, Xing Y, Liu W (2020) Supercritical water gasification of food waste: effect of parameters on hydrogen production. *Int J Hydrog Energy* 45:14744–14755
 129. Zhang J, Hu Q, Qu Y, Dai Y, He Y, Wang C-H, Tong YW (2020) Integrating food waste sorting system with anaerobic digestion and gasification for hydrogen and methane co-production. *Appl Energy* 257:113988
 130. Chang ACC, Chang H-F, Lin F-J, Lin K-H, Chen C-H (2011) Biomass gasification for hydrogen production. *Int J Hydrog Energy* 36:14252–14260
 131. Shie J-L, Chen L-X, Lin K-L, Chang C-Y (2014) Plasmatron gasification of biomass lignocellulosic waste materials derived from municipal solid waste. *Energy* 66:82–89
 132. Parthasarathy P, Narayanan KS (2014) Hydrogen production from steam gasification of biomass: influence of process parameters on hydrogen yield – a review. *Renew Energy* 66:570–579
 133. Nanda S, Isen J, Dalai AK, Kozinski JA (2016) Gasification of fruit wastes and agro-food residues in supercritical water. *Energy Convers Manag* 110:296–306
 134. Osman AI, Skillen NC, Robertson PKJ, Rooney DW, Morgan K (2020) Exploring the photocatalytic hydrogen production potential of titania doped with alumina derived from foil waste. *Int J Hydrog Energy*
 135. Wang Y, Wang D, Chen F, Yang Q, Li Y, Li X, Zeng G (2019) Effect of triclocarban on hydrogen production from dark fermentation of waste activated sludge. *Bioresour Technol* 279:307–316

136. Hu B, Li Y, Zhu S, Zhang H, Jing Y, Jiang D, He C, Zhang Z (2020) Evaluation of biohydrogen yield potential and electron balance in the photo-fermentation process with different initial pH from starch agricultural leftover. *Bioresour Technol* 305:122900
137. Li Y, Zhang Z, Zhang Q, Tahir N, Jing Y, Xia C, Zhu S, Zhang X (2020) Enhancement of bio-hydrogen yield and pH stability in photo fermentation process using dark fermentation effluent as succedaneum. *Bioresour Technol* 297:122504
138. Jayabalan T, Matheswaran M, Preethi V, Naina Mohamed S (2020) Enhancing biohydrogen production from sugar industry wastewater using metal oxide/graphene nanocomposite catalysts in microbial electrolysis cell. *Int J Hydrog Energy* 45:7647–7655
139. Ursua A, Gandia LM, Sanchis P (2012) Hydrogen production from water electrolysis: current status and future trends. *Proc IEEE* 100:410–426
140. Yuzer B, Selcuk H, Chehade G, Demir ME, Dincer I (2020) Evaluation of hydrogen production via electrolysis with ion exchange membranes. *Energy* 190:116420
141. Chakik FE, Kaddami M, Mikou M (2017) Effect of operating parameters on hydrogen production by electrolysis of water. *Int J Hydro Energy* 42:25550–25557
142. Kovač A, Marciuš D, Budin L (2019) Solar hydrogen production via alkaline water electrolysis. *Int J Hydrog Energy* 44:9841–9848
143. Ruth MF, Jadun P, Pivovar B (2017) “H2@Scale: technical and economic potential of hydrogen as an energy intermediate”, Presentation at the Fuel Cell Seminar and Energy Exposition, Long Beach, CA, 9 November, <https://doi.org/10.5065/D6M32STK>.

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.