Correction to: Influences of dielectric and conductive fillers on dielectric and mechanical properties of solid silicone rubber composites

B. S. Manohar Shankar¹ · S. M. Kulkarni¹

Published online: 25 June 2019

© Iran Polymer and Petrochemical Institute 2019

Correction to: Iranian Polymer Journal

<https://doi.org/10.1007/s13726-019-00724-4>

The article listed above was initially published with incorrect Tables 1 and 2 values. In this Correction, Tables 1 and 2 new values are given below.

1. In Table 1 (Properties of DDC composites as per Taguchi L_8 orthogonal array), the effective resistivity @ 1 kHz for the composite samples are to be read as:

Sample code	Effective resistivity @ 1 kHz (Ω m) $\times 10^6$
S0	6.3
S1	5.8
S2	6.1
S3	5.7
S4	5.5
S5	6.0
S6	5.8
S7	5.4
S8	5.7
S9	5.8

2. In Table 2 (Properties of CDC composites), the effective resistivity @ 1 kHz for the composite samples are to be read as:

The original article can be found online at <https://doi.org/10.1007/s13726-019-00724-4>.

✉ B. S. Manohar Shankar
manoharshankarbhat@gmail.com

S. M. Kulkarni
smk@nitk.edu.in

¹ Department of Mechanical Engineering, National Institute of Technology Karnataka, Surathkal, Mangaluru 575025, India

Sample no.	Effective resistivity @ 1 kHz (Ω m) $\times 10^6$
1	1.5
2	1.3
3	1.3
4	1.7
5	1.3
6	1.3
7	1.6
8	1.3
9	1.3

The original article have been corrected.