



Correction to: Simplified methods of the 3D-SVPWM for four-wire three-leg inverter

Fathy H. Awad¹ · Ahmed A. Mansour¹ · Mostafa I. Marei² · Ahmed A. El-Sattar²

Published online: 11 November 2020
© The Korean Institute of Power Electronics 2020

Correction to: Journal of Power Electronics
<https://doi.org/10.1007/s43236-020-00133-4>

$$d_{0i=(1-48)} = M \times (G_i + H_i \times \theta) \quad \text{for } \theta = (0^\circ - 120^\circ). \quad (7)$$

Due to an unfortunate oversight some equations (4, 5, 6 and 7) have been given erroneously, such that:

$\theta = (0^\circ - 20^\circ)$ should be replaced by $\theta = (0^\circ - 120^\circ)$ in the four equations 4,5,6,7.

$$d_{1i=(1-48)} = M \times (A_i + B_i \times \theta) \quad \text{for } \theta = (0^\circ - 120^\circ), \quad (4)$$

$$d_{2i=(1-48)} = M \times (C_i + D_i \times \theta) \quad \text{for } \theta = (0^\circ - 120^\circ), \quad (5)$$

$$d_{3i=(1-48)} = M \times (E_i + F_i \times \theta) \quad \text{for } \theta = (0^\circ - 120^\circ), \quad (6)$$

The original article can be found online at <https://doi.org/10.1007/s43236-020-00133-4>.

✉ Fathy H. Awad
fathyhamed@eri.sci.eg

¹ Power Electronics and Energy Conversion Department, Electronics Research Institute, Cairo, Egypt

² Electrical Power and Machine Department, Faculty of Engineering, Ain Shams University, Cairo, Egypt