ERRATA

**Erratum: “Measurement of the Water Jet Velocity
at the Outlet of Nozzles with Different Profiles”
[Technical Physics 50 (9), 1112–1118 (2005)]**

L. S. Kotousov

*St. Petersburg State Electrotechnical University, ul. Prof. Popova 5, St. Petersburg, 197376 Russia
e-mail: root@post.spb.ru*

(Submitted December 15, 2005; accepted for publication December 15, 2005)

PACS numbers: 99.10.Cd

DOI: 10.1134/S1063784206020265

(1) In the abstract, the range of excess pressures at the nozzle inlet is from 5×10^3 to 3.5×10^5 Pa.

(2) On p. 1112, left column, the last sentence of the first paragraph should read *The static pressure was measured with a precision manometer; at low inlet pressures, a water manometer was used.*

(3) On p. 1112, left column, the last sentence of the second paragraph should read *This quantity also has the meaning of the relative dynamic pressure of the jet, which formally involves the density of the medium at the inlet rather than in the jet.*

(4) On p. 1112, right column, the first sentence of the last paragraph should read *The measuring device (Fig. 1) was placed on a support mounted over the tray.*

(5) On p. 1117, left column, the third sentence of the second paragraph should begin as follows: *A reduction of the absolute static pressure along the streamline from p_1 to p_0 or of p_m to a value much lower than the atmospheric pressure).*...

(6) On p. 1117, left column, in line 2 from bottom of the third paragraph the range of absolute pressures in the jet should be from 500 to 150 Pa.

(7) On p. 1117, formula (11) should read

$$v = v_{st}10^{-6} + v_{liq}(1 - 10^{-6}).$$