

## CORRIGENDUM

## First principles and experimental studies of empty Si<sub>46</sub> as anode materials for Li-ion batteries – CORRIGENDUM

Kwai S. Chan, Michael A. Miller, Wuwei Liang, Carol Ellis-Terrell, and Candace K. Chan

doi: 10.1557/jmr.2016.408, Published by Materials Research Society with Cambridge University Press, 17 November 2016.

In Chan et al.<sup>1</sup>, references 3–17 had several errors and mislabels. The following list is the corrected references:

3. L.Y. Beaulieu, T.D. Hatchard, A. Bonakdarpour, M.D. Fleischauer, and J.R. Dahn: Reaction of Li with alloy thin films studied by *in situ* AFM. *J. Electrochem. Soc.* **150**(11), A1457 (2003).

4. A. Timmons and J.R. Dahn: *In situ* optical observations of particle motion in alloy negative electrodes for Li-ion batteries. *J. Electrochem. Soc.* **153**, A1206 (2006).

5. S.D. Beattie, D. Larcher, M. Morcrette, B. Simon, and J.-M. Tarascon: Si electrodes for Li-ion batteries – A new way to look at an old problem. *J. Electrochem. Soc.* **155**(2), A158 (2008).

6. V.A. Sethuraman, M.J. Chon, M. Shimshak, V. Srinivasan, and P.R. Guduru: *In situ* measurements of stress evolution in silicon thin films during electrochemical lithiation and delithiation. *J. Power Sources* **195**, 5062 (2010).

7. J.Y. Eom, J.W. Park, H.S. Kwon, and S. Rajendran: Electrochemical insertion of lithium into multiwalled carbon nanotube/silicon composites produced by ballmilling. *J. Electrochem. Soc.* **153**(9), A1678 (2006).

8. Y. Zhang, X.G. Zhang, H.L. Zhang, Z.G. Zhao, F. Li, C. Liu, and H.M. Cheng: Composite anode material of silicon/graphite/carbon nanotubes for Li-ion batteries. *Electrochim. Acta* **51**, 4994 (2006).

9. Y. Zhang, Z.G. Zhao, X.G. Zhang, H.L. Zhang, F. Li, C. Liu, and H.M. Cheng: Pyrolytic carbon-coated silicon/carbon nanotube composites: promising application for Li-ion batteries. *Int. J. Nanomanuf.* **2**(1/2), 4 (2008).

10. J.H. Ryu, J.W. Kim, Y.-E. Sung, and S.M. Oh: Failure Modes of Silicon Powder Negative Electrode in Lithium Secondary Batteries. *Electrochem. Solid-State Lett.* **7**(10), A306 (2004).

11. R.A. Huggins and W.D. Nix: Decrepitation model for capacity loss during cycling of alloys in rechargeable electrochemical systems. *Ionics* **6**, 57 (2000).

12. J. Graetz, C.C. Ahn, R. Yazami, and B. Fultz: Highly reversible lithium storage in nanostructured silicon. *Electrochem. Solid-State Lett.* **6**(9), A194 (2003).

13. T. Takamura, S. Ohara, M. Uehara, J. Suzuki, and K. Sekine: A vacuum deposited Si film having a Li extraction capacity over 2000 mAh/g with a long cycle life. *J. Power Sources* **129**, 96 (2004).

14. H. Kim, B. Han, J. Choo, and J. Cho: Three-dimensional porous silicon particles for use in high-performance lithium secondary batteries. *Angew. Chem. Int. Ed.* **47**, 1 (2008).

15. M. Green, E. Fielder, B. Scrosati, M. Wachtler, and J.S. Moreno: Structured silicon anodes for lithium battery applications. *Electrochem. Solid-State Lett.* **6**(5), A75 (2003).

16. C.K. Chan, H. Peng, G. Liu, K. McIlwrath, X.F. Zhang, R.A. Huggins, and Y. Cui: High performance lithium battery anodes using silicon nanowires. *Nat. Nanotechnol.* **3**, 31 (2008).

17. L.-F. Cui, R. Ruffo, C.K. Chan, H. Peng, and Y. Cui: Crystalline-amorphous core-shell silicon nanowires for high capacity and high current battery electrodes. *Nano Lett* **9**, 491 (2009).

The authors regret these errors.

### REFERENCE

1. K.S. Chan, M.A. Miller, W. Liang, C. Ellis-Terrell, and C.K. Chan: First principles and experimental studies of empty Si<sub>46</sub> as anode materials for Li-ion batteries. *J. Mater. Res.* **31**(23), 3657–3665 (2016). doi: 10.1557/jmr.2016.408.