



Energy Focus


Quantum dot funnels increase solar-cell fill factor

Quantum dot funnels—which are devices comprising graded layers comprising quantum dots of different sizes, and therefore bandgaps—offer the possibility of funneling energy toward a suitable acceptor. In the September 14 issue of *Nano Letters* (DOI: 10.1021/nl201682h; p. 3701), I.J. Kramer, E.H. Sargent, and colleagues at the University of Toronto constructed a new solar cell designed around this concept where photoelectrons are efficiently transferred from their source to an electron acceptor. PbS quantum dot funnels were fabricated on TiO₂ electrodes. The resulting solar cells define a path to achieving further improvements in the fill factor of colloidal quantum dot photovoltaics—a crucial determinant of the devices' performance.

The researchers created three funnel types, two of which were graded by their

bandgap to promote or discourage charge-carrier collection, and one control. These were graded, anti-graded, and ungraded, respectively. The researchers started with a base layer of glass, coated in SnO₂/F and then applied a commercially available TiO₂ paste. Multilayer spin coating of solutions of quantum dots generated a graded funnel with three layers of 4.3 nm diameter CQDs (colloidal quantum dots), one layer of 4.2 nm, and one layer of 4.0 nm. Ungraded controls comprised five layers of 4.3 nm CQDs, while anti-graded funnels consisted of three layers of 4.3 nm, one layer of 4.5 nm, and one layer of 4.7 nm diameter CQDs. Each CQD layer was 25 nm thick. Finally, the prepared devices were coated with layers of thin films of gold and silver.

Ungraded control funnels provided a fill factor of 49%, graded



NEW!

**A C / D C F I E L D
H A L L E F F E C T
M E A S U R E M E N T S Y S T E M**

Model 8404 developed with **TOYO Corporation**

Measure mobilities down to 0.001 cm²/Vs

Typical Fields of Study:
Solar Cells—a:Si, CIGS, CdTe
Organic Electronics—OTFTs, OLEDs
Transparent Conducting Oxides—ITO, ZnO, IGZO
Semiconductors—GaAs, GaN, SiGe, HgCdTe, SiC

www.lakeshore.com/8400.html

LakeShore

MRS BOOTH 800



funnels 54%, and antigraded funnels only 37%, where the fill factor provides a measure of the efficiency of the cell. That a 5% increase in fill factor was achieved on changing the structure from ungraded to graded is key to future applications, and the researchers predict the CQD fun-

nels can improve systems with high base fill factors. Additional theoretical modeling shows that such benefits could apply to high-efficiency photovoltaics, as well as the 2–3% efficiency technologies on which these funnels were tested. The research team suggests that CQD funnel

solar cells could enable higher power-per-square-foot densities, lowering the square footage of solar cells needed to power a building.

Benjamin Scheiner

Thin-film heterostructures of Fe- and Co-BaTiO₃ exhibit interface multiferroicity at room temperature

Materials possessing coupled room-temperature ferromagnetic (FM) and ferroelectric (FE) order are currently the subject of intense research for use in spintronic memories that store information through charge and spin. Single-phase materials displaying such multiferroic order are exceedingly rare in nature, so attention has shifted to artificially grown thin-film FM and FE hetero-

structures. In the October issue of *Nature Materials* (DOI: 10.1038/NMAT3098; p. 753), a group led by M. Bibes and A. Barthélemy at the CNRS/Thales laboratory in Palaiseau, France, reports on room-temperature interfacial multiferroicity in BaTiO₃ thin films and substrates covered by Fe and Co layers.

The research team deposited thin-film heterostructures consisting of Fe/BTO or Co/BTO onto a half metallic La_{0.67}Sr_{0.33}MnO₃ (LSMO) layer to form a magnetic tunnel junction. They then performed magnetoresistance and x-ray resonant magnetic scattering (XRMS) measurements to probe the magnetic

structure of the Fe/BTO and the Co/BTO interfaces. The researchers found that the magnetoresistance of the junction depends on the orientation of the FE polarization in the BTO layer, which they interpret as a modulation of the spin polarization of the adjacent Fe and Co layers. The XRMS results also exhibit an asymmetry and hysteresis that corresponds to an induced interfacial magnetic moment in the BTO layer at room temperature. To better understand these observations, the researchers conducted first-principles electronic-structure calculations and determined that moments of $-0.07 \mu\text{B}/\text{Ti}$ atom and

UPCOMING IMI-SEE CO-SPONSORED EVENT



IMI-SEE

International Materials Institute
for Solar Energy and Environment



IUMRS INTERNATIONAL CONFERENCE OF YOUNG RESEARCHERS ON ADVANCED MATERIALS (ICYRAM)

July 1-6, 2012 ■ Singapore

The mission of ICYRAM is to provide a platform for junior researchers to present technical findings of their research, to network within an international community of other young researchers, and to increase the breadth of their general materials-based knowledge.

Senior graduate students, postdoctoral fellows, and junior career faculty from relevant disciplines and working in the US are invited to apply to the IMI-SEE for travel support. Applicants must be US citizens or US Permanent Residents.

Please visit the following website for more information:

www.imi-see.org

Email Contact: imi-see@northwestern.edu

MRS


Organized by: Materials Research Society
SINGAPORE

VARIABLE TEMPERATURE MICROPROBE SYSTEMS



THE WORLD'S RESOURCE FOR
VARIABLE TEMPERATURE
SOLID STATE CHARACTERIZATION

MRS BOOTH 1003



- Highly flexible and adaptable system
- Configurable and modular
- Wide temperature ranges available
- 1 to 7 manipulators possible
- Optical measurements possible
- Easy to use
- Reliable results

www.mmr-tech.com
sales@mmr-tech.com • 847.740.3701