CORRECTION

Correction to: Evaluation of the combined deterioration by freeze–thaw and carbonation of mortar incorporating BFS, limestone powder and calcium sulfate

Wenyan Zhang · Seunghyun Na · Junho Kim · Hyeonggil Choi · Yukio Hama

Published online: 8 November 2017
© RILEM 2017

**Correction to: Materials and Structures (2017)
50:171**
<https://doi.org/10.1617/s11527-017-1039-1>

Due to an unfortunate turn of events, this article was published with an erroneous version of Fig. 9. Please find on this page the correct version of Fig. 9 that should be regarded by the reader as the final version.

The online version of the original article can be found under <https://doi.org/10.1617/s11527-017-1039-1>.

W. Zhang
School of Material Science and Engineering, Henan
Polytechnic University, Jiaozuo 454000, China

W. Zhang
Center of Environmental Science and Disaster Mitigation
for Advanced Research, Muroran Institute of Technology,
27-1 Mizumoto, Muroran 050-8585, Japan

S. Na
Product Development Department, Nippon Steel and
Sumikin Cement Co. Ltd., 64, Nakamachi,
Muroran 050-8510, Japan

J. Kim · H. Choi · Y. Hama (✉)
Graduate School of Engineering, College of
Environmental Technology, Muroran Institute of
Technology, 27-1 Mizumoto, Muroran 050-8585, Japan
e-mail: hama@mmm.muroran-it.ac.jp

Fig. 9 Relative dynamic modulus of mortar samples without carbonation and after pre-carbonation. **a** Non-carbonation mortar samples. **b** Mortar samples after pre-carbonation