ZSCORE: A program for the accurate calculation of z scores, d' , and β

DAVID ROSE

Northwestern University, Evanston, Illinois

Numerous programs have been proposed for calculation of the signal detection parameters d' and β from data for hit rate $p(\text{hit})$ and false alarm rate $p(\text{FA})$ (Ahroon & Pastore, 1977; Emerson, 1979; Fisk, Schneider, & Burkhard, 1982; Gardner & Boice, 1986; McGowan & Appel, 1977). The more recent programs have claimed improved accuracy, especially over published tables, which are computed only to two decimal figures (Elliott, 1964) or which do not include all probability values, making interpolation necessary (Freeman, 1973). For example, Gardner and Boice's (1986) program provides three-decimal-figure accuracy, and is thus suitable for analyzing the results of experiments with over 1,000 trials in which $p(\text{hit})$ and $p(\text{FA})$ have been estimated with high precision. Their program uses an approximation of the inverse normal integral function, which provides accuracy to ± 0.00045 , the same figure as that obtained in the approximation used by Emerson (1979). However, in these cases, errors can occur in the third decimal place after rounding when calculating d' , which requires using the formula twice (once to find the z value for the hits and once for the false alarms, followed by subtraction of these two values to obtain d').

Two alternative solutions exist to this problem. One is to use a more accurate approximation of the inverse normal integral, such as one of those discussed by Brophy (1985). Another solution is to compute the integral directly, to whatever degree of accuracy is desired. With the continuing advent of ever faster and more powerful computers, this latter solution is now realizable even in common desktop machines.

In this paper I describe a program (ZSCORE) that runs on the IBM PC and that integrates the area under the normal curve directly with very low error and run times of only a few seconds (see Appendix). Thus for probability values between .00023 and .99977, the computation is performed with less than 10^{-6} error (Table 1) and takes, on average, 15 sec on an IBM PC/XT, but only 3 sec on a Sperry PC/AT. For most of the central range of the curve (99% of cases), the algorithm is more accurate than any of the approximation formulas given by Brophy (1985). This program has other advantages over those that use approximation formulas, in that (1) the errors are of predictable magnitude and direction for any given value of p , and (2) by simple modifications the accuracy can

be increased even further. For example, the maximum error can be reduced roughly tenfold, albeit with longer run times, by a tenfold decrease in the value of a single variable, the step size S defined in line 20 of the program.

Input. The user types in the probability values $p(\text{hit})$ and $p(\text{FA})$ in response to computer-generated prompts.

Output. ZSCORE prints the z values of both of these probability values, and the values of the signal detection parameters d' and β on the assumption of equal variance noise and signal-plus-noise distributions (Green & Swets, 1966).

Description. The area under the normal curve is divided into 12 sectors of 0.5- z -unit width between $z = -3.0$ and $z = +3.0$ (plus two sectors, one for each tail of the distribution). The program first finds which sector the entered probability value is within, by searching through a stored lookup table of the probability values that lie at the boundaries between these sectors (Abramowitz & Stegun, 1964, p. 966). The program then integrates from the boundary value nearer the mean, in steps of size 0.001 z unit, until the cumulative total exceeds the entered value. The height of the normal curve is calculated using the computationally efficient formula $0.3989422804 \exp(-z^2/2)$. Overflow problems do not occur with the integration (cf. Wood, 1985), because ZSCORE counts only the number of steps until a preentered value is reached. The final z score is then estimated by linear interpolation between the z scores on the step before and the step after the target value is achieved.

Beyond $z = \pm 3.0$ ($p < .00135$ or $p > .99865$), the program will integrate up to $z = \pm 5.0$ ($p < .0000003$ or $p > .9999997$), but not further, so accidental entry of $p = 0$ or $p = 1$ does not cause an infinite loop.

Accuracy. For most cases, then, integration is necessary only over 0-0.5 z unit, and errors can only accumulate over that range (rather than over the whole normal curve). This accumulation is linear, and the error can thus

Table 1
Maximum Error Within Each Sector of the Normal Distribution

Z Range (Modulus)	Maximum Error ($\times 10^{-6}$)	
	Abramowitz & Stegun*	White†
0-0.5	+4	+7
0.5-1.0	+2	+14
1.0-1.5	-4	+9
1.5-2.0	-16	-10
2.0-2.5	-35	+10
2.5-3.0	-64	-22
3.0-3.5	-113	-69

*Maximum error for p values at or just below upper boundary of sector, relative to the values given by Abramowitz and Stegun (1964, p. 966). For example, entry of $p = .691462461274013$ to ZSCORE gives $z = 0.5000000426199413$ instead of exactly 0.5, as listed by Abramowitz and Stegun. †Error, relative to the values given by White (1970) that are closest to the upper boundary of each sector.

Supported by Public Health Service International Research Fellowship 1 FO5 TW03567-01 BI-5 (AHR). The author's permanent address is Department of Psychology, University of Surrey, Guildford, Surrey GU2 5XH, U.K.

be estimated accurately by interpolation. The maximum error that can accumulate occurs at the outer boundary of each 0.5- z -unit wide sector. Table 1 lists the maximum errors that can occur within each sector, relative to two sets of previously published data. Beyond $z = \pm 3.5$, the errors continue to accumulate, but they are still less than 10^{-5} at $z = \pm 4.0$ and less than 10^{-3} at $z = \pm 5.0$.

REFERENCES

- ABRAMOWITZ, M., & STEGUN, I. A. (1964). *Handbook of mathematical functions*. New York: Dover.
- AHROON, W. A., JR., & PASTORE, R. E. (1977). Procedures for computing d' and β . *Behavior Research Methods & Instrumentation*, 9, 533-537.
- BROPHY, A. L. (1985). Approximation of the inverse normal distribution function. *Behavior Research Methods, Instruments, & Computers*, 17, 415-417.
- ELLIOTT, P. (1964). Tables of d' . In J. A. Swets, *Signal detection and recognition by human observers* (pp. 651-684). New York: Wiley.
- EMERSON, P. L. (1979). Computer approximation of the inverse of the normal distribution function. *Behavior Research Methods & Instrumentation*, 11, 397-398.
- FISK, A. D., SCHNEIDER, W., & BURKHARD, J. C. (1982). SENSE: A program for calculating parametric (d') and nonparametric (A' and Ag) indexes of sensitivity. *Behavior Research Methods & Instrumentation*, 14, 361.
- FREEMAN, P. R. (1973). *Tables of d' and β* . Cambridge: Cambridge University Press.
- GARDNER, R. M., & BOICE, R. (1986). A computer program to generate signal-detection theory values for sensitivity and response bias. *Behavior Research Methods, Instruments, & Computers*, 18, 54-56.
- GREEN, D. M., & SWETS, J. A. (1966). *Signal detection theory and psychophysics*. New York: Wiley.
- MCGOWAN, W. T., III, & APPEL, J. B. (1977). An APL program for calculating signal detection indices. *Behavior Research Methods & Instrumentation*, 9, 517-521.
- WHITE, J. S. (1970). Tables of normal percentile points. *Journal of the American Statistical Association*, 65, 635-638.
- WOOD, D. L. (1985). High precision chi-square and normal curve integration. *Behavior Research Methods, Instruments, & Computers*, 17, 429-431.

APPENDIX ZSCORE

```

10 REM ZSCORE : Converts hit and FA rates to z scores, d' and beta.
11 REM Written by Dave Rose, 1982; this version for IBM PC written 1987.
20 S#=.001#
30 INPUT "p(hit):",Y#
40 INPUT "p(FA) :",Y1#
50 LPRINT "p(hit)=";Y#
60 LPRINT "p(FA) =";Y1#
70 GOSUB 200
80 Z1#=Z#
90 Y#=Y1#
100 GOSUB 200
110 Z2#=Z#
120 LPRINT "z(hit)=";Z1#," d'=";Z1#-Z2#
130 LPRINT "z(FA) =" ;Z2#,"Beta=";EXP((Z2#*Z2#-Z1#*Z1#)/2#)
140 LPRINT
150 GOTO 10
200 X#=ABS(Y#-.5#)
210 RESTORE
220 W#=3.5#
230 W#=W#-.5#
240 READ T#
250 IF X#<T# THEN 230
260 X#=X#/S#/.3989422804#
270 T#=T#/S#/.3989422804#
280 U#=EXP(-W#*W#/2#)
290 W#=W#+S#
300 IF W#>5# THEN Z#=5#:GOTO 360
310 V#=EXP(-W#*W#/2#)
320 T#=T#+(U#+V#)/2#
330 IF T#>=X# THEN Z#=W#-S#*(T#-X#)*2#/(U#+V#) : GOTO 360
340 U#=V#
350 GOTO 290
360 IF Y#<.5# THEN Z#=-Z#
370 RETURN
500 DATA 0.49865010196837#,0.493790334674224#,0.477249868051821#
510 DATA 0.433192798731142#,0.341344746068543#,0.191462461274013#,0#

```