Changing change detection: Improving the reliability of measures of visual short-term memory capacity

SØREN KYLLINGSBÆK AND CLAUS BUNDESEN
University of Copenhagen, Copenhagen, Denmark

The change detection paradigm is a popular way of measuring visual short-term memory capacity. Using the paradigm, researchers have found evidence for a capacity of about four independent visual objects, confirming classic estimates that were based on the number of items that could be reported. Here, we determine the reliability of capacity measures found by change detection. We derive theoretical predictions of the variance of the capacity estimates and show how they depend on the number of items to be remembered and the guessing strategy of the observer. We compare the theoretically derived variance to the variance estimated over repeated blocks of trials with the same observer and find close correspondence between predicted and observed variances. Also, we propose a new version of the two-alternative choice change detection paradigm, in which the choice is unforced. This new paradigm reduces the variance of the capacity estimate substantially.

Traditionally, visual short-term memory (VSTM) capacity has been measured using the whole-report paradigm, in which participants are required to report as many items as possible from a set of briefly presented objects (Cattell, 1885). Sperling (1960, 1963, 1967) used letters as stimuli and found that VSTM capacity was limited to about four or five independent items (see also Bundesen, 1990; Bundesen, Habekost, & Kyllingsbæk, 2005; Shibuya & Bundesen, 1988). When familiar, nameable stimuli are used, whole report gives a reliable and easily interpretable measure of VSTM capacity. However, several investigators have objected that the very use of verbalizable stimuli may contaminate the estimate of VSTM capacity due to contributions from verbal working memory (Olsson & Poom, 2005; Vogel, Woodman, & Luck, 2001). Moreover, whole report is not feasible for measuring VSTM capacity for unfamiliar material. For these reasons, among others, the bulk of recent studies of VSTM capacity have used the change detection paradigm.

Phillips (1974) developed change detection for investigating memory of random patterns, and Pashler (1988) extended it for estimating memory for multiple objects. In Pashler's version of the paradigm, a number of unrelated stimuli are presented, and the participant is asked to remember the identity and location of the items. Stimulus presentations are brief (<500 msec) but presumably long enough that VSTM is filled up. After presentation of the memory display, a blank screen is presented for 1–3 sec, followed by a probe display. In half of the trials, the probe display is identical to the memory display (no-change trials); in the other half of the trials, the identity of a single,

randomly chosen item is changed (change trials). The participant is instructed to make a two-alternative forced choice (2AFC) response indicating whether the two displays are identical.

In Pashler's original version of the change detection paradigm, all items in the probe display must be compared with the remembered items in VSTM. The number of comparisons was assumed not to influence the probability of recognizing the change. However, this assumption may be too strong. Thus, several investigators have used a different approach called *single-probe change detection* (Cowan, 2001; Cowan et al., 2005). Here, the probe display following the delay period contains only a single item located at a randomly chosen location previously occupied by an item in the memory display. As compared with the original version of the change detection paradigm, the use of a single probe reduces the role of comparison processes in the task.

Investigations of VSTM capacity by use of change detection have flourished during the past 10 years. In line with previous whole-report studies, many investigations have provided evidence for a limitation of about four independent objects (Awh, Barton, & Vogel, 2007; Luck & Vogel, 1997; Rouder et al., 2008; Todd & Marois, 2004; Vogel & Machizawa, 2004; Vogel et al., 2001; but see also Alvarez & Cavanagh, 2004; Bays & Husain, 2008; Eng, Chen, & Jiang, 2005). Several studies have investigated the consistency of estimates of VSTM capacity across different types of stimulus materials or different points in time. Good correspondences have sometimes been found between different estimates of VSTM capacity for

S. Kyllingsbæk, sk@psy.ku.dk

the same participants (Awh et al., 2007; Scolari, Vogel, & Awh, 2008).

As noted by Vogel and Awh (2008), individual variations in VSTM capacity may be exploited during investigations of fundamental aspects of working memory and attention. Thus, correspondence between individual variations in cognitive and neurophysiological measures may be used to validate the latter. Similarly, both associations and dissociations between cognitive measures may be revealed by an individual-difference approach, provided that sufficiently reliable estimates for the cognitive parameters can be obtained.

In this article, we investigate the reliability of estimates of VSTM capacity derived from the change detection paradigm. We derive theoretical measures of the reliability of the estimates, apply the measures to new empirical data, and show how the paradigm can be optimized. Thus, we show that the reliability is highest when the display size is just above the VSTM capacity of the tested participant. We propose a new version of single-probe change detection that should further improve the reliability of the estimate of VSTM capacity. In this new version of the paradigm, participants are not forced to guess but may respond “don’t know” when they are uncertain about whether or not a change has happened. As we show, this

minor change to the paradigm reduces the variance of the capacity estimate substantially.

The Variability of VSTM Capacity Estimates

The data derived from a change detection paradigm, such as Cowan’s (2001) version of the single-probe change detection paradigm, may be reduced to an observed hit rate, $\hat{P}(H)$, of detecting a change when it is present between the memory and the probe display and a false alarm rate, $\hat{P}(FA)$, which is the relative frequency of erroneously responding “change” when no change is present. From $\hat{P}(H)$, $\hat{P}(FA)$, and the number of items presented in the memory display, N_S , an estimate of VSTM capacity K may be derived from a model specifying the nature of the mental processes involved.

The model proposed by Cowan (2001; Cowan et al., 2005) is shown in Figure 1. In this model, a participant in a single-probe change detection paradigm encodes all of the N_S items in the memory display when VSTM capacity $K \geq N_S$, but encodes a randomly chosen subset of K items from the memory display when $K < N_S$. Information about the locations of the K items is assumed to be perfect, so that the comparison with the probe is not affected by spatial uncertainty of the items in VSTM or the probe. If $K \geq N_S$, the participant successfully notices that the

Figure 1. Tree diagram of Cowan’s model (Cowan, 2001) of 2AFC single-probe change detection, where the probe is shown at a previously occupied location. As an example, a hit in a change-present trial may be accomplished either by successfully encoding the probed item with probability K/N_S or by not encoding the probe with probability $1 - K/N_S$, but guessing “yes” (“change”) with probability P_{gy} . CR, correct rejection; FA, false alarm.

single item in the probe display is different from the corresponding item in the memory display when a change occurs. Likewise, the participant will also correctly identify that the probe item is identical to the item in the memory display in no-change trials.

If $K < N_S$, the probability of successfully encoding the probed item equals K/N_S . If the participant has failed to encode the probed item (which happens with probability $1 - K/N_S$), the participant may guess that the probed item has changed, which happens with probability P_{gy} . The probabilities of hits and false alarms are

$$P(H) = K/N_S + (1 - K/N_S)P_{gy} \quad (1)$$

and

$$P(FA) = (1 - K/N_S)P_{gy}, \quad (2)$$

respectively.

By subtracting Equation 2 from Equation 1, we get an estimate for the VSTM capacity K :

$$\hat{K} = N_S[\hat{P}(H) - \hat{P}(FA)]. \quad (3)$$

$P(H)$ is estimated by the relative frequency of hit trials among trials in which a change has occurred (change trials), and $P(FA)$ is estimated by the relative frequency of false alarm trials among trials in which no change has occurred (no-change trials). Let us assume that the number of change trials and the number of no-change trials are the same (N_T). Thus, if 40 trials are run, N_T equals 20. Let us also assume that the number of hit trials is binomially distributed, with parameters $n = N_T$ and $p = P(H)$, whereas the number of false alarm trials is binomially distributed, with parameters $n = N_T$ and $p = P(FA)$. As is shown in Appendix A, the assumptions imply that the expected variance of the estimate for K is given by

$$V(\hat{K}) = V\left(N_S[\hat{P}(H) - \hat{P}(FA)]\right) \\ = \frac{(N_S - K)\left[K + 2P_{gy}(1 - P_{gy})(N_S - K)\right]}{N_T}. \quad (4)$$

Three predictions follow from Equation 4. (1) The variance of the estimate of K is inversely related to the number of trials, $2N_T$. (2) The variance increases strongly with the number of display items in excess of K . (3) The variance may be minimized by having the participant adopt either a very conservative guessing strategy ($P_{gy} \rightarrow 0$) or an extremely liberal guessing strategy ($P_{gy} \rightarrow 1$). Either strategy reduces the expected variance to $(N_S - K)K/N_T$. On the other hand, the variance is maximal at a value of $(1/2)(N_S^2 - K^2)/N_T$, when $P_{gy} = .5$. Reducing the variance of $\hat{K}$ by lowering the number of items to be remembered (N_S) to a value just above the true value of VSTM capacity K may be done, for ex-

ample, on the basis of a short block of pilot trials, where the performance of the participant is monitored around a memory set size of 3 (± 2 items). Figure 2 illustrates the effect of varying K , P_{gy} , and N_S on the variance of $\hat{K}$ (given by Equation 4).

A New Change Detection Paradigm

As described above, one of the aims of the present article is to present an alternative to the standard 2AFC single-probe change detection paradigm. In the new two-alternative unforced choice (2AUFC) single-probe change detection paradigm, the participant is given a third response option. In addition to “change” or “no change,” the participant may now indicate that the probed item was not encoded in VSTM by responding “don’t know” (i.e., “I don’t know if the probed item was changed”).

A model of the new version of the 2AUFC single-probe change detection paradigm is presented in Figure 3. A single new parameter, P_{gn} , is introduced; P_{gn} is the probability that the participant will guess “no” (“no change”) when the probed item is not encoded in VSTM. Otherwise, the model is similar to Cowan’s (2001; Cowan et al., 2005) model (shown in Figure 1). From the new model, the probability of hits, misses, correct rejections, and false alarms may be derived as shown in Equations 5, 6, 7, and 8, respectively.

$$P(H) = K/N_S + (1 - K/N_S)P_{gy}, \quad (5)$$

$$P(M) = (1 - K/N_S)P_{gn}, \quad (6)$$

$$P(CR) = K/N_S + (1 - K/N_S)P_{gn}, \quad (7)$$

and

$$P(FA) = (1 - K/N_S)P_{gy}, \quad (8)$$

where $0 \leq P_{gy} + P_{gn} \leq 1$. The probability of “don’t know” responses in change trials is given by $\hat{P}(?C) = 1 - \hat{P}(H) - \hat{P}(M)$, and the probability of “don’t know” responses in no-change trials is given by $\hat{P}(?C) = 1 - \hat{P}(CR) - \hat{P}(FA)$.

From Equations 5–8, a new estimate for VSTM capacity K may be derived:

$$\hat{K} = N_S[\hat{P}(H) - \hat{P}(FA) + \hat{P}(CR) - \hat{P}(M)]/2. \quad (9)$$

Let the number of hits, misses, and “don’t know” responses on change trials be multinomially distributed with parameters N_T and $\mathbf{p} = [P(H), P(M), P(?C)]$, and let the number of correct rejections, false alarms, and “don’t know” responses on no-change trials be multinomially distributed with parameters N_T and $\mathbf{p} = [P(CR), P(FA), P(?C)]$. As is shown in Appendix A, the expected variance of the estimate for K given by Equation 9 is presented below in Equation 10.

$$V(\hat{K}) = V\left(N_S[\hat{P}(H) - \hat{P}(FA) + \hat{P}(CR) - \hat{P}(M)]/2\right) \\ = \frac{(N_S - K)\left[K + N_S(P_{gy} + P_{gn}) - (N_S - K)(P_{gy} - P_{gn})^2\right]}{2N_T}. \quad (10)$$

Figure 2. Graphs showing the effect of varying K , P_{gv} , and N_s on the variance of the estimate of VSTM capacity, $\hat{K}$, in the standard 2AFC change detection paradigm (cf. Equation 4). N_T was set equal to 10.

Figure 3. Model for the new 2AFC single-probe change detection paradigm. CR, correct rejection; FA, false alarm; ?C, “don’t know” response in change trial; ?C̄, “don’t know” response in no-change trial.

Equation 10 implies that (1) the variance is inversely related to the total number of trials $2N_T$, and (2) the variance increases with the number of display items in excess of K .

If the participant adopts a conservative guessing strategy (by which both P_{gy} and P_{gn} tend toward 0), the variance of the new K estimate is reduced to half of the expected variance of the traditional K estimate given by Equation 4, when participants are also using a conservative guessing strategy in the 2AFC paradigm (i.e., $P_{gy} \rightarrow 0$).

However, when classic 2AFC change detection (where participants are free to choose their guessing strategy) is compared with the new 2AFC paradigm (where a conservative guessing strategy is stressed in the instruction), the reduction in the variance of the K estimate can be larger than 50%. The maximal relative difference is found when P_{gy} equals .5 in the 2AFC paradigm and both P_{gy} and P_{gn} are 0 in the 2AFC paradigm. Dividing the variance estimate in Equation 10 by the variance estimate of Equation 4, the predicted ratio equals

$$\frac{K}{N_S + K}.$$

As an example, the variance of the K estimate in the new 2AFC paradigm would be 33% of the variance in the 2AFC paradigm for a participant with a K value of 4 trying to remember a display with eight memory items.

One may also ask what the benefit of the new 2AFC paradigm would be in terms of the number of trials that must be run, given a required level of the absolute vari-

ance of the K estimate. Assume, for example, that $K = 3$ and $N_S = 6$, whereas $P_{gy} = .4$ in the 2AFC paradigm, but $P_{gy} = P_{gn} = .1$ in the 2AFC paradigm. How many trials would one have to run in the two paradigms to reach a variance level in the K estimate of .5? Inserting into Equations 4 and 10, and isolating N_T , one finds that $N_T = 27$ trials for the 2AFC paradigm and $N_T = 13$ for the new 2AFC paradigm. Thus, a total of about 54 trials would have to be run in the traditional 2AFC paradigm, whereas the number of trials could be reduced to 26 in the new 2AFC paradigm.

If the sum $P_{gy} + P_{gn}$ approaches 1 (i.e., the participant always guesses and never uses the new third response alternative “don’t know”), the variance of K tends toward the value of Equation 4, as expected. In line with this, Equation 10 reaches its maximum value when $P_{gy} = P_{gn} = .5$.

Finally, we note that the derived variance estimates in both the classic 2AFC paradigm (Equation 4) and the new 2AFC paradigm (Equation 10) are based on unbiased estimates of VSTM capacity (see derivations of expected values of $\hat{K}$ in Appendix B). Thus, the reduction in the predicted variance obtained with the new 2AFC paradigm is due to a reduction in measurement error.

The new response introduced in the 2AFC paradigm requires some metacognitive insight. Specifically, in order to use the “don’t know” response efficiently, the participant must judge whether the probed item was encoded successfully. Thus, our new paradigm should be used with caution during testing of participants who are likely to have reduced metacognitive abilities (e.g., children or

psychiatric or neurological patients). If these participants guess instead of using the “don’t know” alternative, the variance of $\hat{K}$ should increase (cf. Equation 10). On the other hand, if a participant uses the “don’t know” response excessively—even when the probed item is encoded into VSTM—the estimate of VSTM should be reduced, as compared with its true value.

EXPERIMENT 1

To test our theoretical predictions, we ran two successive experiments with the same participants. In Experiment 1, the participants served in alternating short blocks of trials in three conditions: (1) 2AFC single-probe change detection with a *liberal* guessing strategy (2AFC-lib), (2) 2AFC single-probe change detection with a *conservative* guessing strategy (2AFC-con), and (3) 2AUCF single-probe change detection with a *conservative* guessing strategy. Conditions 2 and 3 were designed to reduce the expected variance of the estimate of VSTM capacity in relation to the variance expected in Condition 1, where the standard 2AFC paradigm was used.

VSTM capacity K was estimated twice within each of these blocks, yielding a total of 10 estimates per condition for each participant. The variances of these estimates were then compared among the three conditions. Following the theoretical derivations above (cf. Equations 4 and 10), we should expect the variance of the K estimates to be largest in the 2AFC-lib condition, if participants were guessing “change” and “no change” (with the same probability of .5), second largest in the 2AFC-con condition, and smallest in the new 2AUCF paradigm.

Method

Participants. A group of 21 students served as paid participants. The experiment took approximately 1 h to complete. The participants’ mean age was 25.6 years (range = 20–35). All participants had normal or corrected-to-normal vision.

Stimuli. The stimulus materials consisted of colored disks with a diameter subtending 0.96° of visual angle at a viewing distance of 80 cm. Seven colors—red, green, blue, yellow, purple, black, and white—were shown on a homogeneous gray background. The disks were presented on an imaginary circle with a radius of 4.8° of visual angle from a central fixation cross.

Procedure. When adequately fixating the cross in the middle of the screen, the participant initiated the presentation of the memory display comprising eight colored disks located equidistantly along the periphery of the imaginary circle. The colors of the disks were selected with replacement, with the constraint that no color could appear more than twice in the same display. The disks were presented for 200 msec, followed by a 1,000-msec blank interval. After the delay, a single probe item—a colored disk—was shown at one of the previously occupied locations. In half of the trials, the probe disk was identical in color to the corresponding disk in the memory display. In the other half of the trials, the probe appeared in a different color chosen randomly from among the remaining six colors. The task of the participant was to decide whether (1) the probe disk was identical to the disk at the same location in the memory display or (2) a change in color had occurred.

Each participant served in a total of 15 experimental blocks of 40 trials each. In the 5 blocks comprising the 2AFC-lib condition, a standard 2AFC (“change” or “no change”) response to the probe display was required, and the participants were instructed as fol-

lows: “Perform the task as accurately as possible, guessing whenever unsure.” In the 5 blocks comprising the 2AFC-con condition, a similar 2AFC single-probe change detection paradigm was run. Here, however, the participants were instructed as follows: “Adopt a conservative guessing strategy and respond ‘Change’ only when *fairly certain* that a change has occurred.” In the 5 blocks comprising the 2AUCF condition, three different responses were allowed: “change,” “no change,” and “don’t know.” Also, here, participants were encouraged to adopt a conservative guessing strategy, responding “change” or “no change” only when *fairly certain*, and otherwise responding “don’t know.”

Blocks of each of the three types were run in alternating order and counterbalanced across the participants using a Latin-square design. Before the experimental blocks, the participants were familiarized with the experimental procedure in three warm-up blocks, one block of each type.

Results and Discussion

The mean hit rates calculated across participants were .75 ($SD = .15$) in the 2AFC-lib condition, .56 ($SD = .18$) in the 2AFC-con condition, and .53 ($SD = .18$) in the 2AUCF condition. The corresponding mean false alarm rates were .38 ($SD = .18$), .19 ($SD = .14$), and .13 ($SD = .13$). The miss and correct rejection rates in the 2AUCF condition were .032 ($SD = .044$) and .34 ($SD = .12$), respectively.

For each participant, estimates of VSTM capacity K and guessing rates P_{gy} and P_{gn} were then computed across all trials in each of the three conditions using Equations 1–3 and 5–9, respectively. The mean estimates of K across participants in the three conditions were 2.96 ($SD = 1.29$), 2.94 ($SD = 1.32$), and 2.83 ($SD = 0.98$), respectively, and did not differ significantly from each other ($F < 1$). Correspondingly, the correlations of the K estimates in the standard 2AFC-lib condition with the K estimates in the 2AFC-con [.89; $t(19) = 8.384, p < .0001, d = 3.847, p_{rep} > .999$] and the 2AUCF [.89; $t(19) = 8.616, p < .0001, d = 3.953, p_{rep} > .999$] conditions were high. Note that, if the participants had used partial information to solve the task in the standard 2AFC change detection paradigm, one would have expected a lower K estimate in the new 2AUCF condition, when the possibility of responding “don’t know” was introduced. Thus, our results are in line with other recent results (see Rouder et al., 2008; Zhang & Luck, 2008) that suggest that participants do not use partial information in change detection.

The estimated probabilities of guessing yes (P_{gy}) when the probed item from the array was not encoded into VSTM were .60 ($SD = .21$), .33 ($SD = .22$), and .24 ($SD = .19$) and differed significantly among the three conditions [$F(2,59) = 19.073, p < .0001, \eta_p^2 = .393, p_{rep} > .999$].¹ Pairwise comparisons showed significant differences between the 2AFC-lib and the other two conditions. The mean estimated probability of guessing no (P_{gn}) in the 2AUCF condition was .011 ($SD = .10$).

For each participant, we calculated 10 estimates of K (i.e., 10 values of $\hat{K}$) for each of the three conditions (2AFC-lib, 2AFC-con, and 2AUCF): one estimate for each subblock of 20 consecutive trials (10 change and 10 no-change trials). Thus, N_T in Equations 4 and 10 was equal to 10 in the present paradigm. For each participant

in each condition, the sample variance of the 10 estimates for K defined the observed variance of the estimates.

Corresponding theoretically predicted variances were calculated using the estimates of K , P_{gy} , and P_{gn} from all 200 trials in each condition as *plug-in* estimates. Thus, the estimates of the K , P_{gy} , and P_{gn} parameters used to compute the predicted variances were not dependent on the observed variances computed across the 10 subblocks.

The average results across participants for both observed and predicted variances of $\hat{K}$ are shown in Figure 4. A repeated measures ANOVA on the observed variances yielded a significant effect of experimental condition [$F(2,59) = 9.6736, p < .0001, \eta_p^2 = .247, p_{rep} > .993$]. Pairwise comparisons showed significant differences between the 2AFC condition and each of the two 2AFC conditions.

We calculated the goodness of fit as the correlation between individually observed and predicted variances of the K estimates. The correlation was found to be .65. Estimating the variance of an estimate is inherently difficult, so we ran Monte Carlo simulations using the individually estimated values of K , P_{gy} , and P_{gn} across all trials to compare our observed measure of goodness of fit with the distribution of predicted correlations, given the present sample of participants in the experiment and the number of trials run (using Equations 3, 4, 9, and 10). The expected correlation in the Monte Carlo simulations was found to be equal to .61 ($SD = .059$), very close to our observed correlation between predicted and observed variances of $\hat{K}$.

A closer look at the estimates of the guessing probability in the 2AFC-lib condition showed that the P_{gy} values varied considerably from participant to participant, ranging from .188 to .967. Thus, although all participants

showed a decrease in P_{gy} between the 2AFC-lib and the 2AFC-con conditions, the change in guessing strategy of several participants moved the guessing probability closer to a value of .5 in the 2AFC-con condition. According to Equation 4, this should mask the effect of manipulating the guessing strategy between the 2AFC-lib and 2AFC-con conditions.

To test this hypothesis, we split the measures of the observed variances of K in accordance with the estimated values of P_{gy} across the two 2AFC conditions. The split was done by dividing the P_{gy} values into two sets: those with values between .25 and .75 (i.e., closest to a value of .5) and the remaining values ranging between 0 and .25 and between .75 and 1, respectively. Comparing the observed variances in the two sets by a one-tailed Welch two-sample t test yielded a significantly larger mean variance for the set with P_{gy} values closer to .5 [$t(39.9) = 2.6, p < .001, d = 0.802, p_{rep} = .963$]. The mean observed variances for the two sets were 2.66 and 1.74, respectively. Corresponding predicted mean variances were 2.67 and 1.92, respectively.

EXPERIMENT 2

In Experiment 2, we tested the theoretical prediction that the variance of the estimate of VSTM capacity should increase systematically with the number of stimuli presented in the memory display (cf. Equation 4). Displays of 6, 8, or 12 colored disks were tested in a standard 2AFC single-probe change detection paradigm that was replicated 10 times with each participant. The standard 2AFC change detection paradigm and the range of display sizes were chosen in order to maximize the effect of manipulating the memory set size on the variance of the K estimate (cf. Equations 4 and 10), thus providing a good test of our theoretical predictions.

Method

Participants. Twenty² of the students who had served as participants in Experiment 1 also participated in Experiment 2.

Stimuli. The stimulus materials were the same as those used in Experiment 1.

Procedure. Except for the following details, the procedure was the same as that used in the first experiment. In Experiment 2, the number of stimuli (colored disks) in the memory display was 6, 8, or 12. Ten blocks of 60 trials, each comprising 20 trials per display size, were run in a single session of about 1 h. In all 10 blocks, the participants were required to respond as accurately as possible, guessing whenever unsure, in accordance with the standard 2AFC change detection paradigm. Before the 10 experimental blocks, a single warm-up block was run.

Results and Discussion

The mean hit rates across participants were .85 ($SD = .086$), .81 ($SD = .090$), and .73 ($SD = .15$) for memory set sizes 6, 8, and 12, respectively; corresponding false alarm rates were .32 ($SD = .15$), .43 ($SD = .15$), and .47 ($SD = .18$), respectively. From these values, estimates of VSTM capacity K and the guessing rate P_{gy} were computed using Equations 1–3 across all trials within each participant. The K estimates in the three conditions were 3.18 ($SD =$

Figure 4. The mean observed and theoretically predicted variance of the estimate of VSTM capacity, $\hat{K}$, measured across participants in the three different conditions of Experiment 1: (1) 2AFC single-probe change detection with a liberal guessing strategy, (2) 2AFC single-probe change detection with a conservative guessing strategy, and (3) the new 2AUCF single-probe change detection with a conservative guessing strategy. Error bars indicate standard errors of the means across participants.

Figure 5. The mean observed and theoretically predicted variance of the estimate of VSTM capacity, $\hat{K}$, measured across participants for memory displays with 6, 8, and 12 items in Experiment 2. Error bars indicate standard errors of the means across participants.

0.89), 2.96 ($SD = 1.2$), and 3.07 ($SD = 1.6$), respectively, and the guessing rates were estimated to be .67 ($SD = .16$), .68 ($SD = .13$), and .63 ($SD = .19$), respectively. Repeated measures ANOVAs showed no effect of memory display size on the K estimates ($F < 1$) and a marginally significant effect on P_{gy} [$F(1,3) = 3.8458, p = .057, \eta_p^2 = .0898, p_{rep} = .868$].

For each participant, we then calculated 10 estimates of K for blocks of 20 trials (10 present and 10 absent trials) within each memory set size (6, 8, and 12 items). Thus, as in Experiment 1, N_T was equal to 10 (cf. Equation 4). Then the sample variances across the 10 estimates of K were calculated for each set size. The average results across participants for both observed and predicted variances of K estimated by Equation 4 are shown in Figure 5. A repeated measures ANOVA yielded a significant effect of display size [$F(1,39) = 43.094, p < .0001, \eta_p^2 = .525, p_{rep} > .999$] on the observed variance of $\hat{K}$. Pairwise comparisons showed significant differences for all pairs of display sizes.

The goodness of fit was calculated as the correlation between individually observed and predicted variances of the K estimates and equaled .77. We ran Monte Carlo simulations using the individually estimated values of K and P_{gy} across all trials in order to compare our observed measure of goodness of fit with the distribution of predicted correlations, given the present sample of participants in the experiment and the number of trials run (using Equations 3 and 4). The expected correlation in the Monte Carlo simulations was found to be equal to .78 ($SD = .051$), again very close to our observed correlation between predicted and observed variances of $\hat{K}$.

Finally, we compared estimates of VSTM capacity K between Experiments 1 and 2 in the standard 2AFC change detection condition with eight items to be remembered. This gave us an estimate of the reliability of the estimates

for testing the same participant on different days. The correlation coefficient between the two estimates of K when eight stimuli were to be remembered was .87 [$t(18) = 7.609, p < .0001, d = 3.587, p_{rep} > .999$]. A paired t test yielded no significant difference between the estimates from the two experiments [$t(19) = 0.0277, p = .978$].

Despite the high correlation found both within Experiment 1 and between Experiments 1 and 2, we would like to emphasize that there is always a relative benefit of reducing the variance of $\hat{K}$ using the new 2AUC paradigm. The absolute reduction in the variance of $\hat{K}$ may not be large when many trials are run, as was the case when we estimated K across all 200 trials in Experiments 1 and 2. However, it is generally desirable to reduce the number of trials per condition to a minimum, so that further conditions may be included in an experiment. Also, at the individual level, getting more precise estimates of K by minimizing the variance of $\hat{K}$ is an important consideration.

GENERAL DISCUSSION

Summary

In this article, we first derived closed-form formulas for the theoretical variance of estimates for VSTM capacity K in standard single-probe change detection. The theoretically derived values of the variance closely predict corresponding observed variances in $\hat{K}$ when measured repeatedly in the same individual.

Second, we showed that the variance of estimates of K can be reduced by about 50% by using a new two-alternative *unforced-choice* version of the single-probe change detection paradigm. In this new paradigm, the participant is not forced to respond “change” or “no change” but is allowed to refrain from guessing by responding “don’t know.”

Third, we showed that the guessing strategy of the participants influences the variance of $\hat{K}$ in the standard single-probe change detection paradigm. The variance was minimized when participants adopted a conservative guessing strategy and was maximized when participants guessed “change” and “no change” with equal probabilities.

Finally, we manipulated the number of items to be remembered in single-probe change detection and showed that the variance of the estimates of K increased strongly with the number of items to be remembered. The increase in the variance of $\hat{K}$ with memory set size was again very well predicted by our theoretical derivations.

Recommendations

Three straightforward recommendations for optimizing reliability when measuring VSTM capacity by change detection follows from the present work: (1) Use the new 2AUC paradigm rather than a standard 2AFC change detection paradigm; (2) use a memory set size which is as small as possible but is still above the VSTM capacity of the participant; and (3) instruct the participant to adopt a conservative guessing strategy, responding “change” or “no change” only when he or she is fairly certain that the response is correct.

Extensions

Our methods of analysis can be extended to paradigms other than change detection. A case in point is the change localization paradigm introduced by Luck and his collaborators (e.g., Gold et al., 2006, Experiment 5). In this paradigm, one of N_S items changes on each trial, and the participant must report which item changed, guessing whenever unsure. By the model proposed by Gold et al., the probability of correct report, p , equals $(K + 1)/N_S$. This model makes the strong assumption that all items in VSTM are compared with the corresponding items in the changed display without any errors being made. When the assumptions of the model are satisfied, K can be estimated by $N_S \hat{p} - 1$, where $\hat{p}$ is the observed proportion of correct responses. By the methods of analysis employed in this article, the variance of this estimate for K can be shown to equal

$$V(\hat{K}) = \frac{(N_S - K - 1)(K + 1)}{N},$$

where N is the total number of trials. Thus, the variance of the estimate for K is comparable to the variance obtained with our 2AFC single-probe change detection paradigm when the total number of trials (given by N and $2N_T$, respectively) is the same for the two paradigms and guessing rates are low in the change detection paradigm.

AUTHOR NOTE

This research was supported by grants from the Danish Council for Strategic Research to S.K., from the Danish Research Council for the Humanities to C.B. and S.K., and from the University of Copenhagen to C.B. and S.K. We thank Steven Luck, Nelson Cowan, Ed Awh, and two anonymous reviewers for helpful comments on an earlier version of the manuscript and Malene Foldager and Kristine Swierkosz Kristensen for assisting with the data collection. Correspondence concerning this article should be addressed to S. Kyllingsbæk, Center for Visual Cognition, Department of Psychology, University of Copenhagen, Øster Farimagsgade 2A, DK-1353 Copenhagen K, Denmark (e-mail: sk@psy.ku.dk).

REFERENCES

- ALVAREZ, G. A., & CAVANAGH, P. (2004). The capacity of visual short-term memory is set both by visual information load and by number of objects. *Psychological Science*, **15**, 106-111. doi:10.1111/j.0963-7214.2004.01502006.x
- AWH, E., BARTON, B., & VOGEL, E. K. (2007). Visual working memory represents a fixed number of items regardless of complexity. *Psychological Science*, **18**, 622-628. doi:10.1111/j.1467-9280.2007.01949.x
- BAYS, P. M., & HUSAIN, M. (2008). Dynamic shifts of limited working memory resources in human vision. *Science*, **321**, 851-854. doi:10.1126/science.1158023
- BUNDESEN, C. (1990). A theory of visual attention. *Psychological Review*, **97**, 523-547.
- BUNDESEN, C., HABEKOST, T., & KYLLINGSBÆK, S. (2005). A neural theory of visual attention: Bridging cognition and neurophysiology. *Psychological Review*, **112**, 291-328. doi:10.1037/0033-295X.112.2.291
- CATTELL, J. M. (1885). Ueber die Zeit der Erkennung und Benennung von Schriftzeichen, Bildern und Farben [The time it takes to recognize and name letters, pictures, and colors]. *Philosophische Studien*, **2**, 635-650.
- COWAN, N. (2001). The magical number 4 in short-term memory: A reconsideration of mental storage capacity. *Behavioral & Brain Sciences*, **24**, 87-185.
- COWAN, N., ELLIOTT, E. M., SAULTS, J. S., MOREY, C. C., MATTOX, S., HISMJATULLINA, A., & CONWAY, A. R. A. (2005). On the capacity of attention: Its estimation and its role in working memory and cognitive aptitudes. *Cognitive Psychology*, **51**, 42-100. doi:10.1016/j.cogpsych.2004.12.001
- ENG, H. Y., CHEN, D., & JIANG, Y. (2005). Visual working memory for simple and complex visual stimuli. *Psychonomic Bulletin & Review*, **12**, 1127-1133.
- GOLD, J. M., FULLER, R. L., ROBINSON, B. M., MCMAHON, R. P., BRAUN, E. L., & LUCK, S. J. (2006). Intact attentional control of working memory encoding in schizophrenia. *Journal of Abnormal Psychology*, **115**, 658-673. doi:10.1037/0021-843X.115.4.658
- LUCK, S. J., & VOGEL, E. K. (1997). The capacity of visual working memory for features and conjunctions. *Nature*, **390**, 279-281. doi:10.1038/36846
- OLSSON, H., & POOM, L. (2005). Visual memory needs categories. *Proceedings of the National Academy of Sciences*, **102**, 8776-8780. doi:10.1073/pnas.0500810102
- PASHLER, H. (1988). Familiarity and visual change detection. *Perception & Psychophysics*, **44**, 369-378.
- PHILLIPS, W. A. (1974). On the distinction between sensory storage and short-term visual memory. *Perception & Psychophysics*, **16**, 283-290.
- ROUDER, J. N., MOREY, R. D., COWAN, N., ZWILLING, C. E., MOREY, C. C., & PRATTE, M. S. (2008). An assessment of fixed-capacity models of visual working memory. *Proceedings of the National Academy of Sciences*, **105**, 5975-5979. doi:10.1073/pnas.0711295105
- SCOLARI, M., VOGEL, E. K., & AWH, E. (2008). Perceptual expertise enhances the resolution but not the number of representations in working memory. *Psychonomic Bulletin & Review*, **15**, 215-222.
- SHIBUYA, H., & BUNDESEN, C. (1988). Visual selection from multielement displays: Measuring and modeling effects of exposure duration. *Journal of Experimental Psychology: Human Perception & Performance*, **14**, 591-600.
- SERLING, G. (1960). The information available in brief visual presentations. *Psychological Monographs*, **74** (Whole No. 498).
- SERLING, G. (1963). A model for visual memory tasks. *Human Factors*, **5**, 19-31.
- SERLING, G. (1967). Successive approximations to a model for short term memory. *Acta Psychologica*, **27**, 285-292.
- TODD, J. J., & MAROIS, R. (2004). Capacity limit of visual short-term memory in human posterior parietal cortex. *Nature*, **428**, 751-754. doi:10.1038/nature02466
- VOGEL, E. K., & AWH, E. (2008). How to exploit diversity for scientific gain. *Current Directions in Psychological Science*, **17**, 171-176.
- VOGEL, E. K., & MACHIZAWA, M. G. (2004). Neural activity predicts individual differences in visual working memory capacity. *Nature*, **428**, 748-751. doi:10.1038/nature02447
- VOGEL, E. K., WOODMAN, G. F., & LUCK, S. J. (2001). Storage of features, conjunctions, and objects in visual working memory. *Journal of Experimental Psychology: Human Perception & Performance*, **27**, 92-114.
- WINER, B. J., BROWN, D. R., & MICHELS, K. M. (1991). *Statistical principles in experimental design*. New York: McGraw-Hill.
- ZHANG, W., & LUCK, S. J. (2008). Discrete fixed-resolution representations in visual working memory. *Nature*, **453**, 233-235. doi:10.1038/nature06860

NOTES

1. All accuracy data (proportions of correct responses) were arcsine [$2\arcsin(\sqrt{p})$] transformed to stabilize the variances before the ANOVAs were performed (see Winer, Brown, & Michels, 1991, pp. 354-358).
2. One participant completed the first experiment only.

APPENDIX A

Variances of the Estimates of VSTM Capacity K in 2AFC and 2AUC Single-Probe Change Detection

The variance of the estimate $\hat{K}$ of VSTM capacity K can be derived if we assume that the number of hit trials out of a total of N_T change trials is binomially distributed with parameters $n = N_T$ and $p = P(H)$, and the number of false alarm trials out of N_T no-change trials is binomially distributed with parameters $n = N_T$ and $p = P(FA)$. From

$$V(\hat{K}) = V(N_S [\hat{P}(H) - \hat{P}(FA)]) = N_S^2 [V(\hat{P}(H)) + V(\hat{P}(FA))],$$

$$V(\hat{P}(H)) = V\left(\frac{N_H}{N_T}\right) = \frac{P(H)[1 - P(H)]}{N_T},$$

and

$$V(\hat{P}(FA)) = V\left(\frac{N_{FA}}{N_T}\right) = \frac{P(FA)[1 - P(FA)]}{N_T},$$

we get

$$\begin{aligned} V(\hat{K}) &= N_S^2 \frac{P(H)[1 - P(H)] + P(FA)[1 - P(FA)]}{N_T} \\ &= N_S^2 \frac{[K/N_S + (1 - K/N_S)P_{gy}][1 - K/N_S - (1 - K/N_S)P_{gy}] + [(1 - K/N_S)P_{gy}][1 - (1 - K/N_S)P_{gy}]}{N_T} \\ &= \frac{(N_S - K)[K + 2P_{gy}(1 - P_{gy})(N_S - K)]}{N_T}. \end{aligned}$$

The variance of the estimate of VSTM capacity, K , in 2AUC single-probe change detection can be derived in a similar way. From

$$\begin{aligned} V(\hat{K}) &= V(N_S [\hat{P}(H) - \hat{P}(FA) + \hat{P}(CR) - \hat{P}(M)] / 2) \\ &= \frac{1}{4} N_S^2 [V(\hat{P}(H) - \hat{P}(M)) + V(\hat{P}(CR) - \hat{P}(FA))], \end{aligned}$$

$$\begin{aligned} V(\hat{P}(H) - \hat{P}(M)) &= V\left(\frac{N_H}{N_T}\right) + V\left(\frac{N_M}{N_T}\right) - 2\text{Cov}\left(\frac{N_H}{N_T}, \frac{N_M}{N_T}\right) \\ &= \frac{P(H)[1 - P(H)]}{N_T} + \frac{P(M)[1 - P(M)]}{N_T} + 2 \frac{P(H)P(M)}{N_T}, \end{aligned}$$

and

$$\begin{aligned} V(\hat{P}(CR) - \hat{P}(FA)) &= V\left(\frac{N_{CR}}{N_T}\right) + V\left(\frac{N_{FA}}{N_T}\right) - 2\text{Cov}\left(\frac{N_{CR}}{N_T}, \frac{N_{FA}}{N_T}\right) \\ &= \frac{P(CR)[1 - P(CR)]}{N_T} + \frac{P(FA)[1 - P(FA)]}{N_T} + 2 \frac{P(CR)P(FA)}{N_T}, \end{aligned}$$

we get

$$\begin{aligned} V(\hat{K}) &= \frac{N_S^2}{4N_T} \{P(H)[1 - P(H)] + P(M)[1 - P(M)] + 2P(H)P(M) \\ &\quad + P(CR)[1 - P(CR)] + P(FA)[1 - P(FA)] + 2P(CR)P(FA)\} \\ &= \frac{N_S^2}{4N_T} \{[K/N_S + (1 - K/N_S)P_{gy}][1 - K/N_S - (1 - K/N_S)P_{gy}] \\ &\quad + [(1 - K/N_S)P_{gn}][1 - (1 - K/N_S)P_{gn}] + 2[K/N_S + (1 - K/N_S)P_{gy}][(1 - K/N_S)P_{gn}] \\ &\quad + [K/N_S + (1 - K/N_S)P_{gn}][1 - K/N_S - (1 - K/N_S)P_{gn}] + [(1 - K/N_S)P_{gy}][1 - (1 - K/N_S)P_{gy}] \\ &\quad + 2[K/N_S + (1 - K/N_S)P_{gn}][(1 - K/N_S)P_{gy}]\} \\ &= \frac{(N_S - K)[K + N_S(P_{gy} + P_{gn}) - (N_S - K)(P_{gy} - P_{gn})^2]}{2N_T}. \end{aligned}$$

APPENDIX B
Proofs That Estimators of VSTM Capacity K in 2AFC and 2AUFC
Single-Probe Change Detection Are Unbiased

Given the same assumptions as when we derive the variance of the estimates in Appendix A, the corresponding expected values of $\hat{K}$ may be derived for both the 2AFC and 2AUFC paradigms. From

$$E(\hat{K}) = E\left(N_S [\hat{P}(H) - \hat{P}(FA)]\right) = N_S [E(\hat{P}(H)) - E(\hat{P}(FA))],$$

$$E(\hat{P}(H)) = E\left(\frac{N_H}{N_T}\right) = \frac{1}{N_T} E(N_H) = \frac{1}{N_T} N_T P(H) = P(H),$$

and

$$E(\hat{P}(FA)) = E\left(\frac{N_{FA}}{N_T}\right) = \frac{1}{N_T} E(N_{FA}) = \frac{1}{N_T} N_T P(FA) = P(FA),$$

we get

$$E(\hat{K}) = N_S [K/N_S + (1 - K/N_S)P_{gy} - (1 - K/N_S)P_{gy}] = N_S [K/N_S] = K.$$

Thus, $\hat{K}$ is an unbiased estimator of K .

The expected values of the estimate for VSTM capacity $\hat{K}$ in 2AUFC single-probe change detection can be derived in a similar way. From

$$\begin{aligned} E(\hat{K}) &= E\left(\frac{1}{2} N_S [\hat{P}(H) - \hat{P}(FA) + \hat{P}(CR) - \hat{P}(M)]\right) \\ &= \frac{1}{2} N_S [E(\hat{P}(H)) + E(\hat{P}(FA)) + E(\hat{P}(CR)) - E(\hat{P}(M))], \end{aligned}$$

$$E(\hat{P}(H)) = E\left(\frac{N_H}{N_T}\right) = \frac{1}{N_T} E(N_H) = \frac{1}{N_T} N_T P(H) = P(H),$$

$$E(\hat{P}(FA)) = E\left(\frac{N_{FA}}{N_T}\right) = \frac{1}{N_T} E(N_{FA}) = \frac{1}{N_T} N_T P(FA) = P(FA),$$

$$E(\hat{P}(CR)) = E\left(\frac{N_{CR}}{N_T}\right) = \frac{1}{N_T} E(N_{CR}) = \frac{1}{N_T} N_T P(CR) = P(CR),$$

and

$$E(\hat{P}(M)) = E\left(\frac{N_M}{N_T}\right) = \frac{1}{N_T} E(N_M) = \frac{1}{N_T} N_T P(M) = P(M),$$

we get

$$\begin{aligned} E(\hat{K}) &= \frac{1}{2} N_S [K/N_S + (1 - K/N_S)P_{gy} - (1 - K/N_S)P_{gy} + K/N_S + (1 - K/N_S)P_{gn} - (1 - K/N_S)P_{gn}] \\ &= \frac{1}{2} N_S [2K/N_S] = K. \end{aligned}$$

Again, $\hat{K}$ is an unbiased estimator of K .