
Index

- 1310 nm wavelength band, 383
- 14XX nm pump laser diodes, 121
- 14XX nm pumps, 135
- 40 Gb/s Raman-amplified transmission, 673
- 40 Gb/s bit rate systems, 396
- 40 Gb/s terrestrial transmission, 701

- A figure of merit (FOM), 364
- absorption coefficients, 430
- accelerated aging tests, 127
- acoustic phonons, 325
- acousto-optic modulator, 711
- all-optical cross-connects, 596
- all-optical mesh networking, 596
- all-optical terrestrial system, 627
- all-optical transmission, 627
- all-Raman amplifier, 445, 621
- all-Raman system, 17, 627
- AllWave, 681
- amplified spontaneous emission (ASE), 10, 308, 491, 711
- amplitude shift key(-ed) (-ing), 711
- analytical expression, 576
- anti-Stokes scattering, 38
- arrayed waveguide grating (AWG), 334
- arrhenius relationship, 128
- ASE–ASE beat noise, 524
- attenuation, 317

- backward pumping, 458
- backward Raman pumping, 62
- backward spontaneous Raman noise level, 62
- banded bidirectional signal traffic, 280
- banded schemes, 255

- band-limited phase-shaped binary transmission, 711
- bandwidth-limited PSBT (BL-PSBT), 688
- beat noise, 92
- beat noise variances, 522
- beat-noise limited receivers, 522
- BER measurements, 584
- bidirectional pumping, 135
- bidirectional systems, 459
- bidirectional transmission, 253
- bit error rate (BER), 310, 711
- bit error rate test set, 711
- bit rate scaling, 530
- Boltzmann factor, 38
- booster amplifier, 346
- Bose–Einstein distribution, 12, 456
- Bose–Einstein factor, 101
- Bragg grating stabilized laser diodes, 616
- Brightness Theorem, 355
- butterfly laser module, 125

- cable television, 27
- capture fraction, 44
- carrier injection efficiency, 124
- carrier-suppressed return-to-zero (CSRZ), 479, 511, 711
- carrier-suppressed RZ (CSRZ), 686
- cascaded Raman fiber laser (RFL), 194, 353, 385
- cascaded Raman oscillator, 29
- cascaded Raman resonator, 354
- cavity design, 357
- C-band, 5, 301
- channel launch powers, 569

- channel power management, 574
- channel power transients, 581
- chi-squared distribution, 502
- chromatic dispersion, 602, 676
- cladding-pump fiber lasers, 9
- cladding-pumped fiber (CPF), 355
- classical treatments, 43
- closed loop control system, 322
- coherence time, 493
- complex susceptibility, 51
- constant output power mode, 324
- conventional band of EDFA
 - (~1530 to 1565 nm), 711
- copumped Raman amplifier, 213
- copumping, 135, 343
- corner frequency, 222
- Corning DSF, 115
- Corning LEAF, 115
- Corning NZ-DSF, 115
- Corning SMF-28, 373
- cost metric, 445
- cost-per-transmitted-bit, 673
- counter-pumped Raman amplifiers, 213
- counter-pumping, 135
- counterpropagating pump, 2
- counterpropagating pumping, 310
- counterpumping, 343
- coupled mode equations, 454
- critical launch power, 570
- critical power, 39
- crossgain modulation, 231, 235, 267
- cross-phase modulation, 711
- cross-phase modulation
 - (XPM), 304, 315, 589
- crosstalk ratio, 514

- DCF, 3, 681
- decibel/nanometer scale, 575
- degrades system performance, 569
- degree of polarization (DOP), 512
- degrees of birefringence, 512
- dense wavelength-division-
 - multiplex(-ed) (-ing), 711
- dense wavelength-division-
 - multiplexing (DWDM), 673
- dense WDM, 627
- depolarizer, 146
- device-under-test, 517
- dielectric thin film interference filters, 143

- differential group delay (DGD), 678, 711
- differential phase-shift-key(-ed) (-ing), 711
- discrete or lumped Raman am-
 - plifier (LRA), 1, 30, 301
- dispersion, 162, 301
- dispersion compensation, 303
- dispersion curvature, 161
- dispersion map, 628
- dispersion slope, 317
- dispersion slope compensation, 161
- dispersion slope compensation ratio, 165
- dispersion slope-compensation, 447, 449
- dispersion-compensating Ra-
 - man amplifiers, 186
- dispersion-compensating fiber
 - (DCF), 3, 161, 304, 711
- dispersion-compensating
 - module (DCM), 711
- dispersion-compensating mod-
 - ules (DCM), 679
- dispersion-managed fiber, 384
- dispersion-managed solitons, 627
- dispersion-shifted fibers, 463
- distributed feedback laser, 711
- distributed feedback lasers (DFB), 506
- distributed Raman amplification, 338
- distributed Raman amplifier (DRA), 1, 452
- distributed Raman transmission, 383
- DMS, 627
- double Rayleigh backscattering (DRBS), 304
- double Rayleigh scattering (DRS), 2, 10
- double-heterostructure (DH) laser, 122
- double-Rayleigh backscatter (DRBS), 385
- Double-Rayleigh backscattering, 83
- DPSK (differential phase-shift keying), 669
- DRBS crosstalk, 340
- DRS crosstalk, 459
- dual-band hybrid Raman/EDFAs, 694
- dual-order Raman fiber lasers, 377
- duobinary, single/vestigial side-
 - band modulation, 686
- dynamic gain equalizer, 448, 711

- east-west (EW), 280
- EDFA/Raman amplifier combinations, 445
- EDFA/Raman HA, 413
- effective area, 3, 43, 711
- effective length, 24
- effective mode area, 196

- effective noise figure (ENF), 95, 385
- effective Rayleigh reflection coefficient, 25
- effective upper-state lifetime, 348
- elastic scattering, 502
- ELEAF, 681
- electrical beat-noise measurement, 516
- electrical noise figure, 458
- electrical spectrum analyzer, 174, 517
- electrical time-division-
 - multiplex (-ed) (-ing), 711
- electronic regeneration, 627
- electronically sweeping the wavelength, 62
- end-of-life margin, 483
- energy transfer due to SRS, 573
- engineering design rules, 445
- enhanced phase-shaped bi-
 - nary transmission, 711
- Enhanced PSBT (EPSBT), 687
- epoxy pigtailling, 307
- equipartition energy, 643
- equivalent noise figure, 285
- erbium-doped silica fiber: EDSF, 418
- erbium-doped fiber ampli-
 - fier (EDFA), 1, 301, 711
- external-cavity lasers (ECL), 506

- Fabry–Perot laser, 139, 458
- fast interactions, 569
- fast tunable laser, 66
- fast-gain dynamics, 97, 213
- Fiber Bragg Grating laser, 137
- fiber Bragg gratings (FBG), 353
- fiber nonlinearity, 491, 602
- fiber selection, 600
- field autocorrelation, 497
- figure of merit for the Ra-
 - man amplifier fiber, 317
- fine-tuned dispersion, 447
- first-order backward pumped
 - configuration, 284
- first-order PMD, 678
- fluoride, 30, 306
- fluoride EDF (erbium-doped flu-
 - oride fiber: EDFF, 418
- fluoride or multicomponent silicates, 304
- fluoro-zirconate (ZBLAN), 306
- forward error correction (FEC), 310, 688, 711
- forward pumped unidirec-
 - tional transmission, 266
- forward pumping, 458
- Fourier transform, 497
- four-wave mixing (FWM), 303, 314
- four-wave-mixing (FWM), 79, 589, 711
- frequency domain, 494
- frequency modulation (dithering), 157
- frequency-division-multiplexed, 596
- frequency-swept pumping, 468
- full-width at half-maximum, 711
- fundamental 3 dB noise limit, 45
- fused-fiber coupler, 143

- gain compression term, 263
- gain equalizer (GEQ), 417, 448
- gain feedback, 70
- gain flatness, 66
- gain saturation, 317
- gain slope, 324
- gain spectrum, 2
- gain tilt, 324, 576
- gain-flattening filter (GFF),
 - 311, 448, 694, 711
- gain-shifted EDFA, 418
- Gaussian pulse shapes, 531
- Gaussian-like, 502
- GeO₂-based fibers, 204
- germanium doping, 52
- germano–silicate fiber, 29
- germanosilicate, 194
- Gordon–Haus effect, 648
- graded index separate confinement
 - heterostructure strained layer
 - multiple quantum well structure
 - with buried heterostructure, 122
- grating-stabilized lasers, 458
- GRIN-SCH strained layer MQW
 - structure with BH structure, 122
- group-velocity dispersion, 711
- guiding filters, 661

- heavy metal oxide glasses, 53
- high germanium doping, 161
- high P₂O₅-doped optical fibers, 199
- high pump power laser diodes, 9
- high slope dispersion-compensating
 - fiber (HSDK), 363
- higher-order pumping, 468
- higher-order Raman pumping, 284

- high-slope dispersion-
 - compensating fiber, 711
- homogeneous-like, 320
- hybrid amplifier (HA), 1, 413
- hybrid bidirectional amplification, 274
- hybrid bidirectional scheme, 255
- hybrid pump, 140
- Hybrid Raman/EDFA amplifiers, 617
- hybrid TDFA/Raman amplifier, 342, 440
- hybrid tellurite/silica fiber
 - Raman amplifier, 206
- hybrid tellurite/silica Raman amplifiers, 440

- imbalanced Mach–Zehnder
 - interferometers, 143
- inband crosstalk, 492
- incoherent homodyne detection, 334
- indium gallium arsenide, 305
- indium gallium arsenide phosphide, 305
- indium phosphide, 305
- InGaAsP/InP GRIN-SCH strained
 - layer MQW structure, 121
- inhomogeneous gain saturation, 320
- inline amplifier, 329, 413
- Inner Grating Multimode laser, 140
- insertion loss, 274
- integrated circuit, 711
- integrated dispersion compensation, 348
- intensity autocorrelation, 497
- interband stimulated Raman scattering, 328
- interchannel crosstalk, 267
- interchannel interference, 305
- interchannel nonlinear effects, 683
- interference noise, 92
- interferers, 491
- interleaved bidirectional scheme, 254
- International Telecommu-
 - nications Union, 711
- Internet, 595
- intersymbol interference, 305
- intradband stimulated Raman scattering, 453
- intrachannel cross-phase mod-
 - ulation (IXPM), 544
- intrachannel four-wave mixing (IFWM), 544
- inverse dispersion fiber, 711
- isolators, 431

- jitter-killer, 656
- Jones matrix, 506

- Kerr nonlinearity, 538

- Landsberg–Mandelstam effect, 35
- laser module structure, 125
- L-band, 5, 301
- lightwave communication systems, 491
- LiNbO₃ modulator, 313
- linear noise characteristics, 91
- link design value (LDV), 679, 711
- log-linear loss spectrum, 575
- long distance telephony, 596
- long repeater spacing, 622
- long-haul, 1, 445
- long-wavelength band of EDFA
 - (~1570 to 1605 nm), 711
- Lorentzian laser lineshape, 497
- Lorentzian lineshape, 71
- low degree of polarization (DOP), 135
- low-loss splices, 362
- low-noise preamplifier, 616
- LS fiber, 571
- Lucent Allwave, 115
- Lucent TrueWave, 115
- lumped Raman amplifiers, 338

- Mach–Zehnder modulator, 711
- Mach–Zehnder interferometers, 448
- Maple mathematics, 635
- material dispersion, 162
- maximum RIN transfer, 214
- Maxwellian probability density function, 678
- MBE (molecular beam epitaxy), 122
- MCVD technique, 199
- mechanical splicing, 307
- metropolitan optical network, 306
- microelectromechanical sys-
 - tems (MEMS), 448
- midstage loss, 389
- MOCVD (metal organic chemi-
 - cal vapor deposition), 122
- mode partitioning noise (MPN), 157
- modulation technique, 447
- MPI crosstalk, 340
- MPI–MPI beat noise, 502, 524
- Müller matrices, 512
- multicomponent silicate (MCS), 30
- multipath interference (MPI), 119, 304
- multiple interfering fields, 499
- multiple path interference (MPI), 136

- multiple reflections, 602
- multiple Stokes shifts, 356
- multiple wavelength Raman fiber lasers, 365
- multiple-order pump sources, 354
- multiple-order RFLs, 353
- multiple-wavelength RFLs, 353
- multiple-path interference (MPI), 491, 711
- mutually incoherent, 506

- narrowband HA (NB-HA), 413
- ND-FWM, 282
- NDSF, 115
- net effective coding gain, 711
- new wavelength bands, 26
- noise figure, 12, 46, 305
- noise power spectral density, 495
- noise-induced frequency shifts, 648
- nondegenerate FWM, 282
- nondispersion shifted fiber, 711
- nondispersion-shifted fiber (NDSF), 227
- nonlinear distortion, 91
- nonlinear impairments, 180
- nonlinear index of refraction, 603
- nonlinear interactions, 36
- nonlinear penalty, 1
- nonlinear refractive index, 37
- nonlinear Schrödinger (NLS) equation, 629
- nonreturn-to-zero, 686, 711
- non-return-to-zero (NRZ), 310
- nonzero dispersion fiber, 711
- nonzero dispersion-shifted fiber (NZ-DSF), 64, 226

- on-off keyed data transmission, 676
- on-off keying (OOK), 511
- on-off Raman gain, 421
- open-loop operation, 320
- optical add/drop, 306
- optical add-drop multiplexers, 448
- optical confinement factor, 124
- optical cross-connects, 448
- optical interleaver, 711
- optical noise figure, 458
- optical parametric amplifiers, 303
- optical phonon, 2, 325
- optical signal-to-noise ratio (OSNR), 79, 347, 711
- optical spectrum analyzer (OSA), 114, 517
- optical switch, 712

- optical time domain reflectometry (OTDR), 170
- optical time-division-multiplex(-ed) (-ing), 712
- optical time-division-multiplexed (OTDM), 674
- optical time-domain extinction technique, 519
- optical–electrical–optical (O-E-O), 596
- optimized modulation formats, 685
- OSNR budget, 580
- OSNR penalty, 529
- out-of-band crosstalk, 492
- out-of-band forward error correction, 310

- parametric amplifier, 37
- parametric interactions, 303
- path delay, 493
- path-average noise, 644
- path-average power, 605
- path-average pump powers, 71
- path-average signal power, 67, 644
- pattern dependent crosstalk, 585
- pattern-dependent Raman gain, 267
- periodic-group-delay-complemented dispersion compensation, 663
- phase difference, 493
- phase matching, 303
- phase mismatch, 630
- phase-shaped binary transmission, 686, 712
- phase-shift-key(-ed) (-ing), 712
- phonon population factor, 430
- phonon-stimulated optical noise, 11
- phosphorous-doped fiber, 451
- phosphorus doping, 53
- phosphosilicate Raman fibers, 194
- photosensitivity, 196
- Placzek model, 40
- planar lightwave circuit (PLC), 143
- Planck’s constant, 38
- PMD coefficient, 678
- Poincaré sphere, 512
- Poisson distributed, 93
- polarization beam combiner (PBC), 144
- polarization controller (PC), 517
- polarization dependence, 4, 52
- polarization evolution, 506
- polarization interleaving, 268
- polarization mode dispersion, 712

- polarization mode dispersion (PMD), 145, 602, 678
- polarization multiplexing, 324
- polarization-dependent gain (PDG), 324
- polarization-dependent loss (PDL), 396, 602, 712
- polarization-division-multiplex(-ed) (-ing), 712
- polarization-interleav(-ed) (-ing), 712
- polarization-mode dispersion, 447
- polarized Raman scattering, 44
- power conversion efficiency, 19
- power partitioning, 367
- power spectral density, 240
- power transients, 583
- preamplifier, 346
- principal state of polarization, 712
- probability density function (PDF), 500
- profile dispersion, 162
- pseudorandom bit sequence (PRBS), 240, 712
- pulse arrival times, 648
- pump depletion, 112, 263, 320
- pump efficiency, 384
- pump laser diodes, 121
- pump–pump interactions, 453
- pump–signal RIN transfer, 459
- pump–signal walk-off, 267
- pumping efficiency, 7
- pump-mediated crosstalk, 240
- pump-mediated intersymbol interference (ISI), 267
- pump-mediated signal crosstalk, 385
- pump-to-pump Raman interaction, 76
- pump-to-signal noise transfer, 385
- pure silica core fiber (PSCF), 571
- pure silica-core fiber (PSCF), 712
- pure-silica core, 115

- Q* scaling relationship, 389
- Q*-factor, 712
- Q*-factor-based MPI tolerance factor, 528
- Q*-spectra, 347
- quality factor (*Q*), 228, 339
- quantum approach, 37

- Raman efficiency, 569
- Raman enhanced fiber (RF), 363
- Raman fiber lasers, 353
- Raman figure of merit, 182
- Raman frequency shift, 196
- Raman gain coefficient, 45, 51, 195
- Raman gain efficiency coefficient (C_R), 114
- Raman gain spectrum, 51
- Raman gain tilt, 17
- Raman oscillator wavelength shifters, 29
- Raman pumping unit, 149
- Raman response function, 50
- Raman scattering, 35
- Raman scattering cross-section, 41
- Raman threshold, 569
- Raman-aided Brillouin scattering, 271
- Raman-assisted repeatered transmission, 384
- rare earth-doped cladding-pumped fiber laser (CPFL), 354
- rare earth-doped fiber amplifiers, 303
- Rayleigh backscatter coefficient, 503
- Rayleigh loss coefficient α_r , 339
- Rayleigh scattering, 502
- Rayleigh scattering loss, 503
- Rayleigh scattering of ASE, 102
- recapture fraction, 503
- receiver noise sources, 92
- receiver sensitivity, 383
- recirculating loop, 480
- recirculating transmission loop, 691
- Reed–Solomon, 712
- Reed–Solomon (RS) code, 688
- Reed–Solomon 255/239, 315
- relative dispersion slope, 164, 449, 712
- relative intensity noise (RIN), 135, 498
- reliability, 126
- repeater spacing, 600
- repeaterless transmission systems, 573
- required OSNR, 525
- resolution bandwidth, 712
- responsivity, 93
- return-to-zero, 686, 712
- return-to-zero (RZ), 511
- return-to-zero differential phase shift keying (RZ-DPSK), 511
- return-to-zero differential-phase-shift-key(-ed) (-ing), 712
- reverse dispersion fiber, RDF, 227
- revived interest, 9
- RFL pump module, 354
- RIN transfer, 221
- ring amplifier, 27
- round-trip gain, 505

- RS (255, 239), 689
- RS (255,223), 689
- rule of thumb, 673
- RZ differential-phase-shift-keying (RZ-DPSK), 686
- S+ bands, 309
- same relative dispersion slope, 683
- S-band, 26, 301
- S-band lumped Raman amplifier (SLRA), 310
- S-band Raman amplifiers, 301
- seamless and wideband HA (SWB-HA), 413
- seamless transmission bands, 161
- second-order Raman pumping, 284
- selecting transmission fibers, 591
- self-phase modulation (SPM), 314, 712
- semiconductor laser diodes, 385
- semiconductor optical amplifier (SOA), 30, 303
- sequential pulsing, 62
- short upper-state lifetime, 10
- shot noise, 91
- Shott noise limited, 45
- signal preemphasis, 462, 465
- signal-ASE beat noise, 524
- signal-MPI beat noise, 502, 524
- Signal-pump-signal crosstalk, 267
- signal-spontaneous beat noise, 46, 340
- signal-to-noise (SNR), 92
- signal-to-noise ratio, 1, 45, 451
- signal-to-signal crosstalk, 112
- signal-to-signal crosstalk mediated by the pump, 245
- silica fiber, 309
- single-mode fiber (SSMF), 571
- single-pass analytic models, 259
- single-sided spectral density, 497
- slope efficiency, 356
- slope-compensating fibers, 449
- slow interactions, 569
- small effective area, 161
- small-scale inhomogeneities, 502
- SMART pump, 65
- soliton propagation, 383
- soliton transmission, 598
- Soliton-Soliton Collisions, 649
- splice loss spectral variation, 317
- splice losses, 363
- split-band augmentation strategy, 348
- splitband configuration, 447
- spontaneous Brillouin scattering, 511
- spontaneous emission factor, 11
- spontaneous noise factor, 13
- spontaneous Raman noise, 81
- spontaneous Raman scattering, 37
- spontaneous-spontaneous beat noise, 46
- spontaneously generated photons, 570
- SRS dynamic crosstalk, 331
- SRS-induced transients, 585
- SSMF, 681
- standard single-mode fiber (SSMF), 310, 712
- states of polarization (PSP), 678
- static gain equalizers, 448
- statistical nature, 590
- stimulated Brillouin scattering, 325
- stimulated Raman scattering, 35, 38, 712
- stimulated Raman threshold, 39
- stochastic electrodynamics, 48
- Stokes scattering, 38
- Stokes vector, 512
- super large area fiber, 712
- superposition rule, 131
- tapered fiber bundle, 355
- TDFA/Raman amplifier, 413
- telecommunications, 1
- telegraph, 596
- tellurite, 449
- tellurite/silica Raman amplifier, 413
- Tellurite-based glasses, 205
- temperature dependence, 100, 430
- temperature-dependent ASE, 104
- temperature-dependence of noise figure, 611
- temperature-dependence of the chromatic dispersion, 677
- temporal fluctuations, 374
- temporal gain ripple, 77
- temporal lens, 656
- Teralight fiber, 698
- terrestrial applications, 595
- terrestrial links, 338
- terrestrial optical transmission systems, 673
- terrestrial systems, 600
- thermal distribution of phonons, 112
- thermal management, 150
- thermal noise, 340
- thermal occupation number, 48
- thermally induced phonon noise, 462

- thermoelectric cooler (TEC), 122
- third-order Raman pumping, 286
- third-order susceptibility, 49
- threshold of catastrophic damage, 196
- thulium-doped fiber amplifier (TDFA), 30, 304
- time delay, 37
- time domain, 494
- time domain picture, 49
- time modulation of the pumps, 461
- time response of the Raman effect, 213
- time-division-multiplex(-ed) (-ing), 712
- time-division-multiplexed (TDM), 305, 674
- time-division-multiplexing, 61, 446
- time-multiplexed pumping, 470
- total launch power, 571
- transit time, 218, 348
- transition rate, 37
- transmission fibers, 569
- transparent photonic networks, 585
- transverse mode mixing, 491
- triangular profile, 574
- TrueWave[®] classic (TW) fiber, 571
- TrueWave[®] REACH, 681
- TrueWave[®] RS, 363, 681
- two-component model, 48
- two-path interference, 495
- two-stage Raman amplifier, 320
- two-way signal traffic, 253
- Type-1 SWB-HA, 434
- Type-2 SWB-HA, 435
- Type-3 discrete SWB-HA, 437
- Type-4 discrete SWB-HA, 437

- ultralonghaul submarine, 595
- ultra-long-haul (ULH), 1, 595
- ultra-long-haul fiber-optic transmission systems, 445
- UltraWave[™] IDF, 681

- UltraWave[™] SLA, 681
- undepleted pump approximation, 99
- unidirectional and bidirectional optical transmission, 253
- unidirectional transmission lines, 253
- unintended generation of SRS, 569

- VAD technique, 199
- variable optical attenuator (VOA), 277
- variance of the depletion, 589
- vestigial sideband (VSB), 474, 712
- vibrational mode, 2, 35, 309
- voice traffic, 595

- walk-off, 215
- waveguide, 306
- waveguide dispersion, 162
- waveguide grating router (WGR), 690, 712
- wavelength add-drop devices, 596
- wavelength agnostic, 14
- wavelength converters, 306
- wavelength-division-multiplex(-ed) (-ing), 712
- wavelength-division-multiplexed (WDM), 301, 447
- wavelength-division-multiplexed (WDM) pumping, 121
- WDM backbone networks, 674
- WDM couplers, 142
- WDM transients, 243
- west-east (WE) transmission, 280
- Wide Sense Stationary linear stochastic process, 240
- wideband amplifiers (WBAs), 445
- Wiener-Khintchine theorem, 497

- Yb-doped, 355

- zero dispersion wavelength, 303
- zero-point fluctuations, 48

Springer Series in OPTICAL SCIENCES

New editions of volumes prior to volume 70

- 1 **Solid-State Laser Engineering**
By W. Koechner, 5th revised and updated ed. 1999, 472 figs., 55 tabs., XII, 746 pages
- 14 **Laser Crystals**
Their Physics and Properties
By A.A. Kaminskii, 2nd ed. 1990, 89 figs., 56 tabs., XVI, 456 pages
- 15 **X-Ray Spectroscopy**
An Introduction
By B.K. Agarwal, 2nd ed. 1991, 239 figs., XV, 419 pages
- 36 **Transmission Electron Microscopy**
Physics of Image Formation and Microanalysis
By L. Reimer, 4th ed. 1997, 273 figs. XVI, 584 pages
- 45 **Scanning Electron Microscopy**
Physics of Image Formation and Microanalysis
By L. Reimer, 2nd completely revised and updated ed. 1998,
260 figs., XIV, 527 pages

Published titles since volume 70

- 70 **Electron Holography**
By A. Tonomura, 2nd, enlarged ed. 1999, 127 figs., XII, 162 pages
- 71 **Energy-Filtering Transmission Electron Microscopy**
By L. Reimer (Ed.), 1995, 199 figs., XIV, 424 pages
- 72 **Nonlinear Optical Effects and Materials**
By P. Günter (Ed.), 2000, 174 figs., 43 tabs., XIV, 540 pages
- 73 **Evanescant Waves**
From Newtonian Optics to Atomic Optics
By F. de Fornel, 2001, 277 figs., XVIII, 268 pages
- 74 **International Trends in Optics and Photonics**
ICO IV
By T. Asakura (Ed.), 1999, 190 figs., 14 tabs., XX, 426 pages
- 75 **Advanced Optical Imaging Theory**
By M. Gu, 2000, 93 figs., XII, 214 pages
- 76 **Holographic Data Storage**
By H.J. Coufal, D. Psaltis, G.T. Sincerbox (Eds.), 2000
228 figs., 64 in color, 12 tabs., XXVI, 486 pages
- 77 **Solid-State Lasers for Materials Processing**
Fundamental Relations and Technical Realizations
By R. Iffländer, 2001, 230 figs., 73 tabs., XVIII, 350 pages
- 78 **Holography**
The First 50 Years
By J.-M. Fournier (Ed.), 2001, 266 figs., XII, 460 pages
- 79 **Mathematical Methods of Quantum Optics**
By R.R. Puri, 2001, 13 figs., XIV, 285 pages
- 80 **Optical Properties of Photonic Crystals**
By K. Sakoda, 2001, 95 figs., 28 tabs., XII, 223 pages
- 81 **Photonic Analog-to-Digital Conversion**
By B.L. Shoop, 2001, 259 figs., 11 tabs., XIV, 330 pages
- 82 **Spatial Solitons**
By S. Trillo, W.E. Torruellas (Eds.), 2001, 194 figs., 7 tabs., XX, 454 pages
- 83 **Nonimaging Fresnel Lenses**
Design and Performance of Solar Concentrators
By R. Leutz, A. Suzuki, 2001, 139 figs., 44 tabs., XII, 272 pages
- 84 **Nano-Optics**
By S. Kawata, M. Ohtsu, M. Irie (Eds.), 2002, 258 figs., 2 tabs., XVI, 321 pages
- 85 **Sensing with Terahertz Radiation**
By D. Mittleman (Ed.), 2003, 207 figs., 14 tabs., XVI, 337 pages

Springer Series in
OPTICAL SCIENCES

- 86 **Progress in Nano-Electro-Optics I**
Basics and Theory of Near-Field Optics
By M. Ohtsu (Ed.), 2003, 118 figs., XIV, 161 pages
- 87 **Optical Imaging and Microscopy**
Techniques and Advanced Systems
By P. Török, F.-J. Kao (Eds.), 2003, 260 figs., XVII, 395 pages
- 88 **Optical Interference Coatings**
By N. Kaiser, H.K. Pulker (Eds.), 2003, 203 figs., 50 tabs., XVI, 504 pages
- 89 **Progress in Nano-Electro-Optics II**
Novel Devices and Atom Manipulation
By M. Ohtsu (Ed.), 2003, 115 figs., XIII, 188 pages
- 90 **Raman Amplifiers for Telecommunications**
By Mohammed N. Islam, 2004, 508 figs., XXX, 740 pages