

References and Further Reading

Signal Integrity, Transmission Lines, Electronics:

- [1] Eric Bogatin, “Signal Integrity – Simplified”, Prentice Hall, 2004, ISBN 0-13-066946-6
- [2] Howard Johnson, Martin Graham “High-Speed Digital Design”, Prentice Hall, 1993, ISBN 0-13-395724-1
- [3] Howard Johnson, Martin Graham, “High-Speed Signal Propagation” Prentice Hall, 2003, ISBN 0-13-084408-X
- [4] Stephen H. Hall, Garrett W. Hall, James A. McCall, “High-Speed Digital System Design” John Wiley & Sons, Inc., 2000, ISBN 0-471-36090-2
- [5] Brian Young, “Digital Signal Integrity: Modeling and Simulation with Interconnects and Packages”, Prentice Hall PTR, 2001, ISBN 0-13-028904-3
- [6] Stephen G. Konsowski, Arden R. Helland, “Electronic Packaging of High Speed Circuitry”, McGraw-Hill, 1997, ISBN 0-07-035970-0
- [7] William R. Blood, Jr., “MECL System Design Handbook”, Fourth Edition, Motorola Inc., 1988
- [8] Paul Horowitz, Winfield Hill, “The Art of Electronics”, Second Edition, Cambridge University Press, 1989
- [9] Lee W. Ritchey, “Differential Signaling Doesn’t Require Differential Impedance”, Printed Circuit Design Magazine, March 1999
- [10] Agilent Technologies, Inc., “Differential Trace Design Rules: Truth vs. Fiction”, UltraCAD Design, Inc., and Mentor Graphics Corp., 2002
- [11] Jiayuan Fang, Jin Zhao, “Low Impedance Power Delivery over Broad Frequencies”, Printed Circuit Design & Manufacture, Sept. 2003
- [12] Howard Johnson, “Diode Terminations”, Online Newsletter Vol. 2, Issue 19, July 1998, at www.signalintegrity.com
- [13] Howard Johnson, “Rise Time of Lossy Transmission Lines”, EDN Magazine, Oct 2003

Oscilloscopes & Probes:

- [14] Ian Hickman, "Oscilloscopes" (5th edition), Newnes, 2001, ISBN 0-7506-4757-4
- [15] Ian Hickman, "Digital Storage Oscilloscopes", Newnes, 1997, ISBN 0-7506-2856-1
- [16] "ABCs of Probes", Tektronix Application Note 60W-6053-8, Jan 2004
- [17] "XYZ of Oscilloscopes", Tektronix Application Note 03W-8605-2, May 2001
- [18] Nihal Kularatna, "Digital and Analogue Instrumentation", The Institution of Electrical Engineers, 2003, ISBN 0-85296-999-6
- [19] Mark Burns, Gordon W. Roberts, "An Introduction to Mixed-Signal IC Test and Measurement", Oxford University Press, 2001, ISBN 0-19-514016-8
- [20] Agilent Technologies, "Understanding Oscilloscope Frequency Response and Its Effect on Rise-Time Accuracy", Application Note 1420, 2002
- [21] Dan Strassberg, "Getting the Most from Wideband Scopes – Dos and Don'ts", EDN Magazine, Feb 2005
- [22] Richard Van Epps, Sheri McMasters, "High-Speed Probing for Superior Signal Fidelity", Tektronix Application Note
- [23] Andy Frost, Don Whiteman, Jason Tsai, "Are You Measuring Your Circuit or Your Scope Probe", Agilent Technologies Applications Note, 2000

Statistics & Mathematics:

- [24] W. J. DeCoursey, "Statistics and Probability for Engineering Applications", Newnes (Elsevier Science), 2003, ISBN 0-7506-7618-3
- [25] Richard G. Lyons, "Understanding Digital Signal Processing", Second Edition, Pearson Education, 2004, ISBN 0-13-108989-7
- [26] William H. Press, Saul A. Teukolsky, William T. Vetterling, Brian P. Flannery, "Numerical Recipes in C", Second Edition, Cambridge University Press, 1992
- [27] Tektronix, "CSA/11000 Series Statistical Measurements", Technical Note 47W-7973, 1991
- [28] James R. Andrews, "Deconvolution of System Impulse Responses and Time Domain Waveforms", Picosecond Pulse Labs Application Note AN-18, Nov. 2004

Noise:

- [29] Joshua Israelsohn, "Noise 101", EDN Magazine, Jan 2004
- [30] Dan Seslar, "Opamp Noise and Stability", Texas Instruments Presentation, 2004
- [31] Chris Bowick, "RF Circuit Design", Appendix B: "Noise Calculations", Newnes, 1982, ISBN 0-7506-9946-9

Jitter Measurement:

- [32] Osvaldo Buccafusca, "Back to Test & Measurement Basics: Jitter Measurements", Test & Measurement World, August 2004, download from www.tmworld.com/jitter-tutorial
- [33] Bernd Laquai, "Spectral Error Density Analysis – A New Approach to Identify Jitter Sources in SOC Devices", Test & Measurement World, June 23, 2003, download from www.tmworld.com/SOCjitter
- [34] Tom Waschura, "Using a BER Tester to Make the Fastest Eye Diagram, Mask Template, and Jitter Tests", Application Note SR-TN028, SyntheSys Research, Inc., Jan 2003
- [35] Andy Kuo, Touraj Farahmand, Roberto Rosales, Sassan Tabatabaei, Andre Ivanov, "Bounded Uncorrelated Jitter (BUJ) Characterization Platform for High-Speed Interconnects", IEEE Design and Test of Computers, 2005
- [36] Sassan Tabatabaei, Michael Lee, Freddy Ben-Zeev, "Jitter Generation and Measurement for Test of Multi-Gbps Serial IO"
- [37] T. Yamaguchi et al., "Effects of Deterministic Jitter in a Cable on Jitter Tolerance Measurements", International Test Conference, 2003, pp. 58-66
- [38] "Measuring Jitter in Digital Systems", Agilent Technologies, Application Note 1448-1
- [39] J. Wilstrup, "A Method of Serial Data Jitter Analysis Using One-Shot Time Interval Measurements", International Test Conference, 1998, pp. 819-823
- [40] J. Quirk, "Measuring Deterministic Jitter with a Scope", Communication Systems Design, July 2002, pp. 26-33
- [41] Slobodan Milijevic, "Jitter Generation and Measurement with Off-the-shelf Test Equipment", Zarlink Inc.
- [42] "Jitter Analysis: Correlation: Measurement Techniques, Measurement Methods, Measurement Equipment, Mask Testing, Comparing Results", Tektronix Application Note, Jan 2003
- [43] Art Porter, "Serial-Data Constraints Define Scope-Memory Depth", EDN Magazine, April 2004
- [44] "Using the Architecture of the Tektronix 11801A Oscilloscope to Make Precise Jitter Measurements on Waveforms", Tektronics Inc. White Paper, 1998
- [45] "Measuring Random Jitter on a Digital Sampling Oscilloscope", Maxim Application Note HFAN-04.5.1, Rev 0, Aug 2002
- [46] John B. Rettig, Laszlo Dobos, "Picosecond Time Interval Measurements", IEEE Transactions on Instrumentation and Measurement, vol. 44, no. 2, April 1995
- [47] Steven D. Draving, "How Accurate Are Your Jitter Measurements?", DesignCon 2003
- [48] "Measure Error Rates Quickly and Accurately", Tektronix Technical Brief, 1998
- [49] Mike McTigue, "Single-Ended or Differential? That Is the Question", EDN Magazine, Feb 2003
- [50] Mike Tranchemontagne, "Making Timing Measurements on Differential Clock Signals", Tektronix Application Note, 1996

- [51] Bradley J. Thompson, "Got the Time? An Introduction to Time Measurements", Test & Measurement World, Jan 1999
- [52] "Jitter Analysis Techniques Using an Agilent Infiniium Oscilloscope", Agilent Product Note, Oct 2002
- [53] Nelson Soo, "Jitter Measurement Techniques", Pericom Application Brief AB36, Nov 2000
- [54] Richard A. Quinnell, "Resolving Jitter Measurement Variations", Test & Measurement World, Jan 2004
- [55] Martin Rowe, "Measure Jitter Three Ways: BER Testers, Jitter Analyzers, and Oscilloscopes All Play Key Roles in Communications Testing", Test & Measurement World, Jan 2003
- [56] Steve Fraash, Russ Cook, Mike Li, "Use of Compliant Clock Recovery in Serial Data Test Application", 2nd IEEE International GHz/Gbps Test Workshop, Nov. 2005

Jitter Analysis:

- [57] "Understanding and Characterizing Jitter", Tektronix Application Note 55W-16146-0, Tektronix, Inc., October 2002
- [58] "Jitter Analysis 101", Seminar Handouts, Wavecrest Corp., 2000
- [59] Ransom Stephens, "The Rules of Jitter Analysis", <http://www.analogzone.com/nett0927.pdf>, 2004
- [60] Ransom Stephens, "Analyzing Jitter at High Data Rates", IEEE Communications Magazine, vol. 42, no. 2, Feb. 2004
- [61] Yoshitaka Takasaki, "Digital Transmission Design and Jitter Analysis", Artech House, 1991, ISBN 0-89006-503-9
- [62] Andy Kuo, Touraj Farahmand, Nelson Ou, Sassan Tabatabaei, Andre Ivanov, "Jitter Models for the Design and Test of High-Speed (Gb/s) Serial Interconnects", IEEE Design and Test of Computers, vol. 21, no. 4, Jul-Aug 2004, pp. 302-313
- [63] Y. Cai, S.A. Werner, G.J. Zhang, M.J. Olsen, R.D. Brink, "Jitter Testing for Multi-Gigabit Backplane SerDes – Techniques to Decompose and Combine Various Types of Jitter", International Test Conference, 2002, pp. 700-709
- [64] "Jitter Analysis: The Dual-Dirac Model, RJ/DJ, and Q-Scale", White Paper, Agilent Technologies, Feb. 2005
- [65] T. Yamaguchi, M. Soma, "Extraction of Peak-to-Peak and RMS Sinusoidal Jitter Using an Analytical Signal Method", IEEE VLSI Test Symposium, 2000, pp. 395-402
- [66] M.P. Li, J. Wilstrup, R. Jessen, D., Petrich, "A New Method for Jitter Decomposition Through Its Distribution Tail Fitting", International Test Conference, 1999, pp. 788-794
- [67] "Jitter Separation – 50 Mb/s to Over 40 Gb/s Using the Agilent 86100C Infiniium DCA-J", Agilent Technologies White Paper, 2004
- [68] "An Introduction to Jitter in Communication Systems", Maxim Application Note 1916, March 2003
- [69] Martin Miller, "Transition Density: What Does It Affect and Why Is It Explicitly Specified within the LeCroy SDA?", LeCroy Technical Brief, Jan 2005

- [70] Martin Miller, "Six Tales of RJ and DJ or a Discussion of Which Measurement Approach Is Best Adapted to Specific Needs", LeCroy Technical Brief, 2005
- [71] Martin Miller, "Total Jitter Measurement through the Extrapolation of Jitter Histograms", LeCroy Technical Brief, Jan 2005
- [72] Martin Miller, "The Difference between Edge-to-Reference and Edge-to-Edge Jitter Analysis", LeCroy Technical Brief, Jan 2005
- [73] Martin Miller, "A Simple Method for Estimation of True Jitter for Period, Skew, Half-Period and Cycle-Cycle Jitter", LeCroy Technical Brief, Jan 2005
- [74] "Jitter Analysis: DJ Analysis; DJ and ISI Measurement Floor", Tektronix Application Note
- [75] "Jitter Analysis: Accuracy, Resolution, Jitter Noise Floor, Delta Time Accuracy", Tektronix Application Note, Mar 2003
- [76] "Jitter Analysis: Algorithms: Period Jitter, Cycle-to-Cycle Jitter, Frequency Jitter, Time Interval Error, General Measurements, Clock-Data Measurements, Calculating Statistics", Tektronix Application Note, Jan 2003
- [77] "Understanding and Performing Precise Jitter Analysis", Tektronix Application Note 55W-13769-1, Feb 2004
- [78] Aaron Schultz, "Random Jitter – What Is Really Going On?", EDTN France, Feb 2002
- [79] Mike Story, "Timing Errors and Jitter", dCS Ltd., Oct. 1998, Issue 2
- [80] "Analyzing Jitter Using a Spectrum Approach", Tektronix Application Note 55W-15631-0, March 2002
- [81] "Delta-Time Accuracy: The Good, the Bad, and the Worst Case", Tektronix Application Note 55W-13565-0, Oct 2002
- [82] "Comparing High-Precision Real-Time Jitter Analysis to Equivalent-Time Jitter Analysis", Amherst System Associates Application Note, Oct 2004
- [83] Michael Fleischer-Reumann, "Integrated Evaluation of Jitter", Agilent Technologies Applications Note, 2000
- [84] "Understanding Jitter", Wavecrest Application Note, 2001
- [85] Dan Strassberg, "Eyeing Jitter – Shaking Out Why Signals Shake", EDN Magazine, May 2003
- [86] Guy Foster, "Anatomy of an Eye Diagram – a Primer", Application Note SR-TN0033, SyntheSys Reasarch, Inc., Oct 2004
- [87] "Histograms Simplify Jitter Analysis of Random Jitter", Agilent Application Note AN 1200-9, 1998 & 2000
- [88] Guy Foster, "Look for Jitter in a Bathtub", Test & Measurement World, Dec 2003/Jan 2004

Frequency Domain Measurements:

- [89] "Spectrum Analysis: Amplitude & Frequency Modulation", Hewlett Packard Application Note 150-1
- [90] "Spectrum Analyzer Measurements and Noise", Agilent Application Note 1303, Feb 2003
- [91] "Phase Noise to Jitter Conversion", Fordahl Application Note AN-02-3, www.fordahl.com
- [92] "Jitter Measurement Using Integrated Phase Noise 1: Fundamentals", Toric Limited, 2003, www.toric.co.uk
- [93] I. Zamek, "Crystal Oscillators' Jitter Measurements and its Estimation of Phase Noise", IEEE International Frequency Control Symposium, 2003
- [94] J. McNeill, "A Simple Method for Relating Time- and Frequency Domain Measures of Oscillator Performance", Proceedings of the 2001 IEEE Southwest Symposium on Mixed Signal Design, Feb 2001
- [95] R. Poore, "Phase Noise and Jitter", Agilent Application Note, 2001
- [96] B. Drahlkis, "Calculate Oscillator Jitter by Using Phase-Noise Analysis", Microwave & RF, Jan & Feb 2001
- [97] Aeroflex, "PN9000 Automated Phase Noise Measurement System Application Note #1", download from www.aeroflex.com, 2003
- [98] Aeroflex, "PN9000 Automated Phase Noise Measurement System Application Note #2", download from www.aeroflex.com, 2003
- [99] "Phase Noise Measurement Using the Wavecrest Digital Timing System", Wavecrest Corp. Application Note No. 130, 2001
- [100] "Spectral Analysis: Analyzing a Signal Spectrum", Tektronix Application Note 55W-15429-0, Jan 2002

Index

- 8b/10b encoding 96, 149, 168
- accuracy 18, 26, 35, 39, 43, 46, 47, 49, 50, 56, 57, 84, 88, 104, 115, 116, 136, 189, 191, 195, 197, 199, 202, 203, 205, 214, 216
 - timing 184, 202
- ADC 44, 46, 47, 58
- aliasing 59, 62, 140, 203
- amplifier 41, 43, 47, 49, 67, 69, 71, 76, 78, 123, 133, 195, 213, 218
 - limiting 183
- amplitude 2, 3, 4, 5, 6, 7, 13, 14, 27, 28, 31, 42, 43, 44, 49, 56, 57, 65, 66, 67, 68, 69, 71, 74, 84, 91, 95, 101, 102, 131, 134, 135, 138, 139, 152, 182, 186, 191, 207, 212, 214, 215, 218, 221
- amplitude error 59
- arbitrary waveform generator 182
- attenuation 10, 27, 58, 59, 60, 78, 84, 86, 94, 98, 102, 103, 117, 196, 217, 219
- attenuator 41, 43, 47, 49, 102, 103
- averaging 42, 44, 49, 114, 115, 116, 120, 121, 122, 175, 176, 197, 198, 199, 215, 216, 221
 - exponential 216
- AWG 182
- Balun 83, 92, 93, 195
- bandwidth 4, 6, 7, 9, 10, 14, 15, 16, 23, 29, 31, 33, 42, 47, 49, 50, 58, 59, 60, 61, 65, 67, 68, 70, 73, 76, 77, 78, 82, 83, 86, 88, 89, 91, 92, 94, 98, 100, 101, 102, 103, 104, 116, 117, 119, 120, 121, 122, 137, 138, 139, 144, 181, 182, 183, 189, 190, 195, 197, 202, 207, 214, 218, 221
 - 3 dB 10, 13, 15, 23, 59, 60, 117, 121
 - analog 53, 56, 63
 - digital 61, 62, 63
 - equivalent 77, 121
 - filter 3, 13, 15, 16, 57, 70, 94, 211
 - loop 126

- signal 3, 13, 16, 26, 27, 66, 70, 117, 137
- system 101, 117, 218, 219
- bandwidth limitation 144
- bathub plot 150, 151, 152, 155, 158, 180, 184, 185
- beat frequency 214
- BER 53, 54, 148, 150, 151, 152, 155, 156, 161, 162, 163, 173, 175, 180, 184, 185, 205, 206
- BERT 50, 53, 54, 55, 64, 66, 153, 156, 158, 167, 169, 173, 180, 185, 189, 206
- Bessel 209
- bias level 98
- bias tee 98, 99, 100
- bias voltage 5, 98
- bin 107, 108, 109, 203, 218
 - width 107
- bit error rate 36, 38, 53, 54, 78, 122, 138, 148, 149, 150, 152, 157, 206
- bit error rate tester 53, 54
- bit interval 122, 125, 127, 150, 151, 152, 184, 201
- bit pattern 7, 46, 173, 176, 186
- bit period 52, 54, 95, 126, 151, 153, 154, 174, 198, 202, 203, 204
- bit rate 8, 140, 141, 153, 181
- bit sequence 53, 167, 169
- bit stream 7, 140, 148, 153, 156, 167, 168, 174, 176, 183, 187, 205, 206, 207
 - pseudo-random 7, 53, 80, 96, 167
- cable 11, 13, 14, 16, 18, 20, 22, 27, 28, 29, 30, 31, 66, 69, 70, 72, 74, 75, 76, 79, 84, 85, 86, 87, 88, 89, 91, 101, 103, 182, 196, 218
 - coaxial 15, 22, 26, 28, 29, 30, 34, 35, 75, 84, 87
 - low-loss 42
- capacitance 18, 19, 22, 23, 24, 25, 26, 27, 33, 34, 66, 69, 70, 72, 76, 84, 95, 99
- parasitic 23, 24, 28, 38, 67, 68, 69, 70, 99, 102, 137
- probe 69, 71, 73, 97
- capacitor 21, 40, 94, 95, 96, 97, 98, 99, 101
- capture range 125
- carrier 6, 207, 209, 210, 211, 213, 214
- CDF 109, 110, 129, 130, 131, 132, 152, 205, 207
- clock 6, 7, 9, 11, 19, 26, 29, 50, 64, 80, 95, 96, 123, 124, 125, 126, 127, 128, 141, 142, 149, 153, 154, 155, 164, 167, 169, 170, 174, 181, 182, 190, 191, 195, 196, 197, 198, 199, 203, 204, 205, 207, 208, 209, 212
 - embedded 125, 154
 - recovered 125, 126
- clock domain 203
- clock recovery 123, 125, 126, 127, 181
- CML 95, 97
- CMRR 78
- coherent undersampling 203
- common mode rejection 78, 79
- comparator 35, 41, 51, 53, 55, 56, 199, 200, 202, 204
- confidence interval 112, 113, 150, 162
- confidence level 132
- connector 11, 13, 22, 23, 68, 88, 89, 91
 - 1.0 mm 89
 - 1.85 mm 89
 - 2.4 mm 89, 91

- 2.92 mm 89
- 3.5 mm 89, 91
- BNC 89
- coaxial 88, 89
- SMA 67, 89
- Type-N 89
- convolution 148, 159, 218
- coupling 33, 34, 35, 74, 75, 96, 209
 - AC 79, 94, 95, 96, 99, 100, 168
 - DC 100
- critically damped 72
- crosstalk 11, 33, 34, 39, 82, 136, 141, 147, 157, 178, 210
- cumulative density function 109, 110, 129, 130, 131
- damping 71, 72
- data rate 7, 8, 10, 47, 49, 54, 55, 80, 124, 125, 140, 141, 156, 158, 184, 212, 220
- data stream 6, 8, 10, 51, 52, 53, 54, 55, 64, 95, 96, 100, 122, 123, 124, 125, 126, 127, 130, 135, 141, 142, 143, 144, 145, 146, 147, 150, 153, 154, 155, 156, 158, 159, 162, 167, 169, 170, 171, 173, 174, 187, 205, 212
- DC balanced 79, 95, 96, 100, 168, 169
- DC bias 99, 101
- DC block 98, 100
- DC blocking 94
- DC resistance
 - probe 69, 70
- DCD 142
- DDJ 144
- decomposition 4, 5, 9, 56
- deconvolution 173, 174, 175, 220
- delay 15, 17, 18, 21, 22, 23, 26, 27, 35, 49, 52, 59, 60, 66, 79, 87, 88, 93, 97, 103, 117, 183, 193, 195, 196, 197, 198, 219
 - group 14, 15, 65, 94
 - time 65
- delay line 42, 50, 80, 103, 104, 183
- delta function 143, 145, 217, 218
- derivative 14, 110, 129, 131, 186, 220
- des skew 35, 80, 194
- dielectric 18, 30, 88, 91
 - foamed 87
- differential 33, 38, 77, 81, 83, 92, 143
- differential pair 33, 34, 88, 103
- digital signal processing 58, 63, 215, 217
- digital tester 55
- digitizer 58, 105, 215
- diode clamps 35
- discontinuity 89
 - impedance 144
- dispersion 15, 30, 59, 60, 89
- distortion 9, 10, 14, 15, 18, 23, 27, 58, 59, 86, 89, 93, 94, 103, 145, 174, 196, 202, 218
- distributed 19, 66, 102, 199
- distribution 29, 30, 64, 85, 109, 110, 114, 115, 127, 132, 135, 140, 141, 149, 150, 151, 159, 161, 162, 163, 165, 171, 173, 174, 175, 202, 206
- bimodal 140, 143, 161, 162, 163, 165
- continuous 109, 110, 159
- current 86
- discrete 108, 146, 159
- Gaussian 82, 111, 112, 113, 114, 115, 121, 132, 137, 148, 150, 163, 165, 166, 171, 182, 202, 203, 212, 215

- jitter 121, 141, 144, 146, 148, 150, 159, 184, 212
- Poisson 156
- spectral 172
- timing 147, 157, 205
- drift 115, 125, 139, 181, 216
- driver 2, 25, 27, 66, 67, 70, 82, 86, 94, 95, 97, 99, 100, 116, 139, 143, 144, 147, 174, 186, 195
- DSP 216, 217, 221
- dual-Dirac model 178, 180
- duty cycle 95, 96, 100, 147, 167, 174, 176, 177
- duty cycle distortion 81, 142, 143, 144, 146, 147, 155, 161, 170, 173, 174, 183, 202
- duty cycle effect 147, 176
- ECL 97, 100
- edge 9, 10, 12, 13, 14, 17, 24, 30, 31, 41, 42, 44, 46, 51, 52, 54, 56, 60, 64, 70, 72, 116, 118, 119, 121, 124, 125, 127, 128, 129, 130, 132, 134, 140, 145, 147, 150, 151, 152, 153, 158, 161, 169, 170, 171, 172, 174, 176, 177, 184, 192, 195, 196, 198, 200, 202, 205, 206, 216
- edge placement accuracy 202, 204
- edge shape 10, 13, 14, 17, 30, 31, 192
- edge-centered strobing 124
- edge-to-edge 127, 196
- edge-to-reference 127
- effect
 - data dependent 82, 83, 163, 197, 202, 205
- electromagnetic emissions 33, 35
- EMI 31, 34, 82
- EPA 202
- equivalent timing 205
- error
 - data dependent 174
- estimate
 - differential jitter 83
 - inductance 73
 - jitter 134, 162, 175, 185
 - margin 151
- extrapolation 180, 184, 185
- eye diagram 80, 152, 153, 154, 155, 156, 169, 174, 180
- eye opening 155, 184
- Fast Fourier Transformation 2
- feedback 93, 167, 168, 214
- ferrite choke 76
- FET 25, 27, 97, 147
- FFT 2, 57, 118, 211, 220
- filter 3, 11, 13, 14, 15, 16, 17, 18, 23, 44, 56, 57, 58, 59, 60, 70, 71, 72, 94, 95, 98, 119, 120, 191, 210, 211
 - absorptive 94
 - bandpass 210, 213
 - Bessel 15, 94
 - Butterworth 14, 15, 58, 60
 - Chebyshev 14, 15, 58, 60
 - exponential 58
 - Gaussian 15, 17, 56, 58, 60, 94, 117, 120
 - high-pass 94, 99
 - low-pass 11, 13, 15, 16, 17, 23, 24, 25, 31, 58, 62, 72, 94, 121, 182, 183, 214
 - one-pole 14
 - reflective 94
 - rise time 94
 - two-pole 14
- filter rise time 13, 16, 17
- Fourier series 140, 209
- Fourier transformation 1, 2, 3, 9, 56, 62, 140, 172, 207, 218

- frequency 58, 137, 139, 140, 146, 147, 172, 182, 202, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 219
 - clock 9, 140, 141, 209, 212
- frequency component 2, 5, 9, 10, 13, 58, 59, 60, 62, 63, 87, 89, 99, 117, 184, 207, 210, 219
- frequency domain 1, 4, 6, 7, 8, 9, 10, 11, 13, 14, 15, 16, 29, 52, 56, 60, 63, 85, 94, 116, 140, 141, 171, 172, 207, 210, 217, 218, 219, 220, 221
- fundamental 2, 3, 4, 6, 7, 13, 47, 56, 117, 184, 203, 207
- Gaussian 10, 14, 60, 61, 64, 70, 85, 112, 132, 135, 138, 150, 155, 159, 161, 162, 164, 165, 166, 170, 171, 195, 202
- Gibbs phenomenon 118, 216
- ground bounce 33, 141
- harmonics 2, 4, 6, 7, 9, 62, 117, 208, 209, 212
- histogram 106, 107, 108, 109, 110, 147, 155, 158, 159, 163, 166, 170, 171, 172, 173, 174, 175, 180, 182, 193, 194, 206
 - composite 161
 - timing 148
- ideal position 54, 122, 123, 124, 125, 129, 130, 131, 150
- impedance 5, 21, 22, 23, 25, 26, 27, 30, 33, 34, 35, 36, 38, 39, 42, 49, 65, 66, 67, 69, 70, 78, 89, 91, 94, 95, 97, 98, 100, 101, 102, 104, 135, 137, 138
 - characteristic 21, 38, 84
 - differential 34
 - even mode 34
 - odd mode 34
- impedance control 35, 89, 145
- inductance 18, 19, 22, 23, 26, 27, 33, 34, 66, 71, 72, 73, 76, 84, 93, 99
 - loop 72
 - parasitic 23, 24, 71, 72, 73, 93, 102
 - probe 71
- inductor 5, 98, 99
- interference 75
 - electromagnetic 31, 141, 148
 - inter-symbol 146
- interpolation 44, 55, 61, 118, 197, 198, 216, 217
- interpolator 50, 197, 198
- ISI 144, 146
- jitter 64, 81, 83, 122, 132, 133, 135, 140, 148, 154, 155, 173, 174, 183, 192, 225
 - added 135
 - cycle-to-cycle 128
 - data dependent 28, 81, 86, 103, 144, 145, 146, 147, 157, 158, 159, 164, 167, 170, 171, 173, 174, 175, 177, 180, 183, 185, 186, 187
 - deterministic 132, 157, 158, 161, 163, 164, 165, 166, 170, 175, 184, 185, 203, 205, 206
 - differential 81, 82, 83
 - edge-to-edge 127, 181, 196
 - edge-to-reference 127, 181
 - Gaussian 133, 150
 - high-frequency 123, 210, 213
 - instrument 139, 190, 213
 - low-frequency 212
 - non-Gaussian 147
 - peak-to-peak 122, 138, 139, 157, 173, 175, 193, 202, 212

- period 51, 52, 127, 128, 129, 196
- periodic 57, 81, 140, 141, 143, 157, 158, 160, 170, 172, 173, 174, 182, 183, 189, 197, 202, 205, 206, 207, 208, 211, 212, 213, 214
- phase 9, 52, 213, 214
- PLL 181
- random 53, 58, 66, 68, 79, 81, 83, 93, 103, 120, 122, 132, 133, 135, 138, 140, 141, 143, 144, 146, 147, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 169, 170, 171, 172, 173, 174, 180, 182, 183, 184, 185, 195, 198, 199, 201, 202, 204, 205, 206, 207, 209, 210, 211, 212, 215
- received 137
- RMS 138, 155, 202, 211, 212, 214
- single-ended 82, 83
- sinusoidal 140, 141, 214
- strobe 81, 148
- time base 181, 190, 191, 193, 196, 197, 199
- total 148, 159, 161, 162, 163, 169, 170, 178, 210
- trigger 120, 135
- true 172
- true maximum 128
- unbounded 147
- uncorrelated 81, 132, 147, 178, 194
- uncorrelated deterministic 178
- jitter analysis 11, 42, 113, 148, 155, 157, 158, 163, 180, 182, 185, 189, 202
- jitter analysis software 180
- jitter component 11, 129, 159, 171, 172, 173, 174, 175, 182, 183, 185, 207, 211, 212
- jitter display 128
- jitter extraction 157
 - data dependent 174
 - duty cycle distortion 173
 - duty cycle effects 176
 - periodic 172
 - random 170
- jitter floor 192, 195
- jitter generation 123
- jitter histogram 152, 165, 170, 173, 174, 180, 193
- jitter injection 182
- jitter insertion 123, 182, 195, 196
- jitter modeling 170
- jitter reduction 191
- jitter separation 157, 180
- jitter spectrum
 - discrete 145
- jitter tolerance 182
- jitter transfer 123
- jitter trend 52, 128, 140, 172, 180, 182, 212
- jitter types 111, 129
- knee frequency 10
- level 12, 27, 41, 42, 43, 53, 62, 64, 76, 80, 84, 88, 95, 96, 107, 115, 116, 117, 122, 123, 133, 134, 136, 140, 142, 144, 145, 149, 153, 154, 172, 174, 176, 183, 194, 199, 200, 215
- level error 96
- LFSR 167, 168
- linear system 5, 175, 176, 186, 218, 220
- linear-feedback shift register 167, 168
- linearity 79, 198, 202, 204

- time base 191
- Lissajous plot 190, 191
- load
 - active 36
 - current 36
- loss
 - dielectric 16, 30, 31, 32, 84, 85, 86, 87, 88, 89, 116
 - induction 31
 - ohmic 28, 29, 31, 32, 86
 - radiation 31
 - skin effect 29, 31, 32
- lumped 2, 9, 19, 22, 26
- magnetic permeability 29, 87
- Manchester coding 96
- mean value 106, 108, 111, 112, 113, 114, 115, 139, 166, 184, 215, 216
- measurement resolution 141
- mixer 56, 214
- mode
 - common 39, 40, 79, 92
 - even 34, 100
 - non-TEM 30
 - odd 34, 100
 - TEM 30
- modeling 20, 53
- modulation 208, 209, 213
 - phase 172, 209
- modulation depth 208, 209
- moving average 119
- network 21, 97, 100, 102, 103
- network analyzer 221
- noise 12, 49, 52, 65, 66, 67, 68, 74, 75, 76, 78, 79, 105, 114, 115, 116, 119, 121, 133, 134, 135, 137, 138, 139, 153, 155, 159, 176, 182, 187, 192, 193, 194, 195, 198, 215, 216, 219, 220
 - 1/f 136, 139, 140
 - burst 136, 140
 - common 82, 100
 - extrinsic 136
 - induced 75
 - intrinsic 136, 181
 - Johnson 136
 - phase 51, 190, 210, 212, 213, 214
 - popcorn 136, 140
 - power supply 33, 147
 - random 79, 82, 93, 120, 133, 135, 165, 183, 216, 221
 - relative 138
 - sampling 192, 195
 - shot 136, 138, 139, 203
 - thermal 136, 137, 138, 139
 - total 136, 137
 - white 137, 139, 182
- noise floor 213, 214, 221
- noise insertion 183
- noise pickup 74
- noise power 137, 139, 140, 211
- noise thermal 136
- non-return-to-zero 142
- NRZ 142
- Nyquist frequency 62, 63, 140
- Nyquist theorem 62, 118, 207
- odd mode 39
- offset 47, 75, 94, 98, 141, 142, 147, 155, 174, 183, 186
 - DC 2
 - timing 173
- op-amp 93, 133
- oscillator 140, 214
 - crystal 214
- oscilloscope 2, 13, 15, 22, 26, 27, 35, 41, 42, 43, 46, 50, 56, 57, 64, 65, 66, 67, 68, 69, 75, 76, 77, 78, 80, 81, 84, 85, 92, 94, 95, 98, 103, 116, 121, 124, 126,

- 137, 156, 169, 172, 190, 196,
197, 198, 199, 202, 218
- oscilloscope 158
- oversampling 126
- overshoot 8, 14, 15, 35, 52, 94,
118, 135, 156, 175, 176, 181,
187, 217
- parasitics 11, 17, 22, 24, 26, 27,
31, 32, 66, 68, 70, 76, 94, 99,
135, 144
 - capacitive 22
 - inductive 22
- Parseval Theorem 211
- pass band 14, 15
- pattern generator 80, 182
- PCB 18, 28, 33, 35, 39
- PDF 109, 110, 111, 112, 129,
132, 141, 144, 148, 152, 155,
170, 173, 174, 203, 207
- peak-to-peak spread 106, 113,
163, 194
- PECL 97, 100
- period 2, 3, 6, 20, 26, 51, 54, 55,
95, 96, 151, 152, 169, 174, 186,
191, 196, 197, 198, 199, 202,
203, 205, 207, 208, 210
- persistence 154
 - infinite 154
- phase 2
- phase reference 190, 191
- phase shift 217, 219
- phase-locked loop 123, 125, 141,
182
- PLL 125, 126, 127, 141, 181, 210,
212
 - golden 126
 - software 126
- polarity 7, 22, 30, 34, 41, 51, 96,
124, 144, 176
- population 107, 113, 115, 161,
175
- post-trigger 45
- power combiner 92, 183
- power density 139
- power divider 91, 92, 102
- power splitter 91, 92, 100
- PRBS 53, 96, 167, 168, 169, 182
- preshoot 118, 119, 216
- pre-trigger 45
- printed circuit board 11
- probability 109, 110, 111, 112,
114, 120, 130, 131, 132, 138,
140, 145, 149, 150, 151, 152
- probability density function 109,
110, 129, 131, 140, 158
- probability digitizing 203, 205
- probe 11, 15, 22, 25, 27, 49, 65,
66, 67, 68, 69, 70, 71, 72, 73,
74, 75, 76, 77, 78, 97, 98, 137,
139
 - active 22, 68, 70, 76, 77, 78,
98, 137
 - differential 76, 77, 78, 195
 - passive 66, 69
 - single-ended 76, 78
- probe capacitance 102
- probe resistance 69
- probe shield current 75
- probing
 - differential 76, 78
- propagation speed 20, 21, 88
- propagation time 11, 22, 26, 38
- proximity effect 30
- pseudo-random 80
- pulse 6, 51, 123, 146, 177, 197,
198, 217, 218, 219, 220
- pulse width distortion 142
- Q-factor 26, 72
- receiver 26, 34, 35, 38, 53, 54, 67,
84, 86, 94, 97, 102, 124, 125,
126, 127, 130, 133, 135, 137,

- 143, 148, 149, 150, 181, 182, 195
- reflection 11, 17, 21, 22, 23, 24, 25, 27, 31, 33, 35, 36, 37, 38, 39, 65, 66, 67, 69, 70, 71, 91, 94, 97, 102, 119, 133, 135, 144, 145, 146, 157
- reflection coefficient 21, 24
- resistance 5, 28, 29, 39, 69, 71, 72, 86, 137, 139
 - DC 28, 71, 84
 - ohmic 11, 20, 28, 30, 69, 71, 75, 84, 85, 99
- resistor 1, 5, 21, 36, 37, 38, 39, 40, 47, 67, 97, 100, 101, 102, 136, 138
- resolution 46, 47, 49, 50, 52, 54, 56, 104, 105, 107, 114, 143, 146, 154, 172, 195, 197, 200, 201, 202, 203, 204, 207, 208, 210, 212, 215, 216
 - timing 6, 43, 49, 116, 118, 215, 216
- resonance 71, 72, 99, 186
- resonance frequency 71, 99
- response 5, 6, 13, 14, 17, 24, 58, 59, 60, 120, 125, 176, 210, 218, 219, 220
 - filter 14
 - frequency 87, 117
 - Gaussian 117
 - impulse 186, 187, 217, 218, 219, 220
 - loop 125, 126
 - PLL 126
 - step 175, 176, 186, 187, 220
- return path 19, 33, 71, 75
- RF choke 93
- RF generator 195, 214
- ringing 14, 15, 35, 38, 52, 60, 66, 67, 72, 73, 74, 77, 94, 116, 118, 133, 134, 135, 176, 216, 217
- rise time 7, 8, 9, 10, 12, 13, 14, 15, 16, 17, 18, 20, 22, 23, 24, 25, 26, 27, 28, 29, 31, 33, 38, 51, 56, 58, 60, 61, 65, 70, 71, 72, 74, 76, 79, 84, 85, 86, 94, 101, 106, 116, 117, 118, 119, 120, 121, 122, 131, 134, 135, 138, 139, 142, 143, 144, 145, 175, 183, 186, 187, 191, 193, 194, 195, 196, 201, 202, 219, 220
- RJ 132
- RMS 15, 16, 82, 85, 86, 107, 122, 136, 138, 155, 163, 165, 190, 192, 195, 202
- root-mean-square 15, 32, 76, 107, 195, 214
- running disparity 95
- sample interval 61, 204, 216
- sample rate 49, 57, 59, 61, 62, 63, 117, 118, 119, 140, 155, 207
- sample size 106, 112, 113, 198
- sampler 47, 48, 49, 50, 58, 59, 63, 101, 135, 194, 195, 215, 216
- sampling 43, 44, 45, 46, 47, 48, 49, 55, 57, 59, 61, 62, 63, 80, 85, 118, 119, 130, 138, 140, 149, 191, 193, 194, 212, 215
 - equivalent-time 47, 48, 49, 50, 52, 53, 54, 62, 65, 78, 81, 91, 101, 103, 117, 120, 122, 126, 153, 155, 158, 169, 172, 173, 181, 189, 190, 197, 198, 199, 201, 204
 - real-time 43, 45, 46, 47, 49, 50, 52, 57, 62, 118, 120, 124, 126, 128, 153, 155, 156, 158, 169, 172, 180, 189, 197
- sampling rate 46, 47, 48, 49, 57, 63, 118, 120, 126, 172
- sampling strobe 148

- search
 - binary 201, 202
 - linear 200
- serializer 141
- settling 95, 116, 126, 146, 176, 177, 202
- shift register 167
- sideband 6, 208, 209, 213
- signal
 - differential 33, 34, 39, 49, 77, 78, 79, 80, 81, 82, 83, 92
 - reference 127, 154, 191, 196, 214
- signal integrity 11, 30, 31, 34, 35, 38, 39, 47, 53, 91, 137, 156, 201
- signal processing 216
- signal propagation 17
- signal-to-noise ratio 57, 67, 100, 103, 134, 135, 191, 212, 216, 221
- sine wave 2, 4, 5, 7, 29, 62, 182, 191
- single-ended 33, 34, 35, 38, 39, 40, 55, 76, 77, 78, 79, 80, 81, 82, 83, 92, 93, 143, 191
- single-shot 81, 169, 172, 173, 189
- skin depth 86, 87
- skin effect 16, 29, 30, 31, 32, 84, 85, 86, 87, 116
- slew rate 12, 17, 134, 143, 145, 187, 194
- SMA 98
- smoothing 119, 120
- source impedance 23, 69, 70, 71, 97
- source-synchronous strobing 124
- spectral analysis 207
- spectral error density 205, 206, 225
- spectrum 4, 7, 8, 10, 13, 39, 56, 60, 62, 66, 139, 172, 207, 208, 209, 212, 214
 - discrete 4, 6
 - power 211
- spectrum analyzer 4, 5, 56, 57, 95, 171, 172, 175, 182, 207, 208, 210, 212, 213, 214
 - analog 210
- spread 33, 106, 108, 109, 113
- square wave 3, 4, 7, 9, 190, 191, 207, 212
- standard deviation 106, 107, 108, 109, 111, 112, 113, 114, 115, 121, 132, 161, 162, 165, 166, 171, 172, 182, 184, 185, 193, 194, 203
- statistics 52, 105
- step function 143, 220
- stimulus* 5, 186
- strobe 50, 54, 55, 79, 81, 86, 103, 123, 130, 148, 150, 151, 152, 155, 161, 197, 199, 200, 204, 205, 206
- stub 26, 38, 67, 68
- subharmonics 141
- successive approximation 200
- superposition 153, 176
- swing 12, 13, 51, 67, 96, 97, 98, 116, 144, 194
- system under test 11, 53, 65, 66, 67, 68, 69, 71, 72, 74, 75, 85, 102, 115, 126, 157, 167, 182, 190, 195
- tail fit 173, 180
- termination 22, 25, 26, 27, 35, 36, 37, 38, 39, 40, 47, 65, 70, 91, 97, 98, 100, 103, 135
 - differential 38
 - matched 36

- test equipment 5, 27, 35, 36, 38, 39, 50, 97
 - automated 39, 141
- test pattern generation 167
- Thevenin 23, 38, 70, 97, 98, 100
- threshold 12, 17, 41, 50, 51, 52, 53, 55, 78, 86, 94, 116, 131, 133, 134, 136, 142, 144, 152, 155, 172, 174, 176, 200
- threshold level 155
- time base 50, 64, 124, 126, 181, 190, 191, 197
 - precision 190
- time base accuracy 64
- time base error 65, 198
- time base jitter 181, 190, 193, 196, 197, 199
- time base linearity 191
- time base nonlinearity 64, 103, 198
- time constant 11, 13, 15, 17, 18, 23, 25, 38, 67, 72, 95, 96, 100, 147, 214
- time domain 1, 4, 6, 7, 8, 9, 11, 13, 14, 29, 56, 57, 60, 63, 85, 92, 94, 116, 133, 139, 140, 207, 208, 217, 218, 219, 220, 221
- time interval 9, 117, 119, 147, 197, 198, 199, 218
- time interval analyzer 38, 52, 64, 127, 169, 173, 180
- time interval error 127, 128, 129, 196, 197
- time stamper 50, 51, 52, 53, 54, 124, 127, 158
- timing 17, 50, 64, 122, 125, 135, 153, 174
- timing error 24, 28, 60, 135, 140, 144, 145, 161, 175, 187, 197, 198
 - data dependent 29, 40, 84, 145, 146, 167, 169, 170, 181, 182
- timing instant 12
- timing margin 157
- timing reference 64, 103
- timing system 50, 124, 190, 200
- torque wrench 91
- transformer 93, 178
- transition 7, 9, 12, 14, 21, 23, 24, 28, 29, 31, 32, 33, 34, 54, 55, 64, 82, 84, 119, 122, 124, 125, 127, 129, 130, 131, 132, 133, 134, 135, 136, 140, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 162, 169, 175, 176, 177, 185, 186, 187, 192, 193, 194, 199, 201, 205
- transition density 149, 150, 151, 152, 156, 161, 162
- transition probability 131
- transmission coefficient 21, 91
- transmission line 9, 11, 18, 19, 21, 22, 23, 26, 27, 65, 67, 69, 70, 71, 84, 87, 89, 91, 92, 93, 102
 - differential 33
 - ideal 20
 - loss-less 19, 21
 - lossy 27, 182
 - low-loss 103
 - lumped model 19
- transmission path 9, 27, 31, 33, 35, 95, 98, 144, 145, 150, 158, 175, 182, 186
- transmission paths 17, 31
- trigger 41, 42, 43, 44, 45, 46, 48, 49, 50, 51, 64, 78, 80, 91, 103, 124, 126, 127, 133, 134, 135, 154, 197, 198, 199
- trigger jitter 120
- trombone 104, 195
- uncertainty 12
- unit interval 54, 151, 198

variation 14, 105, 106, 114, 115,
132, 166, 173, 181, 198, 216
victim 176, 177
voltage domain 55, 133, 153

wander 95, 122
warm-up 95, 96, 177
wavelength 14, 30, 31, 87, 89
windowing 221