

Index

- 3D integration, 13, 15, 29, 38, 193
- 8B10B, 63, 76, 136

- Agilent Momentum, 195
- asynchronous signaling, 83, 102, 119

- balls, 161, 163, 172
- band-pass filter, 82
- bit error rate (BER), 54, 70, 95, 106, 108, 118, 134, 171, 187
- board capacitors, 143
- bonding, 159
- bootstrapping, 62
- bridge chip, 76, 158, 163, 171
- buried bump packaging, 141
- burst transmission, 104
- butterfly differential layout, 56

- capacitance, area and fringe, 60
- CDMA, 63
- clocking, 5, 67
- coil, 81, 89, 96, 102, 103, 106, 118, 147, 197
- comparator, 65
- contactless packaging, 127–152
- corner differential layout, 56
- coupling
 - capacitive, 8, 51–76, 127, 129, 158
 - capacitive connector, 143
 - capacitive range, 83
 - inductive, 8, 52, 79–124, 129, 147, 194
 - inductive coefficient, 83
 - inductive range, 83
 - optical, 8, 23, 52
 - optical efficiency, 24
 - through substrate, 84
- crossbar, 74
- crosstalk, 53

- daisy-chain transmitter, 99
- datapath slices, 70
- David Salzman, 129
- DC bias, 62, 92, 137
- decoupling die, 41
- dielectric layers, 57
- differential coil, 110
- differential signaling, 56
- differentiator, 82, 130

- eddy current, 85
- electro-static discharge (ESD), 100, 130, 194
- encoding, 63
- Endicott HyperBGA, 141
- epoxy, 135, 166
- equalization, 131, 180
- error function, 54
- etch pit, 161, 172
- etch, self-terminating, 161

- FDMA, 63
- fiber coupling, 187
- field solver, 59
- flash memory, 113
- flip-chip package, 159
- fluidic I/O, 18, 26
- fractional equalization, 146, 148
- frequency acquisition, 68
- frequency response, 81, 89, 130, 131

- Gaussian pulse, 88

- heat, 13, 14, 27
- heat sink, 30
- high-pass filter, 82, 130

- island chip, 76, 158, 163, 171

- jitter, 62, 71, 120

- keeper, 64
- kickback, 65
- KOH, 161
- layout, 56, 89, 111, 197
- low-pass filter, 81
- MCM, 7
- memory, 113
- metal stackup, 57
- micropipe, 18
- microspheres, 161, 163, 172
- misalignment, 15, 24, 51, 52, 73, 158, 166
 - electrical compensation, 61
 - optical compensation, 25
 - physical alignment, 163
 - power tolerance, 198
- modulation, 63, 87
- Moore's Law, 3, 7
- multi-chip module (MCM), 74
- multi-core processors, 6
- multiplexer, efficient, 62
- mutual inductance, 90
- network, 73
- noise
 - common-mode rejection, 56
 - crosstalk, 53, 56, 60, 85, 107, 110
 - crosstalk shield, 115
 - excess factor, 55
 - input-referred, 55
 - thermal, 54
- non-return-to-zero (NRZ) signaling, 130, 136, 144
- offset voltage, 63, 65, 71
- optical I/O, 15, 18, 23
- optical interconnect, 183
- optical interconnects, 180
- optical interface, 182
- packaging, 158
- parallelism, 6
- parasitics, 53, 81, 90, 149, 195
- peaking, 81
- phase recovery, 68
- photolithography, 161
- plastic packaging, 170
- Polychip, 129
- polymer pin, 18
- power, 13, 31
 - distribution, 33, 35, 141, 158, 163, 194
 - reduction, 94, 100, 115, 130, 138
 - supply, 14
 - supply noise, 33, 36, 39
- processor, 119
- pseudo-random bit sequence (PRBS), 63, 93
- pulse modulation, 88, 92, 103
- pulse shaping, 94
- quantum-well modulators, 183
- reflections, 144, 148
- refresh, 64
- resonance, 199
- resonator, 81
- return-to-zero (RZ) signaling, 132, 144
- scaling, 4
- scrambler, 63
- self-inductance, 81
- sense amplifier, 54, 63, 92
- serializer-deserializer circuits, 8, 180
- signal attenuation, 62
- signal processing, 131
- single-ended signaling, 56
- six-axis manipulator, 187
- skew compensation, 121
- skin resistance, 131
- solder bump, 159, 163, 166
- sombrero chip, 173
- SpecINT, 3
- stacked chips, 17, 92, 96, 99, 106, 108, 113, 114, 118, 119, 193
- steering, 61
- switch, 73
- TDMA, 63, 107
- terminations, 144
- thermal interface material (TIM), 14
- thinned chips, 92, 172
- through-silicon via (TSV), 16, 17, 27, 31, 38, 42, 100, 193
- Tom Knight, 129
- trimodal I/O, 18
- variability, 67, 105, 134, 150
- vertical-cavity surface-emitting laser (VCSEL), 183, 187
- voltage divider, 63
- waveguide, 18, 23
- wire bonds, 17, 170, 185
- wireless power delivery, 193–203
- wires, 8