

# Index

## Symbols

$1 \times 2$  broadband switch, 89  
 $1 \times 2$  Photonic Switching Element, 126  
 $2 \times 2$  microring resonator broadband switch, 57, 59  
LiNbO<sub>3</sub>, 38  
SiO<sub>2</sub>, *see* Silicon dioxide  
Si<sub>2</sub>, *see* Silicon dioxide  
Si<sub>3</sub>N<sub>4</sub>, *see* Silicon nitride  
3D integration, 67, 71

## A

A-Si:H, *see* Amorphous silicon  
Access point, 117, 122, 127, 129, 140, 150, 165–168, 171  
Active switching, 55  
Adiabatic microring resonator, 37  
Adiabatic taper, 33, 59  
All-optical switching, 49, 50, 57, 59  
Amorphous silicon, 29  
Amplification, 65, 91  
Amplifier, 24, 66  
Arbiter, 103  
Arbitrator, 81  
Arrayed waveguide grating, 151  
Athermal device, 123  
Attenuation, 13, 19, 84

## B

B/FLOP, 5  
Back reflection, 33, 86  
Back-end integration, 71  
Backoff, 108  
Bandwidth taper, 6

Bandwidth-distance product, 19, 40  
Bar state, 59  
Basic Element, 83  
Basic Element Model, 80, 84, 88  
Bending loss, 85  
Bending radius, 14  
BER, *see* Bit error rate  
Bit error rate, 16, 93, 132  
Blocking switch, 107, 110  
Blue shift, 44, 50  
Broadband all-optical comb switch, 49  
Broadband ring resonators, 110  
Broadband ring switches, 110  
Broadband switch, 48, 57, 59, 88, 89, 106  
Broadcast, 104  
Broadcast and select, 168  
Buffer, 81, 106, 133, 159, 182  
Buffering, 105  
Building Block Library, 81  
Burst-mode receivers, 115

## C

C++, 79  
C-Si, *see* Single-crystalline silicon  
Cactus, 144  
CAMM, *see* Circuit-accessed memory module  
Carrier, 38  
Carrier lifetime, 38  
CDR, *see* Clock and data recovery  
Chemical-mechanical planarization, 31  
Chip multiprocessor, 145  
Chip multiprocessors, 1  
Chip packaging, 1  
Chirp, 40

Chromatic dispersion, 40  
 Circuit path, 107, 108  
 Circuit switching, 54, 105  
 Circuit-accessed memory module, 150  
 Circuit-path setup, 107  
 Circuit-switched network, 150  
 Circuit-switching router, 106  
 Cladding, 27, 30, 31, 66  
 Clock and data recovery, 18, 115, 165  
 Clock tree, 134, 159  
 Comb switch, 48, 49  
 Communication protocol, 107  
 Communication trace, 81  
 Computer-aided design, 79, 97  
 Concentrated mesh topology, 146  
 Concentrated torus topology, 146  
 Confinement factor, 48  
 Contention, 197  
 Continuous wave, 37, 51, 69, 171  
 Control logic, 117  
 Control matrix, 180, 181  
 Control message, 106, 107, 132, 133  
 Control network, 105  
 Control packet, 105–107  
 Control router, 106–108  
 Core, 30, 66  
 Coupler, 66–68, 87  
 Coupling strength, 47  
 Credit flow control, 104, 133  
 Critical coupling, 48  
 Cross state, 59  
 Crossbar, 159, 182, 184  
 Crossbar circuit, 134  
 Crosstalk, 33, 66, 82, 84–86, 91, 94, 115, 123, 130, 132, 190  
 Crystalline silicon, 14, 32  
 Cut-through routing, 104

## D

Dark current, 64  
 Data integrity, 93  
 Data packet, 106  
 Data switch, 106–108  
 DC balance, 18  
 Deadlock, 108  
 Decoder, 24  
 Default path, 111  
 Delay, *see* Latency  
 Demultiplex, 23, 44, 64  
 Demultiplexing, 12  
 Demultiplexing filter, 64  
 Deserializer, 24, 182

Design methodology, 80  
 Design space, 102  
 Destination contention, 175, 197  
 Destination-routed wavelength bus, 165, 167  
 Detection block, 127  
 Detector, *see* Photo-detector  
 Detector array, 103  
 Detector bank, 112, 115, 119  
 Detector Element, 90, 95  
 Detector sensitivity, 91–93, 168  
 Dimension-order network, 111  
 Dimension-order routing, 119, 127, 133, 175  
 Direct network, 140  
 DRAMSim, 96  
 Driver circuit, 20, 39  
 Drop port, 47, 49, 50, 131  
 Dual in-line memory module, 5, 150  
 Dynamic Element, 88, 95  
 Dynamic Element Model, 88  
 Dynamic routing, 104  
 Dynamic-Ring Element, 88

## E

Effective index, 47, 48, 88  
 Ejection switch, 119, 120  
 Electrical noise, 93  
 Electrical signal, 19  
 Electro-optic modulator, 35, 46  
 Electro-optic ring resonator, 15, 44, 88, 90  
 Electro-optic switching, 54  
 Electron beam lithography, 37, 56, 59  
 Electronic control network, 150  
 Electronic control plane, 101, 103, 117, 131, 192  
 Encoding, 18  
 Energy consumption, 148  
 Energy efficiency, 146  
 Enhanced TDM arbitration, 178, 179  
 Etchless silicon waveguides, 14  
 ETDM gateway, 181  
 ETDM switch, 181  
 Evanescent coupling, 85  
 Execution time, 146  
 External concentration, 184  
 External gateway concentration, 140, 156  
 Extinction ratio, 36, 48, 51, 52, 61, 95, 114, 131, 167  
 Eye diagram, 17, 38–40

## F

Fabrication, 69  
 Facet, 56

Fast fourier transform, 156, 158  
 Fiber, 88  
 Fiber array, 67, 68  
 Filter, 64, 88  
 Filter leakage, 115  
 Finite-difference time domain, 82  
 Firewire, *see* IEEE 1394  
 Folded torus topology, 119, 122, 126, 127, 132, 146  
 Forward error correction, 18  
 Free carrier absorption, 13, 34, 48  
 Free carrier dispersion, 34, 48  
 Free spectral range, 16, 36, 45, 49, 56, 59, 61, 88–90, 166, 190  
 Free-carrier absorption, 27  
 Free-carrier dispersion, 59  
 Free-carrier dispersion effect, 55  
 Free-carrier lifetime, 28  
 Free-carrier plasma dispersion effect, 16, 50  
 Front-end integration, 71  
 Fully-connected TDM arbitration, 174

**G**

G-Pack, 68  
 Gain medium, 65  
 Gateway, 122, 127, 140, 156, 177, 182  
 Gateway access network, 119, 122, 126, 127  
 Gateway concentration, 139, 140, 146  
 Gateway switch, 119, 120  
 Generation, 11, 17  
 Genetic algorithm, 175  
 Germanium, 29, 65  
 Germanium detector, 90  
 Germanium photo-detector, 64, 65, 68  
 GloMoSim, 80  
 GOPS, 158  
 Grain, 28, 71  
 Grain boundaries, 28  
 Grain boundary, 71  
 Grating, 68  
 Grating coupler, 68  
 Group index, 45, 46  
 GTC, 144

**H**

Hamming code, 19  
 Header, 103  
 Heater, 37, 123  
 High-performance computing, 144  
 Holographic lens, 68  
 Hotspot, 96  
 Hotspot traffic, 81

Hydrogenated amorphous silicon, *see*  
 Amorphous silicon

**I**

IEEE 1394, 19  
 III-V semiconductor, 66  
 Index contrast, 34, 66, 88  
 Index of refraction, 16, 18, 48, 71  
 Injection switch, 119, 120  
 Input buffer, 103  
 Insertion loss, 19, 32, 84, 87, 91–93, 114, 118, 120, 123, 126, 128, 130, 137, 160, 167  
 Insertion loss matrix, 84, 86, 88, 95  
 Integrated gateway concentration, 140, 156  
 Integrated heater, *see* Heater  
 Integration, 70  
 Intensity noise, 66, 93  
 Inter-channel crosstalk, 32, 34, 51, 58  
 Inter-message crosstalk, 93, 94, 131, 132  
 Inter-modulation crosstalk, 44  
 Interconnect Building Block Library, 80, 81  
 Interconnection network, 1  
 Interference, 13  
 Intra-message crosstalk, 93, 95  
 Inverse taper, 56, 61, 67

**L**

Lambda router, 97  
 Laser, 20, 65, 66  
 Laser intensity noise, 132  
 Laser noise, 131  
 Laser power, 160  
 Latency, 81, 82, 84, 106, 109  
 Latency matrix, 84–86, 88  
 Lateral coupler, 67, 150  
 Lateral junction, 36  
 Leakage current, 20  
 Lensed fiber, 61  
 Lightweight control network, 106  
 Limiting amplifier, 24  
 Link, 68  
 Link-level simulation, 80, 82, 96, 97  
 Long haul transmission, 40  
 Lookup table, 177

**M**

Mach-Zehnder device, 83  
 Mach-Zehnder Element, 91  
 Mach-Zehnder interferometry, 91  
 Mach-Zehnder modulator, 38, 137

MADBench, 144  
 Manchester coding, 18  
 Mapping and Optimization Runtime Environment, 154  
 Matrix multiply, 155, 158  
 Memory, 150  
 Memory access latency, 5  
 Memory controller, 150, 151  
 MEMS, *see* Micro-electro-mechanical system  
 Mesh topology, 110, 117, 146  
 Message-passing interface, 143  
 Metal heater, 60  
 Micro-electro-mechanical system, 83  
 Microbump, 70  
 Microdisk, 36  
 Microring filter, 166  
 Microring modulator, 68, 137, 166, 167  
 Microring resonator, *see* Ring resonator, 43–45, 47, 59, 61, 69, 70  
 Microring switch, 190  
 Modulation block, 127  
 Modulation rate, 137, 138  
 Modulator, 13, 20, 35, 37, 38, 44, 45, 90, 133, 137, 150  
 Modulator array, 43–45, 90  
 Modulator bank, 112, 113, 119  
 Modulator Element, 95  
 Modulators, 150  
 Multi-layer devices, 159  
 Multi-layer integration, 30  
 Multi-layer mesh, 160  
 Multi-mode interference, 33  
 Multi-write single-read wavelength bus, 165, 168  
 Multiplex, 44  
 Multiplexing, 12

## N

Nearest neighbor traffic, 81  
 NetSim, 80  
 Network bandwidth, *see* Throughput  
 Network building block, *see* Interconnect Building Block Library  
 Network collision, 166  
 Network congestion, 108  
 Network ejection arbiter, 192  
 Network injection arbiter, 192  
 Network interface, 107, 117, 139, 142  
 Network packet, 106  
 Nickel silicide, 37  
 Noise, 91, 93, 95  
 Noise power, 130

Non-blocking  $4 \times 4$  switch, 49, 59, 122  
 Non-blocking switch, 107, 111  
 Non-blocking torus topology, 122, 132  
 Non-return to zero, 37  
 Non-uniform memory access, 6  
 Nonlinear effects, 91  
 Nonlinearity threshold, 92  
 Ns-2, 80

## O

Off resonance, 49, 50, 88, 90, 131, 166–168  
 Off-chip laser, 66, 91  
 Off-chip memory access, 150  
 OIL, 97  
 OMNeT++, 79  
 On resonance, 15, 49, 50, 88, 90, 131, 167, 169, 171  
 On-chip laser, 65  
 On-off keyed, 37  
 OPNET, 80  
 Optical cavity, 65  
 Optical chip, 70  
 Optical feedback, 65  
 Optical fiber, 30  
 Optical link, 11, 21, 103  
 Optical path length, 45  
 Optical power, 91, 93  
 Optical power budget, 82, 90–93, 125, 129, 137  
 Optical pump, 51, 59, 65  
 Optical signal-to-noise ratio, 93, 131  
 Optical-electronic-optical conversion, 103  
 OptiSim, 97  
 Original  $4 \times 4$  Switch, 121  
 ORION, 81, 96, 133  
 Orthogonal signaling, 132  
 OSNR, *see* Optical signal-to-noise ratio

## P

P-I-N, 37, 38, 44, 51, 55, 69  
 Packaging, 67, 68  
 Packet, 103  
 Packet-switched network, 106, 142  
 Packet-switching network, 103  
 Packet-switching router, 104, 106  
 Parametric oscillation, 66  
 Parasitic capacitance, 70  
 PARATEC, 144  
 Path-ACK message, 107, 108, 151, 194  
 Path-blocked message, 107, 151, 194  
 Path-setup message, 107, 108, 193, 194

- Path-setup protocol, 106–108, 132, 141, 150, 151, 173
  - Path-teardown message, 107, 108, 194
  - PathFree, 107
  - PathReserved, 107
  - PathSetup, 108
  - Payload, 103
  - PECVD, *see* Plasma-enhanced chemical vapor deposition
  - Phase-locked loop, 18
  - Phase-locked loops, 115
  - PhoenixSim, 79, 82–86, 88, 90, 95, 138, 198
  - Photo-detector, 23, 64, 65, 69, 90, 91, 95, 115, 133, 166, 167, 169
  - Photo-detector array, 65
  - Photo-detectors, 29, 150
  - Photonic circuit-switched network, 160
  - Photonic circuit-switching network, 109
  - Photonic crystal, 83
  - Photonic data plane, 101, 131
  - Photonic Device Library, 82, 83, 91, 95
  - Photonic interconnection network, 11
  - Photonic spatial switch, 109
  - Photonic switch, 109
  - Photonic Switching Element, 89
  - Photonic wire bonding, 67
  - Photonics, 2
  - Pin count, 150
  - Pin grid array, 68
  - Place and route, 97
  - Plasma dispersion effect, 38, 44
  - Plasma-enhanced chemical vapor deposition, 56
  - PMapper, 154
  - Polarizer, 61
  - Poly-Si, *see* Polycrystalline silicon
  - Polycrystalline germanium photo-detector, 69
  - Polycrystalline silicon, 28, 64, 71, 159, 160
  - Polymer waveguide, 67
  - Polymer-based electro-optic modulator, 69
  - Polysilicon, *see* Polycrystalline silicon
  - Polysilicon ring modulator, 131
  - Power dissipation, 1, 70, 91, 95, 133
  - Power penalty, 17, 39, 44, 51, 57, 63, 137, 138
  - Power waveguide, 171
  - PP, *see* Power penalty
  - Pre-emphasis method, 38–40
  - Processing plane, 101
  - Projective transform, 154, 158, 159
  - Propagation delay, 84, 88
  - Propagation loss, 28, 47, 84
  - PS-1, 157
  - PS-2, 157, 158
  - Pump, *see* Optical pump
- Q**
- Quad, 127
  - Quality factor, 48
  - Quality of service, 18
  - Quantum cascade laser, 93, 131
  - Quantum dot, 66
  - Quantum dot laser, 66
  - Quantum efficiency, 64
- R**
- Racetrack resonator, 55
  - Radiation loss, 33
  - Random traffic, 81
  - Rare-earth-ion laser, 66
  - Reactive ion etching, 37, 56, 59
  - Receiver, 24
  - Receiver sensitivity, 63, 70
  - Reception, 11, 22
  - Receiver, 90
  - Reflection, 84
  - Reflectivity, 66
  - Relative intensity noise, 93, 131
  - Resonant mode, 14, 50, 56, 61, 89, 167, 168
  - Resonant wavelength, 48
  - Resonator, 48
  - Resonator switch, 47
  - Responsivity, 64
  - Reticle, 70
  - Retransmission, 108
  - Ring Element, 88, 95
  - Ring Element Model, 88
  - Ring filter, 90, 167, 171
  - Ring modulator, 131
  - Ring resonator, 14, 34, 55, 88, 106
  - Ring resonator filter, 88, 115
  - Ring resonator modulator, 37, 90
  - Ring resonator switch, 48
  - Ring switch, 131
  - Ring-Resonator Element, 88
  - Router
    - pipelined router, 81
  - Routing, 11, 20
  - Routing domain, 102
  - Routing table, 84–88
  - RS-232, 19
- S**
- Scattering loss, 46
  - Second-order filter, 37

- Selective transmission, 139, 142, 146
  - Self-phase modulation, 32
  - Serial ATA, 19
  - Serialization, 19
  - Serializer, 19, 182
  - Shot noise, 95
  - Sidewall imperfection, 13, 46
  - Signal integrity, 40
  - Signal power, 95
  - Signal-to-noise ratio, 93, 130
  - Silica, *see* Silicon dioxide
  - Silicon, 27
  - Silicon dioxide, 27, 30, 56, 66
  - Silicon modulator, 35
  - Silicon nitride, 14, 29, 33, 71, 159, 160
  - Silicon nitride microring resonator, 66
  - Silicon nitride waveguide, 69
  - Silicon nitride waveguides
    - silicon nitride, 33
  - Silicon on insulator, 28, 30, 56, 59, 70
  - Silicon photo-detector, 64
  - Silicon waveguide, 12, 88
  - Simulation, 79, 96
  - Single mode, 31, 32
  - Single-crystalline silicon, 27, 71
  - Single-write multi-read wavelength bus, 165, 169
  - SNR, *see* Signal-to-noise ratio
  - SOI, *see* Silicon on insulator
  - Source contention, 175
  - Source-routed wavelength bus, 165, 166
  - Space domain, 102
  - Spatial locality, 5
  - Spatial routing, 21, 191
  - Spatial switch, 110
  - Spatial switching, 105
  - Spatial-switching network, 110, 122
  - Spectral bandwidth, 12
  - Spectral width, *see* Quality factor
  - Spectrum, 13, 95
  - Square Root topology, 126–128, 132, 133
  - Standard cell, 101
  - Standard single mode fiber, 40, 66, 67, 87, 88
  - State, 95
  - State variable, 88
  - Store and forward, 103
  - Straight waveguide, 84, 85
  - StraightPath 4 × 4 Switch, 111, 121, 127, 157, 160
  - Substrate leakage, 13
  - Switch, 47–49, 54, 59, 103
    - electronic switch, 81
  - Switch controller, 175
  - Switching, 47, 49, 50, 54
  - Symmetric 4 × 4 Switch, 111, 121
  - Synthetic traffic, 81
  - System-level simulation, 80, 97
  - SystemC, 97, 101
- T**
- TCP, 80
  - TDM controller, 177, 181, 182
  - TDM frame, 174, 183
  - TDM network gateway, 177
  - TDM period, 181
  - TDM slot, 174, 182
  - TDM switch, 175
  - Temporal locality, 5
  - Thermal management, 123
  - Thermal noise, 95
  - Thermal perturbation, 18, 123
  - Thermal tuner, 133
  - Thermal tuning, 60, 95
  - Thermo-optic tuning, 56
  - Threshold voltage, 20
  - Through port, 47, 49, 50, 131
  - Through-oxide via, 70
  - Throughput, 1, 12, 82, 106
  - Time division multiplexed arbitration, 173, 174
  - Time domain, 103
  - Time slot, 173
  - Time-division multiplexed routing, 22
  - Time-division multiplexing, 173
  - Token, 171
  - Token arbitration ring, 165–167, 171
  - Token flow control, 104
  - Topology contention, 175
  - Topology exploration, 126
  - Tornado traffic, 81
  - Torus topology, *see* Folded torus topology
  - TorusNX topology, 126–128, 132, 138, 157, 199
  - Total internal reflection, 30
  - Trace, 60
  - Trans-impedance amplifier, 24
  - Transceiver, 69
  - Transient response, 38
  - Transmission Control Protocol, 108
  - Transverse electric, 61
  - Tunable filter, 167, 169
  - Two-partition router, 189
  - Two-photon absorption, 34, 59
  - Two-photon polymerization, 67

**U**

U-turn, 60  
Uniform random traffic, 132, 133  
Universal Serial Bus, 19

**V**

V groove, 67  
VANDAL, 97  
Verilog, 101  
Vertical coupler, 68, 182  
Vertical junction, 36  
VHDL, 101  
Virtual channel, 22, 104, 191

**W**

Waveguide, 12, 13, 31, 32, 68, 84, 85  
Waveguide bend, 14, 85  
Waveguide coupler, 67  
Waveguide crossing, 14, 32, 82, 86, 87, 124, 126, 127, 129, 131, 159, 160, 165  
Waveguide sidewalls, 28  
Wavelength bus, 165  
Wavelength channel, 89, 90, 92, 95, 137, 138  
Wavelength crossbar, 170

Wavelength division multiplexing, 154  
Wavelength domain, 103  
Wavelength routing, 21  
Wavelength-division multiplexing, 11, 13, 66, 88–90, 103, 105, 150  
Wavelength-routed network, 165, 171  
Wavelength-selective spatial routing, 22, 188, 191  
WDM, *see* Wavelength-division multiplexing  
WDM factor, 92, 93  
WDM parallelism, 91  
WDM partition, 189, 191, 192, 196  
WDM partition receiver, 192  
WDM partition transmitter, 192  
WDM signal, 110  
Wire, 12, 102  
Wire bonding, 67, 70  
Wormhole routing, 104

**X**

X-Y buffer, 181, 183, 188

**Y**

Yield, 71