

Index

■ A

ARM compile options, 215
Average voltage, 183
Averaging effect, 183

■ B

Bipolar stepper modes
 half-step mode, 146–147
 one-phase-on mode, 145
 operation, 145
 two-phase-on mode, 145–146
BroadCom power specifications, 211

■ C

CD4013
 CMOS inputs, 161
 description, 160–161
 flip-flop circuit, 161
 Raspberry Pi GPIO logic levels, 161
Choppy digital-looking signal, 183
Connector pinout
 breadboard, 49
 cable-end connector, 48
 I2C communication, 48
 Raspberry Pi, 49
 wiring, 49
Console commands, 166
CPU percent-busy command, 189–194

■ D

DC resistance, 121
DHT11 sensor
 humidity and temperature, 1
 power supply, 2
 protocol (*see* Protocol, DHT11 sensor)

Raspberry Pi, 2
 source code, 9
DMM, 121, 144
DS1307
 bus speed, 84
 I2C communication, 77
 EEPROM, 78
 PCB, 77
 pin SQW/OUT, 79
 pins X1 and X2, 79
Duty cycle, 183

■ E

Electronics reference
 Ohm's law, 213
 power, 213
 units, 214

■ F

Floppy-disk stepper motor
 driver circuit
 Darlington pair, 123–125
 JP1, 122
 LEDs, 123
 ULN2\ PCB, 122
 5.25-inch, 119
 junk-box motor, 120–121
 winding resistance, 120
 windings, 120–121

■ G

Gnuplot mode
 gnuplot.cmd, 107
 IR signal, 108
 waveform, 106
 xhost command, 108

■ INDEX

GPIOs

- design approaches, 147
- DMM, 144
- dodgy area, 144
- L298 IC, 143
- motor control, 126
- program unipolar.c, 129
- ULN2003A, 143
- transistors, 124–125

GPIO 18 (GEN1), 184

GPIO output signal, 183

■ H

H-Bridge driver

- bipolar stepper modes, 145–147
- GPIO (*see* GPIOs)
- junk-box motors, 148
- L298 (*see* L298 driver)
- L298 PCB, 141–143
- program operation, 149–155
- schematic, 148

■ I

I2C protocol

- register address, 50
- sensor data, 51–52

■ J, K

Junk-box meter, 185

Junk-box motors, 148

■ L

L298 driver

- components, 139
- dual-bridge driver, 140
- full-bridge driver, 139–140
- inputs in1 and in 2, 140
- PCB, 141–143
- protection diodes, 141
- sensing resistor, 140

LED, 162

Light-emitting diodes (LEDs), 123

Linux uinput interface

- device node, 53
- EV_ABS, 56–57
- EV_KEY, 54–55
- EV_REL, 55
- EV_SYN, 60

header files, 53

ioctl(2), 53

mouse buttons, 55

posting EV_KEY, 59

programmers, 52

uinput_user_dev information, 57

UI_SET_EVBIT event, 53

■ M

MCP23017 GPIO

breadboard, 21

byte mode, 22

gpio_open_edge(), 30

I2C bus, 15, 20

i2cdump utility, 22

inputs, 17

INTCAPx, 45

INT line, 19

ioctl(2) call, 45

key debouncing, 44

logic levels, 18

modprobe information, 42

module i2c_funcs.c, 35–36, 38–39

output current, 16–17

PCBs, 15

pinout, 16

poll(2) system, 44

post_outputs(), 30

pull-up resistors, 20

Raspberry Pi, 15, 19

reset timing, 19

ribbon cable, 19

Routine i2c_init(), 30

software configuration

(*see* Software configuration)

standby current, 18

sysgpio.c, 39, 41–42

Mutex and cond variables, 150

■ N

Nunchuk-mouse

connector pinout, 48–50

I2C communications, 47

I2C protocol, 50, 52

input utilities, 62, 65

linux uinput interface

(*see* Linux uinput interface)

timed_wait() call, 65

X-Windows, 47, 61

■ **O**

Ohm's law, 213

ØMQ

- compiling, 164
- description, 163
- download and installation, 163
- linking, 164

■ **P, Q**

PCBs, 141–143

Power, 213

Power standards, 211

Protocol, DHT11 sensor

- bias test results, 7
- data bits, 4
- GPIO, 8
- humidity and temperature, 4
- longjmp, 7
- master control, 3
- pull-up resistor, 3
- sensor bus, 8
- signal protocol, 3
- software, 5–6
- stderr, 8

Pulse-width modulation (PWM)

- average voltage, 183
- averaging effect, 183
- duty cycle, 183
- GPIO output signal, 183
- hardware peripheral, 184
- hardware PWM peripheral, 184
- meter circuit, 185
- parameters, 184
- principle of averaging the signal, 183
- program
 - CPU percent-busy command, 189–190, 192–194
 - GPIO 18, 187
 - hardware and clock-rate registers, 186
 - milliampere meter, 40% deflection, 189
 - mmap() techniques, 186
 - pwm_frequency(), 186
 - pwm_init(), 186
 - pwm_ratio(), 187
 - set command, 188

software (*see* Software PWM program)

Raspberry Pi, 183

software, 184

PWM. *See* Pulse-width

modulation (PWM)

■ **R**

Real-time clock

- 3-volt compatibility, 80–81
- capacitor, 88
- Dallas Semiconductor, 77
- DMM resistance, 82
- DS1307, 77–79
- I2C communication, 86–87
- kernel modules, 87
- PCB, 82
- power, 80
- pull-up resistors, 81, 83
- RAM address, 84, 86
- wiring, 87

Remote-control panel

- CD4013, 160–162
- console program, 165–166
- console source code, 174–180
- flip-flop, debouncing, 160
- flip-flop testing, 162
- LED, 162
- ØMQ, 163–164
- sensing station design, 164
- sensing station program, 165
- sensor source code, 166–172
- switches and push buttons, 159

■ **S, T**

Series-dropping resistor, 185

Software

- cat command, 105
- code organization, 104
- dump mode, 106
- gnuplot mode (*see* Gnuplot mode)
- irdecode utility program, 105
- Raspberry Pi GPIO, 103
- RC5 protocol, 104
- remote control, 102
- signaling works, 102
- stderr output, 105
- waveforms, 102

Software configuration

- DEFVALx, 26
- GPINTENx, 28
- GPIOx, 29
- GPPUx, 25
- INTCAPx, 29
- INTCONx, 26
- INTFx, 28
- IOCON register, 23–24
- IODIRx, 27
- IPOLx, 27
- OLATx, 25
- register addresses, 22

Software PWM program

- chgf and stopf structure members, 198
- CPU percent-busy display, 199–202
- data type, 196
- limiting factors, 198
- pwm_close(), 197
- pwm_open(), 196
- pwm_ratio(), 197
- run, command, 198

Software, stepper motor

- configuration, 130
- GPIO assignments, 129
- pointer knob, 130
- single-character commands, 130–131
- testing, 131–138

Stepper motor

- floppy-disk (*see* Floppy-disk stepper motor)
- full-step drive mode, 128
- half-step drive mode, 129
- input levels, 125
- power-on reset/boot, 126–127
- software (*see* Software, stepper motor)
- wave drive mode, 128

■ U

- ULN2003A driver chip, 122
- Units, 214

■ V, W, X, Y, Z

- VS1838B IR receiver
 - breadboard, 101
 - decipher, 99
 - GPIO, 100
 - photodiode, 99
 - Raspberry Pi, 100–101
 - remote controls, 99, 101
 - resistor, 102
 - signal transistor, 99
 - software (*see* Software)