

A

- Absolute power consumption, 67
- Absorption, 681
- Accumulator, 560
- Acid mine drainage, 35
- Acidity, 29, 32
- Acrylic ester, 552
- Activated carbon, 573, 644
 - applications, 574
 - manufacture, 576
 - regeneration process, 591
 - tertiary treatment, 593
 - thermal regeneration, 591
- Activated sludge
 - appearance, 678
 - contact stabilization, DAF, 490
 - reactor, 663
- Active adsorption zone, 580, 581
- Adsorbate, 644
 - characteristics, 592
 - chain length, 593
 - degree of saturation, 593
 - molecular weight, 593
 - polarity, 593
 - solubility, 592
- Adsorbent, 545, 644
 - characteristics, 592
 - particle size, 592
 - surface area, 592
 - surface chemistry, 592
- Adsorption, 154, 155, 573, 644
 - and bridging, 111
 - bed, polymeric adsorbent, 552, 553
 - breakthrough curves, 586, 587
 - column
 - models, 577
 - series design, graphical approach, 589
 - flotation, 471
 - isotherm tests, industrial wastes, 594
 - polymeric, 545–571
 - properties, 552
 - systems, design, 645
 - technology milestones, 623
 - TNT, 563
- Adsorptive bubble separation, 431–434
- Advanced wastewater treatment plant, AWTP, 573, 635, 657
- Aerated composting, ideal temperature course, 699
- Aeration, 243–246
- Aerobic digestion, 695, 697
 - advantages and disadvantages, 697
- Agglomeration, 637
- Aggregation, 637
- Aggressive index, 225
- Aging, 153, 154
- Aid in coagulation, 321
- Air
 - dissolution, 452
 - feed systems, 341
 - preparation, 341
 - saturated water, 452
 - scour, 522
 - solubility in water, 448, 463
 - stripping, 569
 - to solids ratio, 443–448, 454, 462, 648
- Alkali comparison, 35
- Alkalinity, 29, 32, 33, 118
- Alternative disinfectants, 316, 333
- Alum conditioning, 692
- Aluminum salts, 115, 116
- Amberlite XAD, 551–556, 563
- Ammonia
 - nitrogen, 276, 298
 - oxidizing bacteria, 298
- Ammonium removal, electrolysis, 369
- Anaerobic digestion, 695–698
 - advantages and disadvantages, 698
 - process, sewage sludge, 698
- Anion exchange resin, 649
- Anionic polyelectrolytes, 681
- Anions, 114
- Anthracite coal, 511
- AOB, *see* Ammonia oxidizing bacteria

- Apparent
 - density (AD), 591
 - rate of saturation, 584
- Applications
 - chemical oxidation, 230
 - ozone, 319–321
- Aqueous chemistry, 679
- Arsenic, 103, 104
- Asbestos, 546
- Ashley Water Treatment Plant, 482
- Aspirated air, 452
- Attachment mechanisms, 504
- Autooxidation system, 245
- Available chlorine, 308
- Azeotropic distillation, 558
- B**
- BAC process schematic, 580
- Backswept turbine, 60
- Backwash, 670
 - rate, 535
 - water, 523
- Backwashing, 502
 - operating modes, 522
- Bacteria, 308
- Bacterial removal, filtration rates, 655
- Baffled
 - mixing basin, 54
 - tanks, 123
- Balloon duct, 414
- Bar screen, 4, 10, 16–18
 - net area ratio, 5
- Batch adsorption system, 645, 646
 - single-stage design, 646
 - two-stage concurrent design, 646
 - two-stage countercurrent design, 646
- Batch
 - distillation, 557
 - mixers and reactors, 93
 - settling, 412
- Bed-depth service time (BDST), 587–588
 - curves, 590
 - equation, 588
- Bed expansion, 516
- Beer factory wastewater treatment, design
 - criteria, 652
- Belt filter press, 690
 - advantages and disadvantages, 691
- Belt press, 687
 - advantages and disadvantages, 687
- Belt-type gravimetric feeder, 122
- Bentonite, 114
- Best floc characteristics, 683
- Biological
 - activated carbon (BAC) process, 577
 - BAC filtration, 624
 - filtration, 636
 - oxidation, 264
 - treatment, electrolysis stimulated, 374
- Biosolids
 - oxidative conditioning, 250–256
 - stabilization, 249–256
- Black box approach, 504
- Blade
 - area ratio, 66
 - shape ratio, 66
- Blenders, 124
- Blocking, 508
- Blood purification, 564
- BOD (biochemical oxygen demand), 511, 577
- Bohart–Adams equation, 618–621
- Boltzmann’s constant, 507
- Bone char, 546
- Bottom-mounted turbine, baffled vessel, 80
- Breakpoint chlorination, 280, 334
- Breakthrough curve, 619
- Brewery wastewater treatment plant, flow
 - chart, 652
- Bridging, 681
- Bromination, 294, 308
- Bromine, 272, 283–284, 294
 - dissociation, 283
 - hydrolysis, 283
- Brownian movement, 106, 637
- Bubbles, 435, 436
- Buckingham pi theorem, 62
- Buffer capacity, 30
- Bulk density, resin adsorbent, 556
- Bulk diffusion, 49
- Bulking factor, 507, 509
- C**
- Cairox method, 260
- Calcium
 - carbonate, 207
 - hydroxide, 301
 - hypochlorite, 301
 - neutralizers, 35
- Car painting industry, raw materials recovery,
 - 666

- Carbon adsorption
 - industrial waste treatment systems, 594
 - mass transfer model, 583
 - physical chemical treatment (PCT) plants, 594
 - system, construction cost, 601
 - technology, milestone, 575
 - tertiary treatment plants, 594
- Carbon
 - dioxide, 199, 208, 211, 212, 224, 463
 - makeup, 595
 - treatment, waste management facilities, 595
- Carbonate
 - hardness, 31
 - precipitation, 145, 159, 160
- Carman–Kozeny equation, 507
- CARO membranes, 673
- Car-painting industry, processes, 665
- Catalytic oxidation system, 245
- Cation, 114
 - exchange resin, 649
- Cationic polyelectrolytes, 681
- Caustic soda, 35
- Cellulose acetate (CA) RO membranes, 671
- Centrifugal
 - dewatering, 690
 - thickener, 686
- Centrifugation, 683
- Centrifuge
 - advantages and disadvantages, 690
 - basket type, 689
 - continuous solid bowl conveyor type, 689
 - disk type, 689
 - sludge dewatering, advantages and disadvantages, 692
- Ceramic membrane, 661
 - reactor, 672
- Characteristic length, 62, 63
- Charge neutralization, 110, 111, 681
- Chemical
 - adsorption, 573, 644
 - coagulation, 518, 525
 - experiment, 457
 - magnesium carbonate, 206
 - feeding, 121, 122
 - handling, 155, 156
 - kinetics, 241
 - mixing, 58
 - oxidation, 229–268, 308
 - precipitation, 141–197
 - chemicals for, 165
 - properties of ozone, 317–319
 - reaction, 52, 573
 - treatment, DAF, 455
- Chloramines, 277, 309
- Chlorination, 288, 308, 528, 635
 - break-point, 280
- Chlorine, 211, 272, 288–294, 309, 230
 - demand, 308
 - dioxide, 281–283, 294, 309
 - generation, 281
 - reactions, 282
 - dissociation, 275
 - free available, 275
 - hydrolysis, 274
 - reactions, 275, 279
 - residual, 308
- Chromic acid oxidation, 256–258
- CIP (clean-in-pipe) system, 670
- Circular
 - sedimentation tank, 397, 398, 640
 - thickeners, 405
- Clarification, 435–440, 683
 - class 1, 381–386
 - class 2, 381, 386, 387
 - DAF, 485, 486
 - equation, 505
- Clarifier, 35
- Clarification, 308
- Clariflocculator, 640
- Clay, 106
 - /alum suspensions, 509
 - /polymer suspensions, 509
- Cleveland Water Treatment Plant, 482
- Clogged filter beds, 505
- CMF unit, 669
- CNH, *see* Cyanogen halide
- Coagulant, 114–118, 296, 298
 - aids, 118
 - dosage, 112
- Coagulated floc, 680
- Coagulating
 - agents, 638
 - and precipitation, 168, 169
 - control, 118–121
 - sweeping, 680
 - zone, 679
 - Zone I, 678
 - Zone II, 678

- Zone III, 678
 - Zone IV, 680
 - Coagulation, 54, 103–137, 637, 678
 - flocculation, 635, 636
 - Coarse screens, 2
 - Coating, 508
 - Chemical oxygen demand (COD), 262, 263, 577
 - Coefficient of drag, 383, 384
 - Colloidal
 - structure, 107–109
 - system, 105–107
 - Colloids, 105–114
 - Color removal, 320
 - Combined
 - available chlorine, 308
 - residual chlorination, 308
 - sewer overflow, 104
 - Comminution, 1, 6–9
 - design, 14
 - Comminutors, 7
 - Common ion effect, 150
 - Complete
 - mixing, 52
 - suspension, 77
 - Composting, 695
 - Compression settling, 390, 641
 - Concentration fraction, 50
 - Condenser, 558, 568
 - Conditioner
 - choice, 681
 - selection, guidelines, 683
 - Constant
 - pressure filtration, 519
 - rate filtration, 519
 - effluent rate control, 519
 - influent flow splitting-rate control, 519, 520
 - Contact
 - coagulation filtration process, 524
 - time, 308
 - concentration time (CT), 319, 320, 322–325, 344, 347
 - Continuous
 - counterflow column, 587
 - flow
 - system, 52, 76
 - reactors, 95
 - fractional distillation, 557–558
 - microfiltration (CMF) units, 662
 - Control
 - algae, 321
 - taste and odor, 321
 - Conventional
 - physicochemical treatment processes, 636
 - thickener, design, 686
 - Conversion of ammonia to dichloramine, 235
 - Coprecipitation, 146
 - Cost
 - data, granular carbon systems, 600
 - gravity thickeners, 416
 - investment and operating cost, carbon
 - adsorption, municipal wastewaters, 599
 - optimization, carbon adsorption systems, 599
 - ozonation systems, 349–353
 - sedimentation tanks, 414–416
 - tube settlers, 416, 417
 - Counterions, 141
 - Coxsackie Water Treatment Plant, 476–477, 483, 492
 - Critical speed, 83
 - of Zwietering, 83
 - Crossflow
 - filtration, 661
 - microfiltration (CFMF), 661
 - Cryptosporidium*, 104, 320
 - cysts, 518
 - Crystal growth, 153, 154
 - CSO, 262
 - Curved blade turbine, 60, 70
 - Cutting oil, recovery and recycle, 665
 - Cyanate, 279
 - Cyanide
 - precipitation, 145, 161
 - removal, electrolysis, 369
 - Cyanogen halide, 298
 - Cylindrical tank baffling, 97
- D**
- DAF, *see* Dissolved air flotation
 - Dairy wastewater treatment, 675
 - ceramic MBR vs conventional activated sludge, 675
 - DBP, *see* Disinfectant by-product
 - DBPs, 104
 - DCDF, *see* Dissolved carbon dioxide flotation

- DCP, 264
- Dead-end
 - filtration, 661
 - microfiltration, 661
- Dechlorination, 308
- Denitrification, electrolysis, 375
- Density, 56
- Desalination, 525
- Design
 - of facilities
 - examples, 88, 89, 91, 94, 95, 96
 - guidelines, 91
 - mechanically mixed systems, 90
 - mixing, 86
 - pipes, ducts, channels, 86
 - self-induced and baffled basins, 89
 - of grit chamber, 402, 493
 - of thickeners, 405, 406
- Desired effluent water quality, 511
- Destabilization, 636
 - of colloids, 109–111
- Destabilized suspensions, 643
- Detachment
 - coefficient, 506
 - mechanisms, 504
- Detention time, 55, 392–395
- Dewatered cake, solid content, 688
- Dewatering, 679
 - processes, 684
 - filtration, 684
 - post-treatment, 684
 - pretreatment, 684
 - thickening, 684
- DGF, *see* Dissolved gas flotation
- Dhahran
 - North Sewage Treatment Plant, 657
 - Saudi Aramco, AWTP, 656
- Dialysis, 636
- Dichloramine, 276, 278
- Dielectric tubes, 341
- Differences, RO, UF, MF, 659
- Differential settling, 637
- Diffused air mixing system, 55
- Diffusion, 502
- Diffusivity coefficient, 56
- Digestion processes, 695
- Direct electrooxidation process, 370
- Direct filtration, 511
- Discharge velocity vectors, 70
- Disinfectant, 286–309
 - by-product, 296–299, 310
 - organic, 296, 299–300
- Disinfection, 271–314, 308, 670
 - against pathogens, 319, 320
 - bromine, 294
 - by-products (DBP), 316, 320, 333, 334
 - chlorine dioxide, 294
 - control, 287
 - design, 300
 - electrocoagulation, 366
 - modes and rate of killing, 285
 - pH, 287
 - potable water, 303–304
 - temperature, 286
 - wastewater, 301–303, 305–308
- Dispersed air flotation, 438, 648
- Dispersing agents, 443
- Dispersion, 90
- Dissociation
 - bromine, 283
 - chlorine, 275
 - iodine, 284
- Dissolution, 115, 116
- Dissolved air flotation, 220, 431–500, 648
 - activated sludge contact stabilization, 490
 - applications, 483–491
 - clarification, 485, 486
 - control factors, 443
 - cost, 465
 - denitrification, 487
 - design, 450, 453
 - energy, 465, 466
 - full flow pressurization system, 442, 444, 459
 - history, 438–440
 - hydraulic loading, 445, 449
 - laboratory apparatus, 459
 - laundry waste, 488
 - nitrification, 487
 - operation and performance, 442, 453–455, 464, 467
 - partial flow pressurization, 442, 446, 460
 - petroleum refining waste, 489
 - pressure
 - calculations, 449
 - tank, 452
 - primary DAF clarification, 490

- process
 - configurations, 441
 - description, 440
- rectangular, 481, 491
- recycle flow pressurization, 442, 447, 461
- SBR, 470
- secondary DAF clarification, 490
- solid/liquid separation, 453
- solids loading rate, 451
- startup, 463
- theory, 444
- Dissolved air–ozone flotation, 472
- Dissolved carbon dioxide flotation (DCDF), 471
- Dissolved gas flotation, DGF, 471
- Dissolved nitrogen flotation, 471
- Dissolved oxygen, 230
- Dissolved pressure air flotation, 648
 - factors, 648
 - flow diagram, 649
- Dissolving air into water, 450
- Distillation, 545–571
 - application, 560
 - azeotropic, 558
 - batch, 557
 - column, 558
 - continuous fractional, 557
 - design, 560
 - extractive, 559
 - molecular, 559
 - process description, 557
- Distribution
 - carbon dioxide, 210
 - system, 310
- Diverse organic halogens (DOX), 298
- DNT degradation, electrochemical, 374
- Dolomitic lime, 35
- Dora Creek Sewage Treatment Plant, 662
- Dose response curve, 327–329
- Double-layer compression, 110
- Downflow
 - buoyant-medium packed-bed filtration system, 643
 - conventional biological GAC systems, 625
 - fixed bed, 587
 - gravity fixed-bed process, 577
- DOX, *see* Diverse organic halogens
- Drag
 - coefficient, 55, 64, 123
 - force, 123, 382
- Dry solids (DS), 683
- Dry weather flow (DWF), 653
- Drying bed, 687
- Drying bed
 - advantages and disadvantages, 687, 690
- Dual
 - conditioning, 682
 - media
 - filter, 512
 - filtration, 642
- Duolite, polymeric adsorbent, 556
- Dyeing industry, blue colorant recovery, 666
- Dynamic (absolute) viscosity, 123
- E**
- Eddy diffusion, 49
- Effect of flocculation on sedimentation, 386, 387
- Effect of particles concentration on sedimentation, 388
- Effective
 - adsorption capacity, 583
 - size, 513
- Effluent
 - neutralization, 38
 - weir, 519
- Electric double layer, 107
- Electrical power supply, 344
- Electrochemical
 - methods, 360
 - processes, 362
- Electrochlorination, 367
- Electrocoagulation, 638
 - advantages, 365
 - application, 365
 - chemical reactions, 361
 - system, 366
 - technology, 372
- Electrodialysis (ED), 658
- Electrokinetic properties, 105, 106
- Electrolysis, 359
 - disinfectant, 368
 - mechanisms, 362
 - process plant, 361
 - voltage, 365

- Electrolytic
 - cell, 362
 - oxygen generation, 375
 - processes, 360
 - wastewater treatment, 360
- Electrolytically stimulated bioreactors, 375
- Electronegativity of elements, 232
- Electrophoretic method, painting, 664
- Electroprecipitation, 142
- Electrostatic repulsive forces, 105–109
- Elimination of organic compound, 321
- Empirical models, 504
- Encapsulated phosphate buffers, 39
- Energy spectra, 56
- Entrapment of bubbles, 435
- EPA Manual, 590
- Equalization (*see also* Flow equalization), 21–25, 52, 90
 - basin or tank, 37, 42
 - mixing and aeration, 25
 - quick lime, 42
- Equilibrium
 - constant, 239
 - isotherm curve, 585
- Equipment amortization, 595
- Eraring Water Reclamation Project, 663
 - membrane process, performance, 663
- Euler number, 63
- Eulerian concentration correlation, 50
- Eutrophication, 141
- Expansion coefficient, 534
- Explosive
 - contaminated groundwater remediation, 372
 - electrolysis, 373
 - removal, electrochemical, 373
- External loop membranes, 672
- Extractive distillation, 559
- F**
- Faraday's constant, 237
- Ferric chloride suspensions, 507
- Ferric ion, 280
- Ferrous ion, 280
- Filter
 - coefficient, 506, 507
 - configurations, 511, 512
 - design, trial-and-error, 539
 - loading rate, 534
 - media
 - depths, 511
 - design values, 513
 - effective sizes, 511
 - layer, depth, 534
 - porosity, 536
 - sizes, 511
 - specific gravities, 511
 - types, 511
 - net water production, 539
 - operating
 - modes, 519
 - advantages, 519
 - disadvantages, 519
 - variables, 518
 - physical variables, 511
 - run length, 538
 - surface area, 534
- Filterability, 107
- Filtration, 310, 501, 683
 - hydraulic theory, 511
 - rate, 514, 517, 518
 - secondary effluent, 513
 - systems, troubleshooting, 523
 - technology, 643
- Final disposal, 677
- Fine screens, 2
- First
 - class clarification, 639
 - stage recarbonation, 35
- Fixed bed
 - adsorption system, 645, 647
 - parallel operational mode, 647
 - operating cycle, 657
 - reactors, 644
- Flat-blade radial discharging type, 59
- Float, 444
- Floating medium
 - domestic wastewater treatment, 654
 - farm wastewater recycle, 655
 - farm wastewater treatment, 655
 - filter, 643
 - backwash method, 644
 - flocculator/filter, 643
- Flocculant dosage, 684
- Flocculation, 35, 55, 125–137, 156, 157, 681
- Flocculator, 35
- Flocs mixing, 435

- Flotation (*see also* Dissolved air flotation), 431–500, 648
 aid, 456
 experiment, 457
 -filtration, DAFF, 472–486
 tests, 457
 thickener, 686
 thickening, 456, 468
- Flow equalization, 21–25, 40–42
 basin calculations, 23
- Fluid
 shear, 54
 viscosity, 54
- Fluidized bed
 adsorption system, 646, 647
 downflow operation, 646
 upflow operation, 646
 furnace (FBF), schematics, 700
- Fluorine, 271
- Foamer, 438
- Fraction of particles removed, 385–387
- Frame press, advantages and disadvantages, 689
- Free
 available chlorine, 275, 310
 chlorine, 286, 310
 energy, 237
 residual chlorination, 310
- Freezing and thawing treatment, 692
- Freundlich constant determination, 617, 618
- Friction factor, 56, 64
- Froude number, 63, 64
- G**
- GAC, 309, 336, 340, 528, 546, 566, 645
 adsorber, operating curve, 584
 adsorption
 case studies, 593
 design examples, 602–623
 recent developments, 623
 anaerobic filters, 575
 breakthrough curve, 580, 581
 column
 design, 585
 operation modes, 585
 economics, 595
 factors affecting, 592
 material cost, 610
 operating costs, 595
 performance, 593
 process flow diagrams, 576, 577, 578
 properties, 576
 regeneration, multiple hearth furnace, 591
 physical properties, 576
 specification, 576
- Garnet sand, 511
- Gas
 constant, 239
 mixing, 57
 to solid ratio, 444–448
 transfer rate, 242
- Gate peddle, 61
- Gel copolymer, 553
- Geometric similarity, 62, 64
- Giardia*, 104, 323, 324, 344
 cysts, 518
- Gibbs free energy, 146
- Grain diameter, 595
- Granular activated carbon, *see* GAC
- Granular carbon regeneration, fluid bed
 process
 construction cost, 614
 labor and total costs, 616
 operation and maintenance requirement, 615
- Granular filters, tertiary treatment, 526
- Gravity carbon contactor, 601, 602
 operation and maintenance requirement, 602, 603
- Gravity
 filters, design, 509
 filtration, 501
 application, 524
 design examples, 529
 empirical models, 509
 mathematical models, 504
 physical nature, 502
 straining, 502
 transport mechanism, 502
 granular media filter, 524
 settler, 413, 414
 thickener, 686, 689
 operation, 687
 thickening, 403–406
- Gray water reuse, treatment processes, 650
- Greenville Water Treatment Plant, 483, 489–491
- Grit
 chamber, 2, 398–403

- collector, 4
- removal, 23
- Groundwater, 310, 320, 567–568
 - decontamination, 567–568
 - disinfection rule, 320
- Guidelines for transferred ozone dosage, 330, 331
- H**
- HAA, *see* Haloacetic acid
- Haloacetic acid (HAA), 297, 310
- Halogenation, 230, 271–314, 308, 310
 - of organic materials, 334
- Halogens, 285
- Hard water, 220
- Hardness, 31, 220
- Head loss, 123, 124
 - comparisons, 510, 517
 - constants, 509
 - curves, 516
 - development, 515
 - equation, 507
 - expanded media, 535, 537
- Heavy metal removal, 141
- Helmholtz–Smoluchowski equation, 120
- Hemodialysis, 564
- Henry’s law, 317
- High rate
 - filters, 519
 - filtration plant, 656
 - floating-medium filter, 654
 - semi-pilot scale application, 654
- High shear application, 682
- High speed disk, 79
- High temperature wet oxidation, 248–256
- Highly aggressive water, 225
- Hindered settling, 77
- History
 - of ozone, 315, 316
 - of sedimentation, 379
- Hollow-fiber propylene membrane, 670
- Homogeneous suspension, 77
- Horizontal shaft flocculator, 81
- Housing costs, 352
- Howell Water Treatment Plant, 478–479, 482, 492
- Humic
 - materials, 104
 - substances, 320, 333
- Hydrated lime, 35, 42
- Hydration, 106
- Hydraulic
 - application rate, 518, 519
 - flocculator, 639
 - jump, 124
- Hydrodynamic forces, 502, 504
- Hydrogen peroxide, 246–248
- Hydrogen solubility in water, 463
- Hydrogen sulfide, 279, 280
- Hydrograph, 42
- Hydrolysis, 115, 116, 637
 - bromine, 283
 - chlorine, 274
 - iodine, 284
 - process, 691
 - comparisons, 695
- Hydrophilic
 - particles, 106, 113
 - solid, 436
- Hydrophobic
 - particles, 106, 113
 - solid, 436
- Hydroxide precipitation, 142–144, 158, 159
- Hydroxo complexes, 151, 152
- Hydroxyl radicals, 322, 337
- Hypochlorite, 301
- Hypochlorous acid, 301
- I**
- ICR, *see* Information collection rule
- Ideal mixing, 52
- Idealized models, 504
- Impeller
 - characteristics, 58
 - design, 27
 - discharge, 69
 - rate, 72
 - power
 - curves, 65
 - requirement, 26
 - selection, 78
- In process neutralization, 37
- Index of refraction, 106
- Indigo recovery, 666
- Indirect electrooxidation process, 370
- Indirect potable use (IPU), 525
- Industrial
 - neutralization, 37
 - waste treatment, 104
 - granular activated carbon process, 598

Inert electrodes, 363
 Inertial forces, 502
 Influent
 pH neutralization, 36
 water characteristics, 510
 Information collection rule, 296
 Inlets and outlets control, 391
 In-line
 flocculation, 643
 filtration systems, 528
 flow equalization, 23
 Inorganic
 coagulants, 678
 membrane, 661
 salts and inorganic polyelectrolytes,
 comparisons, 682
 In-plant neutralization, 36
In situ bioremediation, 39
 Interception, 502
 Investment and operating costs, carbon
 adsorption treatment, 600
 Iodination, 295, 310
 Iodine, 272, 273, 295
 dissociation, 284
 hydrolysis, 284
 reactions, 285
 Ion change, 649
 Ion exchange, 142
 process
 application, 657
 batch mode, 657
 continuous feed, 657
 fixed bed, 657
 fluidized bed, 657
 Ionic
 activity, 148, 149
 strength, 148, 149
 Iron
 and manganese removal, 320
 salts, 116
 Isotropic turbulence, 56

J
 Jar test, 119

K
 Kinematic viscosity, 123
 Kinetic energy, 109, 110
 Kraft mill wastewater treatment, 368
 Krofta Engineering Corporation, 472,
 484, 493

L
 Labile regime, 153
 Laboratory
 column test, 590
 scale up, 27
 Lake Erie water, filtration, 511
 Lake Vangum Water Treatment Plant, 483
 Lakeville Water Treatment Plant, 483
 Lamella
 separator, 410–412
 settler, 437
 Langelier Index, 206, 218, 224
 Laundry waste, DAF, 488
 Leachate treatment, electrolysis, 369
 Lee Water Treatment Plant, 479–480, 483
 Lenox Institute of Water Technology,
 472, 484, 493
 Lenox Water Treatment Plant, 472–476,
 483, 492
 Lignosulfonate recovery, pulp industry, 664
 Lime, 680
 feeding, 43
 post-treatment process, 695
 stabilization, 695
 /soda ash softening, 162, 201, 203, 220
 Limestone, 35
 Linear mixing, 57
 Longitudinal flow flocculator, 638
 Lysis, 359

M
 MacLaurin series expansion, 508
 Macroreticular, polymeric adsorbent, 546, 565
 Magnesium
 carbonate, 206–207
 neutralizers, 35
 oxide precipitation, 162
 Manganese ion, 281
 Mass
 balance equation, 505
 diffusivity, 56
 Material balance, 587
 Maximum
 contaminant level (MCL), 296–297,
 310
 goal (MCLG), 310
 mixedness, 54
 residual disinfectant level, 296
 MBR, industrial wastewater treatment, 677
 MCL, *see* Maximum contaminant level

- MCLG, *see* Maximum contamination level goal
- Mean velocity, 56
- Mechanical
- bar screen, 4
 - flocculator, 637
 - mixers, 124
 - mixing equipment, 58
 - processes, 685
 - surface aeration, 58
- Mechanically mixed system, 55
- Membio process, 673
- design, 673
 - flow diagram, 674
 - performance data, 673
- Membrane
- bioreactor (MBR), 671
 - wastewater treatment and reuse, 671
 - filtration, 220
 - process, 636, 658
 - application, 661
 - principle, 658
 - system
 - cost comparison, 668
 - performance, 668
- Membrane-based treatment, 526
- pretreatment, 526
- Memcor-60M10 (Memcor-US Membrane), 671
- Memtec-US Filter Ltd., 673
- Mercury intrusion, 554
- Metal
- precipitation, 34
 - removal, electrolysis, 370
 - sorption, 35
- Methane, 281
- MF membrane, industrial wastewater treatment, 675
- Microbial contamination, 310
- Microfilter membrane, 661
- Microfiltration (MF), 636, 658
- domestic wastewater treatment, 668
- Microorganism, 310
- Microscreens, 11
- Millwood Water Treatment Plant, 479, 483
- Milos Krofta, 472, 492, 493
- Mine drainage, 34
- Minimum fluidization velocity, 516
- Mitsui Petrochemical Industries (MPI), 663
- Mixed sludge, microphotographs, 682
- Mixer, 25
- power requirements, 26
- Mixing, 47, 48, 122–125
- basic concepts, 48
 - batch flow system, 73
 - continuous flow system, 73
 - degree, 50, 52, 76
 - criteria, 50
 - efficiency, 52
 - equipment, 55, 156, 157
 - data, 92
 - history parameter, 54
 - index, 77
 - intensity-duration, 55
 - length, 55, 56
 - requirement, 55
 - parameters, 50
 - performance, 52
 - power consumption, 61
 - processes, 55
 - tank volume, 27
 - time, 74
 - data, 74
 - parameters 57
- Mixture segregation, 50
- Moderately
- aggressive water, 225
 - hard water, 220
- Molecular
- diffusion, 49
 - distillation, 559
- Molecule movement through membrane, 660
- Monochloramine, 275, 278, 309
- Moreton Bay prawn pond effluent
- characteristics, 656
- Motionless mixers, 71, 73
- MRDL, *see* Maximum residual disinfectant level
- Mt. Vernon Water Treatment Plant, 482
- MTBE, 262
- Multicomponent adsorbates, 585
- Multimedia filters, 509, 512
- Multiple hearth
- furnace (MHF), 699
 - granular carbon
 - labor and total costs, 613
 - operation and maintenance requirement, 612
 - regeneration, construction cost, 611

- Multiple
 - trays settling chamber, 414
 - turbine impeller, 83
- Multistage biological nutrient removal
 - technology, 652
- Municipal wastewater treatment, 104
- Munition wastewater treatment, electro-chemical, 373
- N**
- Nanofiltration (NF), 636, 658
 - membrane, 659
- Nanty Glo Water Treatment Plant, 478–479, 483, 492
- National Research Council, 626
- Negative head, 502
- Nernst
 - equation, 239
 - potential, 108
- Neutralization, 21, 284, 679
 - agent, 37
 - basin, 40
 - chemicals, 38
 - design, 39
- NEWWATER Project, 525
- Ngau Tam Mei Water Works, 626
- Niagara Falls Physical Chemical
 - Wastewater Treatment Plant, 624
- Nitrogen
 - removal, biological treatment, electrolysis stimulated, 374
 - solubility in water, 463
 - trichloride, 276
- Nitrogenous matter, chlorine reaction, 275
- NOM, 104
- Nominal design filtration rate, 539, 540
- Nonaggressive water, 225
- Non-ideal mixing, 54
- Nonionic polyelectrolytes, 681
- Non-mechanical processes, 685
- NTU, 511
- Nucleation, 153
- O**
- Off-center propeller, 79
- Office building wastewater reuse treatment,
 - design criteria, 651
- Off-line flow equalization, 23
- Oil and grease removal, 455
- One-stage recarbonation, 35
- Operating and equilibrium curves, 618
- Operation and maintenance costs, 352
- Optimal dose, conditioner, 682
- Optimum sludge characteristics, 681
- Orange County Water District (OCWD)
 - plant, reverse osmosis, MF pretreatment, 670
- Organic
 - disinfectant, 296,
 - matter, 310
 - polymers, 117, 118
 - solids removal, 363
 - electrocoagulation, 364
 - electrolysis, 363
- Orthokinetic flocculation, 637
- OTV (BIOSEP process), 672
- Overall particles removal, 386
- Overflow
 - rates, 393, 395, 402, 405, 406, 410, 648
 - structure, 23
- Oxidation, 230, 231, 308
 - kinetics, 240–242
 - reactions, 359
 - state values, 232, 233
 - ozone, 334–337
 - potentials, 238, 335
 - reduction, 162, 230, 231
- Oxygen
 - balance, 242
 - solubility, 463
- Oxygenation, 243–256, 340–349, 295, 299, 310, 315–354
- Ozonation, 594
- Ozone, 230, 286, 295, 299, 309
 - advantages and disadvantages, 319
 - contact basin, 346
 - contacting, 345–348
 - contactor exhaust gas, 348, 349
 - controllers, 349
 - design considerations, 321–340, 348
 - dosage, 326, 331–333
 - equipment
 - costs, 349–352
 - installation, 352
 - generation, 344, 345
 - monitors, 349
 - process, 261, 262
 - considerations, 321–340
 - with high pH levels, 340
 - with hydrogen peroxide, 340
 - ultraviolet, 340

P

- PAC (Powdered activated carbon), 647
 - advantages, 648
 - disadvantages, 648
 - activated sludge process, 573
- PACT (Powdered activated carbon treatment)
 - adsorption, schematic diagram, 648
- Paddle, 27
 - flocculator, 638
 - parameters, 639
 - impeller, 61
 - mixer, 81
 - power data, 67
 - wheel flocculator, 82
- Paint recovery, metal-painting wastewater, 664
- Parasitic protozoa, 310
- Parshall flume, 399–402
- Particle
 - size, resin adsorbent, 556
 - transport mechanism, 503
- Passive neutralization, 36
- Pathogen, 310
- PCT (Physical–chemical treatment), 574
 - disinfection, 577
 - filtration, 577
 - full-scale plant performance, 595
 - pilot plant performance 595
 - wastewater treatment, 525
- Peclet number, 507
- Pentachlorophenol (PCP), 262
- Percentage mixed values, 77
- Permanganate
 - oxidation, 258–261
 - reagent, 259
- Permeate flux, 659
- Peroxygen reagent, 246–248
- Pervaporation, 636
- Pesticides, 339
 - petroleum refining waste, DAF, 489
- pH, 105, 113, 118, 143, 152, 231, 310, 317, 331, 340, 347
- Phenol, polymeric adsorption, 555
- Phenolic
 - compounds, 283
 - waste, 559–562
- Phosphate removal, 141
 - electrolysis, 368
- Phosphorous precipitation, 162, 163
- Physical adsorption, 573, 575, 644
- Physical chemical treatment plants,
 - municipal wastewaters, 597
- Physical properties of ozone, 316
- Physical-chemic treatment, *see* PCT
- Physicochemical processes, 651
- Pilot
 - column test, 587
 - plant
 - operation data, 536
 - test, 590
 - scale study, 655
- Pipe diameter, 56
- Pitched
 - blade
 - axial discharging type, 59
 - impeller, 60
 - vane turbine, 60
- Pittsfield Water Treatment Plant, 477–478, 482, 492
- Plain chlorination, 310
- Plastic beads, 643
- Plate and frame press, 687
 - advantages and disadvantages, 691
- Plate press, advantages and disadvantages, 689
- Plug flow processes, 577, 578
- Pneumatic mixers, 124
- Polyaluminum chloride (PACl), 117, 680
- Polyelectrolytes, 117
- Polymer properties, 117
- Polymeric
 - adsorbent, 545, 550, 552
 - adsorption and distillation system, 545–571
 - air stripping, 569, 570
 - application, 548
 - evaluation, 548, 550
 - limitations and reliability, 550
 - process adoption, 549
 - process description, 547
 - regeneration, 547
 - inorganic salts, 117
- Polymerization, 115, 116
- Polymers, 114, 118
- Polynuclear complexes, 152
- Polystyrene, 552
- Pore
 - distribution, adsorbent, 554
 - size

- distribution, 592
 - resin adsorbent, 556
 - Porosity, 507
 - Positive displacement pumps, 122
 - Post-lime stabilization, advantages and disadvantages, 696
 - Post-treatment, 677
 - Potable water
 - disinfection, 303–308
 - filtration, 524, 527
 - Powdered activated carbon, *see* PAC
 - Powdered activated carbon treatment, *see* PACT
 - Power
 - dissipation rate, 54
 - functions, 66, 67
 - number, 64
 - prediction, 64
 - requirement, 67
 - Prawn pond effluent characteristics, 656
 - Prechlorination, 310
 - Precipitation, 679
 - and coagulation, 168, 169
 - design
 - considerations, 155–158
 - criteria, 157, 158
 - kinetics, 152–155
 - principles 146–152
 - process, 141
 - advantages, 163, 164
 - applications, 158–163
 - evaluation, 163–165
 - limitations, 163, 164
 - performance, 165
 - reliability, 164
 - types, 142–146
 - Pressure
 - carbon contactors
 - construction cost, 607
 - labor and total costs, 609
 - operation and maintenance requirement, 608
 - filtration, 501
 - tank, 452
 - Pressured air, 452
 - Pretreatment, 677
 - Primary
 - clarification, DAF, 490
 - clarifier, 2
 - sedimentation tanks, 394
 - Process chemistry, recarbonation, 201, 213
 - Propeller, 27
 - axial type, 58
 - baffled vessel, 79
 - marine-type, 58
 - mixing time correlation, 76
 - Properties
 - of ozone, 316–319
 - of water, 127
 - Proportional weir, 399, 400, 404
 - Pulsed beds, 587
 - adsorption system, 646
 - Pure water production, 659
- Q**
- Quantity of grit removal, 403
 - Quicklime, 35
- R**
- Radial flow turbine, 60
 - Radionuclides, 103, 104
 - Raised turbine, 83
 - baffled vessel, 80
 - Rapid
 - filter, 519
 - schematic diagram, 642
 - filtration, 640
 - mix system, 55
 - mixing, 636
 - sand filter plants, 524
 - Rapid-Mix, 124–131
 - Raw water, 310
 - particles, 680
 - RDX, 263
 - Reaction
 - equilibria, 146, 147
 - kinetics, 52
 - of ozone with
 - inorganic compounds, 317, 318
 - organic compounds, 318, 319
 - Reboiler, 558
 - Recarbonation, 35, 199–228, 215–310
 - design, 208, 213–220
 - process description, 199
 - single-stage, 215
 - Rechlorination, 310
 - Rectangular tanks, 396, 397
 - sedimentation, 640
 - Recycled water
 - quality criteria, 654
 - specifications, 653

- Recycling and recovery, benefits, 677
- Reduction, 230, 231
 - reactions, 360
- Reedy Creek Services District, 671
- Regenerant
 - distillation, 545–571
 - polymeric adsorbent, 552, 561
- Regulatory standards, 393–395
- Relative
 - moisture removal ratio, sludge dewatering, 686
 - size group, 507
- Removal
 - of ammonium chloride, 163
 - of heavy metals, 163
 - of humic substances, 163
 - of iron, 234
 - of manganese, 235
 - of mercury, 163
 - of phenol, 235
 - of radium, 155
- Repulsive electric force, 107–110
- Residence-time distribution, 53, 54
 - function, 53, 54
 - frequency function, 54
- Resin adsorbent, *see* Polymeric adsorbent
- Resin adsorption, *see* Polymeric adsorption
- Retreating blade turbine, 60
- Reverse osmosis (RO), 142, 636, 658, 662
 - system, 528
 - water reclamation, 661
- Revolving
 - screen, 3
 - drum, 3
 - vertical disk screen, 11
- Reynolds number, 56, 57, 62, 123, 383
- Rhone–Poulenc system, 663
- Rippl diagram 23–24
- Risk assessment, 311
- Root-mean-square (rms), 50
 - velocity, 56
- Rotary feeder, 122
- Rotating paddle, 55
- Rouse Hill STP, 652
- Ryznar index, 225
- S**
- Sacrificial anodes, 363
- Safe Drinking Water Act, 296
- Safety in using ozone, 353
- Sand
 - bed, 690
 - filters, 35
 - specification, 515
- Saskatchewan–Canada Biological GAC filtration plant, 625
- Saturated zone, 580
- SBR (*see also* Sequencing batch reactor), 470
- Schmidt number, 56
- Schmutzdecke, 518
- Schultze–Hardly rule, 110
- Scour coefficient, 506
- Screen, 1–9, 23
 - cleaning, 5
 - design, 3–5, 12–14
- Screening, 1–19
- Screenings, quantity and disposal, 6
- Screw feeder, 122
- SDWA (Safe Drinking Water Act), 296
- Second
 - class clarification, 639
 - stage recarbonation, 35
- Secondary
 - clarification, DAF, 490
 - sedimentation tank, 394
- Sedimentation, 379–426, 435–438, 502, 635, 639
 - field-flow fractionation (SdFFF), 411, 412
 - flotation, 486, 487
 - in air streams, 412–414
 - tank
 - design, 393, 394
 - geometry, 392
 - horizontal flow, 639
 - design criteria, 641
 - loading, 393, 406
 - types, 395, 396
 - use in wastewater treatment, 394–398
 - use in water treatment, 390–394
- Segregation
 - degree, 52
 - intensity, 50, 51, 52
 - scale, 50, 51
- Sequencing batch reactor (SBR), flotation, 470
- Settling velocities, 382
- Sewage sludge, anaerobic digestion, 696
- Shaft-mounted impellers, 58
 - paddlers, 58

- propeller, 58
- turbine, 58
- Shallow depth settling, 407–411
- Shear, 54
 - forces, 54
- Short circuiting, 392
- Shredder, 2
- Significance of sedimentation, 380
- Silica
 - gel, 546
 - sand, 511
- Silo equipment, 43
- Single
 - media conventional filter, 512
 - stage
 - digester, 697
 - lime/soda-ash softening, 220, 222
 - turbine impeller, 83
- Site remediation, 570
- Slow
 - mixing, 636
 - sand filters, 518
- Sludge
 - blanket clarifier, 640
 - composting, 698
 - advantages and disadvantages, 699
 - conditioning
 - performance, 681
 - processes, 678
 - contact clarifier, 641
 - dewaterability, 683
 - dewatering, 687
 - drying, 701
 - advantages and disadvantages, 701
 - capital cost, 701
 - floc
 - appearance, from pH change, 693
 - characteristics, effect of pH change, 694
 - floculant system, 683
 - incineration, 699
 - advantages and disadvantages, 701
 - lime stabilization, 695
 - origin, 677
 - recycling and recovery, 677, 678
 - stabilization, 249–256
 - processes, 691
 - thickener, 686
 - thickening, 685
 - treatment system, 677
 - network, 677, 679
 - volume
 - index (SVI), 406, 410
 - ratio (SVR), 406
- Slurry
 - liquid interface, 77
 - viscosity effect, 83
- Soda ash, 35
- Sodium
 - aluminate, 116, 117
 - hydroxide, 301
 - hypochlorite, 301
 - neutralizers, 35
- Soft water, 220
- Softening, 199, 201
- Soil, 546
- Solid
 - contact
 - clarifier, 640
 - required, various treatment processes, 685
 - liquid separation, 453
 - processes, 683
 - suspension, 77
 - suspension, effectiveness, 77
- Solids
 - separation, 157
 - suspension, 96
- Solubility
 - diagrams, 152
 - equilibria, 147
 - of chemicals, 166
 - product constant, 147, 148
- Soluble complex formation, 151, 152
- Solvent regeneration, 562
- Specific
 - gravity, resin adsorbent, 556
- Specific
 - resistance, filtration, activated sludge, 685
- Speed of rotation times diameter (*ND*), 63
- Stability
 - characteristics, 225
 - diagram, alum salt, 680
- Stack gas, 209, 215
- Static
 - floculator, 643
 - mixer, 84, 85, 86, 124
 - design procedures, 86
 - new development, 86
- Steady-state

- adsorption column, 584
 - operation line, 586
- Steel gravity carbon contactors
 - construction cost, 604
 - labor and total costs, 606
 - operation and maintenance requirement, 605
- Stern
 - layer, 107, 108
 - potential, 107
- Stoichiometry, 234–236
- Stokes' Law, 383
- Streaming current detector, 121
- Submerged
 - biofilter, electrolysis, 376
 - membrane process
 - flow diagram, 672
 - industrial wastewater treatment, 672
 - turbine units, 58
- Substituted chlorophenol, polymeric adsorption, 555
- Sulfide precipitation, 144, 145, 160, 161
- Supercritical water oxidation (SCWO), 264, 702
- Superficial rate of saturation, 584
- Surface
 - area, resin adsorbent, 556
 - of shear, 107–109
 - water, 311
 - treatment rule (SWTR), 300, 316, 323, 324
- Suspended solids removal, 363
 - efficiency, 514
 - electrocoagulation, 364
 - electrolysis, 363
- Suspension criterion (S), 83
- Sutro weir, 400
- SWTR, *see* Surface water treatment rule
- Sydney Sewage Treatment Plant, Membio process, performance data, 674
- Synthetic organic flocculants, 681
- T**
- TCE, 264
- TDS, 149
- Temperature, 114, 117, 317, 341
- Tertiary treatment, 574
 - flow diagrams, 577
 - plants, municipal wastewaters, 596
 - wastewater, 515
 - wastewater treatment, MBR, 674
- Test, flotation, 457
- Textile wastewater treatment,
 - electrocoagulation, 366
- Theory
 - oxidation, 233–242
 - sedimentation, 381–390
- Thermal treatment, 692
 - processes, 699, 702
 - phase diagram, 702
- Thermodynamics of oxidation, 236–240
- Thickening, 683
 - flotation, 456
- Thin film composite (TFC) RO membrane, 671
- THM, *see* Trihalomethane
- Three-blade, 66
 - propellers, 66
- Threshold odor number (TON), 321
- TNT (trinitrotoluene), 562, 563
- TOC, 263
- Total
 - coliform reduction, 327
 - hardness, 32
 - organic carbon (TOC), 320
 - trihalomethane, 296–297
- Tracer behavior, 53
- Traditional treatment, 525
- Transfer efficiency (TE), 326, 331–333
- Transferred ozone (T), 326, 327–330
- Transition-metal ions, 243
 - systems, 256–261
- Treated effluent standards, Rouse Hill STP, 653
- Treatment
 - of aluminum forming industry wastes, 192
 - of auto and laundry industry wastes, 197
 - of battery industry wastes, 193
 - of coil coating industry wastes, 188, 189
 - of copper industry wastes, 195
 - of electrical and electronic industry wastes, 194
 - of foundry industry wastes, 175
 - of inorganic chemicals Industry wastes, 183
 - of iron and steel industry wastes, 179
 - of metal finishing industry wastes, 176–178
 - of nonferrous industry wastes, 190, 191

- of ore mining and dressing industry wastes, 184, 185
- of organic and inorganic industry wastes, 196
- of paint manufacturing industry wastes, 187
- of porcelain industry wastes, 186
- of steam electric industry wastes, 181, 182
- of textile mills wastes, 180
- technologies, 337–339
- Trichloramine, 276
- Trichloroethylene (TCE), 340
- Trickling filter secondary effluent filtration, 517
- Trihalomethanes (THMs), 104, 296–299, 309, 311
- Trinitrotoluene (TNT), 562, 563
- Trivalent metallic cations, 114
- TTHM, *see* Total trihalomethane
- Tube settlers, 408–410
 - applications, 409, 410
 - design criteria, 410
- Turbidity, 311, 511
 - removal, 528
- Turbine, 27
 - agitator propellers, 68
 - discharging type, 59
 - impeller, 26, 59, 67
 - design, 59
 - mixing time correlation, 75
 - power correlation, 67
- Turbulence, 56
- Turbulent mixing batch reactors, 644
- Two-stage
 - lime/soda ash softening, 221
 - recarbonation, 35
 - tertiary lime process, 219–220, 225
- Tyndall effect, 106
- Types
 - of clarification, 380, 381
 - of grit chambers, 399, 380
- U**
- US Primary Drinking Water Regulations, 511
- UBIS system, 663
- UF (ultrafiltration), 528, 636, 658, 660
 - blue colorant recovery, rinsing bath, 667
 - design, 664
 - domestic wastewater treatment, 663
 - industrial wastewater treatment, 664
 - metal workshop cutting oil recovery, 667
 - pretreatment for RO, red meat abattoir industry, 666
- Ultrasound treatment, 692
- Ultraviolet light (UV), 296, 300, 309, 311, 337, 340, 344
 - H₂O₂, 263
 - ozone, 263
 - processes, 262, 263
 - radiation, 296, 309, 311
- Unhindered settling velocity, 536
- Uniformity coefficient, 513
- Universal gas constant, 146
- Upflow
 - biological aerated flooded filter (BAFF), 669
 - expanded, 587
 - fluidized bed
 - biological GAC systems, 627, 628
 - process, 577
 - pressure fixed-bed process, 577
- V**
- Vacuum filtration, 501
- Van der Waals' attractive forces, 109
- Vapor pressure, carbon dioxide, 213
- Variable declining-rate filtration, 519, 520, 521
- Velocity
 - control devices, 399–402
 - eddy, 56
 - gradient, 27, 54, 55, 123, 637
- Vertical flocculator, 638
- Very hard water, 220
- Vessel geometry, 28
- Vibrating trough feeder, 122
- Ville Franque (France) wastewater treatment plant, 672
 - MBR performance, 672, 673
- Virus inactivation, electrochemical, 368
- Viruses, 311
- Viscosity, 56
- Void volume, resin adsorbent, 556
- Volatile organic compounds (VOCs), 337, 338
- Vorti-mix turbine, 81
- W**
- Wastewater
 - characteristics, 655

- disinfection, 301–303, 305–308
 - flow variation with time, 41
 - reclamation, 524, 525, 529, 530
 - membrane-based treatment, 525
 - traditional treatment, 525
 - recycle, 635
 - plant, flow chart, 650
 - reuse, 635
 - treatment
 - and reuse, physicochemical processes, application, 651
 - filter, design problems, 524
 - Water
 - backwashing flow rates, 522
 - contaminant
 - membrane process, 668
 - removal range, 668
 - factory, 21, 525, 670
 - treatment process, flow diagram, 671
 - mining plant, Canberra, Australia, 668, 669
 - performance, 670
 - quality
 - final effluent, 530
 - pretreated feed water, 529
 - reclamation, Eraring Power Station, 662
 - softening resin system, 658
 - design criteria, 658
 - softening, 34, 141, 162
 - stability index, 225
 - stabilization, 205, 224
 - temperature, 511
 - treatment, 104
 - variables, 510
 - Waterborne disease, 311
 - Watershed, 311
 - Wave number, 56
 - West Nyack Water Treatment Plant, 483
 - Westmoreland Water Treatment Plant, 483
 - Wet air oxidation, 702
 - Wet oxidation, 263, 264
- Z**
- Zebra mussel, 320
 - Zeta
 - meter, 120
 - potential, 107, 108, 112, 683
 - biological sludge, 684
 - Zimmerman process, 252–255
 - Zone settling, 387–390, 639
 - Zones of settling basin, 391
 - Zwitering's technique, 96