

Additional References

- Bae JH, Park M-H, Lee J-H (1999) Local flow and heat transfer of a 2-row offset strip fin-tube heat exchanger. *J Enhanc Heat Transf* 6:13–29
- Balachandar S, Parker SJ (2002) Onset of vortex shedding in an in-line and staggered array of rectangular cylinders. *Phys Fluids* 14(10):3714–3732
- Beecher DT, Fagan TJ (1987) Effects of fin pattern on the air-side heat transfer coefficient in plate finned-tube heat exchangers. *ASHRAE Trans* 93(2):1961–1984
- Bergles AE (1985) Techniques to augment heat transfer. In: *Handbook of heat transfer applications*. McGraw-Hill, New York
- Brauer H (1964) Compact heat exchangers. *Chem Frog Eng (London)* 45(8):451–460
- Brigham BA, VanFossen GJ (1984) Length to-diameter ratio and row number effects in short pin-fin heat transfer. *J Eng Gas Turbines Power* 106:241–246
- Chen L, Zhang HJ (1993) Convection heat transfer enhancement of oil in a circular tube with spiral spring inserts. In: Chow LC, Emery AF (eds) *Heat transfer measurements and analysis, HTD-ASME Symp.*, vol 249, pp 45–50
- Chokeman Y, Wongwises S (2005) Effect of fin pattern on the airside performance of herringbone wavy fin-and-tube heat exchangers. *Heat Mass Transf* 41:642–650
- Chyu MK, Hsing YC, Natarajan V (1998) Convective heat transfer of cubic fin arrays in a narrow channel. *J Turbomachinery Trans ASME* 120:362–367 341
- Chyu MK, Hsing YC, Shih TIP, Natarajan V (1999) Heat transfer contributions of pins and endwall in pin-fin arrays: effect of thermal boundary condition modeling. *J Turbomachinery Trans ASME* 121:257–263
- Coetzee H, Liebenberg L, Meyer JP (2001) Heat transfer and pressure drop characteristics of angled spiralling tape inserts in a heat exchanger annulus. In: Paper RA, Aminemi NK, Toma O, Rudland R, Crain E (eds) *Proceedings of the ASME process industries division*. ASME, New York
- Colburn AP, King WJ (1931) Relationship between heat transfer and pressure drop. *Ind Eng Chem* 23(8):918–923
- Cox B, Jallouk PA (1973) Methods for evaluating the performance of compact heat exchanger surfaces. *J Heat Transf* 95:464–469
- Date AW (1973) Flow in tubes containing twisted tapes. *Heat Ventilating Eng* 47:240–249
- Date AW (1974) Prediction of fully-developed flow in a tube containing a twisted tape. *Int J Heat Mass Transf* 17:845–859
- Date AW, Saha SK (1990) Numerical prediction of laminar flow in a tube fitted with regularly spaced twisted tape elements. *Int J Heat Fluid Flow* 11(4):346–354

- Date AW, Singham JR (1972) Numerical prediction of friction and heat transfer characteristics of fully developed laminar flow in tubes containing twisted tapes, ASME Paper 72-HT-17. ASME, New York
- Davenport CJ (1984) Correlations for heat transfer and flow friction characteristics of louvered fin. In: Heat transfer-Seattle 1983, AIChE Symposium Series No. 225, vol 79, pp 19–27
- Dhir VK, Chang F (1992) Heat transfer enhancement using tangential injection. ASHRAE Trans 98(2):383–390
- Dhir VK, Tune VX, Chang F, Yu J (1989) Enhancement of forced convection heat transfer using single and multi-stage tangential injection. In: Goldstein RJ, Chow LC, Anderson EE (eds) Heat transfer in high energy heat flux applications, ASME Symp. HTD, vol 119
- Ebisu T (1999) Development of new concept air-cooled heat exchanger for energy conservation of air-conditioning machine. In: Kakac S et al (eds) Heat transfer enhancement of heat exchangers. Kluwer Academic, Dordrecht, pp 601–620
- Edwards FJ, Sheriff N (1961) The heat transfer and friction characteristics for forced convection air flow over a particular type of rough surface. In: International developments in heat transfer. ASME, New York, pp 415–425
- Emerson WH (1961) Heat transfer in a duct in regions of separated flow. In: Proc. third international heat transfer conference, vol 1, pp 267–275
- Engineering Sciences Data Unit. Low-fin staggered tube banks: heat transfer and pressure loss for turbulent single phase crossflow. Engineering Sciences Data Unit, ESDU Item 84016
- Evans LB, Churchill SW (1963) The effect of axial promoters on heat transfer and pressure drop inside a tube, Chem. Eng. Prag. Symp. Ser: 59, vol 41, 36–46
- Fiebig M, Mitra NK, Dong Y (1990) Simultaneous heat transfer enhancement and flow loss reduction of fin-tubes. Heat Transf 3:51–55
- Fu WS, Tseng CC, Huang CS (1995) Experimental study of the heat transfer enhancement of an outer tube with an inner tube insertion. Int Heat Mass Transf 38(18):3443–3454
- Gao X, Sundén B (2001) Heat transfer and pressure drop measurements in rib-roughened rectangular ducts. Exp Thermal Fluid Sci 24(1–2):25–34
- Gianolio E, Cuti F (1981) Heat transfer coefficients and pressure drops for air coolers under induced and forced draft. Heat Transf Eng 3(1):38–48
- Goldstein L, Sparrow EM (1976) Experiments on the transfer characteristics of a corrugated fin and tube heat exchanger configuration. J Heat Transf 98:26–34
- Goldstein LJ, Sparrow EM (1977) Heat/mass transfer characteristics for flow in a corrugated wall channel. J Heat Transf 99:187–195
- Gupte N, Date AW (1989) Friction and heat transfer characteristics of helical turbulent air flow in annuli. J Heat Transf 111:337–344
- Hatada T, Senshu T (1984) Experimental study on heat transfer characteristics of convex louver fins for air conditioning heat exchangers, ASME paper, 84-H-74, New York
- Hatada D, Ueda U, Oouchi T, Shimizu T (1989) Improved heat transfer performance of aircoolers by strip fins controlling air flow distribution. ASHRAE Trans 95(1):166–170
- Hay N, West PD (1975) Heat transfer in free swirl in flow in a pipe. J Heat Transf 97:411–416
- Hitachi Cable Ltd. (1984) Hitachi high-performance heat transfer tubes, Cat. No. EA-500. Hitachi Cable, Ltd, Tokyo, Japan
- Holtzapple MT, Carranza RG (1990) Heat transfer and pressure drop of spined pipe in cross flow. Part 1: pressure drop studies. ASHRAE Trans 96(2):122–129
- Holtzapple MT, Allen AL, Lin K (1990) Heat transfer and pressure drop of spined pipe in cross flow. Part III: heat transfer studies. ASHRAE Trans 96(2):130–135
- Hong SW, Bergles AE (1976) Augmentation of laminar flow heat transfer in tubes by means of twisted tape inserts. J Heat Transf 98:251–256
- Hong K, Webb RL (1999) Performance of dehumidifying heat exchangers with and without wetting coatings. J Heat Transf 121:1018–1026
- Hong K, Webb RL (2000) Wetting coatings for dehumidifying heat exchangers. Int J Heat Ventilation Air Condition Refrig Res 6(3):229

- Hou Kuan T, Lap Mou T, Ghajar AJ, Sik Chung T, Tong Z (2012) Experimental investigation of heat transfer, friction factor, and optimal fin geometries for the internally microfin tubes in the transition and turbulent regions. *J Enhanc Heat Transf* 19(5):457–476
- Hsieh S-S, Kuo M-T (1994) An experimental investigation of the augmentation of tube-side heat transfer in a crossflow heat exchanger by means of strip-type inserts. *J Heat Transf* 116:381–390
- Itoh M, Kogure H, Miyagi M, Mochizuki S, Yagi Y, Kunugi Y (1995) Development of an accordion-type offset fin heat exchanger. *Trans Jpn Assoc Refrig* 12(2):219–224. [in Japanese]
- Jacobi AM, Shah RK (1998) Air-side flow and heat transfer in compact heat exchangers: a discussion of enhancement mechanisms. *Heat Transf Eng* 19(4):29–41
- Jakob M (1938) Heat transfer and flow resistance in cross flow of gases over tube banks. *Trans ASME* 60:384
- Jang J-Y, Chen L-K (1997) Numerical analysis of heat transfer and fluid flow in a three-dimensional wavy-fin and tube heat exchanger. *Int J Heat Mass Transf* 40:3981–3990
- Jang JY, Yang JY (1998) Experimental and 3-D numerical analysis of the thermal hydraulic characteristics of elliptic finned-tube heat exchangers. *Heat Transf Eng* 19(4):55–67
- Jang J-Y, Shieh K-P, Ay H (2001) Three-dimensional thermal-hydraulic analysis in convex louver finned-tube heat exchangers. *ASHRAE Trans* 107(2):503–509
- Jayaraj D, Masilamani JG, Seetharamu KN (1989) Heat transfer augmentation by tube inserts in heat exchangers, SAE Technical paper 891983, Warrendale, PA
- Jones TV, Russell CMB (1980) Heat transfer distribution on annular fins, ASME Paper 78-H-30, New York
- Kang HC, Webb RL (1998) Evaluation of the wavy fin geometry used in air-cooled finned tube heat exchangers. In: *Heat transfer 1998, Proceedings of the 11th international heat transfer conference Kyongju, Korea, vol 6*, pp 95–100
- Kim NH, Youn B (2013) Airside performance of fin-and-tube heat exchangers having sine wave or sine wave-slit fins. *J Enhanc Heat Transf* 20(1):43–58
- Koch R (1958) Druckverlust und Waermeuebergang bei verwirbeiter Stroemung, *Vei: Dtsch. Ingen Forschungsheft Ser. B* 24(469): 1–44
- Lopina RF, Bergles AE (1969) Heat transfer and pressure drop in tape-generated swirl flow of single-phase water. *J Heat Transf* 91:434–442
- Maezawa S, Lock GSH (1978) Heat transfer inside a tube with a novel promoter. In: *International Heat Transfer Conference Digital Library*. Begel House Inc.
- Manglik RM (1991) Heat transfer enhancement of in-tube flows in process heat exchangers by means of twisted-tape inserts. Ph.D. thesis, Department of Mechanical Engineering, Rensselaer Polytechnic Institute, Troy, NY
- Manglik RM, Bergles AE (1992a) Heat transfer and pressure drop correlations for twisted-tape inserts in isothermal tubes: part I. Laminar flows. In: Pate MB, Jensen MK (eds) *Enhanced heat transfer*, ASME Symp. HTD, vol 202, pp 89–98
- Manglik RM, Bergles AE (1992b) Heat transfer and pressure drop correlations for twisted-tape inserts in isothermal tubes: part II. Transition and turbulent flows. In: Pate MB, Jensen MK (eds) *Enhanced heat transfer*, ASME Symp. HTD, vol 202, pp 99–106
- Matos RS, Laursen TA, Vargas JVC, Bejan A (2004) Three-dimensional optimization of staggered finned circular and elliptic tubes in forced convection. *Int J Therm Sci* 43:477–487
- Mergerlin FE, Murphy RW, Bergles AE (1974) Augmentation of heat transfer in tubes by means of mesh and brush inserts. *J Heat Trans* 96:145–151
- Metzger DE, Berry RA, Bronson JP (1982) Developing heat transfer in rectangular ducts with staggered arrays of short pin fins. *J Heat Transf Trans ASME* 104:700–706
- Müller-Menzel T, Hecht T (1995) Plate-fin heat exchanger performance reduction in special two-phase flow conditions. *Cryogenics* 35(5):297–301
- Oliver DR, Aldington RWJ (1986) Enhancement of laminar flow heat transfer using wire matrix turbulators. In: *Heat transfer–1986 Proc. eighth international heat transfer conference, vol 6*, pp 2897–2902

- Park Y, Cha J, Kim M (2000) Heat transfer augmentation characteristics of various inserts in a heat exchanger tube. *J Enhanc Heat Transf* 7:23–34
- Pulvirenti B, Matalone A, Barucca U (2010) Boiling heat transfer in narrow channels with offset strip fins: application to electronic chipsets cooling. *Appl Therm Eng* 30(14–15):2138–2145
- Rabas TJ, Huber FV (1989) Row number effects on the heat transfer performance of inline finned tube banks. *Heat Transf Eng* 10(4):19–29
- Razgatis R, Holman JP (1976) A survey of heat transfer in confined swirl flows. *Heat Mass Transf Process* 2:831–866
- Rich DG (1973) The effect of fin spacing on the heat transfer and friction performance of multi-row, plate fin-and-tube heat exchangers. *ASHRAE Trans* 79(2):137–145
- Rich DG (1975) The effect of the number of tube rows on heat transfer performance of smooth plate fin-and-tube heat exchangers. *ASHRAE Trans* 81(1):307–319
- Robertson JM, Lovegrove PC (1983) Boiling heat transfer with Freon 11 brazed-aluminium plate fin heat exchanger. *Trans ASME J Heat Transf* 105:605
- Saboya FEM, Sparrow EM (1976a) Transfer characteristics of two-row plate fin and tube heat exchanger configurations. *Int J Heat Mass Transf* 19:41–49
- Saboya FEM, Sparrow EM (1976b) Experiments on a three-row fin and tube heat exchanger. *J Heat Transf* 98(3):520–522
- Saboya FEM, Rosman EC, Carajilescov P (1984) Performance of one- and two-row tube and plate fin heat exchangers. *J Heat Transf* 106:627–632
- Saboya SM, Saboya FEM (2001) Experiments on elliptic sections in one and two-row arrangements of plate fin and tube heat exchangers. *Exp Therm Fluid Sci* 24:67–75
- Saha SK, Dutta A (2001) Thermohydraulic study of laminar swirl flow through a circular tube fitted with twisted tapes. *J Heat Transf* 123:417–427
- Saha SK, Gaitonde UN, Date AW (1989) Heat transfer and pressure drop characteristics of laminar flow in a circular tube fitted with regularly spaced twisted-tape elements. *Exp Therm Fluid Sci* 2:310–322
- Sahin B, Taguchi A (2007) Approach for determination of optimum design parameters for a heat exchanger having circular-cross sectional pin fins. *Heat Mass Transf* 43(5):493–502
- Schmidt TE (1951) Heat transmission and pressure drop in banks of finned tubes and laminated coolers. *Proc Gen Discuss Heat Transf II*:186–188
- Schmidt E (1963) Heat transfer at finned tubes and computations of tube bank heat exchangers, *Kaltetechnik*, No. 4, 15, 98; No. 12, 15, 370
- Seshimo Y, Fujii M (1991) An experimental study on the performance of plate and tube heat exchangers at low Reynolds numbers. In: *Proc. 1981 ASME-JSME thermal engineering conference*, vol 4, pp 449–454
- Sethumadhavan R, Raja Rao M (1983) Turbulent flow heat transfer and fluid friction in helical wire coil inserted tubes. *Int J Heat Mass Transf* 26:1833–1845
- Shah RK, Bhatti MS (1987) Laminar convective heat transfer in ducts. In: Kakac S, Shah RK, Aung W (eds) *Handbook of single phase heat transfer*. Wiley, New York, pp 3–20
- Shivkumar C, Rao MR (1998) Studies on compound augmentation of laminar flow heat transfer to generalized power law fluids in spirally corrugated tubes by means of twisted tape inserts. In: Jacobs HR (ed) *ASME Proc. 96, 1988 national heat transfer conference, HTD, 96*, vol 1, 685–692
- Smithberg E, Landis F (1964) Friction and forced convection heat transfer characteristics in tubes with twisted tape swirl generators. *J Heat Transf* 87:39–49
- Thomas DG (1967) Enhancement of forced convection mass transfer coefficient using detached turbulence promoters. *Ind Eng Chem Process Design Dev* 6:385–390
- Thorsen R, Landis F (1968) Friction and heat transfer characteristics in turbulent swirl flow subjected to large transverse temperature gradients. *J Heat Transf* 90:87–89
- Torii K, Kwak KM, Nishina K (2002) Heat transfer enhancement accompanying pressure-loss reduction with winglet-type vortex generators for fin-tube heat exchangers. *Int J Heat Mass Transf* 45:3795–3801

- Trupp AC, Lau ACY (1984) Fully developed laminar heat transfer in circular sector ducts with isothermal walls. *J Heat Transf* 106:467–469
- Uttawar SB, Raja Rao M (1985) Augmentation of laminar flow heat transfer in tubes by means of wire coil inserts. *J Heat Transf* 105:930–935
- Valencia A (1999) Heat transfer enhancement due to self-sustained oscillating transverse vortices in channels with periodically mounted rectangular bars. *Int J Heat Mass Transf* 42:2053–2062
- Wang C-C, Chi K-Y, Chang C-J (2000a) Heat transfer and friction characteristics of plain fin-and-tube heat exchangers. Part II: correlation. *Int J Heat Mass Transf* 43:2693–2700
- Wang C-C, Lin Y-T, Lee C-J (2000b) Heat and momentum transfer for compact louvered fin-and-tube heat exchangers in wet conditions. *Int J Heat Mass Transf* 43:3443–3452
- Wang CC, Lee W-S, Sheu W-J (2001) A comparative study of compact enhanced fin-and-tube heat exchangers. *Int J Heat Mass Transf* 44:3565–3573
- Wang CC, Liaw JS, Yang BC (2009) Airside performance of herringbone wavy fin-and-tube heat exchangers—data with larger diameter tube. *Int J Heat Mass Transf* 54:1024–1029
- Webb RL (1983a) Enhancement for extended surface geometries used in air-cooled heat exchangers. In: *Low Reynolds number flow heat exchangers*. Hemisphere, Washington, DC, pp 721–734
- Webb RL (1983b) Heat transfer and friction characteristics for finned tubes having plain fins. In: *Low Reynolds number flow heat exchangers*. Hemisphere, Washington, DC, pp 431–450
- Webb RL (1990) Air-side heat transfer correlations for flat and wavy plate fin-and-tube geometries. *ASHRAE Trans* 96(2):445–449
- Webb RL, Gupta N (1990) Design of light weight heat exchangers for air-to-two phase service. In: Shah RK, Kraus A, Metzger DE (eds) *Compact heat exchangers: a Festschrift for A.L. London*. Hemisphere, Washington, DC, pp 311–334
- Webb RL, Iyengar A (2000) Oval finned tube heat exchangers—limiting internal operating pressure. *J Enhanc Heat Transf* 8:147–158
- Weierman C, Taborek J, Marner WJ (1978) Comparison of inline and staggered banks of tubes with segmented fins. *AIChE Symp Ser* 74(174):39–46
- Wongwises S, Chokeman Y (2004) Effect of fin thickness on airside performance of herringbone wavy fin-and-tube heat exchangers. *Heat Mass Transf* 41:147–154
- Xie L, Gu R, Zhang X (1992) A study of the optimum inserts for enhancing convective heat transfer of high viscosity fluid in a tube. In: Chen X-J, Veziroglu TN, Tien CL (eds) *Multiphase flow and heat transfer; second international symposium, vol 1*. Hemisphere, New York, pp 649–656
- Yan W-M, Sheen P-J (2000) Heat transfer and friction characteristics of fin-and-tube heat exchangers. *Int J Heat Mass Transf* 43:1651–1659
- Youn B (1997) Internal report, Samsung Electronic Co.
- Youn B, Kil Y-H, Park H-Y, Yoo K-C, Kim Y-S (1998) Experimental study of pressure drop and heat transfer characteristics of 10.07 mm wave and wave-slit fin-tube heat exchangers with wave depth of 2 mm. In: *Heat transfer 1998, Proceedings of 11th international heat transfer conference, vol 6*, Kyongju, Korea
- Youn B, Kim NH (2007) An experimental investigation on the airside performance of fin-and-tube heat exchangers having sinusoidal wave fins. *Heat Mass Transf* 43:1249–1262
- Yun JY, Kim H-Y (1997) Structure of heat exchanger. U.S. patent 5697432
- Yun JY, Lee K-S (2000) Influence of design parameters on the heat transfer and flow friction characteristics of the heat exchanger with slit fins. *Int J Heat Mass Transf* 43:2529–2539
- Zhang YM, Han JC, Lee CP (1997) Heat transfer and friction characteristics of turbulent flow in circular tubes with twisted-tape inserts and axial interrupted ribs. *J Enhanc Heat Transf* 4(4):297–308
- Zhang LW, Balachandrar S, Tafti DK, Najjar FM (1997a) Heat transfer enhancement mechanisms in in-line and staggered parallel-plate fin heat exchanger. *Int J Heat Mass Transf* 40(10):2307–2325

- Zhang YM, Han JC, Lee CP (1997b) Heat transfer and friction characteristics of turbulent flow in circular tubes with twisted-tape inserts and axial interrupted ribs. *J Enhanc Heat Transf* 4 (4):297–308
- Zhuo N, Ma QL, Zhang ZY, Sun JQ, He J (1992) Friction and heat transfer characteristics in a tube with a loose fitting twisted-tape insert. In: Chen X-J, Veziroglu TN, Tien CL (eds) *Multiphase flow and heat transfer. Second international symposium, vol 1*. Hemisphere, New York, pp 657–661
- Zimparov V (2001) Enhancement of heat transfer by a combination of three-start spirally corrugated tubes with a twisted tape. *Int J Heat Mass Transf* 44:551–574
- Zimparov V (2002) Enhancement of heat transfer by a combination of a single-start spirally corrugated tubes with a twisted tape. *Exp Thermal Fluid Sci* 25:535–546
- Zimparov V (2004a) Prediction of friction factors and heat transfer coefficients for turbulent flow in corrugated tubes combined with twisted tape inserts. Part I: friction factors. *Int J Heat Mass Transf* 47:589–599
- Zimparov V (2004b) Prediction of friction factors and heat transfer coefficients for turbulent flow in corrugated tubes combined with twisted tape inserts. Part 2: heat transfer coefficients. *Int J Heat Mass Transf* 47:385–393
- Zukauskas A (1972) Heat transfer from tubes in cross flow. In: Hartnett JP, Irvine T Jr (eds) *Advances in heat transfer, vol 8*. Academic Press, San Diego, CA, pp 93–160

Index

A

- Advanced internal fin geometries, 93
 - condensation heat transfer coefficient, 133, 136
 - condensation pressure drop, 133, 135
 - cross-flow heat exchanger, 141, 144
 - cross-section view of tube, 153, 156
 - efficiency index, 129, 130
 - effectiveness, fins, 146, 149
 - friction factor vs. Reynolds number, 153, 156
 - heat transfer enhancement, 127
 - heat exchangers, 150, 154
 - kinetic energy, 150, 152
 - mass flux
 - vs. condensation frictional pressure drop, 133, 136
 - vs. condensation heat transfer coefficient, 133, 136
 - microfins (*see* Microfins)
 - Nusselt number vs. Reynolds number, 153, 156
 - PCM (*see* Phase change material (PCM))
 - pressure drop and heat transfer correlations, 133, 135
 - SIMPLE algorithm, 145, 147
 - streamline of velocity, 150, 153
 - surface heat transfer coefficient, 150, 151
 - thermal energy, 143
 - thermophysical properties, Al₂O₃ nanoparticles and water, 150
 - transient variations, melt fraction, 146, 149
 - wall temperature and heat transfer coefficient variations, 138, 142
- Aluminium fins, 143

- Aluminium heat exchangers, 79
- Annular winglet type VGs, 57
- Annuli, 100, 108, 163
 - axial fins, 137
 - computational domains, 145, 146
 - and correlations, 137
 - double-pipe, 153
 - finned cylindrical, 148
 - PCM, 145
 - plain cylindrical, 147
 - thermal conductivity fluids, 153
 - transient variations, melt fraction, 149
- Arithmetic mean temperature difference (AMTD), 42

B

- Blossom-shaped internal fins, 106
- Buoyancy effect, 138

C

- Circular fins
 - effect of fin angles, 36
 - fin spacing, 34
 - finned tube banks, 34
 - fin-tube heat exchanger, 31, 32
 - longitudinal spacing, 31, 32
 - radiation heat transfer, 36
 - spiral and serrated fin geometry, 34–36
 - staggered tubes, 31
 - streamline plots, 32, 34
 - temperature distribution, 32, 35
 - transverse spacing, 31, 33

- Circular fins (*cont.*)
 - tube bank geometries, 34
 - VG, 31, 32, 34, 35
- Circular grooved tube, 113
- Coatings, 77–81
- Colburn factor, 7
- Convex louvre surface geometries, 48–50
- Crimped spiral fins, 141, 144
- Cross-flow heat exchangers, 141

- D**
- Delta winglet type VGs, 58
- Dimpled tubes
 - geometrics, 97, 99
- Double-pipe heat exchanger, 150

- E**
- Entropy generation, 16, 18
- Externally finned tubes, 163

- F**
- Fanning friction factor, 7
- Fin efficiency, 1, 2
- Fin geometry, 16, 17
- Fin numbering
 - optimization, 16
 - rate of entropy generation, 16, 18
 - and spacing, 9
 - total heat loss, 16, 19
- Fin pitch
 - axial, 46, 47
 - circular, 46, 47
 - heat transfer and pressure drop
 - characteristics, 42
 - independent, 52
 - and tube rows, 48
- Fin spacing, 144
 - and development, 22
 - four-row plain plate fin heat exchanger, 18, 20
 - vs. heat transfer coefficient, 23
 - height ratio, 23, 24
 - and numbers, 9
 - plate cubic pin fin, 9
 - thermal resistance, 13
 - three-dimensional simulation, 22
- Finned tube banks, 34
- Finned tube heat exchangers
 - air-side geometries, 1, 3
 - circular tubes, 1, 2
 - internally finned tubes, 2, 4
 - single-phase/two-phase heat transport, 1
 - three-dimensional nature, 5
 - three-row, 1, 4
 - types, 2
 - variables, 5
- Finning disc and sample tube, 97, 98
- Fin-tube heat exchanger, 31, 32, 48
- Fitness-relative deviations, 88, 92
- Flat microfin tubes
 - cross section, 99, 100
 - and oval (*see* Oval and flat tube geometries)
- Friction factor, 152
 - characteristics, 130
 - definition, 5
 - variation with Reynolds number, 11, 15

- G**
- Gas-side fouling limits, 163
- Gas-side heat transfer coefficient, 1
- Global velocity distributions, 23
- Goetler vortices, 40
- Grooves, 112, 113, 115–118

- H**
- HCFC123, 7
- Heat exchanger geometries, 78
- Heat-recovery equipment, 31
- Heat transfer
 - characteristics, 130
 - efficiency, 115
 - enhancement, 14
- Helical fins, 85
- Herringbone fin, 39, 40, 43
- Hydrophilic coatings, 163

- I**
- In-line arrangements, 22, 23, 25
- In-line tube geometry, 18
- Internal helical finned tube, 111, 112
- Internally finned tubes, 2, 4, 163
 - configurations, 94, 98, 106, 107
 - dimensions, 85, 86
 - experimental measurements, 95
 - fitness-relative deviations, 88, 92
 - friction data, 92, 93
 - friction factor with Reynolds number, 85, 91
 - fully developed laminar flow, 85, 89
 - fully developed Nusselt number data, 92, 94
 - geometrical parameters, 92
 - hydrodynamic entrance length parameters, 85, 90

- in-line and staggered segmented internal fins, 85, 89
 - natural convection, 85, 87
 - Nusselt number, 85–88
 - optimal fin number variation, 102, 106
 - optimization parameters, 102, 105
 - performance, 92, 96
 - Rayleigh number, 85, 86
 - segmented and continuous, 85, 90
 - solid model, 92, 96
 - S-, Z- and V-shaped fin profiles, 85, 91
 - thermal entrance lengths, 85, 90
 - thermal resistance, 102, 104
 - thermo-hydraulic performance, 102
 - three-dimensional, 93
 - tube geometries, 92, 97
 - values of different fluid–material, 85, 90
 - variation of Nusselt number, 85, 91
 - viscosity, 85, 88
 - wavy-fin array, 93, 97
- J**
- Jacob correlation, 25
- K**
- K - ϵ turbulence model, 22, 85
 - Kim correlation, 24
 - Kinetic energy, 150, 152
- L**
- Laminar flow, 85–87, 89, 97, 111, 130, 150–152, 155
 - Large Eddy Simulation (LES) turbulence model, 79
 - Local heat transfer coefficient
 - coatings, 77–81
 - numerical simulation, 77–81
 - patents, 77–81
 - performance comparison, 77–81
 - plain fins, 74, 77
 - Log mean temperature difference (LMTD), 42
 - Longitudinal spacing, 31–33
 - Louvered fin, 52, 54
 - automotive radiator geometry, 71
 - automotive radiator with in-line tubes, 73
 - geometric parameters, 8, 10
 - at low Reynolds number, 8
 - pressure drop vs. flow velocities, 8, 11
 - semi-louvered fin, 8, 11
 - and tube heat exchanger, 9
 - Low integral fin tube, 34
- M**
- Mesh fin geometry, circular fin-tube heat exchangers, 54–56
- Microfins**
- buoyancy effect, 138
 - characteristics, 133
 - copper tube, 127
 - efficiency index, 138, 141
 - flow characteristics, 128
 - friction factors, 130, 133, 140, 143
 - and geometrical parameters, 139, 143
 - in heat exchanger, 139
 - heat transfer augmentation of single-phase flow, 138
 - heat transfer characteristics, 130, 134, 139
 - heat transfer enhancement, 138, 139
 - helical tube, 127
 - horizontal, 150
 - inlet configurations, 130
 - isothermal friction enhancement index, 138, 140
 - laminar, transition and turbulent regions, 130
 - non-dimensional temperature t^+ , 128
 - Nusselt number, 140
 - and plain tubes, 130, 131, 133
 - pressure drop, 139
 - R410A, 131
 - Reynolds number, 127, 141
 - sectional view, 130, 131
 - single-phase heat transfer enhancement, 127, 128
 - and smooth tube, 138
 - spiral angle, 130
 - tube geometry, 128, 129
 - two-phase heat transfer enhancement, 127
 - wall temperature difference, 139
- Microfin tube, 85**
- aspect ratio, 101, 103
 - cross section, 99, 100
 - frictional pressure drops, 102, 104
 - geometrics, 99
 - heat transfer coefficients, 101
 - RMS errors, 101, 103
 - thermo-hydraulic performance of R-410A, 97
 - transition of friction and heat transfer data, 130, 132
- Multi-louvered fins, 52**
- geometric parameters, 8
- N**
- Non-dimensional parameters, 78
 - Numerical simulation, 77–81

O

- Offset-strip fins, 52, 53
- Optimal fin geometries
 - characteristics, 130
- OSF geometry, 51, 52
- Oval and flat tube geometries
 - air-side performance, 69, 71
 - average Nu and f with fin pitch, 70, 73
 - heat transfer and friction characteristics, 69, 70
 - Nu_H vs. Re_H , 72, 76
 - numerical calculation, 70, 71
 - three-row staggered tube configuration, 72, 75
 - tube dimensions, numerical calculations, 69, 71
 - VG, 72
 - winglet pairs, 74

P

- Paraffin wax, 143
- Patents, 77–81
- Perforated fin, 42, 52
- Performance comparison, 77–81
- Phase change material (PCM), 143–148
- Pin-fin arrays, 58
- Plain-plate fins
 - average heat transfer coefficients, 19, 21
 - average Nusselt number, 17, 20
 - co-angular, 13
 - Colburn factor, 7
 - co-rotating pattern, 14
 - Fanning friction factor, 7
 - fin friction vs. Re_{st} , 19, 21
 - flow pattern, 7
 - friction factor, 22
 - geometry, 9, 12
 - global velocity distributions, 23
 - heat transfer and friction characteristics, 18, 20
 - heat transfer coefficient, 9
 - correlations, 11, 16
 - and vapour quality, 7, 8
 - heat transfer correlation, 19
 - louvred fin (*see* Louvred fin)
 - Nusselt number vs. Rayleigh numbers, 7, 9, 14
 - pressure drop, 22
 - thermal resistance with fin spacing, 9, 13
 - variation of η , 11, 16
 - wavy fin (*see* Wavy fin)
- Plain tube
 - transition of friction and heat transfer data, 130, 132

Plate cubic pin fin

- geometry, 9, 12
- Plate fin and circular fin geometries
 - air-side test, 52, 54
 - AMTD, 42
 - convex louvre surface geometries, 48–50
 - fin pattern, 50
 - friction factor variation with Reynolds number, 39, 42, 50, 51
 - heat transfer and pressure drop values, 43, 46
 - herringbone fin (*see* Herringbone fin)
 - LMTD, 42
 - multilouvred fins, 52
 - numerical results, 43, 45, 46
 - Nusselt number and friction factor, 47
 - Nusselt number variation, 39, 41, 42, 50, 51
 - offset-strip fins, 52, 53
 - one-row fin-tube heat exchanger, 52, 54
 - OSF, 48, 51, 52
 - perforated fin (*see* Perforated fin)
 - performance evaluation index, Nu/f vs. Re , 39, 42, 50, 52
 - regression correlation, 40
 - segmented/spine (*see* Segmented/spine fin)
 - thermo-hydraulic characteristics, 42
 - VGs (*see* Vortex generators (VGs))
- Polyalphaolefin, 52
- Pressure drop, 16, 152

R

- Radiator, 18
- Rectangular fins
 - co-angular, zigzag, co-rotating and co-counter rotating configurations, 11, 15
- Round tubes, plain-plate fins, *see* Plain-plate fins
- Row correction factor, 34
- Row effects
 - in tube banks, 74, 76, 77

S

- SAE5W30 engine oil, 52
- Segmented/spine fin
 - in air-conditioning applications, 60
 - and circular fin geometries, 59
 - copper tubes, 61
 - seven-row in-line tube, 60
 - staggered and in-line tube layouts, 60
- Semi-implicit method for pressure-linked equations (SIMPLE) algorithm, 145, 147

Semi-louvered fin, 8, 11
 Smooth tube
 aspect ratio, 101, 103
 friction factor, 152
 frictional pressure drops, 102, 104
 geometrics, 99
 heat flux, 139
 heat transfer coefficients, 101
 mass fluxes, 138
 viscous sub-layer, 140
 Smooth tube (SMT), 116
 Smooth wave configuration, 39, 40, 47
 Solid–liquid phase change process, 145
 Spiral angle, 128
 Spiral fin and serrated fin geometry, 34–36
 Spirally fluted tubes
 aluminium, 107, 109
 axial distribution, heat transfer coefficient, 112, 114
 curve fit and performance parameters, 108, 110
 dimensionless geometric parameters, 108, 109
 friction factor characteristics, 110
 indented tube, 107, 109
 in-tube flow and annular flow, 108
 mass flux effect, 101, 102
 Nusselt number vs. Darcy friction factor, 107, 108
 quality effect, 101, 102
 stainless steel tube, 107, 109
 Staggered arrangement, 19, 22, 23
 Staggered tubes, 31
 Stainless steel, 116
 Straight grooved tubes (SGT), 116
 Surface temperatures, 16, 17

T

Taguchi method, 46
 Test fins
 dimensions, 9, 12
 Test section, 116, 117
 Test tubes
 dimensions, 133, 134
 geometric parameters, 111, 128, 130, 133, 134
 specifications, 131
 Thermal energy, 143

Three-dimensional dimpled tubes
 heat transfer analysis, 95
 pressure drop analysis, 95
 Transverse spacing, 31, 33
 Tube banks, 5, 18, 22
 row effects, 74, 76, 77
 Tube bundles
 dimensions, 22
 flow visualization, 55
 Tube geometries, 92, 97
 Turbulent flow, 85, 92, 93, 97, 106, 111, 112, 127, 130, 133, 147, 150, 153

V

Vapour quality, 101
 Vortex generator (VG), 14, 31, 32, 34, 35, 72
 annular winglet type, 57
 configurations, 43
 delta winglet type, 58
 fin-and-tube heat exchanger, 57
 fin, rib and wing configurations, 56
 fin surface, 55
 flow-down configuration, 56, 57
 flow-up configuration, 56
 heat exchanger, 56
 heat transfer rate and pressure drop, 43
 location, 43, 44
 louvre fin, 58
 and model names, 43, 44
 production and orientation, 58
 tube wake region, 59
 type, 43, 46
 winglet, 43, 58, 59
 wing-type, 56, 57

W

Wavy fin, 93, 97, 163
 behaviour, 13
 characteristic dimensions and top view, 7, 10
 geometric parameters, 8, 10, 39, 40
 heat transfer augmentation, 50
 heat transfer coefficient, 39
 smooth and herringbone, 39, 40
 thermo-hydraulic characteristics in air-cooled compact, 7
 thermo-hydraulic performance, 69
 Wing-type VGs, 1, 43, 56, 57