

Index

A

- Absorbance spectra, 57
- AFM-transferring quantum elements, 97
- Amine-terminated GQDs (Am-GQDs), 233, 234
- Amplified stimulated radiation (ASE), 179
- Annealed p-doped QDs (QDAP), 215
- Annealed undoped QDs (QDAU), 215
- Antireflection coatings (ARCs), 34, 35
- Anti-solvent precipitation, 180
- Architecture design, CQD PVs
 - band engineering, 52
 - EBIC, 52
 - mini-band structure, 52
 - type II structure, 52
 - type-III structure, 52
 - wider-bandgap *p*-type NiO, 52
- Artificial atoms, 89
- Atom–photon entanglement progress
 - applications, 160
 - DBR mirror, 160
 - DFG, 160
 - Fabry–Pérot interferometer, 166
 - light–matter quantum interface, 168
 - measurement/preparation pulse, 164, 167
 - optical pumping technique, 160
 - photon autocorrelation function, 164
 - photon collection system, 160
 - resonance fluorescence, 162, 163
 - Schottky diode structure, 160
 - single-electron charging plateau, 161
 - spin–photon, 162
 - SSPD, 164
 - Voigt configuration, 161

- Automated ELO production equipment, 8
- Avalanche photodiodes (APD), 142

B

- BB84 protocol, 137
- Bell state measurement (BSM), 139
- Bioresources, 233–235, 239, 248, 249
- Bipolar electrical switching, 259
- Bipolar resistive switching
 - gold nanoparticles, 281
 - solution-based method, 286
 - switching voltages, 286
- Bis(trimethylsilyl) sulfide (TMS₂), 72
- Black phosphorus (BP), 181
- Boson sampling, 86
- Bragg grating, 85

C

- Capture and escape mechanisms, 13
- Carbofuran, 245
- Carbon nanotubes (CNT), 113, 295
- Carbon/graphene composites
 - Arylamine-based, 295
 - carbon-based switching devices, 293
 - CNT, 295, 296
 - device-to-device fabrication, 295
 - films, 293
 - GQDs, 293
 - memory switching behavior, 293
 - oxides, 294
 - retention characteristics, 295
 - switching memories, 293

- Cesium lead halide perovskite quantum dots (CsPbX₃ QDs)
 applications (*see* CsPbX₃ QDs applications)
 fabrication methods, 179–182
- Charge extraction by the linearly increasing voltage (CELIV), 58
- Charge injection and trapping, 261, 262
- Charge-type qubits, 114
- Cobalt selenium quantum dots (CSQDs-PVP), 290
- Coherence time, 121, 122
- Colloidal quantum dot (CQD)-based solar cells, 50
- Colloidal quantum dots (CQDs)
 architecture (*see* Architecture design, CQD PVs)
 CQD materials and shapes, 71–73
 defect recombinations, 63
 device structure engineering, 70–71
 EHPs, 51
 fabrication of CQD PVs, 52–56
 limiting factors, 69
 MEG, 50 (*see also* Multiple exciton generation (MEG))
 synthesis, 50
- Compliance current (CC), 258
- Concentrator photovoltaic (CPV) systems, 3
- Confocal laser analysis (CLSM), 248
- Continuous-wave (CW), 153
- Conventional memory technology, 254
- CQD materials and shapes
 Ag₂S, 73
 bandgaps, 71, 72
 core/shell CQD structure, 72
 EQE measurement, 72
 lead chalcogenide nanocrystals, 71
 light absorption properties, 73
 material modification properties, 72
 selenium, 72
 TAS, 72
 TMS₂, 72
- CsPbX₃ QDs applications
 defect tolerance, 187
 high carrier mobility, 188
 high quantum yield, 187
 single-photon emission, 187
 third-order nonlinear optical properties, 188
- CuInS₂ (CIS), 59
 CuInSe₂ (CISe), 59
- D**
- Deep-junction (DJ) configuration, 10, 11
- Defect recombinations
 interface, 65
 sub-bandgap, 63–65
- Defect tolerance, 187
- Density functional theory (DFT), 285
- Device structure engineering
 Fermi level pinning, 70
 hetero-interface, 70
 heterojunction architecture, 70
 hydrothermal methods, 70
- Difference frequency generation (DFG), 160
- Diffraction grating test, 32
- Dimethyl sulfoxide (DMSO), 180
- Direct normal irradiation (DNI) levels, 3
- Distributed Bragg reflector (DBR), 85, 142, 154, 160, 209, 222
- Distributed feedback (DFB), 208
- Droplet epitaxy method, 92
- Dynamic RAM (DRAM), 254
- E**
- Electric field-induced quantum-confined Stark effect, 91
- Electric polarization, 271
- Electrical carrier injection, 99
- Electrically erasable programmable read-only ROM (EEPROM), 254
- Electrochemical IS (ECIS), 68
- Electrochemical metallization
 active solid electrolytes, 265
 coplanar structures, 265
 dendritic growth, 265, 266
 dissolution and deposition, 264
 filamentary growth, 265
 SET processes, 265
 SET voltages, 266
- Electrode magnetization, 274
- Electroluminescence (EL) analysis, 10
- Electron-beam lithography (EBL), 111, 114, 211
- Electron beam-induced current (EBIC), 52
- Electron-hole pairs (EHPs), 51
- Electron spins, 117
- Electron transport layers (ETLs), 52, 56
- Electron tunneling, 108
- Electronic memory, 253
- Electro-optic modulator (EOM), 141–142
- Electrostatic/electronic effects
 charge injection and trapping, 261, 262
 ferroelectric polarization reversal, 264

- ferroelectric tunnel junction, 261
 - MIT, 263
 - Embedded QDs, 91
 - Entangled-light-emitting diode (ELED), 150
 - Entangled photon emitters, *see* Entanglement
 - Entanglement
 - advantages, 91
 - cavity-enhanced Raman transition, 93
 - concept, 90
 - droplet epitaxy method, 92
 - embedded QDs, 91
 - fidelity, 92
 - FSS, 91, 92
 - limitation, 91
 - NOON states, 93, 94
 - photonic states, 93
 - photons, 94
 - piezoelectric actuators, 91, 92
 - post-growth tuning methods, 91
 - QDs, 91
 - solid-state sources, 90
 - spin-photon, 84
 - structure and spectral properties, 92, 93
 - time-bin-encoded single-photon
 - W-states, 93, 94
 - Entanglement swapping, 139, 140
 - Epitaxial lift-off (ELO)
 - DJ and SJ configurations, 10, 11
 - HF solution, 7
 - peeled film technology, 7
 - planar rear mirror, 26–28
 - sacrificial layer, 7
 - surface morphology, 7
 - thin-film III–V structures, 7
 - wafer-based technology, 6
 - wafer-sized thin-film, 7–10
 - Epitaxial QDs, 96
 - Erasable-and-programmable ROM (EPROM), 254
 - Er-doped fiber (EDF), 225
 - Er-doped glass oscillator (ERGO), 223
 - Error correction protocols, 92
 - Excited-state dynamics, perovskite QDs
 - fluorescence lifetime
 - measurement, 183–185
 - optoelectronic properties, 182
 - transient absorption spectroscopy, 185–187
 - External quantum efficiencies (EQE), 189
 - Ag/Cu reflectors, 28
 - characteristics, 10
 - and EL characteristics, 27, 28
 - and J-V characteristics, 14, 15, 27, 28
 - measurement, 18
 - photoluminescence (PL) spectra, 14
 - QD layers, 23
- F**
- Fabrication of CQD PVs
 - Finke-Watzky's theory, 53
 - hot-injection method/LaMer model, 53
 - layer-by-layer spin coating, 54
 - LSW theories, 54
 - nanocrystals, 52
 - spin-coating/drop-casting, 55
 - synthesis, 54
 - techniques, 55
 - Fabry-Pérot (F-P) laser, 208
 - Fenugreek (F-GQD), 234
 - Ferroelectric polarization reversal, 264
 - Ferroelectric tunneling
 - charge transport, 271
 - electric polarization, 271
 - electrode-ferroelectric interface, 271
 - energy band, 271
 - FJTs, 271
 - Ferroelectric tunneling junctions (FJTs), 264, 271
 - Fidelity, 122, 123
 - Field-effect transistors (FET), 178, 190
 - Fine structure splitting (FSS), 91, 92
 - Finke-Watzky's theory, 53
 - Fluorescence lifetime measurement, 184
 - components, 184
 - fluorescent substance, 183
 - photocatalysis, 184
 - Stern-Volmer plots, 183, 184
 - streak camera, 184
 - TCSPC, 183
 - Fluorescent sensors, 233
 - Fluorine doped tin oxide (FTO), 70
 - Formamidineium (FA), 178
 - Fourier transform infrared (FTIR), 233
 - Fowler-Nordheim tunneling, 271
 - F-P/DFB lasers applications
 - data transmission, 220
 - error-free operation, 220
 - GS and ES lasing, 217
 - GS saturation profile, 217
 - large-signal measurements, 219
 - laser cavity length, 217
 - modulation p-doping, 219
 - narrow emission spectrum, 220
 - non-radiative recombination, 218
 - P-I* characteristics of QDP, 218
 - shortened cavity length, 217

Frequency-stabilized QDs, 89
 Full width at half maximum (FWHM),
 178, 224
 Fluorescent emission, 240

G

GaAs, 110, 111
 GaAs n-p solar cell, 12
 GaAs wafers, 8
 Gain magnetoresistance (GMR) effect, 273
 Gate-defined quantum dots (GDQD)
 carbon nanotubes, 113
 charge states, 114, 116–118
 coherence time, 121–123
 concepts, 108, 109
 fidelity, 122, 123
 GaAs, 110, 111
 hybrid states, 118–120
 man-made nanoscale devices, 107
 nano-/micromechanical
 resonators, 127–129
 nanowires, 113, 114
 scalability, 123, 124
 SEM micrograph, typical device, 114, 115
 silicon, 111, 112
 silicon-based donor qubits, 107
 spin states, 116, 118
 spin-type qubits, 116
 superconducting microwave resonators,
 124, 126, 127
 2D materials, 113, 114
 Graphene, 114
 Graphene oxide (GO), 248
 Graphene quantum dots (GQDs), 293
 Am-GQDs, 233
 amine-functionalize, 236
 applications, 232
 binary system, 241
 biotoxicity assay, 234
 carbofuran, 243, 245
 characteristics, 239
 chlorophylls, 234
 classification, 232
 CLSM, 248, 249
 coffee grounds, 237
 DOAZOC1, 243
 DOAZOC1 vs. carbofuran, 244, 245
 emission intensity, 246, 247
 fluorescence property, GQD-DOAZOC1,
 243, 244
 fluorescent emission, 240
 functionalization, 233
 GO, 248

HeLa cells, 236, 237
 honey, 239, 243
 molecular keypad lock, 247, 248
 molecular logic gate, 244
 N-GQDs, 234
 optical properties, 237, 240
 optoelectronic applications, 234
 and PEI-GQDs, 237, 238
 photoluminescence, 240
 physical and chemical properties, 232
 RH, 236
 RH-GQDs, 237
 rice grains, 235
 security ink, 242
 synthesis, 233
 synthetic routes, 232
 truth table, 245, 246
 utilization, bioresource, 233, 234
 UV-visible absorption spectra, 242
 white-light emission, 241
 zero-dimensional in nature, 232
 Graphite oxide (GO), 289
 Gratings
 absorbance spectra, 30–32
 bi-periodic pyramidal, 30, 31
 blazed, 33
 diffraction test, 32
 ELO thin-film QD cells, 30
 half-sphere, 33
 optical profilometer measurement, 33
 planar ARC, 30
 planarizing polymer layer, 30
 polymer, 34
 pyramid, 33
 pyramidal, 33
 RCWA method, 30
 specular reflectance, 33
 structures, 30
 total and specular reflectance, 33, 34
 uni-periodic, 30, 31
 Ground state bleaching (GSB), 186

H

High carrier mobility, 188
 High resistance state (HRS), 257, 259
 High resolution transmission electron
 microscopy (HRTEM) image, 57
 High-speed lasers, 207, 208
 Hole transport layers (HTLs), 52
 Hong-Ou-Mandel experiment, 89
 Hot-injection synthesis, 180
 Hybrid memory devices, 254
 Hybrid qubit, 118–120

Hydrofluoric (HF) solution, 7

Hydroxyl group (-OH), 63

I

In situ electron beam lithography, 97, 98

In situ lithography, 97

InAs/GaAs QDSCs

intrinsic and extrinsic reductions, 11

I–V characteristics, 22–24

light diffraction, 30–34

MBE growth (*see* Molecular beam epitaxy (MBE))

V_{oc} reduction, 11–17

InAs/GaAs QD-SESAM

advantages, 209

applications, 225

Er:laser cavity, 223

Er:Yb-doped glass plate, 223

operating wavelength, 209

picosecond pulse duration, 225

ultrafast pulse lasers, 221

InAs/GaAs quantum dots (QDs)

Er:Yb:glass laser, 223

high-speed lasers, 207, 208

optical properties (*see* Optical properties, InAs/GaAs QDs)

QD-SESAM, 225

1550 QD-SESAMs fabrication, 221–223

ultrafast lasers, 209, 221

ultrashort cavity F-P/DFB lasers, 210, 211

Inductively coupled plasma (ICP), 211

Inorganic-organic frameworks (MOFs), 295

Integrated quantum devices, 96, 97

Interface defects

charge generation distribution, 66, 67

charge interfacial recombination, 66

ECIS, 68

Fermi level, 65, 69

hetero-interface, 69

hole extraction, 67

HTLs, 69

nanowire structure, 69

passivation, 65

PbS QDs bandgap, 66

PbS/ZnO interface, 68

PbS-EDT photo-anode, 68

PCE, 66

thermal annealing, 66

TPC/TPV, 66

types, 65

ultrafast interfacial charge separation, 65

ZnO electrode, 68

Intermediate band solar cell (IBSC), 4

Intrinsic and extrinsic V_{oc} loss, 14–17

I–V characteristics, InAs/GaAs QDSCs, 22–24

L

Laser annealing techniques, 91

LED and display, 189

Lifshitz-Slyozov-Wagner (LSW) theories, 54

Light diffraction

InAs/GaAs QDSCs, 30–34

Light-emitting diodes (LEDs), 50, 178, 188

Light trapping (LT), 3

enhanced QDSCs, 25, 26

periodic diffraction grating, 25

and photon recycling, 39

in QDSCs, 34

Linear polarization states, 137

Low resistance state (LRS), 258

M

Magnetic field-induced Zeeman shifts, 91

Magnetic RAM (MRAM), 275

Magnetoresistance (MR), 272

Magnetoresistive

electrode magnetization, 274

ferromagnetic electrodes, 275

ferromagnetic layer, 273

GMR effect, 273, 274

magnetic tunnel junctions, 274

MR, 272, 273

STT, 275

Mainstream and emerging memory

technologies, 259, 260

Masked ROM (MROM), 254

Measurement/preparation pulse, 164, 167

Measurement-based quantum computers, 93

Mechanochemistry, 181

Memory devices

carbon quantum dots/poly(vinyl alcohol), 297

categories, 254

conventional memory technology, 254

CSQDs-PVP, 290

features, 254

ferroelectric, 271

hybrid, 254

information and communication

technologies, 254

low-voltage flash, 289

memristors, 255

multifunctional optoelectronic, 292

non-charge-based, 255

nonvolatile fabrication, 280, 281

- Memory devices (*cont.*)
nonvolatile memories, 295
organic/polymer compounds, 298
quantum dot-based, 301
RNA-quantum dot-based, 299
transparent and flexible, 294
- Memristive devices, 292
- Memristors
bipolar electrical switching, 259
circuit elements, 255–257
current-voltage plot, 258
definition, 255
HRS, 259
mechanisms (*see* Resistive switching effect mechanisms)
ON and OFF states, 259
ON/OFF resistance ratio, 259
QDs (*see* QDs memristors)
resistance switching effect, 257
RRAM devices, 257
structure, 255, 256
types, 257
- Metal chalcogenides
carrier-phonon interaction, 293
CSQDs-PVP, 290
double floating gate memory, 289, 290
electrically programmed photonic memory, 292
GO, 289
grain boundaries, 290
light-erasable transistor memories, 292
memory applications, 289
memristive devices, 292
nanocomposites, 289
PbS QDs, 289
photo-sensitive materials, 292
semiconductors, 289
silicon-based, 291
silver-based, 291
2D monolayer, 290
UV-induced de-trapping, 292
WROM, 291
- Metal mirrors, 85
- Metal nanoparticles
bipolar resistive switching, 281
copper phthalocyanine, 282
core-shell structure, 282
electrical switching, 281
energy band, 283
organic/polymer layers, 283
retention measurement, 281, 282
- Metal organic vapour phase epitaxy (MOVPE), 8
- Metal oxides
annealing, 286
binaries, 283
controlled tuning, 284
copper, 286
dip coat patterning method, 287
endurance and retention, 286, 287
films, 283
innovative approach, 288
NiO-based device, 283, 285
ON/OFF ratio, 285
resistance switching, 283
silicon, 288
TiO₂ nanorod arrays, 286
transparent resistive switching, 286
ZnO nanocrystals, 286
- Metal-insulator-metal (MIM), 264
- Metallic silver nanowires (AgNWs), 70–71
- Metal-organic chemical vapour deposition (MOCVD), 11
- Metal-organic frameworks (MOFs), 181
- Micro-machined PMN-PT actuator, 97
- Microwave-assisted synthesis, 180
- Million tonnes of oil equivalent (Mtoe), 50
- Mode-locked ERGO laser, 223
- Molecular beam epitaxy (MBE)
contact metals, 18
DJ and SJ architectures, 17
InAs/GaAs QDSC I–V characteristics, 22–24
light management and photon recycling, 18
optical emission properties, 18
PL, 18, 19
QD density, 17
QD sheets, 18
silicon and beryllium, 17
surface characteristics, 19–21
V90/V80H, 17
XRD characteristics, 20–22
- Molecular beam epitaxy (MBE)-grown InAs/GaAs QDSCs
surface characteristics, 19, 20
- Molecular memory, 277
- Molecular switching
charge transport, 277
electrode-molecule interfaces, 279
functional organic molecules, 277
mechanisms, 277
molecular memory, 277
phenylene ethynylene oligomers, 278
single-molecule switching, 278
- Molybdenum disulfide (MoS₂), 290
- Molybdenum oxide (MoO₃), 69
- Mott's metal-insulator transition (MIT), 263
- Mott-Gurney model, 266

- Multi-ferroic tunnel junctions, 264
- Multi-junction solar cells, 2, 3
- Multiple exciton generation (MEG)
 - effect on device PCE, 62, 63
 - high-energy solar photons, 61
 - photo-charging process, 60
 - QD materials, PVs, 57–59
 - quantum-size effect, 56, 57
 - QY, 56, 61
 - relaxation pathways, 60
 - semiconductor bandgap energy, 61
 - TA, 61

- N**
- Nano-/micromechanical resonators, 127–129
- Nano-electromechanical switches (NEMS), 275
- Nano-gratings, 34, 35
- Nanolasers, 190–192
- Nano-mechanical memories, 275–277
- Nanostructured absorbers, 4
- Natural atoms, 116
- Near-infrared (NIR), 50
- Neem (N-GQD), 234
- Ni-DNA system, 299
- N,N-dimethylformamide (DMF), 180
- Nonlinear optical applications
 - materials parameter, 192
 - optical limiting, 193
 - saturable absorbers, 193
 - third-order nonlinear responses, 192
 - valley appears, 192
 - Z-scan technique, 192
- Nonvolatile RAM (NVRAM), 254
- NOON states, 93, 94
- Novel mechanosynthesis method
 - advantages, 182
 - experimental parameters, 181
 - mechanochemistry, 181
 - milling time, 182, 183
 - stoichiometric ratio, 181

- O**
- Oleic acid (OA), 180
- On-chip Hong-Ou-Mandel experiment, 97
- On-chip integration
 - CMOS-compatible photonic circuit, 95
 - deterministic single-photon sources, 95
 - electrical-driving QDs, 99
 - epitaxial QDs, 96
 - fabrication techniques, 95
 - GaAs QDs, 96, 97
 - hybrid and scalable approach, 95, 96
 - III–V quantum photonic circuits, 95
 - in situ electron beam lithography, 97, 98
 - InGaAs/GaAs QDs, 95
 - integrated quantum devices, 96
 - photonic integration, 94
 - photonic nonlinearity, 95
 - quantum elements, 96
 - quantum photonics, 98
 - semiconductor QDs, 95
 - silicon photonic devices, 95
 - site-selected QDs, 98
 - super-resolve and selectively excite quantum emitters, 97
 - 2D mapping, 99
 - whispering-gallery-mode lasers, 99
- Optical/electronic properties, CsPbX₃ QDs
 - nanolasers, 190–192
 - nonlinear optical applications, 192–194
 - optoelectronic devices, 188–190
 - photocatalysis, 194
 - scintillators, 194, 195
- Optical emission, 18
- Optical limiting, 193
- Optical properties, InAs/GaAs QDs
 - Ga vacancy propagation, 214
 - InGaAs capping layers, 212
 - intermixing effect, 214
 - phonon-assisted carrier relaxation, 216
 - PL peak positions, 214
 - QDAP and QDAU, 216
 - QDU and QDP, 212, 213
 - RTA treatment, 214
 - temperature-dependent PL spectra, 212, 215
- Optoelectronic devices
 - FET, 190
 - LED and display, 189
 - photodetectors, 190
 - solar cells, 189
- Optoelectronic materials, 232, 234, 249
- Organic LEDs (OLED), 189
- Organometallic halide perovskites (OHPs), 177
- OrmoComp polymer gratings, 34
- Ovonic diode, 270
- Oxide perovskite (ABO₃), 176

- P**
- Passivation
 - CuInS₂/CdSe/ZnSe structures, 59
 - iodide molecules, 56
 - ligand exchanging, 52
 - low-temperature-processed SnO₂ film, 66
 - remedies, 69

- Passivation (*cont.*)
 surface modification, 63, 64
 treatment, 64, 72
- Passive Q-switching, 225
- PbSe nanorods (NRs), 71
- PbS-EDT photo-anode, 68
- P-doped as grown QDs (QDP), 212
- Peeled film technology, 7
- Perovskite QDs
 practical applications, 196
 stability issues, 195
 toxicity issues, 195
- Perovskites
 ABX₃, 176
 all-inorganic metal halide perovskite, 178
 BaTiO₃, 177
 crystal structure, 176, 177
 CsPbX₃ QDs, 179
 definition, 176
 halide, 177
 inorganic halide, 178
 LiNbO₃, 177
 morphology, 179
 organometallic, 178
 photoinduced excited-state dynamics, 179
 semiconductor materials, 179
 stability, 178
 tolerance factors, 178
- Phase change effect
 amorphous semiconductors, 269
 challenges, 270
 crystallization phase transitions, 270
 electric switching, 270
 multicomponent amorphous solids, 270
 ovonic diode, 270
- Photocatalysis, 194
- Photodetectors, 190
- Photoluminescence (PL), 14, 240
 characteristics, 18, 19
 emission, 18
 mapping tool, 18
- Photoluminescence excitation spectrum (PLE), 240
- Photon confinement and recycling, 36–38
- Photon management
 ARCs, 34, 35
 ELO QD cells, 26–28
 gratings, 30–34
 LT, 25, 26
 patterned rear mirror/contact, 36–38
 planar reflectors, 28–30
- Photon recycling, 9, 18
- Photon turnstile, 141
- Photonic crystal cavities, 86
- Photonic integration, 94
- Photonics quantum technologies, 84
- Photovoltaic applications
 wafer-sized thin-film, 7–10
- Photovoltaic industry, 3
- Photovoltaic process, 4
- Planar back surface reflectors, 28–30
- Planar rear mirror
 ELO QD cells, 26–28
- Plasmonic nano-antenna array, 86
- Plasmonic nanostructures, 86
- Plasmonic nanowires, 97
- Plasmonics, 86
- Poisson equation, 13
- Polarization insensitive isolator (PI-ISO), 225
- Polarizing beam splitter (PBS), 141
- Poly(3-hexylthiophene) (P3HT), 298
- Post-growth tuning methods, 91
- Power conversion efficiency (PCE), 50, 178, 189, 190
- Programmable ROM (PROM), 254
- Pump-push photocurrent (PPP) spectroscopy, 64
- Q**
- QD-based devices
 atom–photon entanglement
 progress, 159–168
 QKD, 140–150
 quantum teleportation progress, 150–159
- QD-corrected transport model, 11
- QD materials, PVs
 CIS/ZnS core/shell structure, 59
 effective electron mass, 57
 high-frequency dielectric constant, 57
 HRTEM image, 57
 I-III-VI₂, 59
 lead chalcogenides, 57
 PbS CQD-based solar cells, 58, 59
 TRPL spectroscopy, 57
 XRD pattern, 57
- QD memristors
 carbon/graphene composites, 293–295
 memory devices, 281
 metal chalcogenides, 289–293
 metal nanoparticles, 281–283
 metal oxides, 283–288
 nanomaterials, 279
 QCE, 279
 QD organic composites, 295–301
 single-electron transistors, 281

- surface chemistry nanoparticles, 279
 - surface plasmon effect, 279
 - ZnO nanoparticles, 280
- QD organic composites
 - biological molecules, 298
 - CdS quantum dots, 295
 - DNA:PbS films, 298
 - GO, 298
 - heterointerfaces, 299
 - ITO-coated PET substrate, 298
 - methyl ammonium lead halide perovskite, 298
 - MOFs, 295
 - multilevel electrical switching, 299
 - nanocomposite films, 297
 - Ni-DNA system, 299
 - polymer-carbon quantum, 296
 - resistive switching, 295
 - semiconductor, 298
 - switching behavior, 296
 - Virus-templated CdSe/ZnS, 299
- Q-switched fiber laser, 225
- Quantum communication, 84
 - goal, 135
 - QKD, 136–140
 - quantum teleportation, 138, 139
- Quantum computing, 84
- Quantum confinement effect (QCE), 279, 289
- Quantum cryptography distribution (QKD)
 - BB84 protocol, 137, 138
 - goal, 137
 - photons, 138
 - public–private key cryptography, 136
 - routines, 136
 - secret key, 136
- Quantum dots (QDs), 108
 - electronic structure, 14
 - intradband carrier thermalization, 4
 - light-trapping approaches, 5
 - optical absorption, 5
 - photogeneration, 5
 - and QW, 4
 - radiation tolerance, 4
 - semiconductor (*see* Semiconductor QDs)
 - solar cells (*see* Quantum dot solar cells (QDSCs))
 - space applications, 4
 - stack, 12
 - 3D, 4
- Quantum dot solar cells (QDSCs)
 - description, 13
 - high-efficiency, 5
 - IB concept, 4
 - intrinsic effect, 5
 - thin-film III–V (*see* Thin-film III–V QDSCs)
- Quantum efficiency (QE), 61
- Quantum emitters
 - entangled photon emitters, 90–94
 - on-chip integration, 94–99
 - single-photon emitters, 85–90
- Quantum information processing systems, 84
- Quantum key distribution (QKD)
 - APD, 142
 - arrival time distributions, 148
 - BB84 protocol, 144, 147
 - communication rates, 142
 - EOM, 142
 - error correction algorithm, 145
 - excitation, 144
 - figures of merit, 140
 - GLLP theory, 144
 - HBT experiment, 146
 - multiphoton emission, 146
 - photoluminescence, 143
 - photon turnstile, 141, 142
 - QBER, 148
 - quantum efficiency, 148
 - security, 142
 - SMF, 147
 - SNSPD, 149
 - SPS, 144, 145
 - telecommunication wavelength, 142
 - transmission distance, 145
 - UMZI, 147
- Quantum kinetic approaches, 12
- Quantum metrology, 84
- Quantum networks
 - classical Internet, 135
 - photon entanglement, 160
 - quantum repeater, 139
 - teleportation, 150
- Quantum point contact (QPC), 109, 111
- Quantum technologies, 84
- Quantum teleportation
 - ancilla and target photons, 153
 - autocorrelations, 154
 - Bell state *B* detection, 158
 - Bell state measurement, 151
 - BSM, 139
 - CW, 153
 - DBR, 154
 - definition, 138
 - ELED, 150
 - HOM visibility, 158
 - orthogonal linear polarization, 155

- Quantum teleportation (*cont.*)
 quantum entanglement, 139
 quantum teleportation, 156
 reasonable extensions, 157
 sub-Poissonian and anti-bunching properties, 152
 teleporting arbitrary state, 153
 third-order intensity correlation, 152
 three-photon correlations, 156
 tomography, 158
- Quantum well (QW), 4, 208
- R**
- Rapid thermal annealing (RTA), 208
 Rear mirror/contact, 36–38
 Refractive indexes, 32
 Remote QDs, 89
 Resistive random-access memory (RRAM), 255
 Resistive switching effect mechanisms
 electrochemical metallization, 264–266
 electrostatic/electronic effects, 261–264
 ferroelectric tunneling, 271
 magnetoresistive, 272–275
 molecular switching, 277–279
 nano-mechanical, 275–277
 phase change, 269–270
 thermochemical, 267, 268
 valence change, 266, 267
- Resonance fluorescence, 162
 Rice husk ash (RHA), 236
 Rice husk biomass (RH), 236
 Rice husk carbon (RHC), 236
 Rice husk GQDs (RH-GQDs), 236
 Rigorous coupled-wave analysis (RCWA)
 method, 30
 Rubidium-cyclodextrin (Rb-CD)-based MOFs, 295
- S**
- Saturable absorber (SA), 193, 221
 Scalability, 123, 124
 Scalable quantum computing methods, 127
 Scanning electron microscopy (SEM), 33, 112
 Scanning tunneling microscopic (STM), 278
 Scintillators, 194, 195
 Semiconductor QDs
 artificial atoms, 84
 and color centers in diamond, 84
 on-demand entangled photon pairs, 84
 photonic system possessing, 84
 quantum emitters (*see* Quantum emitters)
 single-photon sources, 84
 Shallow-junction (SJ) configuration, 10, 11
 Shockley-Queisser (SQ) limit, 2
 Shockley-Read-Hall (SRH) theory, 13
 Silicon, 111, 112
 Silicon-based donor qubits, 107
 Silver sulfide (Ag₂S), 73
 Simulated emission (SE), 186
 Single electronic spin system, 118
 Single-junction GaAs solar cells, 2
 Single-mode fiber (SMF), 141, 147
 Single-molecule switching, 278
 Single-photon emission, 187
 Single-photon emitters
 applications, 87
 artificial and natural atoms, 89
 Bragg grating, 85
 cavities, 86
 electrically controlled, 85
 emission enhancement, 85
 extraction efficiency, 86
 frequency-stabilized QDs, 89
 GaN QDs, 88
 heralded absorption, 89
 InGaAs QDs, 85
 microcavities and photonic crystals, 85
 multilayer metamaterial nanostructures, 86, 87
 on-demand photon generation, 85
 phonon-assisted two-photon excitation scheme, 89
 photonic crystal cavities, 86
 plasmonics, 86
 quantum correlation, 90
 quantum networks, 89
 remote QDs, 89
 room-temperature colloidal QDs, 87, 88
 scattering, 86
 telecommunication band, 86
 wavelength-tunable Q-LED, 89, 90
 Single-photon sources, 84
 Site-controlled QD growth, 97
 Solar cells, 189
 thin-film III–V (*see* Thin-film III–V QDSCs)
 Space applications, 9
 Spacecraft applications, 3
 Spin-photon entanglement, 84
 deterministic generation, 162
 hole spins, 168
 nuclear spin environment fluctuation, 164
 Spin-transfer torque (STT), 275
 Spin-type qubits, 116
 Spontaneous parametric down conversion (SPDC), 142

- SQ theory, 5
 SRH lifetime, 14–16
 Stark tuning, 91
 Static RAM (SRAM), 254
 Stern-Volmer plots, 184
 Strain-suppressed FSS, 91
 Streak camera measurement, 184, 185
 Sub-bandgap defects
 - QOD absorption spectrum, 63, 64
 - description, 63
 - passivation, 64
 - PbS QDs classification, 64, 65
 - PDMII/EMII, 63
 - photo-generated carriers, 63
 - PPP spectroscopy, 64
 Sun illumination, 4
 Superconducting microwave resonators, 124, 126, 127
 Superconducting single-photon detector (SSPD), 164
 Surface characteristics, 19–21
 Surface plasmon resonance (SPR)
 - in metal reflectors, 33
- T**
- Telecommunication band, 86, 98
 Telecom-wavelength InGaAs/GaAs QDs, 91
 Tetracyanoethylene (TCNE), 186
 Tf2 devices, 9
 Thermal annealing, 66
 Thermal barrier emission, 271
 Thermal intermixing effect, 208
 Thermalization processes, 2
 Thermochemical effect, 267, 268
 Thin-film
 - III–V semiconductors (*see* Thin-film III–V QDSCs)
 Thin-film III–V QDSCs
 - ELO, 6–11
 - InAs/GaAs (*see* InAs/GaAs QDSCs)
 - photon management (*see* Photon management)
 - tf2 devices, 9
 Thin-film III–V solar cells
 - cost reduction, 3
 - CPV systems, 3
 - multi-junction, 2, 3
 - nanostructured absorbers, 4
 - photovoltaic industry, 3
 - power/cost ratio, 3
 - single-junction GaAs, 2
 - spacecraft applications, 3
 - SQ limit, 2
 - thermalization processes, 2
 - triple-junction, 3
 - wafer separation and reuse technology, 3
 Thin-film quantum dot (TFQD) solar cells, 26, 27
 Third-order nonlinear optical properties, 188
 Time-correlated single-photon counting (TCSPC), 183
 Time of flight (TOF) method, 58
 Time-resolved photoluminescence (TRPL) spectroscopy, 57
 Traditional synthesis methods
 - anti-solvent precipitation, 180
 - CsPbBr₃, 179
 - hot-injection, 180
 - microwave-assisted, 180
 - phases, 179
 - ultrasonic synthesis, 181
 Transient absorption (TA), 61
 Transient absorption spectroscopy
 - advantages, 186
 - Auger recombination process, 186
 - charge carrier, 186
 - complicated dynamic behaviors, 185
 - luminescent/non-emissive samples, 185
 - trapping and recombination, 186
 - ultrafast dynamic processes, 186
 - use of, 186
 Transient absorption spectroscopy (TAS), 72
 Transient photocurrent (TPC), 66
 Transient photo-voltage (TPV), 66
 Transitional metallic dichalcogenides (TMDCs), 194
 Transmission electron microscopic analysis (TEM), 239
 Transmission electron microscopy (TEM), 58, 222, 233
 Transmission line method (TLM), 29
 Transparent carrier, 9
 Transparent resistive switching, 286
 Triple-junction III–V cells, 3
 Two-dimensional electron gas (2DEG), 110, 114
 Two-photon absorption (TPA), 193
- U**
- Ultrafast lasers, 209
 Ultrashort cavity F-P/DFB lasers
 - applications (*see* F-P/DFB lasers applications)
 - materials and fabrication, 210, 211
 - modulation p-doping, 210
 Ultrasonic synthesis, 181
 Ultra-violet (UV), 50

Unbalanced Mach-Zehnder interferometers (UMZIs), 147
Undoped as grown QDs (QDU), 212
Uniaxial strain induced by piezoelectric materials, 91
Unipolar electrical switching, 259

V

Valence change mechanism, 266, 267
Vertical cavity surface emitting (VCSE), 191–192
 V_{oc} reduction mechanisms
 intrinsic and extrinsic loss, 14–17
 QD-corrected transport model, 11
 V_{oc} scaling, 16

W

Wafer-based technology, 6
Wafer-sized thin-film
 photovoltaic applications, 7–10
Wavelength division multiplexing (WDM), 208, 225
Wavelength-tunable Q-LED, 89, 90
Whispering gallery mode (WGM)
 laser, 99, 191
Write-once-read-many-times (WROM), 291

X

X-ray diffraction (XRD), 57
 characteristics, 20–22
X-ray photoelectron spectroscopy (XPS), 233
X-ray spectroscopy (XPS), 57