

Index

A

Actuator, 50–59, 64, 75, 76, 81, 83, 86–88, 94, 95, 119–121, 128, 132
American Society of Civil Engineers, 4, 16, 48
Anhalt University, 4
Architectural fabric, 9, 12, 14–16, 38, 40, 42, 55, 62, 78, 81, 84, 109, 110, 113, 121

B

Barrel vault, 16
Biaxial behaviour, 40, 60, 98, 107, 126
Biaxial sample, 82, 98, 104
Biaxial test, 4, 5, 35, 36, 38, 40, 41, 43, 45, 49, 53–55, 60, 62, 68, 69, 74, 82, 91, 92, 98–100, 102, 105, 106, 119, 120, 122–124, 127, 128
Bursting test, 4, 39, 128

C

Calibration, 16, 95, 96, 114–116
CEN TC248, 5
CEN TC250, 3, 31
Clamping, 16, 50, 54, 56–59, 61, 77, 80, 81, 84, 88, 94, 98, 119, 121, 132, 133
ClusTEX, 16, 59, 81, 82, 87, 89, 91, 96, 98
Coated fabrics, 4, 5, 9, 12, 15, 16, 36, 38, 40, 44, 45, 47, 52, 84, 90, 91, 97, 99, 101, 102, 105, 107, 110, 119, 120
Coatings, 1, 14–16
Compensation factor, 36, 120
Cone, 10, 16
Control system, 16, 58, 84, 86–88, 94, 124
Cylinder test, 4, 39, 40, 45

D

Designing codes, 16, 38
Digital Image Correlation, 39, 53, 54, 91, 101
Dynamic analysis, 16
Dynamic relaxation, 3, 16

E

Elastic modulus, 16
EMPA, 5, 55, 58, 61, 63, 64, 67, 68, 89
ETFE, 3, 14, 16, 35, 126–128, 130–133
Eurocode, 3, 5, 16
Extensometer, 51, 53, 54, 56, 58, 59, 63, 82, 91, 92, 95, 101, 120, 121, 124, 127, 128, 130–133

F

Fibre, 1, 10–14, 16, 35, 92, 109
Floating frame, 49, 52, 57, 68, 74, 103
Foil, 3, 4, 9, 16, 35, 38–40, 59, 73, 90, 97, 99, 119, 126–130, 132, 133
Force density, 3, 16
Form finding, 2, 16

G

Gdansk University, 5
Glass-fibre, 16

H

Hypar, 16

I

Independent servomotors, 49, 50, 53, 59, 68, 103, 121, 128
Industrial Fabrics Association International, 3
Institute for Lightweight Structures and Conceptual Design, 48
Inter-laboratory study, 55

K

Konarka Power Plastic, 129–134

L

Labor Blum, 44, 53, 93, 99
Lightweight Structures, 2, 4, 16

- Lightweight Structures Association of Australasia, 3
- Load cell, 51, 53–58, 63, 83, 88, 89, 95, 96
- Loading profile, 36, 37, 43, 60–62, 65, 83, 85, 94, 95
- M**
- Manufacturing, 3, 4, 16, 36, 85, 97
- Material model, 16, 112, 113
- Mechanical properties, 4, 9, 13, 16, 40, 60, 73, 81, 109, 126, 127
- Membrane Structures Association of Japan, 3–5, 16, 41, 43, 45, 48, 61, 74, 75, 79, 84–86, 94, 101, 102
- N**
- Newcastle University, 55, 57, 61, 63, 64, 68, 80, 84, 91, 93
- Non-linear, 16, 44, 100, 107, 110, 112, 113
- Nylon, 12, 13, 16
- O**
- Open mesh fabric, 9, 16
- P**
- Patterning, 2, 16
- Picture frame, 45
- Plane stress, 42, 43, 97, 100, 107, 110, 112, 113, 119
- Poisson's ratio, 36, 41, 45, 61, 100, 107, 113, 127
- Politecnico di Milano, 5, 50, 55, 58–61, 63, 64, 81, 82, 87, 91, 96, 98, 120, 126
- Polyester, 1, 12, 14, 16, 36, 54, 60, 61, 73, 76, 78, 97, 98, 105, 106, 108, 109, 112, 121
- PTFE, 1, 12, 14–16, 68, 77, 81, 92, 97, 108
- PVC, 1, 14–16, 36, 54, 60, 61, 68, 78, 81, 90, 92, 97, 98, 105, 106, 108, 109, 112, 121
- R**
- Reproducibility, 105
- Response surface, 45, 69, 98, 100, 110
- Round robin, 54, 55, 60
- S**
- Safety factor, 16, 43, 47, 98, 99
- Shear deformation, 45–47
- Shear modulus, 45
- Shear test, 45
- Square frame, 46, 49, 53, 59, 103, 121, 128
- Static analysis, 16
- Stress-strain, 36, 38–40, 45, 68, 69, 100, 110, 111, 113, 127
- Symmetrical loading, 49, 51, 103
- T**
- Taiwan Textile Research Institute, 5, 68
- Tear test, 38, 47
- Technical University of Wien, 4
- Tensairity, 16
- Tensile stiffness, 36, 41, 92, 100, 107
- TensiNet, 3, 16, 43, 48, 93, 101, 102, 105
- Testing protocol, 81, 84, 93, 97, 100, 102, 105
- U**
- Uniaxial test, 4, 38, 43, 47, 54, 74, 84, 92, 99
- University Duisburg-Essen, 55, 56, 61, 63, 64
- Y**
- Young's modulus, 61, 107