

Index

A

- Absorption, 15, 18, 19, 21, 111
- Adiabatic flow, 38
- “A” heat inflows, 15, 24, 26, 37
- Air
 - liquid properties, 28
 - properties at NBP, 9
 - safety, 124
- Anoxia, 122–123
- Argon
 - liquid properties, 71
 - properties at NBP, 71
 - safety
- Asphyxia, 121–123
- Auto-stratification, 3, 65, 66, 85, 87–91, 106

B

- Baffles, vapour cooled, 24–26
- Bénard convection cells, 57, 58
- “B” heat inflows, 15, 24, 26
- Boiling
 - convective, 16, 34, 46
 - heat transfer, 9, 46–47, 115
 - heterogeneous nucleate, 43–44
 - homogeneous nucleate, 44–45
 - pool, 43–44
 - quasi-homogeneous nucleate (QHN), 43, 45–46, 61–62
- Boiling liquid expanding vapour explosion (BLEVE), 129
- Boiling points, normal, 2, 6–8, 42, 86, 87, 109

- Boil-off Rate (BOR), 2, 10, 31, 34, 42, 55, 62, 64, 72, 75–78, 86, 90, 92, 97, 98, 100, 129
- Boundary layer, 9, 16, 21, 33, 34, 46, 53, 71, 73, 80, 87, 97, 103, 105, 106
- Brittle failure, 123

C

- Choked flow, 5, 45, 99
- Cold burns, 122, 125
- Cold damage, 125
- Cold electronics, 93
- Compressibility of cryogenic liquids, 125
- Condenser reboiler, 127
- Convection
 - double diffusive convection and mixing, 75
 - intermittent convection, 50, 52–54, 57, 58, 60
- Convective heat transfer, 9, 26, 29, 43, 46–47
- Cool down
 - large mass, 115
 - tank, 115, 117
 - transfer line, 115
- Critical constants, 77
- Cryogenic concrete, 125, 129
- Cryogenic liquid
 - boiling points, 96
 - definition, 6–7
 - properties, 75
 - safety, 127

D

- Density
 - gases, 9
 - liquids at NBP, 86
 - liquid/vapour ratio, 9
- Dewar vessel, 28
- Distillation, 67, 99
- Double diffusive convection, 61, 64, 72, 74–75, 99, 103

E

- Effective thermal conductivity, 29, 52, 54
- Emissivity, 20, 25, 27, 28, 32
- Enhancement of heat transfer, 21, 26
- Enthalpy, 8, 9, 14, 18, 24, 26, 41, 46, 105, 118
- Evacuated powders, 23, 31–32
- Evaporation coefficient, 42, 51, 52, 54, 55, 59, 77, 100
- Evaporation rate, 2, 10, 11, 16, 18, 28, 42, 43, 45, 57, 59, 61, 64, 68, 69, 72, 75, 77, 78, 81, 95, 128

F

- Fanno flow, 115, 116
- Fibreglass paper, 33
- Flow
 - adiabatic, 110
 - flash calculation, 110
 - meters, 5, 61, 88
 - single phase, 116
 - two phase, 45, 106, 111
- Foam insulation, 14, 23, 27
- Freezing point of cryogenics, 29
- Frost heave and in-ground heaters, 21, 24, 29

G

- Gas conduction, 27, 31, 32
- Gases, properties of, 99–100
- Getters, 33
- Geysering, 45
- Glass foam insulation, 29

H

- Heat
 - balance, 26, 41, 42
 - flux, 9, 10, 16, 17, 30, 44, 46, 48, 49, 51, 52, 54, 67, 81, 105, 128
 - latent, of vaporisation, 19, 24, 41, 72, 102, 105

- of mixing, 2, 72, 75, 77, 78, 96, 97
 - transfer, 9, 10, 17, 21, 26, 28, 29, 38, 43, 44, 53, 115, 117
 - transfer coefficient, 17, 117
- Hydrostatic pressure, 19, 110, 112, 114

I

- Ice
 - bridge, 29
 - thermal conductivity, 29
- Instrumentation
 - cold electronics, 93
 - high precision for industrial application, 93
- Insulation
 - evacuated powder, 23, 31–32
 - gas purged, 2, 3, 23, 28–31, 37, 113
 - multi-layer, 23, 33
 - opacified powder, 102
 - vacuum, 114
- Isothermal flow, 44

K

- Kelvin temperature scale, 52, 53

L

- Latent heat of evaporation, 2, 13, 42, 51, 116, 117
- Liquefied petroleum gases (LPG)
 - composition, 3, 74, 124
 - containers, 4, 16, 46, 94, 124
 - properties, 2, 4
 - rollover, 3–4, 43, 99–100
 - storage, 1–3, 14–21
 - transportation, 14
- Liquid natural gas (LNG)
 - composition, 2
 - containers, 2, 128
 - properties, 128
 - rollover, 43, 64–66, 94, 98–99
 - storage, 2, 6, 13–21, 26
 - transportation, 2, 14
- Liquid transfer lines, 115, 119
- LPG *See* Liquefied petroleum gases (LPG)
- Loss rate, 42, 117

M

- Marangoni effect, 89, 128
- Materials for low temperature use
 - alloys, 25
 - composites, 27

- concrete, 29
- glass, 28
- metals, 25
- safety, 25
- Methane
 - properties, 9
 - safety hazards, 30, 105
 - storage, 1, 30, 68, 70
- Mixtures
 - boiling and condensation, 67
 - heats of mixing, 4, 96
 - properties, 4, 6, 99–100
 - rollover, 6, 75, 79
 - stratification, 72, 79, 87–91, 99–100
 - temperature diagrams, 73
- Multi-layer insulation (MLI), 23, 28, 32–33, 102
- Multi shielding, 24

- N**
- Net Positive Suction Pressure Head (NPSH)
 - problems, 112
- Nitrogen
 - liquid properties, 10
 - properties at NBP, 9, 71
 - safety, 121
- NPSH problems *See* Net Positive Suction Pressure Head (NPSH) problems
- Nucleate boiling, 9, 16, 18, 43–46, 49, 61, 67, 78, 96, 118

- O**
- Opacified powders, 20
- Oscillations
 - flow, 22, 119
 - pressure, 45
 - thermo-acoustic, 22, 37–38
- Overfill, liquid, 2, 14, 17, 20, 42, 72, 93, 125
- Overfill–thermal, 8–9
- Oxygen/nitrogen mixtures
 - liquid properties, 71
 - safety, particularly with liquid air, 122, 123
 - temperature-composition diagrams, 77

- P**
- Path dependent mixing, 85, 96, 129
- Phase equilibrium, 41, 67, 69
- Polyurethane foam (PUF), , –, 27, 29, 31
- Pool boiling, 43
- Powder insulations, 14, 23, 31–32
- Precooling, 115

- Pressure drop
 - single phase flow, 116
 - two phase flow, 106, 110
- Pressure subcooling, 9, 111, 113
- Pressurised liquid tanks, 14, 98, 101–107, 124, 129
- Pressurising, 14, 45, 72, 90, 92, 98, 101, 102, 104–106, 112, 114
- PUF *See* Polyurethane foam (PUF)
- Pumps
 - reciprocating, 38, 112
 - rotary, 31, 110, 114
 - vacuum, 31, 32
- Purge gases, 30, 107

- R**
- Radiation
 - baffles, 24–26, 37
 - traps, 37
- Reflectivity, 20
- Rollover
 - convective mixing of 2 stratified layers at 1 bar pressure, 79
 - LNG, 4, 43, 64–66, 79, 85–100
 - LPG, 3–4, 43, 65–66, 79, 99–100
 - maximum evaporation rate to be expected, 93
 - multi-component liquids, 10, 74
 - single component liquid, 67
 - stratification as precursor, 87

- S**
- Safety laboratory, 98, 125–127
- Safety valves, 44–46, 82, 105
- Schlieren pictures of surface convection, 57, 58
- Sea tankers
 - LNG, 4, 91
 - LPG, 4, 91
- Secondary membrane, 124
- Shields
 - multi, 24
 - radiation, 24
 - vapour cooled, 14
- Solubility of impurities, 69–70
- Storage tanks and vessels, 124
- Stratification
 - composition, 61, 64, 79, 88, 99
 - density, 2, 3, 21, 33, 64, 65, 71, 72, 74, 86, 87, 92, 93, 99
 - temperature, 61, 72, 79, 99, 103
- Subcooled liquid, 9, 91–92, 109–110, 116

- Superheat, 8, 9, 14, 16, 18–20, 34, 42, 44–46, 48–49, 51, 53–55, 58, 59, 61, 71, 77, 78, 81, 86, 88, 90, 100, 105, 107
- Superheated liquid, 8, 20, 42, 46, 53–55, 58, 59, 62, 71, 81, 86, 88
- Surface evaporation, 6, 8, 10, 17, 18, 34, 36, 61, 64, 68–69, 73, 77, 81, 86, 87, 99, 107
- Surface tension of cryogenic liquids, 43, 50
- T**
- Tankers
 rail, 124
 road, 124
 sea, 4, 6, 30, 92, 128
- Temperature-composition (T–x) diagrams, 67, 68
- Temperature scales, 2, 86
- Thermal(s), 8, 9, 13, 15–18, 23, 24, 29, 31, 32, 36, 37, 42, 44, 47, 50, 52, 54, 58, 59, 64, 71, 73, 74, 77, 85, 91–92, 96, 97
- Thermal conductivity, 21, 27–30, 32, 34, 50, 52, 54, 58, 77
- Thermal insulations, 2
- Thermal overfill, 2, 8–9, 14, 17–20, 42, 47–58, 61, 64, 72, 74, 75, 77–78, 92–97, 103
- Thermal subcooling, 9, 106, 111
- Thermal underfill, 91–92
- Thermo-acoustic oscillations, 22, 37–38
- Thermometry, 49, 93
- Topping-out precautions, 119
- Transfer line
 cooldown, 115
 insulated, 124
- Triple point, 6, 7
- Two-phase flow, 6, 44, 106, 109–111, 113–119
- U**
- Underfill, thermal, 91–92
- V**
- Vacuum
 gauges, 46
 insulation, 2, 3, 6, 14, 23, 28, 31, 45, 48, 72, 101–107
 pumps, 28, 31, 32, 38
- Valves
 cryogenic liquid, slow opening, 125
 safety, 44–46, 64, 82, 105
- Vapour cooling, 15, 21, 24, 26, 116
- Velocity of sound, 110
- W**
- Water
 prevention of ingress, 29
 properties, 6
 thermal conductivity, 29
- Z**
- Zero delivery, 109, 118