

# Index

## A

Acoustic coupling (to superconducting qubits), 219, 226–228  
Acoustic reflection (of SAWs), 231–233  
AC-Stark phase shift (in superconducting qubits), 209  
Active area (in SNSPD practical detection efficiency), 4, 7  
Active area (of SNAPs), 18, 20  
Active area (of TES), 40  
Active area (performance trade-offs in SNSPDs), 13  
Adiabatic demagnetization refrigerator (ADR), 40  
Admittance (of IDT), 224  
Afterpulsing (in SNAP), 17  
Afterpulsing (in SNSPDs), 5  
Amorphous superconductors (for SNSPDs and SNAPs), 8, 12, 13, 25  
Analog feedback (for superconducting qubits), 164, 179  
Anharmonicity (in superconducting qubits), 140, 143, 144, 230, 236, 241  
Anti-bunching (of photons), 159  
Arm-trigger regime (in SNAPs), 17  
Array  
  of SQUIDs for TES readout, 36  
Array factor (for IDT), 225  
Arrays (of optical fibers), 95  
Arrays (of single photon sources), 64  
Arrays (of SNSPDs), 24, 25

Arrays (of superconducting qubits), 183  
Artificial atom, 140, 145, 151, 153, 160, 168, 218, 228–230, 240  
Attenuation (in optical fiber), 99, 100, 116  
Attenuation (in optical waveguide circuits), 92  
Attenuation (of SAW), 221, 234  
Avalanche photodiode (semiconductor), 32, 41, 75, 149, 166  
Avalanche regime (of SNAP), 15–17, 21

## B

Backaction (in superconducting qubit measurements), 164–167, 169, 170, 172–174, 177, 179, 183  
Bandwidth (in microwave photon detection), 151  
Bandwidth (of coupling to superconducting qubit), 158, 174, 182, 194, 197, 236  
Bandwidth (of IDT), 220, 226, 235, 237  
Bandwidth (of optical stack), 37, 38  
Bandwidth (of SQUID readout for TES), 42  
Bandwidth (SNSPD readout), 24, 68, 100  
Bandwidth, spectral (of SNSPD), 89, 116  
Bell measurement, 130  
Bell test, 46, 49–51  
Bell's inequality, 49, 50, 146  
Black-body radiation/photons, 5, 36, 43, 101  
Bloch sphere, 149, 168, 173, 175, 197  
Born's rule, 164, 165, 230  
Bragg grating, 127, 128, 231

Bragg mirror/reflector, 64  
 Bunching (of photons), 47

## C

Cascade recombination (in quantum dots), 63  
 Cascade switching (in superconducting nanowires), 4, 14, 20  
 Cavity QED, 146, 158, 168, 218, 219  
 Circuit model (of IDT), 224, 227  
 Circuit model (of SNAP), 15, 18  
 Circuit model (of SNSPD array), 24  
 Circuit model (of SNSPD), 10, 11  
 Circuit QED (cQED), 140, 146, 158, 167–169, 172, 174, 192, 193, 197, 198, 201, 204, 206, 207, 211, 212, 218, 231, 239–242  
 Coherence, 128, 129, 131, 139–141, 146, 168, 177, 191, 201, 204, 208, 241  
 Coherent state superposition (CSS), 47, 48  
 Collapse (of quantum superposition), 164, 208  
 Collapse (of wavefunction), 165, 177, 188  
 Constrictions, 8, 9, 12, 13  
 Controlled-NOT gate (CNOT), 63  
 Conversion efficiency (in wavelength conversion), 128  
 Cooper pair, 88, 89  
 Cooper-pair box (CPB), 141–143, 147, 241  
 Coupling (in cQED), 140, 147, 153, 157, 169, 172, 202, 219  
 Coupling efficiency (optical), 5, 6, 51, 55, 56, 69, 70, 72, 78, 120  
 Coupling of modes (COM) method, 224  
 Coupling, electron-phonon, 34, 41, 53  
 Cross-Kerr, 142, 148, 149, 153–157  
 Crosstalk (between optical fibers), 109  
 Crosstalk (between SNSPD elements), 74, 75  
 Crosstalk (SAW), 239

## D

Dark count rate (DCR), 4, 5, 7, 17, 32, 62, 71, 72, 86, 88, 89, 96, 99, 101, 108, 120  
 Dark counts, 5, 23, 36, 50, 54, 79, 117, 120, 129, 151  
 Dark fiber, 115, 116  
 Dead time (for feedback in superconducting circuits), 183  
 Dead time (of SNSPD), 10, 13, 18, 74, 89, 122

Dead time (of TES), 41  
 Decoherence, 62, 168, 174, 179–181, 206, 209  
 Decoy-state QKD protocol, 110, 112, 120  
 Detection efficiency (DE), 4, 6, 8, 9, 12, 17, 19, 22, 26, 32, 33, 36, 40, 45, 46, 50, 52–56, 69, 71, 77, 86, 89, 95, 108, 111, 129, 151, 153  
 Detection loophole (for Bell test), 46  
 Detector Packaging, 40  
 Detector tomography, 44  
 Deterministic entanglement, 189, 205, 207, 211, 212  
 Deterministic reset (for superconducting qubits), 201  
 Device detection efficiency (DDE), 5, 13, 16, 17  
 Differential phase-shift quantum key distribution (DPS-QKD), 110, 113  
 Digital feedback control, 188–190, 193–195, 197, 198, 200, 202, 204, 205, 207, 208, 210, 212  
 Dilution refrigerator, 88, 182, 198, 201, 218, 222, 233

## E

Electron beam lithography (EBL), 9, 65, 67, 68, 88, 92, 98, 222  
 Electron-phonon coupling, 53  
 Electrothermal (ET) model, 10, 24, 78  
 Electrothermal feedback, 34  
 End-fire coupling, 68  
 Entangled photon pair source, 121, 123–125, 128, 129, 131  
 Entanglement, entangled states, 49, 50, 56, 126, 130, 166, 167, 170, 189, 190, 205–207, 209–212  
 Evanescent coupling, 51, 52, 93, 97

## F

Fabry-Perot, 69, 71, 78, 168, 241  
 Fair-sampling loophole (in Bell test), 49, 50  
 Feedback, Feedback protocol, 163, 164, 179–183, 188–192, 198–207, 211, 212, 219, 240, 242  
 Feedforward (for qubit control), 189  
 Field-programmable gate array (FPGA), 113, 114, 199, 200, 205, 207, 211  
 Figure of merit (single-photon detectors), 75, 86, 87  
 Fock state, 44, 145, 157–159

**G**

- GaAs/AlGaAs waveguide, 64, 69, 70
- Gallium arsenide (GaAs) waveguide circuit, 67, 71, 73, 76, 95
- Grating coupler (optical), 99

**H**

- Heralded photon-subtraction, 54
- Heralded single-photon source, 121, 122, 125, 126, 130
- Heralded state detection, 46–48, 54
- Homodyne detection, 49, 54
- Hong-Ou-Mandel (HOM) interference, 46, 47, 130
- Hotspot (in superconducting nanowire), 9, 10, 12, 15, 74, 77

**I**

- Indirect measurement (of qubit), 165, 166, 169
- Instrument response function (IRF), 6, 21
- Interdigital transducer (IDT), 219–226, 228, 230, 231, 233–239

**J**

- Jaynes-Cummings Hamiltonian, 147, 158, 164, 168
- Josephson coupling, 142
- Josephson inductance, 226
- Josephson junction, 36, 140, 141, 150, 171, 197, 218
- Josephson parametric amplifier (JPA), 171, 192, 193, 197, 207
- Josephson parametric converter (JPC), 174
- Joule heating, 9, 11, 12, 34, 64

**K**

- Kinetic inductance, 10, 11, 13, 72, 73, 76, 96
- Kinetic inductance detector (KID), 23
- Kramers-Kronig relation, 157

**L**

- Lamb shift, 230, 241
- Latching (of SNSPD), 10
- Lattice parameters (NbN and substrates), 65
- Lindblad decoherence, 168
- Lindblad superoperators, 230
- Linear detector, 145, 149, 153, 159
- Loophole (of Bell test), 46, 49, 50

**M**

- Magnesium diboride ( $\text{MgB}_2$ ), 8
- Magnetron sputtering, 65, 66
- Markovian approximation, 154, 230
- Master equation, 155, 168, 174–177, 201, 205, 209, 230
- Measurement-based quantum computing, 190
- Metastable state, 149–151
- Microcalorimeter, 33, 34
- Microring resonator, 91, 97, 98
- Microwave photon generation, 140, 158
- Microwave photon source, 159
- Microwave quantum photonics, 140–142, 144, 145, 147–151, 153–160
- Microwave single-photon detection, 140, 151, 160
- Mid-infrared (mid-IR) single-photon detection, 5, 7, 12, 37
- Molybdenum germanium (MoGe) superconducting nanowire, SNSPD, 8, 9, 13
- Molybdenum silicide (MoSi) superconducting nanowire, SNSPD, 7–9, 13
- Multi-photon correlation function, 22
- Multi-time correlation function, 149, 159

**N**

- Niobium nitride (NbN) refractive index, 70
- Niobium nitride (NbN) superconducting nanowire, SNSPD, 7–9, 11–13, 16, 18, 65, 67, 69, 70, 72–76, 79, 88, 93–96, 116, 122
- Niobium nitride (NbN) thin film, 65–68, 71, 72, 88
- Niobium titanium nitride (NbTiN) superconducting nanowire, SNSPD, 7, 12, 88, 95, 96, 99, 122
- Noise equivalent power (NEP), 87, 88, 96, 99
- Non-linear detector, 43
- Non-locality, quantum, 46, 79
- Number resolution, 51

**O**

- On-chip detection efficiency (OCDE), 69, 71, 77, 89, 95, 96, 101
- On-chip detector calibration, 55
- One-time pad (OTP), 108, 110, 114, 115
- Optical coupling, 13, 40, 50, 55, 64, 68–70, 87, 91, 108
- Optical stack, 9, 37, 38

Optical time domain reflectometry (OTDR),  
99–101, 109, 118

## P

Parametric amplification, 146  
Parity measurement, 183, 188, 189, 205–212  
Performance metrics (for SNSPDs), 4, 6, 13,  
26, 86, 101  
Performance trade-offs (for SNSPDs), 13  
Periodically-poled KTiOPO<sub>4</sub> (PPKTP),  
121–126  
Periodically-poled lithium niobate (PPLN),  
127, 128  
Phase qubit, 141, 151, 158  
Phase-sensitive amplifier, 170, 172, 173  
Photon statistics, 46, 47, 49, 64, 78, 124, 126,  
159  
Photon subtraction, 48, 51, 54, 56  
Photon-number resolution, 4, 23, 26, 36, 43,  
44, 53, 56  
Photon-number-resolving (PNR) detector, 4,  
21, 36, 43, 56, 71, 74, 75, 77–79  
Photonic crystal, 62, 91  
Photonic qubit, 63  
Piezoelectric materials, 220  
Pointer system, 166, 169  
Positive-operator-valued measure (POVM),  
44, 45, 164–167  
Postselection, 194, 196, 202, 203, 209–212  
Projective measurement (of superconduct-  
ing qubit), 165–167, 176, 179, 188,  
190–192, 195, 197

## Q

Quantum acoustics, 218, 242  
Quantum bit error rate (QBER), 111, 112,  
114  
Quantum computation, quantum computing,  
47, 61, 62, 86, 101, 102, 146, 188–  
190, 212  
Quantum dot (QD), 62, 64, 70, 139  
Quantum efficiency (QE), 65, 71–73, 78, 87,  
89, 96, 97, 151, 167  
Quantum Electrodynamics, QED (in super-  
conducting circuits), 140, 146, 149,  
*see also* Circuit QED (cQED)  
Quantum feedback, 163, 179, 188  
Quantum information (QI) network, 107,  
108, 121  
Quantum interface, 107, 108, 126, 127, 129–  
131

Quantum key distribution (QKD), 7, 62, 74,  
87, 108–111, 113–116, 120  
Quantum non-demolition (QND) measure-  
ment, 148, 150, 153, 158, 160, 165,  
166, 176  
Quantum non-locality, 46, 49  
Quantum photonic circuit, 64, 85, 86, 102  
Quantum photonic integrated circuit (QPIC),  
61, 65, 70–72  
Quantum repeater, 126, 128, 130, 131, 189  
Quantum simulation, 61, 62  
Quantum state tomography, 124, 129, 175,  
182, 183, 201, 208–211  
Quantum trajectory, 167, 174–177  
Qubit, 62, 140–143, 146–148, 151, 152,  
158, 159, 164–170, 172–183, 188–  
195, 197, 198, 200–212, 218, 219,  
226–228, 231, 235–242

## R

Rabi oscillations, 150, 163, 164, 177, 179–  
182, 190, 195, 196  
Rabi splitting, 238  
Ramsey cavity, 149, 150  
Ramsey fringes, 150  
Rayleigh waves, 220  
Readout (for SNAP), 23  
Readout (for SNSPD array), 4, 24, 25  
Readout (for SNSPD), 6, 9–11, 14, 89, 91,  
95, 102  
Readout (for superconducting qubits), 148,  
151, 167–169, 191–197, 199–203,  
206–210  
Readout (for TES), 35, 36, 42  
Refractive index, 38, 39, 70, 90, 92, 94, 99,  
100  
Refrigeration (for SNSPD), 95, 108, 122,  
129  
Refrigeration (for superconducting qubits),  
182, 198, 218  
Refrigeration (for TES), 40  
Reset (of superconducting qubit), 188, 189,  
191, 199, 201–205, 212  
Reset time (of SNAP), 17–19  
Reset time (of SNSPD), 4, 10, 89, 94, 96  
Rise time, 10, 20, 42, 78  
Rotating-wave approximation, 230  
Row-column readout (of SNSPD arrays), 24,  
25  
Rydberg atom, 149, 150, 158, 159, 218, 241  
Rydberg states, 147, 149, 228

**S**

- Sagnac interferometer, 123
- Sagnac loop configuration, 50, 124
- Schrödinger cat state, 47, 48
- Second-order correlation function, 49, 62, 72, 74, 80
- Signal-to-noise ratio (SNR) (SNSPDs and SNAPs), 14, 15, 22, 75
- Silica waveguide, 51, 52, 74
- Silicon nitride photonic circuits, 91, 92, 94–96
- Single-Cooper-pair box, SCB, 241
- Single-photon detection, 7, 12, 56, 62, 79, 87, 88, 101, 108, 140, 148, 151, 152, 155
- Single-photon detector, 12, 15, 17, 32, 41, 51, 55, 56, 61, 62, 67, 69–71, 74, 77, 88, 99, 101, 108
- Single-photon source, 61, 62, 65, 86, 108, 122, 125, 159
- Spontaneous parametric down-conversion (SPDC), 47, 50, 62, 122
- Sputtering, 39
- Superconducting nanowire avalanche photodetector (SNAP), 4, 11, 14–19, 21, 22
- Superconducting nanowire-single photon detector (SNSPD or SSPD), 4, 7–19, 22, 24, 25, 32, 41, 62, 64, 75, 76, 87–89, 95–101, 108–110, 112, 113, 115, 116, 118, 120–126, 129–131
- Superconducting quantum interference device (SQUID), 35, 36, 42, 53, 140, 141, 226, 237, 240
- Surface Acoustic Wave (SAW), 218–223, 226–230, 232, 233, 235–242
- Surface Acoustic Wave (SAW) device fabrication, 220, 222
- Surface Acoustic Wave (SAW) device materials, 220, 221, 233
- Surface Acoustic Wave (SAW) resonator, 221, 225, 231–233, 241
- Surface Acoustic Wave (SAW)-lasing, 242
- Surface Acoustic Wave (SAW)-qubit interaction, 226, 228, 235, 240
- System detection efficiency (SDE), 4, 19, 33, 50, 69, 89, 108

**T**

- Tantalum nitride (TaN) superconducting nanowire, SNSPD, 7, 88
- Thermal expansion coefficients, 39, 221
- Time-correlated single-photon counting (TCSPC), 6, 89, 100
- Time symmetry, 178
- Timing jitter, 4, 6, 7, 13, 20, 26, 39, 41, 42, 51, 74, 87, 89, 96, 98, 108, 122, 129
- Tokyo QKD network, 109, 110, 114, 116, 131
- Transition edge sensor (TES), 31–39, 41, 42, 44–46, 48–57
- Transmon qubit, 141–145, 147, 148, 150, 153–159, 181, 191, 192, 194, 197, 201, 202, 204–207, 218, 226–230, 235, 236, 240–242
- Tungsten (for TES), 33, 34, 37–39, 41, 42, 53
- Tungsten silicide (WSi) superconducting nanowire, SNSPD, 7–10, 12, 13, 20, 25, 65, 88

**U**

- Ultrastrong coupling, 240, 241
- Unitary evolution, 164, 176, 177, 179
- Unstable regime (in SNAP operation), 17, 18
- UV laser writing, 52

**V**

- Vacuum Rabi splitting, 142, 147, 148, 159

**W**

- Waveguide autocorrelator, 70, 72–74
- Waveguide circuit, 32, 95
- Waveguide-integrated SNSPD, 68, 71, 90, 96
- Waveguide-integrated TES, 55
- Waveguide photon-number-resolving detector (WPNRD), 75–79
- Waveguide PPLN, 128
- Waveguide QED, 218, 219, 240
- Wavelength conversion, 108, 126–128, 130, 131
- Weak measurement (of superconducting qubit), 163, 164, 167, 172–174, 176, 177, 179, 180, 183, 188
- Wigner function, 48