

# Index

## A

- Abstraction, 26, 37, 40–43, 48, 52, 53, 65, 94–95, 170, 175, 196, 197, 199, 204, 206, 211, 222–225
- Abstraction levels, 3, 4, 18, 23–53, 71, 86, 187, 188, 192
- Abstraction methodology, 196, 204, 206
- Accelerometer, 8, 10, 14, 19, 49, 51, 52, 154–157, 163, 165, 166, 191, 205–208, 210–212, 218
- Actuator, 1, 4, 5, 14, 16, 23, 29, 56, 97, 171, 196–204
- Airbag, 10
- Algorithmic noise tolerance (ANT), 3, 69, 72–86
- Analog, 1, 4, 5, 8, 16–18, 24, 26, 28, 29, 35, 38–41, 43–45, 48–51, 55–57, 64, 75, 97, 100, 124, 146, 148, 152, 163–165, 170–173, 176, 187, 188, 195, 198, 200, 202, 204, 207, 208, 211, 217–220, 222, 225
- Analog mixed-signal (AMS), 16, 146, 152, 163
- Approximate computing (AC), 3, 55–86
- Architecture, 2, 7–9, 11, 12, 14–18, 27, 46, 55, 59–61, 63, 66–72, 74, 76, 77, 79–83, 85, 164, 167, 171–173, 186, 191, 192, 205
- Automata, 25, 33–37, 40–42
- Automotive, 2, 7, 92, 172

## B

- Battery, 12, 56, 169, 182, 183, 185, 188–190, 205
- Biomedical, 13

## C

- CAD. *See* Computer aided design (CAD)
- Circuit power model, 176
- Circuit simulation, 112, 126, 137, 139
- Code conversion, 25
- Code manipulation, 42
- Computer aided design (CAD), 101, 147, 148
- Consumer applications, 14–15
- Converter efficiency, 187
- Co-simulation, 3, 20, 24–26, 31–32, 52, 53, 91, 100, 103, 145, 146, 154–156, 165, 167, 189, 196, 208,
- Cyber-physical systems, 5

## D

- Data types, 37, 42, 46, 48, 222
- DC-bus, 172
- DC-DC converter, 92, 122, 134–139, 186, 187, 191
- Defense, 10
- Delay errors, 74
- Design, 1–4, 7–9, 11, 17–20, 23–53, 55, 56, 60, 61, 64, 66, 69, 76, 83, 85, 91, 92, 95, 96, 118, 122, 139, 145–147, 149–151, 153, 154, 163–167, 176, 195, 196, 198, 200, 215, 217, 218, 225
- Design domains, 3, 23–53, 200, 217
- Device level, 7, 30
- Digital, 1, 4, 5, 8, 14, 16, 18, 23, 24, 28, 33, 37–38, 40–43, 47, 48, 51, 52, 55–86, 97, 98, 148, 163, 165, 170–173, 176, 193197–200, 203, 208, 218, 219, 221, 222, 224

Digital signal processing (DSP), 1, 5, 23, 64, 72, 86, 165  
 Discrete power device, 91–140

**E**

EDA/CAD methodologies, 2, 3, 27, 61, 93, 101, 147, 148  
 Electrical circuit equivalent model, 178  
 Electrical energy system, 15  
 Electrical linear network (model of computation), 27, 188, 200  
 Electronic design automation (EDA), 2, 3, 27, 61, 93, 109, 147  
 Energy harvesting, 10, 13  
 Energy storage device (ESD), 5, 15, 170, 180–185  
 Enhanced power bus, 175  
 Environment, 2, 4, 5, 8, 9, 13, 14, 16, 18–20, 24–27, 29, 30, 43, 45, 55–57, 92, 94, 95, 103, 111, 122, 126, 128, 129, 136, 139, 145–148, 153, 154, 163–166, 169, 171, 178, 180, 188, 196, 205, 207, 212, 213, 215, 218, 220, 221, 225  
 Error control (EC), 69, 73, 78  
 Error prediction, 77  
 Error resilience, 56–61, 71, 72  
 Error tolerance, 58

**F**

Finite element method (FEM), 3, 20, 93, 94, 106–108, 112, 118, 121–124, 126, 127, 129, 131, 134, 136, 137, 139, 146, 151, 158  
 Food/beverage, 13  
 Functional level, 30–40  
 Functional power model, 176

**G**

Global positioning system (GPS), 8  
 Gyroscope, 10, 147–149, 154, 159, 161, 205–212, 217,

**H**

HDL intermediate format (HIF), 27, 37–40, 42, 43, 201, 220–222  
 Healthcare, 2, 13, 205  
 Heterogeneous simulation, 28, 218, 225  
 HIF. *See* HDL intermediate format (HIF)  
 HIFSuite, 26, 27, 37–40, 42–44, 46–50, 52, 201–203, 218–222, 224

Home automation, 11  
 Homogeneous simulation, 24, 25, 33

**I**

Industrial automation, 11–12  
 Inertial body motion reconstruction, 4  
 Inertial measurement unit (IMU), 205  
 Integrated power electronics module (IPEM), 91–95, 97–114  
 Integration challenges, 36, 38, 40, 45  
 Integration strategies, 36, 37, 40, 45  
 IP-XACT, 218–223

**K**

Kalman filter, 205, 213  
 Kirchhoff's laws, 39

**L**

Layered approach, 94  
 Load, 8, 73, 97, 100, 114, 121, 132–134, 137, 138, 146, 169, 170, 172–178, 181–183, 191–193  
 Logistics, 2, 11–12

**M**

Magnetometer, 205–208, 210–213, 215  
 Management function, 36, 37, 41, 42, 207  
 Manufacturing systems, 11  
 Maximum power point transfer (MPPT), 172  
 MEMS simulation, 3, 4, 145–167  
 Metal-oxide-semiconductor field-effect transistor (MOSFET), 3, 15, 92, 98, 101–104, 122–139  
 Micro-electro-mechanical systems (MEMS), 3, 4, 8, 10, 12, 16, 29, 43, 49–51, 97, 145–167, 173, 176, 178, 191, 195, 198, 205, 207, 211  
 Microsystem, 13, 145–146, 165  
 Military, 10, 92  
 MoC. *See* Model of computation (MoC)  
 MoC conversion, 26, 31–34, 36, 37, 45, 53  
 Model, 4, 8, 17, 19, 20, 28, 31, 33, 46, 60, 70, 93–97, 99, 100, 103, 106, 110, 112, 114, 118, 122, 124, 125, 128, 130, 134, 136, 146, 149, 151, 153, 155, 158–159, 162, 164, 170, 172, 176, 182–186, 190–193, 196, 198–203, 207–212, 215–217, 220, 225  
 Model of computation (MoC), 26, 28, 31–37, 40, 45, 48, 164, 165, 200, 202, 208

- Model order reduction (MOR), 4, 146, 148, 159, 167
- Modified nodal analysis, 39
- MOSFET modeling, 92, 120, 128–130
- Multi-domain simulation, 3, 28, 91
- Multi-physics, 18, 145, 151, 158, 208
- N**
- Noise tolerance. *See* Algorithmic noise tolerance (ANT)
- O**
- OpenSim, 210, 215, 216
- Open-source test case (OSTC), 196, 217–225
- P**
- Peukert's equation, 182
- Photovoltaic cell, 15, 174, 179, 181
- Physical level, 30, 60
- Pico-projector, 4, 196–204
- Piezo-electric power source, 180
- Power
- arbitrator, 174, 175, 191, 192
  - bridge, 98, 115, 174, 175, 185
  - converter, 106, 170, 186–187
  - distribution, 13
  - flow, 97, 169–193
  - generation, 13
  - interconnect, 170, 185
  - interface, 174–175
  - model, 169, 175–178, 193
  - perspective, 170–173, 188
  - simulation, 170, 188–190, 193
  - source, 1, 4, 23, 29, 130, 170, 172, 174–176, 178–181, 191
  - state machine, 177, 178
- Probabilistic computing (PC), 58, 60
- R**
- Reduced precision redundancy (RPR), 76, 78–86
- S**
- Safety, 2, 5, 7, 8, 10–11, 13, 14, 16
- Scavenger, 15, 171, 172, 176, 178
- Scheduling, 3, 27, 33, 35, 37, 38, 40, 71
- Security, 2, 5, 10–12, 14
- Sensor(s), 5, 8, 10, 11, 13, 14, 16, 23, 29, 57, 75, 97, 98, 154, 165, 171, 191, 196, 205–207, 210, 211, 213, 214, 217
- actuator, 1, 5, 14, 16, 23, 29, 97
  - fusion, 4, 205–208, 212, 217
- Smart bulb, 14
- architectures, 15–17
- Software (SW), 3, 4, 11, 16, 19, 25, 52, 60, 61, 71, 86, 91, 93–96, 101, 108, 122, 145, 163–167, 195, 196, 198, 208, 215, 218, 223, 225
- Solar cell, 15, 175, 192
- Stochastic computing (SC), 59, 188
- Structural level, 30
- Super capacitor, 15, 174, 180, 184–185, 191–193
- Superjunction MOSFET, 123, 139
- Surveillance, 10
- Survey, 65, 66
- Synchronization
- challenges, 40
  - of data and events, 28, 33, 35–36, 40, 41
- Synthesis, 57, 68, 70–71, 82, 83, 107, 110, 111, 166, 202
- SystemC-AMS, 3, 4, 26–27, 43–45, 48–51, 164–167, 187–192, 198, 200–204, 207, 208, 211, 217, 222
- SystemC-TLM, 37, 38, 48, 188, 193, 208
- SystemVue, 26–28, 32, 41, 45–48, 51–53, 95, 206–208, 210, 215–217
- T**
- Taxonomy of design domains/abstraction
- levels, 3, 18, 23–53, 71, 86, 187, 188, 192
- Technology computer aided design (TCAD), 122, 126, 129
- Telecommunications, 10
- Thermal analysis, 92
- Thermal-impedance, 93, 94, 98, 107–109, 114–116
- 3-D electrothermal simulation, 122, 134, 139
- Timed data flow (model of computation), 188, 200
- Transactional level, 26, 30, 32, 40–48, 51, 53, 188, 224
- Transportation, 5, 8–9, 12
- U**
- Unclamped inductive switching test (UIS), 3, 92, 122, 124, 126, 131–134

UNIversal VERsatile Computational Model  
(UNIVERCM), 26, 28, 33–38,  
40–42  
Unmanned aerial vehicle (UAV), 8

**V**

Virtual prototyping platform, 4, 197–204  
Voltage over-scaling (VOS), 69–71, 73–79,  
81–85