

Index

- 1–3 composite 352
- AC 98
- acoustic attenuation 14
- acoustic emission 16, 362
- acoustic foam 391
- acoustic wave propagation 337
- acousto-ultrasonics 376
- ACROBAT 20
- actin filament 470
- actin-myosin interaction 474
- active damping 371
- active aerodynamic measure 434
- active blade tips 388
- active bracing 433
- active control 429
- active damping 88, 137, 372, 390
- active damping system 413
- active flap 19
- active flow 371, 377, 383
- active flow control 384
- active flutter and vibration control 18
- active functional material 30
- active interface 399
- active jet 384
- active mass damper 429
- active mount 398
- active optics 86
- active piezo sensor 354
- active power 273, 279
- active rudder 20
- active sensor 358
- active structural damping 14
- active tendon 429
- active type (AMD) 432
- active vibration absorber 105, 106
- active-passive composite tuned mass damper 432
- actuating cylinder 426
- actuator 9, 24, 126, 302
- actuator design 104
- actuator dynamic 100
- actuator equation 252, 253, 260, 263
- actuator model 259
- actuator-sensor configuration 99
- actuator-sensor module 99
- adaptability 1
- adaptive architecture 24
- adaptive cabin noise reduction 392
- adaptive control 17, 55–62, 72, 98, 445
- adaptive diagnostic system 500
- adaptive feed forward controller 407
- adaptive network controller 497
- adaptive process control 415
- adaptive rotor 372, 392
- adaptive structure 360, 362
- adaptive system 5, 491
- adaptive wing programme 372
- adaptronic concept 281
- adaptronic spindle 418
- adaptronic structure 3, 4, 6, 30, 33, 37, 42, 79, 84, 491
- adaptronic strut 423
- adaptronic system 95, 491
- adaptronics 29, 30
- Adaptronik 1
- ADC 304
- aero-servo-elastic control of vibration 18
- aerodynamic control 18
- aerodynamic device 434
- aerodynamic force 19
- aerodynamic performance 380, 387, 391
- aeroelastic rotor experimental system (ARES) 372

- aeronautics 371, 373
- aeroservoelastic control 385
- aging 12
- air glider 335
- aircraft wing 18
- amplified piezo actuator 115, 116, 118
- analogue amplifier 101, 279
- analogue power amplifier 269
- analogue processing 304
- analogue-to-digital converter 304
- angle of attack 384
- ANN 491
- anomaly 29, 31, 32
- ANSYS 105
- antagonist muscle 11
- antenna structure 384, 385
- anti-resonance dynamic absorber 445
- antiferromagnetic 45
- APA 115, 117, 118
- arc-track type absorber 447–449
- ARMA process model 415
- articulating fold mirror 390
- artificial insects 393
- artificial intelligence 12
- artificial knee 201
- artificial limb 495, 496
- artificial muscle 12, 13
- artificial nerve 13
- artificial neural network 491, 496
- artificial sense 13
- ASAC 408
- ASIC 301, 307, 312–314
- astronomical telescope 86
- ATP 474
- austenite 146, 156
- austenitic phase 41, 148
- auto-calibration 313, 314
- automation engineering 98
- automotive 15
- autonomic healing response 24
- auxiliary energy 96
- auxiliary mass damper 104
- AVC 408
- aviation technology 8
- axial sensor 355

- balanced reduction 84
- bench testing 19
- bending elements 113
- bending resonance 20
- bending sensor 355
- bimorph 113
- bimorph structure 212
- Bingham plastic 164, 167, 168, 174, 176, 179, 184
- bioartificial organ 502
- biocompatible 499
- bioelectrical signal 495
- biological system 491
- biomimetic robot 219
- bionics 470
- bipolar 266
- birth-to-retirement 22
- blocked force 132
- blocking force 112
- blood flow 501
- blood vessel connector 214
- Boeing active flow control systems (BAFCS) 384
- bond strength 334
- boring bar 422
- Bragg grating 15
- Braille display 214
- brain stem 491
- brain-machine-interface 499
- brake 14, 185
- bridge pier 434
- buffet problem 20
- bump 383
- bus system 407
- bus topology 315
- butterfly trajectory 109

- cabin noise 373, 385, 388, 392
- Cadillac 197
- calcification 25
- CAN BUS 198
- car roof 402
- carbon nanotube 204
- carbonyl iron 186
- cardiac control 494
- casting 214
- catastrophic failures 23
- CBM 22
- CBN 415, 416
- CCD microscanning 119
- CDC 398
- center of gravity 444, 447

- center of oscillation 446, 448
 center point 413
 central processor 16
 ceramic metal composite 353
 chair lift 450
 charge control 274
 chatter 414, 422
 chemical valve 207
 chevron 383
 chimney 430
 choke 267, 269
 choke coil 268, 281
 civil engineering 198, 199
 civil infrastructure 15
 clamping force 112
 clock frequency 272
 closed control loop 98, 245
 closed-loop control 98, 245, 413, 425
 closed-loop instability 17
 clutch 14, 166, 170, 179–181, 183, 185
 clutch drive 179
 CMG 453
 CNC 421
 coating 334, 341
 coating strength 334
 cochlea system 499
 cochlear implant 214
 coefficient of thermal expansion 119
 coil spring 153, 154
 communication 315
 compact hybrid actuators program
 (CHAP) 372, 380
 compensation 262, 263
 compensation filter 262
 compensation model 417
 compensators 260
 complex hysteretic nonlinearity 260
 composite 29, 30, 46, 49, 334
 composite laminate 24
 composite material 30
 compression bar 153, 154
 compression tube 153
 computational network 9
 computer aided control engineering
 404
 condition-based maintenance 22
 conducting polymer 204, 210
 connectivity 351
 constant-gain active control 20
 constant-power grinding 416
 constitutive law 79, 80
 contamination 277
 continuous damping control 398
 control 9, 16
 control algorithm 17
 control circuit 271
 control moment gyroscope 453
 control of muscle activity 488
 control processor 24, 98, 305
 control strategy 98
 controllability 77
 controllable fluid 187
 controller 100
 controller output 96
 controller synthesis 98
 conventional actuator 101, 102
 convertible 399
 corrosion 333
 corundum 415, 416
 Corvette 197
 Couette flow analysis 169
 Couette viscometer 164, 167, 181
 Couette-shear flow 175
 coupling sleeve 147
 crack growth 362
 crack intrusion 24
 crash 409
 creep 108, 252, 275
 creep dynamics 261
 creep effect 246, 249
 cross-sensitivity 302, 306
 crossed extensor reflex 488
 crystal structure 13
 CTE 119
 cubic crystalline boron nitride 415,
 416
 Curie point 41
 Curie temperature 109, 110
 current control 274
 current density 173
 current transformer 95
 cut-off frequency 272
 cutting-volume rate 422
 cybernetics 16
 damage proceeding 362
 damper 185

- damping 13, 126, 371, 373, 384, 385, 387, 389
- damping force 423
- DARPA 372, 380, 384
- data communication 305
- data conversion 304
- debonding 334
- decoupling 103
- deductive compensation 303, 304
- deep-coating 214
- defibrillator 494
- deformation measurement 322
- delamination 23, 325
- depolarization 109
- design cycle 18
- design goal 18
- detect cracking 362
- development methodology 403
- diagnostic function 408
- diaphragm 228
- dice-and-fill 352
- dielectric elastomer 205, 217
- dielectric anomaly 31
- differential type actuator 161
- digital processing 304
- digital signal processor 17, 259
- direct control 55
- direct conversion 19
- direct-shear mode 189, 191
- directionally attached piezoelectric actuators (DAP) 388
- discrete joint 12
- displacement amplification 18, 105, 114
- distributed active vibration absorbers (DAVA) 391
- distributed actuation system 12
- distributed actuators 101
- distributed fiber sensor 322
- distributed sensors 332
- disturbance signature 18
- domain boundary 36
- domain engineering 48
- domain wall 36
- domains 34, 41
- Doppler signal detection 502
- double looped ring 316
- draw-tower FBG grating 335
- dressing 416
- drift 118, 119
- drift effect 337
- drug delivery system 492, 502
- DSP 17, 265
- dual-state control 273
- dual-state operation 276
- dwelt-time 195
- dynamic compliance 422
- dynamic instability 414
- dynamic loading 428
- dynamic strain measurement 337
- dynamic vibration absorber 444, 446, 456
- dynamic wind load 433
- e-NDE 362
- EAP 204
- earthquake 199, 429
- eddy current 268, 279, 375
- effective coupling factor 131
- efficiency 131
- efficient aerodynamics 19
- eigensystem realization algorithm (ERA) 56
- elbow joint 11
- electric dipole 31
- electrical breakdown 118
- electrical dipole 13
- electrical stimulation 495
- electroactive polymer 204, 372
- electrocardiogram 495
- electrochemical cell 211, 216
- electrochemical deposition 214
- electrochromic device 211
- electrokinetic phenomena 207
- electromagnetic force 451
- electromagnetic transducer 96
- electromechanical coupling 39
- electromechanical equivalent circuit 112
- electromechanical equivalent circuit diagram 248, 249, 251, 252
- electromechanical impedance method 360
- electronically trainable artificial neural network 64
- electrophoresis 180, 266, 276
- electrophoretic migration 208

- electrorheological 372
- electrorheological effect 426
- electrorheological fluid 2, 13, 14, 163, 266, 273, 276, 396, 411
- electrostatic micropump 237
- electrostatic valve 235
- electrostriction 39, 43
- electrostrictive 14
- electrostrictive effect 38, 108
- electrostrictive material 127
- electrostrictive polymer 205, 218
- electroviscous effect 163
- Elliptec motor 117
- embedded catalyst 24
- embedded control 407
- embedded microcontroller 17
- embedded NDE 23
- embedded non-destructive evaluation 362
- embedded sensor network 361
- embedded system 407
- endoscopic diagnostic 500
- energy buffer 272
- energy control 275
- energy controller 95, 96, 100
- energy conversion 19, 37
- energy converter 95, 96, 100
- energy harvesting 124, 318
- energy recovery 101, 271
- energy supply 270
- energy transduction 12
- engine distress monitoring system (EDMS) 375
- engine mount 174
- epoxy matrix 24
- equivalent mass ratio 447
- ER actuating cylinder 426
- ER fluid valve 426
- ERF 276, 411
- ETANN 72
- EU Framework Programmes 372
- EUCLID 372
- European Space Agency (ESA) 390
- excitation control 304
- external plunge grinding 413
- extrusion 214

- Fabry-Perot interferometer 15, 323, 333
- fast hydraulic drive 137
- fault detection 308, 309
- FBG 323
- FBG strain sensor 333
- FEA 70
- feature extraction 308
- feed axis 417, 420
- feed-forward control 155
- feed-forward converter 269, 275
- feedback control of furnace temperature 489
- feedback control of muscle length 489
- feedforward controller 101
- FEM 69, 81, 105
- ferrimagnetic 44, 45
- ferroelastic 42
- ferroelectric 30, 31, 34, 37–39, 42, 46, 108
- ferroelectric material 30, 109
- ferrofluids 184
- ferroic 42
- ferromagnetic 42, 44
- ferromagnetic material 126
- fiber actuator 212
- fiber Bragg grating sensor 323
- Fiber Fabry-Perot interferometer sensor 325
- fiber optic sensor 319, 336
- fiber reinforced composite 361
- fibrous bone 25
- field-programmable gate array 17
- film sensor 349
- fin box 386, 387
- fin buffet 373, 385
- final controlling element 96
- final controlling equipment 97
- final output stage 279
- fine finishing 413
- finite element analysis 70
- finite element method 69, 81
- finite stroke 18
- flexible structure 70
- flexible wingspan 22
- flexoelectric polymers 205
- flexure hinge 160, 162
- flight control 21
- flight loading 335
- flight muscles, insects 481, 484

- flight vehicle 18
- flipperons 384
- flow mode 165, 167, 277
- flow rate 174
- flow separation 383
- fluid shear stress 392
- flutter boundary 18
- flyback converter 268, 275
- foam 372, 391
- force impulse 442
- force-speed relation, muscle 479
- form filter 415
- four-quadrant amplifier 266, 279
- Fourier transformation 256
- FPGA 17, 265
- FPI 323
- frequency converter 416
- frequency response 302, 303
- friction force 115
- frictional device 14
- fuel injection 272
- fuel injector 137
- full authority digital control (FADEC) 375
- full vehicle test stand 411
- full-bridge 268, 279
- full-scale active brace 440
- functional 37
- functional composite 49
- functional density 428
- functional electrical stimulation 497
- functional material 1, 4, 29–32, 40, 45, 49
- fuzzy 491
- fuzzy logic 496

- gauge length 333
- giant magnetostrictive alloy 126
- grain boundary 32, 34, 40, 46
- gravity force 448
- grinding arbour 416
- grinding machine 414
- grinding operation 415
- grinding spindle 416
- grinding wheel 413, 416
- gripper 150, 160
- guided ultrasonic wave 360
- guided wave 359
- gyro rotor 444
- gyroscope 446
- gyroscopic absorber 453, 455
- gyroscopic moment 444, 452

- H_2/H_∞ controller design 71
- H_∞ controller 70
- H_∞/μ synthesis approach 71
- HALE 22
- Hankel singular values 77
- haptic feedback 501
- hardware structure 304
- hardware-in-the-loop 405
- HDLC 316, 317
- healing agent 24
- health and usage monitoring system (HUMS) 374
- health monitoring system 247
- heat sink 271
- Hedström number 176
- helicopter blade control 137
- helicopter rotor blade 18
- high current 181
- high power transducer 138
- high speed train 434
- high voltage amplifier 421
- high voltage source 426
- high winds 428
- high-voltage source 105
- HMI 98
- Hubble Space Telescope 390
- human skin 15
- human-machine interface 98
- hybrid amplifier 271, 280
- hybrid power amplifier 270
- hybrid test stand 411
- hybrid type (HMD) 432
- hydraulic circuit 426
- hydraulic force-displacement transformer 115
- hydraulic pipe 19
- hydraulic pressure 340
- hydraulic valve 14
- hydrophilic properties 209
- hydrophone 15, 50
- hydrostatic MR fluid bearing 424
- hysteresis 99, 118, 119, 135, 146, 150, 152, 155, 156, 171, 180, 182, 249, 252, 274, 275, 279, 354
- hysteresis compensation 280

- hysteresis effect 263
- hysteresis loss 269
- hysteresis operator 260, 265
- hysteresis-free 274
- hysteretic behaviour 109
- hysteretic nonlinearity 257
- hysteretic transfer characteristic 103
- hysteretic transmission behaviour 246

- identification method 69
- IEEE standard 1451.4 307
- impact detection 362
- implant 493
- implantable force sensor 498
- implantable neuromuscular stimulator 497
- in-flight tracking 20
- in-use-thickening 189
- inchworm motor 116, 126, 140
- incline correction table 417, 419
- independent modal space control 401
- indirect control 55
- induced strain actuator 12
- inductance 195
- inertia force 448
- ingested debris monitoring system (IDMS) 375
- injection valve 272
- ink-jet printing 215, 232
- input matrix 76
- input/output requirement 18
- insect flight muscles 481, 484
- insect jumps, muscles 485, 486
- inside turning 422
- inspection tasks 159
- integrated force feedback 401
- integration capability 354
- intelligent actuator 102
- intelligent sensor 301, 311, 318
- intelligent structure 9
- intelligent system 1
- interface zone 341
- internal circular grinding 415
- internal sensoric effect 155, 156, 159
- interrogation unit 326
- inverse filter 103
- inverse model 275
- inverse modelling 280
- inverse piezoelectric effect 38, 107

- ion pump 27
- ionic polymer metal composite 204
- ionic polymeric membrane 208
- IPMC 204

- jumps, insects 485, 486

- Kalman filtering 70
- Krasnosel'skii-Pokrovskii operator 260

- Lamb wave 359
- lamellar bone 25
- laminar translator 113
- large-signal characteristic 249, 251
- large-signal operation 250, 252, 253, 263
- lathe 420
- leading and trailing edge flap 388
- leaf spring 153
- leakage current 118
- LFR 69, 70
- lifetime 213
- linear actuator 135, 140
- linear fractional Representation 69
- linear quadratic performance 55
- linear system model 257
- linearisation 76, 103, 302
- liquid crystal 182
- liquid level sensor 15
- load cell 306, 311
- load spectra 17
- loads monitoring 374, 375
- local pressure sensing 339
- local stimulus 17
- locking device 410
- loitering flight 22
- long-gauge-length sensor 323
- long-span bridge 430
- long-term sensor characteristic 341
- longitudinal effect 107, 110, 111
- look-up table 302
- Lord corporation 190
- loudspeaker 138
- Love wave 359
- low-voltage actuator 111
- LQ 72
- LQ optimal control 434
- lubricating system 238

- MACE 70
 Mach-Zehnder 15
 machine controller 418
 machining precision 421
 macroactuator 214
 macroscopic 33, 36, 37, 43, 46, 49, 52
 MagneRide™ 197
 magnetic field 184
 magnetic fluid 182
 magnetic head 14
 magnetic ride 398
 magnetic saturation 195
 magneto-elastic coefficient 127
 magnetorheological 389
 magnetorheological effect 426
 magnetorheological fluid 13, 14, 185,
 279, 372, 396, 425
 magnetostrain 126
 magnetostriction 45, 126
 magnetostrictive actuator 247, 250,
 267, 279
 magnetostrictive effect 47, 230
 magnetostrictive film 142, 144
 magnetostrictive material 13, 81, 127,
 145, 396
 magnetostrictive motor 126, 140
 manipulated variable 96
 martensite 40, 41, 48, 49, 146, 156
 martensitic phase 41, 148
 martensitic phase transformation 13,
 145
 mass ratio 447
 mass-spring type absorber 449
 mast 430
 MATLAB 105
 maximum control force 438
 measurement of acoustic emissions
 337
 mechanical gripper 160
 mechanical structure 104
 mechano-chemical reactions 206
 medical device 159
 memory effect 206
 MEMS 371, 373, 375, 376, 392–394
 mesoscopic 33, 34, 37, 46, 48, 52
 metal removing rate 413
 micro aerial vehicles (MAV) 371, 393
 micro assembly 159, 160
 micro dosing element 236
 micro-electro-mechanical-system 406
 micro-mixer 238
 micro-satellites 371, 394
 microactuator 127, 142, 143, 225
 microanalysis system 238
 microcapsules 24
 microcontroller 13
 microdosing system 238
 microdrop injector 239
 microengineering 318
 microgripper 161, 214, 502
 microimplant 495
 micromotor 142
 micropositioner 14, 126, 137
 micropump 236
 microrobot 214
 microscopic 33, 34, 45, 52
 microstrain sensor 333
 microstructure 34
 microstructured fiber 342
 microsystem 493
 microvalve 244
 microvibration isolation 121
 Middeck active control experiment 70
 milliactuator 244
 milling cutter 420
 milling process 418
 milling spindle 418
 miniature gripper 160, 163
 minimal invasive surgery 500, 502
 missiles 385
 mission-adaptable wing 378
 MITI 6
 MLA 118
 modal analysis 105
 mode 164
 model reduction 83
 model reference adaptive control 18,
 55, 61, 64, 65
 modeling 127
 monitored compensation 303
 monitoring of moisture 332
 monitoring system 408
 monomorph 113
 moonie 50
 moonie transducer 114
 morphing aircraft 21

- morphing structures 18
- Morphing Wing 372, 378, 392
- morphotropic 46
- moving vehicle 433
- MPB 46, 47
- MR 14
- MR fluid 184, 185
- MR fluid damper 188
- MR fluid shock absorber 188
- MRAC 18, 55, 72
- multifunctional 46
- multifunctional composite 51
- multifunctional element 2, 4, 491
- multifunctional material 5, 30, 51, 95
- multifunctionality 1, 4, 99, 245
- multilayer actuator 115
- multilayer ceramic 109
- multilayered neural network 62
- multisensor system 315
- muscle spindle 487
- muscle type 469
- muscle, antagonists 479
- muscle, basic functions 481
- muscle, boulder analogy 472
- muscle, contraction types 476, 477
- muscle, extension control 486
- muscle, force-length graphs 478
- muscle, force-speed graphs 479
- muscle, length control 490
- muscle, stress control 487
- muscle, striated: crosssections 470
- muscle, striated: longitudinal sections 470
- muscle, universal actuator 469
- muscular control 9
- muscular levers 483
- muscular work 476
- muscular-cybernetic analogy 489
- myofibril 470
- myosin filament 470
- myosin-actin interaction 474

- Nafion 204, 208
- nanotube 216
- NASA 372, 373, 378, 382, 385
- nastic structures 26
- NC axis 417
- NDE 23, 359
- NDI 359
- NDT 359
- near wall vortex generator 384
- need-based maintenance 23
- nerve potential 495
- neural controller 62
- neural interface 495, 498
- neural network 17, 56
- neural network controller 388
- neural network-based adaptive control technique 61
- neural network-based adaptive controller 55
- neural prostheses 493, 495
- neural signal 493
- neural stimulator 493
- neurocontroller 62
- neuromodulation 497
- Newtonian properties 164
- Nitinol 13
- Nitinol actuator 59
- noise 302, 303, 308, 371, 372, 385, 388, 390, 391
- noise damping 8
- noise reduction 383, 385, 392
- non-destructive evaluation 359
- non-destructive inspection 359
- non-destructive technique 359
- non-destructive testing 359
- non-linearity 99, 302
- nondestructive evaluation 23
- nonlinearity 75
- normal grinding force 416
- notched tensile coupon 13
- novelty detection 310
- numerical time integration 85
- NVH 397

- observability 77
- observability Gramians 77
- off-state 195
- on-line adaptive control 57, 64
- on-state 195
- one-quadrant operation 277
- one-way effect 147
- operating point 249, 251
- operating region 249, 252
- optical fibers 14
- optical tracking device 14
- optimal load 131

- optimization 89
- osmotic pressure 27
- output matrix 76
- output power 131, 132
- overvoltage 274

- pacemaker 493
- parallel gripper 161
- parameter drift 302
- parametric vibration 433
- parametrization 89
- Parkinsons disease 495
- passenger gondola 451
- passive 371, 390
- passive damping 427
- passive filter 270
- passive functional material 29
- passive gyroscopic absorber 454, 455
- passive piezo sensor 354
- passive sensor 355
- passive type (TMD) 432
- passive vibration absorber 104, 105
- payload 12
- PC 100
- PCF 342
- PDF 307
- pendulum-type dynamic absorber 449
- pendulum-type structure 446
- pendulum-type tuned active damper 441
- perovskite structure 46
- personal computer 98, 100
- PFC 352
- phase boundary 46
- phase transformation 150
- phase transformation temperature 13
- phase transition 29, 31, 34, 37, 40–42, 45, 46
- phased array 501
- photochromic glass 1, 3
- photoelastic damage control 13
- photolithography 24, 214
- photonic crystal fiber 342
- piezo actuator 266, 273
- piezo fiber composite 352
- piezo proof mass 120
- piezo transducer 358
- piezoactive motor 140
- piezocapacitive effect 222
- piezoceramic 229
- piezoceramic stack actuator 400
- piezoelectric 36–38, 42, 48, 50, 107, 304
- piezoelectric actuator 98, 100, 247, 414, 416
- piezoelectric ceramics 14, 140
- piezoelectric composite 15
- piezoelectric composite sensor 351
- piezoelectric disc plate 427
- piezoelectric drive 230
- piezoelectric effect 36, 39, 43, 107, 229
- piezoelectric element 502
- piezoelectric foil 499
- piezoelectric material 13, 81, 108
- piezoelectric MEMS 354
- piezoelectric motor 115
- piezoelectric polymer 205
- piezoelectric sensor 342
- piezoelectric stack actuator 421
- piezoelectric stack translator 424
- piezoelectric transducer 96, 501
- piezoelectric ultrasonic motor 116, 140
- piezomagnetic effect 44
- piezomagnetic law 127
- piezoresistive DLC layer 411
- piezoresistive pressure sensor 500
- plastic optical fiber 342
- PMN 43
- pneumatic valve 233
- POF 342
- Poiseuille flow analysis 169
- Poiseuille valve flow 175
- polyaniline 204, 210, 214
- polycrystalline ceramic 108
- polyelectrolyte gel 204
- polymer 348, 499
- polymer composite 13, 24
- polymer gel 205
- polymer network 205
- polymer strain gage 221
- polymeric matrix 209
- polymerisation 24, 214
- polypropylene 110
- polypyrrole 204, 210, 214
- polyvinylidene difluoride 348
- polyvinylidene fluoride 15, 108, 110

- position control 155
- positioning device 421
- positioning drive 425
- positioning system 114, 262
- power amplifier 96, 100, 265
- power electronic 100, 101, 265, 406
- power harvesting 17
- power spectral density 20
- power spectrum density 386
- power stage 266
- power supply unit 271
- PP 110
- PPF controller 100
- PPM 120
- Prandtl-Ishlinskii operator 260, 262
- pre-processing 308
- predator birds 21
- Preisach operator 260
- Preisach-model 156
- pressure measurement 326
- pristine state 23
- probability density function 307
- process computer 413
- process identification 98
- process model 413
- process parameter 415
- prognosis 23
- prostheses 495
- prosthesis 201, 492
- PSD 21
- pseudo-elasticity 148, 149
- PTC 29, 32, 34, 40
- pulse control 429
- PVDF 108, 110, 229, 348
- PVDF films 15
- PVDF sensor 57
- PWAS 23
- pyroelectric effect 15
- pyroelectric material 42
- PZT 34, 37, 46–48, 50, 51, 119
- PZT ceramic 108
- PZT compound 108
- PZT disk 51
- PZT fiber 352
- PZT rod 352

- quartz 108
- quasi-static operation 101
- quasistatic motor 116

- Rabinow 185
- radar absorbing material 392
- Rainbow actuator 391
- Rayleigh wave 359
- reaction chamber 238
- reactive element 269
- reactive power 273, 279
- real-time system 100
- recalibration 308, 310
- reciprocal piezoelectric effect 107
- reconfiguration 308, 310
- reconstruction 263
- reconstruction filter 258, 261
- reconstruction model 260, 261
- recoverable strain 13
- refractive index 327
- regulator circuit 1
- relaxor 46
- reliable sensor system 335
- remote damage 362
- repeatability of measurement 323
- repolarization 109
- resistance feedback 157
- resonance 126
- response time 195, 213, 276
- retinal encoder 499
- retinal prosthesis 499
- retinal stimulation 499
- retirement 12
- Reynolds number 176, 195
- rheological behaviour 168
- rheological property 14
- ride quality 18
- rigid-body pendulum 447
- ring topology 316
- robotic device 150
- robust actuator 438
- robust control 55, 57, 69, 71
- root locus curve 88
- ropeway 446
- ropeway gondola 448, 453
- rotor blade twist 387
- rotor blades 372, 373, 384, 388
- run-flat 398
- runability of vehicle 434

- safety (fatigue) 430
- Sagnac 15
- saturation 109

- saturation magnetization 185
- Sawyer-Tower circuit 259
- Schottky barrier 32, 40
- seismic 198
- seismic mass 422, 423
- self diagnoses 247
- self tuning regulator 18
- self-check 314
- self-healing 24
- self-repair 10, 22, 24
- self-sensing actuator 95, 100, 103, 156, 159, 245, 246, 258, 263
- self-sensing effect 245, 256
- self-sensing model 252
- self-supporting 26
- self-test 304, 313, 316
- semi-active 186
- semi-active control 185
- semi-active damper 427
- semi-active soft engine mount 398
- semiaactive type (SAMD) 432
- sensing element 304
- sensitivity 345
- sensor application 333
- sensor array 337
- sensor design 349
- sensor equation 83, 252, 253, 260
- sensor material 347
- sensor model 256, 259
- sensor network 10
- sensory structure 361
- serviceability 430
- servo-hydraulic actuator 18
- servovelocity seismometer 439
- shape control 371, 377, 384
- shape memory 41, 48
- shape memory actuator 156–160, 163
- shape memory alloy 5, 13, 34, 41, 145–148, 151, 152, 157, 231, 265, 372, 396, 410, 502
- shape memory coil spring 149
- shape memory effect 42, 145, 147, 149, 150, 156
- shape memory gel 206
- shape memory polymer 372
- shear element 114
- shear lag effect 357
- shear mode 277
- shear stress 165, 169, 191
- SHM 22, 360
- SHM system 412
- shock absorber 2, 3, 172, 173, 185
- short-gauge-length sensor 325
- side intrusion beam 410
- signal conditioning 308
- signal processing 376
- signal processing unit 103
- silicon gripper 161
- silicon microchip 24
- SIMO 70
- single input-multiple output 70
- single input-single output 57
- SISO 57
- skeletal muscle 491
- skeletal structure 12
- slender, tower-like structure 430
- slew rate 280
- SMA 13, 410
- SMA wire actuator 379, 393
- smart aircraft and marine propulsion system demonstration (SAMPSON) 372
- smart layer 375
- smart material 1, 9
- smart microwave window 392
- smart skins 371, 391, 392
- smart structural system 55, 65
- smart structure 1, 17, 55, 101
- smart structure test article 55, 57, 72
- smart strut 389, 390
- smart suitcase 375
- smart wing programme 378
- soft lithography 215
- software tool 91
- solid–solid phase transition 146
- solid-state actuated flap 18
- solid-state actuator 247, 253
- solid-state transducer 101, 414
- sonar 138
- space technology 8
- speech processor 499
- speed-force diagram 479
- spillover 85
- spin-coating 214
- spinal cord 491
- spinal cord stimulation 497

- spring-damper element 426
- sputtering 159
- squeeze mode 174, 277
- STA 7
- stability 78, 84
- stack translator 111, 114
- star topology 315
- state of the art 430
- state space representation 76
- state variable 82
- state vector 76
- state-space 82
- static compliance 422
- static condensation 82
- stealth 391
- stepping motor 140
- stepping piezomotor 116
- Stoneley wave 359
- STR 18
- strain gauge 98, 304–306, 420
- strain monitoring 335
- strain profile 335
- strain resolution 330
- strain rosette 336
- strain sensitivity 328
- strain sensor 354
- strain transfer 333
- strengthening 25
- stress concentration 13
- stress distribution 334
- stress transfer 334
- stress, muscle 474
- stress-free deformation measurement 327
- striated skeletal muscle 469
- structural aging 23
- structural compensation 303
- structural diagnostic 23
- structural dynamics 82
- structural health bulletin 23
- structural health monitoring 22, 360, 371, 372, 374
- structural impedance 12
- structural mechanic 22
- structural safety 23
- structural uncertainty 70
- structure assessment 326
- super-elasticity 148
- surface-attached fiber sensor 334
- surface-mounted fiber strain sensor 335
- suspension 399
- switching amplifier 101, 279
- switching power amplifier 19, 267
- symmetry 31, 33, 35, 37, 39, 43, 44, 46
- system component 97
- system identification 260
- system integration 407
- system inversion 256
- system matrix 76
- system model 258, 260, 261, 263
- tail buffeting 19
- tailored compensation 303
- tall building 430
- TDT 20
- technology readiness level (TRL) 373
- TEDS 308
- tele-operation 501
- tele-surgery 501
- temperature influence 335
- temperature sensor 330
- tendon system 433
- tensile bar 153, 154
- tensile tube 153
- tensile wire 153, 154
- Terfenol-D 45, 47, 126, 128–131, 135–138, 140, 145, 396
- tetanus, muscle 475
- thermal deformation 417
- thermo-symmetric layout 417
- thermomechanical effect 230
- thermomechanical valve 234, 236
- thermopneumatic effect 230
- thermopneumatic valve 234
- thermosetting polymer 25
- thick-film technology 306
- third-wave machine 177
- thixotropic 188
- time constant 171, 177
- time response 302, 303
- torque converter 95
- torsion bar 153, 154
- torsion helical spring 153, 154
- torsion tube 153
- torsion wire 153, 154
- torsional stiffness 388

- tourmaline 108
- traffic load 433
- trailing edge flap 19
- transducer 126, 302, 315
- transfer characteristic 102
- transfer function 78
- transformation temperature 146, 150, 155
- transition 44
- transonic dynamics tunnel 20
- transonic shock wave 383
- transversal effect 107, 110, 113
- travelling wave ultrasonic motor 116
- travelling waves 384
- trim tab 20
- truss structure 100
- tunable damper 14
- tuned mass damper (TMD) 431
- turning tool 421
- twin 36, 37, 40, 41
- twist 388
- twitch, muscle 475
- two-quadrant amplifier 279
- two-quadrant operation 277
- two-way effect 38, 147–149, 152

- ultrasonic monitoring 501
- ultrasonic motor 140, 143
- ultrasonic NDE method 359
- ultrasonic piezomotor 142
- ultrasonic transducer 15, 50
- ultrasonic travelling wave motor 380
- ultrasonic wave 23, 362
- unconventional actuator 265
- undervoltage 274
- unimorph bilayer bender 212
- uninhabited aerial vehicles (UAV) 371
- unipolar 266
- unmanned aircraft 22
- USM 116

- validation methods 341
- validation procedure 335
- valve 170, 180
- valve mode 190, 277
- variant 34, 39
- varistor 32
- VDI Technology Centre 1, 7
- VDR 32, 34
- velocity feedback 401
- Vibramount 408
- vibration 198, 385
- vibration absorber 104, 444
- vibration control 12, 186
- vibration damping 8, 120
- vibration fatigue 18
- vibration isolation 14
- vibration suppression 19, 55, 72, 390
- viscometer 165
- viscosity 184
- viscous damper 456
- vision prosthesis 499
- voltage control 274
- vortex-induced cross-wind vibration 431
- vulnerability 19

- wavelet analysis 496
- whirl tower 19
- wind tunnel 19
- wind turbine 337
- wing extension 21
- wing folding 21
- wing sweep 21
- Winslow 185
- Winslow effect 166
- wireless sensor network 317, 408
- work-per-volume 159
- worst-case scenario 12
- WSN 317

- yield shear stress 165
- yield strength 184, 192
- yield stress 164, 169, 174, 187

- Z-membranes 471
- zero-point data loss 323
- zero-point reference 335, 340

About the Authors

Horst Baier was born in 1950 near Frankfurt. He gained his degree in mechanical engineering at Technische Universität Darmstadt in 1972. From 1972 until 1977 he was a research assistant at the Institute of Lightweight Structures in Darmstadt, with emphasis on finite element techniques and multi-criteria optimization methods. In 1977 he joined Dornier Satellitensysteme where he soon became responsible for structural analysis and technology of mechanical systems. He became increasingly involved in the interaction of mechanical and control systems, and adaptive structures became one of his research interests. In the summer of 1997 he was appointed professor and head of the Institute of Lightweight Structures at Technische Universität München. His main research activities are in adaptive structures, fiber composite structures, as well as multidisciplinary structural and design optimization.

Christian Boller studied Structural Engineering at the Technical University of Darmstadt/Germany and received a Dipl.-Ing. degree in 1980 and a Dr.-Ing. degree in 1987. He was awarded a Japanese government scholarship for a stay with the Fatigue Testing Division of the National Research Institute for Metals in Tokyo/Japan in 1984/85. His involvement in smart technologies dates back to 1990 when he joined the Military Aircraft Division of MBB (now EADS) in Ottobrunn/Germany. He was appointed on the newly established chair in Smart Structural Design at the University of Sheffield/UK in 2003 which includes research work in structural health monitoring and micro aerial vehicles. He is the European editor of 'Smart Materials and Structures', a major international journal and has more than 100 papers and books published.

Peter Boltryk graduated in 2000 from the University of Southampton, UK, with an MEng in mechanical engineering. In 2004 he successfully completed a PhD which specialised in developing certain aspects of signal processing and data-based model techniques for application in a novel ultrasonics-based navigational aid for underwater submersibles. His current post-doctorial research interests at the University of Southampton, include non-contact surface metrology, audio recovery from mechanical sound recordings, signal processing, intelligent sensing and condition monitoring, and data analysis. He is an associate member of the IMechE.

William A. Bullough was born in Westhoughton, Lancashire in 1939. He was a trade apprentice, student engineer and assistant hydraulics engineer with De Havilland Aircraft. Following his M.Sc. in thermo fluid mechanics at the University of Birmingham he worked as a systems analyst with Hawker Siddely Dynamics and was latterly research associate in the Osborne Reynolds Hydraulics Laboratory, University of Manchester. From 1967 he has worked as lecturer, senior lecturer and reader at the University of Sheffield, UK where he is currently Honorary Reader. He is, among other things, a chartered engineer, a fellow of the Institution of Mechanical Engineers and a member of the Royal Institution.

Wenwu Cao received his PhD degree in condensed matter physics from the Pennsylvania State University, USA in 1987. After working briefly at the Laboratory of Atomic and Solid State Physics, Cornell University, he joined Penn. State University to become a faculty member in 1990. Currently, he is a professor of mathematics and materials science, a joint appointment between the Department of Mathematics and the Materials Research Institute of Penn. State. He conducts both theoretical and experimental research mainly on functional materials and their applications. To date, he has authored and co-authored more than 230 scientific journal articles. He is a member of the American Physical Society.

J. David Carlson, born in Erie, Pennsylvania in 1946, earned degrees in physics from Case Western Reserve University (B.S.) in 1968 and the University of Colorado (PhD) in 1972. Since 1976 he has been with the Lord Corporation, a global manufacturer of vibration and motion control systems and specialty materials, where he is senior engineering fellow. Since the mid 1980s he has provided technical leadership that has transformed magnetorheological (MR) fluid technology from an interesting concept to a successful business. He holds 59 US patents and is the author of over 130 technical papers and books. He is the inventor of the 'MR fluid syringe' that has been used worldwide to effectively demonstrate the marvel of smart MR fluids. He is an adjunct professor in mechanical engineering at Virginia Tech University and a fellow of the American Physical Society.

Federico Carpi was born in Italy in 1975. He received the Laurea degree in electronic engineering in 2001 from the University of Pisa, Pisa, Italy. He received the PhD degree in bioengineering in 2005 from the University of Pisa. Since 2000 he has carried on his research work at the Interdepartmental Research Centre Piaggio, University of Pisa, where he currently has a post-doctoral position. His main research activities are related to polymer based materials and devices for biomedical engineering and robotics. He is author of several technical and scientific publications.

Frank Claeysen, born in 1962, received in 1985 an engineering diploma from ISEN, Lille. He achieved a PhD Thesis at INSA Lyon in 1989 from his work at DCN (French Navy) on low frequency electro-acoustic transducers (design & construction of magnetostrictive sonar transducers). In 1989, he joined Cedrat to fund the active materials applications (AMA) activities dealing with smart materials and applications. Since 2001, he has been the technical & marketing director of Cedrat Technologies S.A., covering AMA and electrical engineering activities. He has invented several patented devices such as piezoelectric, magnetostrictive and magnetic actuators, motors and sensors. Some such as the famous APAs are manufactured and successfully marketed by Cedrat Technologies S.A.

Brian Culshaw is professor of optoelectronics at the University of Strathclyde, where he has acted as head of department and as vice dean of the engineering faculty. His research, spanning over 30 years has encompassed microwaves, optics and ultrasonics, both at device and system level, with applications in communications and sensing. He has published seven research texts in microwave semi-conductors, fibre sensing and smart structures and over 400 journal and conference contributions including many invited. He has been active in professional societies including two periods as a director of SPIE, of which he is currently president elect and as an editor of Applied Optics. He is a founder director of OptoSci limited and of Solus Sensors. He has chaired numerous technical conferences in the UK and abroad in optical fibre sensors and smart structures

Danilo De Rossi received the Laurea degree in chemical engineering in 1976 from the University of Genova, Genova, Italy. From 1976 to 1981, he was a researcher with the Institute of Clinical Physiology of CNR. Since 1982, he has been with the School of Engineering, University of Pisa, Pisa, Italy, where presently he is a full professor of bioengineering. He has been president of the Biomedical Engineering Teaching Track of the University of Pisa. Since 1999, he has also been an adjunct professor of material science with Wollongong University, Wollongong, Australia. His scientific activities are related to the physics of organic and polymeric materials, and to the design of sensors and actuators for bioengineering and robotics. He is the author of over 150 technical and scientific publications, and is co-author of several books.

Frank Döngi was born in Worms, Germany in 1966. He studied aerospace engineering at Universität Stuttgart and at the Cranfield Institute of Technology, England, where he was awarded an engineering diploma in 1991 and M. Phil. in 1993, respectively. In 1996 he received his doctorate in engineering from the Universität Stuttgart for a dissertation on active flutter suppression by means of smart structures. He then joined Daimler-Benz Aerospace/Dornier Satellitensysteme GmbH as a structural mechanics engineer where he was responsible for smart structures and active structural

control. From 1999 to 2005, he was responsible for system design, engineering, and projects within Jena-Optronik GmbH, a company producing optoelectronic sensors and instruments for aerospace and defence applications in Jena. In January 2006, he joined EADS Astrium Satellites in Toulouse, France, where he is operations and process improvement manager within central engineering.

Göran Engdahl Doctor in Electricity in 1981, Uppsala University, Uppsala. Professor in electrotechnical design in 2001, Kungliga Tekniska Högskolan, Stockholm. Research field: theory, methods, and tools for design of electrotechnical systems and components based on data from material characterisations, and new phenomenological modelling algorithms with special interest in hysteresis and magnetoelastic phenomena in magnetic materials. Research interests: applied electro-mechanics and electromagnetism and modelling of electrotechnical components and systems comprising materials or phenomena involving functional, nonlinear or hysteretic behaviour. Publications: more than 70 international journals and conference publications.

Victor Giurgiutiu is professor of mechanical engineering and director of the Laboratory for Adaptive Materials and Smart Structures at the University of South Carolina, USA. He received his aeronautical PhD. (1977) and B.S. (1972) from the Imperial College, London, UK. In 1992–1996, he worked as research professor in the Center for Intelligent Materials Systems and Structures in Virginia Polytechnic Institute and State University, USA. From 1977 until 1992 he worked in the Aviation Research Institute, Bucharest, Romania. His research interests include adaptive materials and smart structures, structural health monitoring, mechatronics; embedded ultrasonic with piezoelectric wafer active sensors (pwaa); active biomedical sensors, integrated nano sensors. He serves as associate editor of the Journal of Structural Health Monitoring; he has been guest editor for several journals. Dr. Giurgiutiu is a fellow of the Royal Aeronautical Society and of the American Society of Mechanical Engineers.

Martin Gurka was born in Öhringen, Germany in 1967. He received his diploma in experimental physics from the Ruprecht-Karls-University of Heidelberg in 1994. From 1994 to 1998 he was research associate at the Institute of Applied Physical Chemistry at the University of Heidelberg, where he received his PhD in physical chemistry in 1998. From 1998 to 2000 he was project manager R&D in the automotive industry. Since September 2000 he has been the managing director of Neue Materialien Würzburg (NMW) GmbH, an R&D-Service-Provider in the field of multifunctional materials. NMW also manufactures custom made PZT-Composites for application as sensors or actuators in adaptive structures.

Wolfgang R. Habel, born in 1949, received the diploma degree from the Technical University of Ilmenau, and the doctoral degree in engineering from the Technical University of Berlin. Since 1984 he has been engaged in research and development on fibre optic sensors for monitoring of structures and characterization of materials. In 1997, he joined the Federal Institute for Materials Research and Testing (BAM), where he has been head of the research group for fibre optic sensors since 2003. His main research activities concern strain transfer of embedded and surface-applied fibre optic deformation sensors as well as reliability and validation aspects for their practical use. He is a member of several German and international societies, head of the study group 'fibre-optic measurement technology' within the German VDI/VDE Association, and author or co-author of numerous national and international invited publications.

Jürgen Hesselbach was born in Stuttgart in 1949. From 1968 to 1975 he studied mechanical engineering at the University of Stuttgart and received his PhD degree from the Institute of Control Engineering of Machine Tools in 1980. Afterwards he joined the department of 'Industrial Equipment' of the Robert Bosch Company. From 1990 to 1998 he headed the Institute of Production Automation and Handling Technology (IFH) at the Technical University (TU) of Braunschweig. Since 1998 he has been the head of the Institute of Machine Tools and Production Technology (IWF) which was incorporated with the IFH. The institute is researching robotics, microassembly, product and life cycle management, fine and wood machining, and new actuators. Besides the institute leadership he was elected for President of the TU Braunschweig in 2005.

Gerhard Hirsch[†] was born in Pogege, Lithuania, in 1924. He received his Engineering diploma from the Aachen University of Technology 1954. From 1954 to 1972 he was assistant and senior assistant lecturer. Lecturing and research work on structural dynamics and vibration control of lightweight structures were the basis for the senior lectureship that he held from 1972 onwards. He retired in 1996 and worked as a consultant for TMM Ltd., Eschweiler. G. Hirsch died in October 2003.

Hartmut Janocha was born in 1944 and studied electrical and mechanical engineering at the Technical University (today: Leibniz-University) in Hannover, Germany. In 1969 he graduated in the field of high-frequency technology, finished his doctorate in 1973 and his habilitation in 1979. Since 1989 he has been professor at Saarland University, where he holds the chair of the Laboratory of Process Automation (LPA). Between 1992 and 1994 he served as president of the German Assembly of Electrical Engineering Departments, between 1995 and 1997 as vice president of Saarland University, and between 2002 and 2004 as dean of the faculty of physics and mechatronics. His main

fields of work include unconventional actuators, 'intelligent' structures, new signal processing concepts, and machine or robot vision.

Klaus Kuhnen, born in 1967, received the Dipl.-Ing. degree in electrical engineering at the University of Saarland in 1994. Following graduation, he has been working there as a scientific collaborator at the Laboratory of Process Automation (LPA) in the fields of solid-state actuators and control of systems with hysteresis and creep. Since 2000 he has worked as scientific assistant at the LPA in the fields of self-sensing solid-state actuators, active vibration damping with active material systems and adaptive identification and compensation with convex constraints. He received the Dr.-Ing. degree in engineering sciences at the University of Saarland in 2001. His research interests are in mechatronic systems with active materials, and the control of systems with hysteresis and creep and adaptive control theory.

Ronan Le Letty was born in Pont l'Abbé, France in 1967. He graduated with an engineering degree from the Institut Supérieur d'Electronique et du Numérique (ISEN Lile) in 1990. He got his PhD from the Institut National des Sciences Appliquées (INSA Lyon) in 1994, working on modelling of piezoelectric motors. He has been with Cedrat Technologies since 1991, working on piezoelectric and magnetic actuators, and adaptronics applications, especially for the aerospace industry. He is now technical director in charge of production.

Hiroshi Matsuhisa was born in Osaka, Japan in 1947. He received his B.S. in mechanical engineering from Kyoto University in 1970, and his MS in industrial engineering from Georgia Institute of Technology 1972 and his doctoral degree from Kyoto University for the study of vibration and noise of train wheel in 1982. Since 1976 he has been an instructor, associate professor and professor at Kyoto University. His main fields of research are vibration control, noise control and human dynamics.

Dirk Mayer was born in 1973 in Bochum, Germany. He studied electrical engineering at Ruhr-Universität Bochum from 1993 to 1998. From 1998 to 2003 he worked as a research assistant at Otto-von-Guericke-Universität Magdeburg, Institute of Mechanics. The focus of his research work within several public funded and industrial projects was the active control of vibrations. In 2003, he received a doctoral degree at the Technische Universität Darmstadt for his thesis on the application of adaptive filters for identification and control of smart structures. Since 2003, he has been working at the Fraunhofer Institute for Structural Durability and System Reliability (LBF) in the mechatronics/adaptronics department, being concerned with research on system integration and control.

Alberto Mazzoldi[†] graduated in Chemical Engineering from the University of Pisa in 1993. From then to 1995 he worked on biosensors based on conducting polymers and enzymes. From 1995 to 1998 he performed his PhD studies in Bioengineering at University of Pisa, working on conducting polymer fibres as dry actuators. Following post-doctoral fellowship, from 2000 to 2005 he was a researcher at the school of engineering of the University of Pisa. His main scientific interests concerned sensors and actuators for biomedical and robotic applications. He has been author of several technical and scientific publications. He died prematurely in May 2006.

Tobias Melz was born in Hildesheim, Germany in 1968. He studied mechanical engineering at the Technical University Braunschweig and received his diploma in 1996. He then joined the Institute of Structural Mechanics at the German Aerospace Center (DLR) and was responsible for several R&D aerospace projects involving smart structures. He received his PhD at TU Darmstadt in 2001 for active vibration reduction of mechanical cryocoolers for small satellites, and joined the Fraunhofer Gesellschaft in the same year. Since then he has been leading a research department in smart structure technology at Fraunhofer LBF (Institute for Structural Durability and System Reliability) in Darmstadt which is directed by Prof. H. Hanselka. He is also the managing director of the Fraunhofer Alliance Adaptronics (FVA).

Jörg-Uwe Meyer received his engineering degree from the Applied Sciences University in Giessen, Germany, in 1981 and his PhD degree in Biomedical Engineering from the University of California, San Diego, USA, in 1988. He worked as a principal investigator at the NASA-Ames Research Center, Moffett Field, USA. In the years 1990–2002 he was heading the sensor systems and microsystems department at the Fraunhofer Institute for Biomedical Engineering, St. Ingbert, Germany. Since August 2002, he has been leading the research unit at the Draegerwerk AG, a human safety and medical device company (www.draeger.com). Jörg-Uwe Meyer is a member of the technical and natural science faculty at the University of Lübeck. His expertise is on biomedical and industrial sensors and on integrated systems at the acute point of care (APOC). He is a member of the board of directors of the German Biomedical Engineering Society (DGBMT).

Uwe Müller was born in 1975 in Neu-Ulm, Germany. From 1996–1998 he completed the first part of his mechanical engineering studies ('Vordiplom') at Universität Stuttgart. From 1998–2002 he completed the second part of his mechanical engineering studies ('Hauptdiplom') at Technische Universität München with a focus on the simulation of aerospace structures and materials. In 2000 he spent six months under the supervision of professor Nesbitt Haggood as a visiting student at the active materials and structures lab. (AMSL) at the Massachusetts Institute of Technology (MIT) in Cambridge, USA. Since receiving his degree in 2002 he has been working as a research assistant

under the supervision of Professor Horst Baier at the institute of lightweight structures at Technische Universität München. His areas of interest are smart structures, monitoring and sensor systems.

Werner Nachtigall, born 1934 in Saaz, studied biology and technical physics in Munich. After working as an assistant lecturer in the zoology and radiobiology departments of the Munich University and as research associate at the University of California, Berkeley, he was appointed director of the Zoology Department at the University of Saarland, Saarbrücken. His main fields of research were movement physiology and biomechanics. For several years he has offered a training in Technical Biology and Bionics. Combining biology and physics is an important subject of interest to him. He retired in 2002.

Dieter Neumann was born in 1955 in Gelnhausen, Germany. After finishing his studies in physics and sports he earned the degree of doctor at the University of Göttingen. He started his career in Göttingen at the Max-Planck-Institute for Fluid Mechanics. From 1991 to 1998 he worked as a technology consultant at the VDI Technology Centre and directed VDIs IT department in Düsseldorf (Germany). During the following years Dr. Neumann held several leading positions, being employed by major well-known IT-companies as area manager or divisional head. Since September 2005, Dr. Neumann has been Managing Director of Acteos GmbH in Gilching (Germany). Acteos provides solutions for implementing advanced mobile technologies to synchronize processes, material and information flow along the entire supply chain.

Raino Petricevic 1988–1995 study of physics at University of Würzburg and State University of NY at Buffalo; 1995 diploma; 2000 conferral of doctorate; project manager at the Bavarian Centre of Applied Energy Research. Working fields: material development for advanced energy storage technologies (fuel cells, super capacitors, lithium ion cells). Since 2000: project manager at Neue Materialien Würzburg GmbH. Working fields: development/processing of adaptive materials, composites and structures, unconventional piezo actuators and sensors, polymer actuators, functional material, electro-rheological fluids.

Helmut Seidel was born in Munich, Germany in 1954. He received his diploma in physics in 1980 from Ludwig-Maximilians-University in Munich and his PhD in 1986 from the Free University in Berlin, Germany. In 1980 he joined the Fraunhofer-Institute for Solid-State Technology in Munich, Germany as a research scientist. His research focuses on micro electro mechanical systems (MEMS) ever since that time. In 1986 he joined the aerospace company Messerschmitt-Bölkow-Blohm (MBB), which later became part of Daimler-Benz Corporate Research. In 1996 he joined Temic, managing the department for microsensor development. His main focus was on developing sensors for automotive applications, particularly airbag accelerometers,

gyroscopes and pressure sensors. In 2002 he became a full professor at Saarland University, Saarbrücken, Germany, holding the chair for micromechanics, microfluidics/microactuators. He has obtained more than 30 patents and has co-authored a large number of publications.

Thomas Stieglitz was born in Goslar, Germany, in 1965. He received the Dipl.-Ing. degree in electrical engineering from the University of Technology Karlsruhe (Germany) in 1993. From 1993 until 2004, he was with the Fraunhofer-Institute for Biomedical Engineering, St. Ingbert (Germany). He received a Dr.-Ing. degree (summa cum laude) in electrical engineering in 1998 and qualified as a university lecturer in 2002, both at the University of Saarland (Germany). In 2000 Dr. Stieglitz received the science award of the Saarland state for his work on flexible, neural prostheses. Since 2004 he has been a full professor of biomedical microtechnology in the department of microsystems technology (IMTEK), University of Freiburg. His research interests include biomedical microdevices, neural prostheses, neuromonitoring, and functional electrical stimulation.

Martin Thomaier was born in 1975 in Groß-Gerau, Germany. He gained his degree in mechanical and process engineering at Technische Universität Darmstadt in 2003. From 1992 until 1995 he did an industrial apprenticeship at Carl Schenck AG, Darmstadt as a technical drawer/mechanical engineer. Subsequently he worked as a technical drawer at Schenck PPSystems GmbH, Darmstadt. Until January 2004 he was a research assistant at the Fraunhofer-Institute for Structural Durability and System Reliability (LBF) in Darmstadt within the department of mechatronics/adaptronics. His work is focused on the design, simulation and development of active systems for vibration and noise reduction especially for automotive applications.

Neil White holds a personal chair in the school of electronics and computer science, University of Southampton. He has been active in sensor development since 1985. In 1988 he was awarded a PhD from the University of Southampton. He has considerable experience in the design and fabrication of a wide variety of sensors, formulation of novel thick-film sensing materials and intelligent sensor systems. Professor White is director and co-founder of the University of Southampton spin-out-company Perpetuum Ltd. He has over 200 publications in the area of instrumentation and advanced sensor technology. His professional qualifications include chartered engineer, fellow of the IET, fellow of the IOP, chartered physicist and senior member of the IEEE.

Thomas Würtz attended the Hochschule für Technik und Wirtschaft in Saarbrücken, Germany (Saarland University of Applied Sciences). Since 1993, at the Laboratory of Process Automation (Saarland University), he has been responsible for the area of power electronics for driving unconventional actuators. In addition to developing product lines mainly for driving piezo actu-

ators used in fuel injection, he has contributed, in some cases as task leader, to various multi-lateral research projects funded by the EU and the Federal Ministry of Education and Research. Also in these cases the focus was on the development of power electronics and signal processing, tailored to the technical problem and the selected actuator.