

Index

- 3D Microprobes, 146
- 3D-model synthesis, 56

- a-C, 91, 92, 99–102
- absolute accuracy, 272, 284
- aerostatic guide, 110
- Air Bearing Surface (ABS), 437
- air hammer effect, 110
- Al₂O₃, 113
- anodic bonding, 391
- artefact, 160, 161
- assembly process, 406
- assembly strategies, 351
- assembly system, 370
- AUTOBIN, 415
- automatic optical inspection (AOI), 416

- Ball Grid Array (BGA), 417
- batch processes, 331
- beam propagation method, 129
- beam splitter, 136
- bearing, 12, 13, 19, 21, 22
- bearing force, 110
- BICEP³S, 51
- bistable microvalve, 379
- bonding processes for microsystems, 331
- boreholes, 260
- borosilicate glass, 112
- boss membrane, 147
- buck converter, 32
- building blocks, 51, 55

- capacitive displacement sensor, 121
- centrifugal feeder, 289, 307
- Chemical-mechanical Polishing (CMP), 432
- clamping device, 289, 308

- closed-loop gap control, 111
- CMM, 151, 153
- coefficient of friction, 101–103
- CoFe, 173, 175, 176, 186
- coil, 12, 14, 16, 17, 20–22, 26, 27
- collimator, 135
- Computational Fluid Dynamics, 113
- Computed Torque Feed Forward, 284
- construction kit, 302, 305
- contact area, 156
- copper losses, 26
- CVD coated grinding pins, 260
- CVD coated grinding wheels, 247

- dead volume, 111
- desktop factories, 399
- DFB laser diode, 137
- diffraction simulation, 62
- digital control, 111
- dimensional standards, 160
- displacement sensors, 111
- DLC, 75–84, 86, 98, 101, 438
- drive systems, 29
- dry lubricating film, 90–92, 101, 104
- dual-stage actuators (DSA), 427

- Eagle2000, 129
- ED-resist, 213
- eddy current, 25, 26
- efficiency, 32, 33, 37
- electro contact discharge dressing (ECDD), 252
- electro-depositable photoresist, 190, 193, 203
- electro-depositable resist, 205
- electromagnetic guide, 118

- electroplating, 169–171, 174–176, 181, 182, 186
- fast process cycles, 332
- Finite Element Method, 13
- flexibility, 398
- force, 12–15, 18–20, 22–25
- FOTURAN, 300, 306
- friction, 71, 74, 76, 86
- friction force, 100–106
- field-programmable array (FPGA), 139
- flow resistance, 110
- flying height, 441
- gas flow sputtering, 186
- GRIN lens, 136
- gripper, 353
 - active heat management, 363
 - passive heat management, 359
- guidance, 12, 13, 19, 25
- Hard Disk Drives (HDD), 427
- hard magnetic materials, 167, 168, 179, 181, 183
- Harmonic Drive, 280
- head gimbal assembly, 439
- heat management, 354
 - active, 354, 362
 - passive, 354, 356
- helical coil, 189, 190, 198, 203–205, 215
- High Aspect Ratio Micro Structure Technology (HARMST), 191, 205, 226, 237, 432
- HMA film processing, 337
- HMA particles processing, 337
- hot melt adhesives (HMA), 331
- hybrid step motor, 11, 17, 18, 225, 227
- hybrid-bonding, 335
- In-Circuit Test (ICT), 416
- incremental sensor, 128
- indentation hardness, 157
- indentation measurements, 155
- indentation modulus, 156
- infusion pump, 380
- inspection
 - photogrammetric sensor, 312
- InterVia 3D-N, 216
- inverse dynamic model, 284
- joining technologies, 351
- kinematic synthesis, 271
- LabVIEW, 138
- laser, 132
- Laser Doppler Vibrometer (LDV), 440
- laser micromachining, 301
- laser tracker, 283
- linear series regulator, 31
- linear stepper motor, 209
- look-&-move, 277, 326
- low process temperatures, 331
- magnetic anisotropy, 13
- magnetic flux, 189, 190, 201
- magnetic material, 11–13, 21
- meander coil, 189, 190, 198, 199, 201–205, 212
- metal bonded grinding pins, 261
- metal bonded grinding wheels, 252
- Micabo F2
 - photogrammetric sensor, 313
 - robot, 273
- micro adhesive bonding, 331
- Micro Electro-mechanical System (MEMS), 427
- micro force sensor, 95
- Micro Harmonic Drive, 280, 401
- microactuator, 369, 427
- microassembly, 369, 406
 - automated, 370
 - challenges, 406
 - inspection, 312
 - look-&-move, 277, 326
 - photogrammetric sensor, 312
 - requirements, 370
 - sensor-guided assembly, 312
- microcoil, 196, 197, 205
- microendoscopes, 419
- microfriction, 89, 94
- microgears, 401
- microgrinding, 246
- microgrinding pins, 260
- microgripper, 289, 299
- microguide, 90, 91, 93, 97, 101
- microlens array, 141
- micromotor, 225, 370
- micronozzles, 112
- micropattern, 89, 90, 92, 101–103, 106
- microstructure, 99, 100
- microtribology, 69, 70, 77
- miniaturized machine components, 401
- miniaturized robot, 277, 403
- modified sliding mode controller, 42
- modular software environment, 51
- multiple direction accuracy, 272, 282
- NiFe45/55, 168, 173–176, 186, 229, 236

- NiFe81/19, 168, 173–175, 178, 226, 228
- nozzle, 110
- optical coupler, 129
- optical grating, 134, 135
- optical interferometer, 127
- parallel robot structure, 278
- Parvus robot, 280, 281
- path accuracy, 272, 283
- pattern projection, 422
- PECVD, 78
- permanent magnet, 11, 16–22
- permeability, 13, 23, 24, 27
- phase of preliminary design, 51
- photo detector, 137
- photogrammetric sensor, 311
 - calibration, 323
 - illumination, 318
 - imaging, 314
 - microassembly, 312
 - mirror optics, 314
 - prism module, 316
- photogrammetry
 - camera model, 322
 - epipolar association, 324
 - evaluation, 322
 - part localization, 325
 - signalization, 318
- PID control, 117
- piezoresistive elements, 149
- piezoresistors, 149
- planar waveguide, 129
- Plasma Enhanced Chemical Vapor Deposition (PECVD), 432
- pneumatic, 289, 299, 303, 307, 308
- pocket bearing, 110
- polymer magnet, 219
- polymer magnet rotor, 222
- position control, 40
- pre-deflected membrane, 386, 390
- probing forces, 157
- probing repeatability, 151
- process chain, 407
- process sequence synthesis, 58
- process variants
 - active heat management, 356, 363
- PVD, 69, 77, 78
- pyrex glass, 389, 390
- Q-Model, 51
- quadrant photo diode, 137
- reactive hot melts, 335
- refractive index modification, 129
- relative permeability, 168, 172, 174, 177, 178, 185
- relative position, 275
- relative positioning, 273
- repeatability, 272, 279, 282
- resist
 - fluorescent, 321
- robot design, 278
- rotating stepper motor, 215
- rotor, 217
- saturation flux density, 168, 172, 174, 175, 178, 186
- SC DC-DC converter, 33
- SCARA, 278
- Schönflies, 269, 278
- scratch test, 72, 80
- second stage actuation, 427
- sensitivity analysis, 271, 278
- serial robot structure, 278
- shape memory alloy, 300, 307, 382, 384, 389
- shielding electrodes, 122
- Si_3N_4 , 189, 197, 201, 205
- signalization, 318
 - by circular marks, 319
 - by fluorescent features, 320
 - by polygons, 318
 - by scattering features, 319
- silicon, 388–390
- silicon direct bonding, 391
- silicon on insulator, 302
- simulation, 13, 23, 27
- size-adapted robot, 272
- Slider with an Integrated Microactuator (SLIM), 428
- Sliding Mode Controller, 41
- soft magnetic materials, 167, 168, 171, 173, 174, 178
- speckle reduction, 424
- spiral coil, 189, 190, 198–202, 205
- state control, 117
- stepping mode, 39
- stick-slip, 93, 100, 103, 105, 106
- stiffness of membrane, 153
- SU-8, 189, 190, 194–198, 202–205, 236
 - fluorescent, 321
- synchronous micromotor, 225, 230
- synchronous motor, 11, 16, 17, 20–22, 219
- system identification, 44
- system integration, 436

- thermal expansion, 289, 304
- thinning-by-dicing, 436
- tip rounding, 155
- tolerance analysis, 56
- tool development, 248
- torque, 14, 18, 21
- track following, 429
- transmission error, 283
- tungsten thin film, 382

- ultrasonic assisted holegrinding, 261
- UV adhesive, 127
- UV depth lithography, 201, 202, 432

- variable reluctance micromotor, 225, 226
- variable reluctance step motor, 11, 15–19, 22, 24–26

- waveguide coupler, 128
- waveguide writing, 129
- wear, 69, 70, 72–76, 79, 82, 84–86
- wet-etch simulation, 60
- workspace, 281

- X-ray inspection, 419
- xy-microactuator, 225, 234, 369