

# Index

## A

Aberration-corrected STEM, 380–381, 383  
Abnormal bone mineralization, 8  
Advanced atomic analysis at atomic scale bonding mapping, 396–399  
     $\text{Ca}_2\text{FeCoO}_5$ , coordination state, 398–399  
    multiwalled C nanotube, 396–397  
    oxidation state in  $\text{Mn}_3\text{O}_4$ , 397–398  
Algebraic reconstruction technique (ART)  
    HAADF-STEM, 627  
    reconstruction algorithms, 627  
    volume reconstructions, TEM tomography, 628  
Analytical 3D-TEM  
    Co/TiO<sub>2</sub>-SiC catalyst, 652–653  
    nitrogen-doped carbon nanotubes, 649–652  
    validation, methodology, 647–649  
Analytical mode, STEM/TEM  
    EDXS, 339–341  
    EELS, 341–342  
Analytical tomography  
    EFTEM mode, 629  
    filtered images, acquisition, 630  
    limiting factors, 624  
    low signal to noise ratio, 624  
    multi-scattering effect, 624  
    residual diffraction contrast, 624  
    resolution, 632  
    technical difficulties, 624  
Anisotropic soft-X-ray emission  
    graphite and hexagonal BN, 317  
    intensity distributions, 319–320  
    K-emission spectra, BN, 320, 321  
    schematic diagram, emission intensity, 317–318  
    single-crystalline graphite, 318–319  
Annular bright field (ABF) imaging, 376, 386–389

Annular dark field (ADF) imaging technique  
    coherence effects, 387  
    3D electron microscopy, nanosciences, 623  
    grain boundary regions, 388  
    images of projected YH<sub>2</sub> structure, 388–389  
    interfacial misfit dislocations, 389, 390  
    set up, 384, 386  
    SrTiO<sub>3</sub>, 386–387  
Aragonite platelets, 10  
AS1411, 32, 33  
Atomic force microscope (AFM), 141, 161, 197, 244, 684, 687  
Atomic resolution, nanostructures  
    effects, 125  
    electro-optical design, 126  
    K-edges, of GaAs, 126, 127  
    L-edges, of GaAs, 126, 128  
    localization distance, 126, 127  
Atom probe tomography (APT)  
    composition analyses, 481, 482  
    thermoelectric nanomaterials, 431–434  
Au@Cu<sub>2</sub>O nanoparticles  
    HAADF approach, 260–261  
    HRTEM imaging, 267–268  
Au distribution in Si and GaAs  
    catalytic contamination, 401  
    diffusion, 399–400  
    interstitials, 399–400  
    twin boundary, 401

## B

Backscattered electron image, CZTS, 74, 75  
Bacterial flagella templates, 19, 21  
Bacteriophage templates, 17–19  
Ball models, CZTS, 63, 64  
Band gap  
    PbTe, 468  
    strain engineering, 676  
    thin film photovoltaic materials, 45  
    variations, 673

- Bimetallic core-shell and alloy nanoparticles, 252, 254–255
- Bio-inorganic nanocomposites, 2
- externally introduced inorganic nanoparticles, 27, 31–34
  - naturally occurring bio-inorganic nanocomposites, 6–12
  - negative staining, 5
  - positive staining, 4–5
  - synthetic inorganic nanomaterials, 13–19, 21–27
  - ultramicrotome, 3–4
- Biotemplates, 2, 13, 21–27, 35
- Boron
- allotropes, 301
  - crystal structure, rhombohedral B, 302
  - DOS, 304–305
  - intensity comparison, 303
  - metal hexaboride  $MB_6$  structure, 304, 306
  - rhombohedral crystal structure, 302
  - spectrum of rhombohedral B, 302–303
  - structure of metal hexaboride  $MB_6$ , 304, 306
- Boron@boron oxides nanowires, elemental mapping
- EELS spectrum, 272–273
  - spatial distribution of boron and oxygen, 273–274
- Bound rubber, 141, 145, 146, 158, 171, 172
- Brick-and-mortar-assembled structure, 10
- Bright field (BF) imaging, 92, 97, 98, 108. *See also* Dark field (DF) imaging
- Bright-field transmission electron microscopy (BF-TEM)
- biological applications, 623
  - images, 338, 352
- C**
- Cadmium telluride (CdTe)
- chlorine activation, 52
  - Joule heating, 227, 228
  - planar defects, 53, 54
  - sphalerite structure, 53, 55
  - sulfur diffusion, 54–55
  - superstrate CdS/CdTe cell, 52, 53
- Calcium carbonate-based bio-inorganic nanocomposites
- aragonite platelets, 10
  - sea urchin spine, 10–11
- Carbon
- 1D-, 2D-, 3D- $C_{60}$ , 308–309
  - $\pi^*$ -resonance excitation, 310
  - single-crystalline diamond, graphite, and fcc monomer- $C_{60}$ , 307–308
  - types of structures, 306–307
- Carbon black network structure
- carbon black-filled NR compounds, 145–146
  - CB aggregate distance, 146, 148
  - 3D-TEM images, 146, 147
  - fractions of cross-linked, branched and isolated chains, 149–151
  - nanofiller aggregate network, 149, 150
  - skeletonized network structure, 147, 149
  - volume resistivity, 146–148
- Carbon black/rubber interaction layer visualization
- AFM phase image, 161, 162
  - coefficient of thermal expansion, 167
  - 3D images, 163
  - storage modulus, 164–166
  - volume fractions, 164
  - volume ratios, 164, 165
- Carbon K-emission spectra
- 1D-, 2D-, 3D- $C_{60}$ , 308–309
  - diamond, graphite, and fcc monomer- $C_{60}$ , 307–308
  - $\pi^*$ -resonance excitation, 310
  - types of structures, 306–307
- Catalytic nanomaterials. *See* Metallic nanocatalysts
- Cathodoluminescence (CL)
- description, 44
  - inorganic solar cells, 72–75
- $^{13}C$  CP MAS NMR spectra, PK/PA polymer alloy, 184, 185
- CdTe-and Cu(In,Ga)Se<sub>2</sub> (CIGS), 48
- CIGS/Mo interface, 56, 58
  - CL spectra, 59, 61–62
  - grain boundary distribution, 59, 61
  - grain size, 57, 60
  - sodium in, 62, 63
  - three-stage evaporation process, 57, 59
- Ceramic matrix nanocomposites (CMNC), 335. *See also* Titanium nitride (TiN)
- Chaperonin, 22
- Charge coupled device (CCD), 100, 101
- Charge transfer (CT) state, 50, 51
- Chemical analysis at atomic scale
- $Bi_{0.5}Sr_{0.5}MnO_3$  structure, 393–394
  - cations distribution in  $Ba_{0.03}Sr_{0.97}TiO_3$ , 393, 396
  - C nanotubes with La and Er inclusions, 394, 396
  - $SrTiO_3/LaVO_3$  multilayer system, 393, 395

- Chemical analysis techniques, 44
- Chemical solution deposition (CSD) route,  
oxide epitaxial films  
LSMO thin films, 541–542  
MOD solution synthesis, 541  
thickness dependence, 542
- Clusters, semiconductor nanomaterials  
anatase TiO<sub>2</sub> nanorod, 122  
CdTe tetrapod, 119, 120  
coherent electron diffraction imaging,  
121–123  
multiple-twinning model, 121  
nano-diffraction pattern, 124  
phase-retrieved diffractive image, 124–125  
Shannon's theorem, 123
- Coefficient of thermal expansion (CTE), 167
- Cold welding, 229–231
- Collagen–apatite bio-inorganic  
nanocomposites., 6–8
- Column-to-column compositional  
quantification, III–V semiconductors  
HAADF-STEM image, ZnO  
nanowires, 663  
InAs<sub>x</sub>P<sub>1-x</sub>/InP interface, HAADF, 661–662  
integrated intensities, 662–663  
limitations, 660  
MBE, 661  
segregation and interdiffusion, 660  
Z-contrast imaging, 661
- Convergent beam electron diffraction  
(CBED), 100  
LACBED, 117–118  
whole pattern, 116–118
- Core-multishell semiconductor nanowires,  
elemental mapping, 274–275
- Core-shell Al<sub>x</sub>Ga<sub>1-x</sub>N/GaN nanowires  
diffusion, 681–682  
EDS profiles, 679–680  
HAADF-STEM image, 677  
HRTEM image, 679  
morphology and composition distribution,  
680–681  
thickness profiles, 678
- Core-shell nanomaterials  
classes of, 245–246  
diffraction contrast imaging, 248–252, 254,  
255, 260  
elemental mapping, 270–275  
HAADF approach, 260–266  
HRTEM imaging, 267–272  
statistical data analysis, 244–245  
synthesis of, 246–247  
TEM technique, 247–248
- Coster-Kronig transition, 290, 296, 311, 313
- Co/TiO<sub>2</sub>-SiC catalyst analytical 3D-TEM,  
652–653
- Cryo-TEM examination, negatively stained  
collagen fibril, 7
- Curing  
compounding recipes, 154, 155  
3D-TEM images, 157–159  
elongation ratio, 161, 162  
image analysis technique, 158  
interparticle distance determination, 158  
network images, 160, 161  
residual elongation ratios, 156  
two-step curing process, 155–156  
volume resistivity vs. residual elongation  
ratios, 156
- Cu<sub>2</sub>ZnSn(S,Se)<sub>4</sub> (CZTS), 49  
ball models, 63, 64  
IBM hydrazine solution route, 65, 67  
phase decomposition, 64, 66  
STEM-EELS analysis, 63–65
- D**
- Dark field (DF) imaging, 97, 111. *See also*  
Bright field (BF) imaging
- Data treatment procedure  
EELS spectrum, 631  
preprocessing steps, 630  
skin calculation, 632  
Zero Loss tilt series, 631
- Deformation twinning, 10
- 1D filamentous biological templates  
bacteriophage templates, 17  
tobacco mosaic virus templates, 14, 16–17
- 3D electron microscopy, nanosciences  
analytical 3D-TEM, 647–653  
analytical tomography, 624, 629,  
630, 632  
annular dark field imaging, 623  
artifacts, tomography requirements,  
625–626  
artificial nanomaterials, 621  
bright-field transmission electron  
microscopy, 623  
data treatment procedure, 630–632  
definition, 619–620  
2D intensity distribution, 621–622  
3D voxel matrix, 622  
electron tomography, 621  
energy-filtered TEM, 623–624  
faceted nanoparticles, 639–643  
long-range ordering, 643–646

- 3D electron microscopy, nanosciences (*cont.*)  
low-resolution electron tomography, 623  
overview of, 620  
quantitative 3D-TEM, 634–646  
radon projection, 622  
reconstruction algorithms, 626–627  
reconstructions, combined analysis, 647  
short review, previous works, 633–634  
STEM-HAADF tomography, 623  
TEM tomography, 627–628  
Z-contrast tomography, 628–629
- Density functional theory (DFT), 106, 119
- Diatoms, 12
- Diffraction contrast imaging, core-shell  
nanomaterials  
bimetallic nanoparticles, 252, 254–255  
hollow core-shell nanomaterials,  
254–260  
silica coatings, 248–252
- Dipole transition, 289, 294, 302
- Donolato's EBIC method, 72
- Double-display phage system, 19
- Double Schottky barrier, 68
- E**
- EELS  
advanced atomic analysis at atomic scale,  
396–399  
advantages, 393  
chemical analysis at atomic scale,  
393–396  
electronic structure and electronic  
transitions, schematic drawing of,  
288–289  
energy-dispersive X-ray spectroscopy  
(EDS), 291  
inner-shell electron excitation, 289  
photoelectron emission spectroscopy  
(PES), 290  
valence electron excitation, 288–289  
wavelength-dispersive X-ray spectroscopy  
(WDS), 291
- EELS and SXES spectrum  
Al, 322, 323  
BN, 322, 324  
Mg, 321–322
- Electrical conductivity/Seebeck, TE coefficient  
measurements, 443–444
- Electron diffraction, semiconductor  
nanomaterials  
experiments, 92–93, 100  
symmetries in, 116–111
- Electrical pulsing, nanowires, 224–227
- Electrochemistry, in situ TEM  
charging-discharging effects, 232  
SnO<sub>2</sub>, 232–234
- Electron-beam-induced current (EBIC)  
method, 72
- Electron coherent diffraction imaging (EDI),  
100, 122–125, 133
- Electron energy-loss magnetic chiral dichroism  
(EMCD), 128–129, 131
- Electron energy-loss near edge structure  
(ELNES), 129, 131
- Electron energy-loss spectroscopy (EELS)  
advanced atomic analysis at atomic scale,  
396–399  
advantages, 393  
atomic resolution, nanostructures,  
125–128  
chemical analysis at atomic scale,  
393–396  
electronic structure and transitions,  
288–289  
energy-dispersive X-ray spectroscopy  
(EDS), 291  
inner-shell electron excitation, 289  
photoelectron emission spectroscopy  
(PES), 290  
PK/PA polymer alloy, 181–182  
semiconductor nanomaterials, 101–103  
valence electron excitation, 288–289  
wavelength-dispersive X-ray spectroscopy  
(WDS), 291
- Elemental mapping, 270–271  
boron@boron oxides nanowires,  
272–274  
core-multishell semiconductor nanowires,  
274–275
- Energy crisis and energy conversion efficiency,  
TE nanomaterials  
examples, 435  
nuclear energy, 436  
recycling lost waste heat, 433, 436  
renewable energy, 434–435  
significance and scale, 434
- Energy dispersive X-ray spectroscopy  
(EDXS)  
effects, 125  
electro-optical design, 126  
K-edges, of GaAs, 126, 127  
semiconductor nanomaterials experiments,  
100–101
- Energy-filtered TEM (EFTEM) mode, 102,  
623–624, 629

- Energy-loss magnetic chiral dichroism, 131, 132
- Experimental and instrumental methodology, TE
- APT, 445
  - electrical conductivity/Seebeck, 443–444
  - SEM, 444
  - synthesis, 443
  - TEM, 444–445
  - thermal conductivity, 444
  - X-ray diffraction, 443
- Ex situ TEM techniques, nanowires and nanorods
- Co<sub>3</sub>O<sub>4</sub>, 201–203
  - copper nanowires, CuPd and CuPt, 204–205
  - hollow nanowires, 202
  - Kirkendall effect, 205–208
  - oriented attachment, 212–216
  - PbS, 199–200
  - structural defects, in silicon nanowires, 208–212
  - TiO<sub>2</sub>, 202
  - vapor–liquid–solid mechanism, 199
  - zinc, 201
- Extension for higher-energy region
- drawback, 327
  - energy dispersion, 324
  - indium–tin–oxide, 325–326
  - KNbO<sub>3</sub>, 325–326
  - multilayer-coated grating, 325
- Externally introduced inorganic nanoparticles
- biodegradation behavior, 27–31, 33
  - cell internalization, 32–34
- F**
- Faceted nanoparticles, quantitative 3D-TEM
- CeO<sub>2</sub> nanoparticles, 639–641
  - modeling, 640, 642–643
  - molecular dynamics-assisted shape
- False-color crystal-phase amplitude maps, 115, 116
- Fermi edge, 294–296
- Figure of merit (ZT). *See* ZT
- Fill factor (FF), 46
- Finite element analysis, 664
- Fischer–Tropsch (FT) synthesis, 591, 593
- Fish scale, 8, 9
- Flagella, 14, 19–21
- Focused ion beam (FIB) milling, 95
- Fresnel contrast method, 76–77
- G**
- Gas reaction, E-TEM
- column, 606–607
  - CoO<sub>x</sub>/SiO<sub>2</sub> nanocomposite system, 604, 608
- Geometric phase analysis (GPA)
- Bragg peaks, 431
  - displacement measurement, 429–430
  - fast Fourier transformation, 429
  - HRTEM, 428–429
  - image processing, 429
  - mean dilatation, 430
  - quantitative method, 431
  - rotation, 430
  - strain tensor, 430
- Grain boundaries
- ab initio simulations, 71
  - band bending profile, 69
  - electronic band structure, 67, 68
  - luminescence spectrum, 70
  - Na diffusion, 70
  - numerical simulations, 69
- H**
- Head-to-head approach, cold welding, 229, 231
- Heating of nanowires and in situ TEM
- electrical pulsing, 224–227
  - electron beam, 224, 225
  - Joule heating, 227
- Heat treatment, carbon black
- characteristics, 154
  - cross-linked point densities, 153
  - 3D-TEM images, 152–153
- Heteroepitaxial systems, strain field maps
- simulation by FEM, 664
- High-angle annular dark-field (HAADF) imaging
- Au@Ag, 261–262
  - Au@Cu<sub>2</sub>O nanoparticles, 260–261
  - dealloyed Pt–Ni, 264, 265
  - 3D electron microscopy, nanosciences, 623
  - drawbacks, 385
  - heterostructure interfaces, 384–386
  - Pd@Au and Au@Pd, 263–264
  - Pt@Ag particles, 264, 266
  - semiconductor nanomaterials, 98–99
  - set up, 383, 384
  - uncorrected vs. aberration-corrected systems, 384, 385
- High energy-resolution EELS. *See* Electron energy-loss spectroscopy (EELS)

- High-resolution transmission electron microscopy (HRTEM) imaging, 428  
 Au@Cu<sub>2</sub>O nanoparticles, 267–268  
 core-shell Al<sub>x</sub>Ga<sub>1-x</sub>N/GaN nanowires, 679  
 dumbbell identification, 404  
 geometric phase analysis, 428–429  
 LAST(T), 505–509  
 nanorods, ZnO growth on Si (111) using three step method, 670  
 PbTe/CdTe core-shell nanoparticles, 268–270  
 PbTe/CdTe nanoparticles, 268–270  
 PbTe, doped, 446, 448–450  
 PbTe + XTe, 458  
 polarity assignment, semiconductor nanowires, 404  
 Pt@Pd core-shell nanoparticles, 270, 272  
 Pt@Pd nanoparticles, 270, 272  
 semiconductor nanomaterials imaging experiments, 98  
 strain mapping, 543–545  
 TiN-Ag nanocomposites, 352  
 ZnSe/GaAs heterostructure, 109  
 Zn/ZnO core-shell nanobelts, 269–271  
 Zn/ZnO nanobelts, 269–271
- Hollow core-shell nanomaterials  
 $\alpha$ Fe<sub>2</sub>O<sub>3</sub>/SiO<sub>2</sub> nanotemplates, 259–260  
 formation process of V<sub>2</sub>O<sub>3</sub>-SnO<sub>2</sub> composite, 258  
 monodisperse latex and silica spheres, 254  
 Ostwald ripening processes, 256–257  
 rattle-type carbon-alumina particle formation, 258  
 V<sub>2</sub>O<sub>3</sub>-SnO<sub>2</sub> double-shelled nanocapsules, 255–256
- Hydrophilic silica VN-3, 168  
 Hydroxyapatite–collagen nanocomposites, in bone and fish scales, 6–8
- I**  
 Impact resistance, 142, 143, 189  
 In-line holography, 76–77  
 Inorganic solar cells  
 CIGS devices, 48–49  
 grain boundaries, 67–71  
 material issues in, 52, 55, 56, 62, 63, 66  
 recombination velocity, 72–75
- In situ environmental TEM (E-TEM) study  
 gas reaction, 601–602, 604, 607–609  
 liquid reaction, 609–612
- In situ TEM techniques, heating nanowires  
 electrical pulsing, 224–227  
 electron beam, 224
- In situ TEM techniques, nanowires  
 electrochemistry, 232–234  
 elemental analysis, Si-Ge heterojunction, 220  
 mechanical and electrical characterization, 228–232  
 nucleation, 221  
 oriented attachment growth, 221–222  
 video imaging, 217–218  
 VLS and VSS growth mechanisms, 216–218
- InAs<sub>x</sub>P<sub>1-x</sub> quantum wires deposition  
 nucleation and evolution, 683–693  
 spatial distribution and size homogeneity, 683  
 Stranski-Krastanov (SK) mode, 683  
 stress field, 682
- Iron oxide nanoparticles (IONPs), 28–30
- J**  
 Joule heating, nanowires, 227, 228
- K**  
 K-emission  
 beryllium, 295–296  
 boron, 301–306  
 carbon, 306–310  
 lithium, 294–296
- Keyhole coherent electron diffraction imaging (KEDI), 125
- Kirkendall effect  
 CeO<sub>2</sub> nanotubes, 206–207  
 Cr<sub>2</sub>Te<sub>4</sub>O<sub>11</sub>, 207  
 description, 205  
 Sn-SnO<sub>2</sub> nanotubes, 205, 206  
 Te nanowires, 207–209  
 ZnAl<sub>2</sub>O<sub>4</sub>, 208, 210
- L**  
 Large angle convergent beam electron diffraction (LACBED) pattern, 117–118  
 Laser ablation, 200

- LAST(T), TE nanomaterials  
Ag–Sb-rich chains, 505–508  
DP, 505–509  
HRTEM images, 505–509  
 $\kappa$  lowering, 508  
microstructural base, 501  
microstructures, 510, 512, 513  
temperature dependence, 510–512  
XRD patterns, 504  
ZT, 504
- L-emission  
Co, 311–312  
Mg and Al, 296–297  
Mn, 311  
radiative electronic transition,  
299–300  
Ti, 312–313  
 $\text{TiSi}_2$ , 300–301
- Liquid reaction, E-TEM  
carbon foils and graphene sheets, 609  
3D view, 609, 610  
growth,  $\text{Pt}_3\text{Fe}$  nanowires, 610, 612  
time sequence, 610, 611
- Load-displacement curve, 184, 185
- Local-electrode atom-probe (LEAP)  
tomograph, 432, 433
- Long-range ordering, quantitative  
3D-TEM  
3D meta-crystals, 643–645  
stacking faults, periodically ordered  
mesoporous material, 645–646
- M**
- Manganites. *See* Nanocomposite oxide  
thin films
- Maryna umbrellata*, 11–12
- Material issues  
CdTe, 52–55  
CIGS, 56–62  
CZTS, 63–66
- M-emission  
Cu, 298  
Gd, Tb, Dy, Ho, Er, Tm and Yb compounds,  
314, 316  
integrated intensity ratio, 316, 318  
La, Ce, Pr, Nd, Sm and Eu compounds,  
314–315  
schematic level drawing with decay  
processes, 315, 317
- Mesoporous silica nanoparticles (MSNPs),  
27–28
- Metallic nanocatalysts  
definition, 577–578  
EELS and EDS, spectroscopy, 580–581  
electron beam effect, 581  
elemental distribution, STEM techniques,  
594–600, 602, 603  
ex situ characterization, 579  
industrial applications, 579  
nanodiffraction and CBED, 581  
overview of, 578  
phase, 583–585  
shape, 587–594  
in situ environmental TEM study, 601, 602,  
604, 606, 609, 613  
size distribution, 582  
STEM-SEM, 604, 605  
strategy, 579  
structural and chemical characterization, 582  
surface defects, 586–588  
TEM and STEM, imaging, 580
- Metallic nanocatalysts elemental distribution  
in STEM/TEM  
core–shell noble catalysts, 594–595, 598  
Fe distribution, 596–597, 600  
 $\text{Pt}_3\text{Co}$  electrocatalyst, 599, 602  
signal-to-noise ratio, 595  
STEM-EELS, 599, 603
- Metal matrix nanocomposites (MMNC), 336
- Metal-organic chemical vapor deposition  
(MOCVD), 274, 676
- Microstructural evolution tracking  
annealing, 549–550  
LSMO films, topographic images, 548  
SFM topographic images, 547, 549
- Microstructure and nucleation control  
CSD-derived pyrolyzed film, 545  
kinetic point of view, 546  
temperature, 546
- Middle-angle bright field (MABF),  
389–391
- Misfit strain relaxation, film thickness  
effect  
density of dislocations, 560  
displacement, 560  
LSMO composite film, 558  
plastic dislocation, 560–563  
thickness dependence, 557–558
- Molecular beam epitaxy (MBE), 94,  
107, 129
- Multiple order twinning polarity driven  
growth, GaAs on Si, 410–415
- Multiple twinning (MT), 588

**N**

- Nacre, 8
- Nanocomposite materials  
 classification, 335  
 CMNC, 335 (*see also* Titanium nitride (TiN))  
 MMNC, 336  
 PMNC, 336, 356–363  
 schematic diagram, distribution-dispersion relation, 334–335  
 TEM/STEM methods, 336–339, 342–346
- Nanocomposite oxide thin films  
 colossal magnetoresistance manganites, 539–540  
 definition, 538  
 fabricate approach, 539  
 GPA and HRTEM, strain mapping, 543–545  
 La excess content accommodation, 564–568  
 microstructural transformation, 540–541  
 oxide epitaxial films, chemical solution deposition route, 541–542  
 spontaneous phase separation, 545–564  
 TEM, 543–545
- Nano-diffraction pattern (n-DP), 100, 123, 124
- Nanofiller filled rubber vulcanizate, 140, 145
- Nanofiller network structure, 140, 143
- Nanoparticles  
 Au@Cu<sub>2</sub>O, 260, 261, 267, 268  
 bimetallic core-shell and alloy, 252, 254–255  
 PbTe/CdTe, HRTEM imaging, 268–270  
 Pt@Pd core-shell, HRTEM imaging, 270, 272
- Nanoparticles, 3D localization  
 functionalities, 635  
 nanoparticles localization, curved surface, 637–639  
 nanoparticles spatial distribution, 635  
 nano-wire Au/Si, 638, 639  
 palladium particles, carbon nanotube, 636, 637  
 particles scattered, plane surface, 636–637  
 P3HT–CdSe hybrid film, 638
- Nanorods. *See also* Nanowires and nanorods  
 CBD methods, 669  
 high VPT temperature effect on, 673, 674, 676  
 using three step method, 670–672
- Nanostructured semiconductors. *See* Semiconductor nanomaterials
- 1D-Nanostructures  
 applications, 659  
 III-V semiconductors, 660–663
- InAs<sub>x</sub>P<sub>1-x</sub> quantum wires deposition, MBE on InP, 682, 683, 693  
 strain field maps simulation, heteroepitaxial systems by FEM, 664  
 ternary III-N grown by catalyst-free PAMBE, 677–682  
 ZnO nanorods growth, Si (111), 669–676  
 ZnO nanowires growth, CdTe (111), 664–669
- Nanowires  
 boron@boron oxides, elemental mapping, 272–274  
 core-shell Al<sub>x</sub>Ga<sub>1-x</sub>N/GaN, 677–682  
 ZnO growth, CdTe (111), 664–669
- Nanowires and nanorods  
 ex situ TEM techniques, 199–205, 208, 212, 216  
 HAADF imaging, 198  
 in situ TEM techniques, 216–218, 220–222, 224–234
- Naturally occurring bio-inorganic nanocomposites  
 calcium carbonate, 10–11  
 hydroxyapatite–collagen, 6–8  
 silica, 11–12
- Negative staining, 5, 14, 26
- NISSAN ARC-AK method, 144
- Nitrogen-doped carbon nanotubes, analytical 3D-TEM, 649–652
- O**
- Optical transparent polymers, 142
- Organic bulk heterojunction solar cells  
 bright-field electron tomography, 79, 80  
 charge transfer state, 50  
 mean electron energy loss spectrum, 80, 81  
 operating principles, 50  
 principal component analysis, 80  
 thermal annealing, 51
- Oriented aggregation, nanowire  
 CdS nanowires, 213–214  
 growth mechanism, 212  
 pearl chain structures, 213  
 Sb<sub>2</sub>O<sub>3</sub> coaxial nanowires, 215–216  
 silver sulfide, 214–215
- Osteoporosis, 8
- P**
- Partial dislocation emission, 10
- PbTe/CdTe core-shell nanoparticles, 268–270



- PbTe, doped  
  crystallographic directions, 446  
  HRTEM studies, 446, 448–450  
  microstructural features, 446  
  Na/K doped p-type, 445–446
- PbTe + PbX  
  APT, 481, 483  
  A-site substitution, 468  
  displacement layers, 481, 485  
  GPA analysis, 481, 482  
  high-density stacking faults, 485–487  
  lattice mismatch, 474–479  
  low-magnification STEM image, 487  
  low-magnification TEM images, 468, 471, 476, 479  
  Moiré fringes, 18, 477  
  precipitate, 478–480  
  p-type dopant element Na role, 478  
  SEM images, 483–485  
  in situ nanostructure formation, 468, 470, 473  
  spinodal decomposition, 470–471  
  TEM investigations, 483, 485, 486  
  thermopower, 468–470
- PbTe-Sb<sub>2</sub>Te<sub>3</sub>TE compounds  
  chalcogenide systems, 523  
  interfacial structure of precipitates, 528–530  
  nanostructured TEs, 523, 526  
  rock salt structure, 525–528
- PbTe + X  
  Bi sample precipitate, 491  
  Burger's circuit, 490–491  
  low-magnification TEM images, 493–494  
  Pb- and Sb-rich precipitates, 494–495  
  Pb/Sb codoped system, 492  
  pherical-like precipitates, 488, 489  
  phonons scattering, 487–488  
  platelet-like precipitates, 488, 489  
  SEM images, 496–497  
  S<sup>2</sup>σ enhancement, 492–493
- PbTe + XTe  
  atomic-scale doping/substitution, 453–455  
  Cd substitution, 464, 466–467  
  HRTEM images, 458  
  MgTe, 463–465  
  nanostructures, 453  
  PbTe–BaTe bulk TE system, 456–458, 460  
  phonon blocking and charge transmitting, 448–449  
  phonons, 461–463  
  precipitates and matrix boundaries, 460, 461
- SPS, 456  
  SrTe, 451–453  
  temperature dependence, 450, 451
- Photovoltaic (PV) materials  
  barrier height, 76–78  
  device operation, 46–48  
  inorganic solar cells (*see* Inorganic solar cells)  
  organic solar cells, 50, 51, 79–81  
  thin films, 44–45
- Polarity assignment, semiconductor nanowires  
  CBED, 404  
  EELS, 404–405  
  electronic and optoelectronic properties, 415, 417–419  
  GaN on diamond, 408–409  
  HRTEM, 404  
  with medium and high atomic number atoms, 405–406  
  model, 407–408  
  multiple order twinning polarity driven growth, GaAs on Si, 410–412  
  polarity, 402  
  polytypes, 403  
  single ZnTe nanowires, -tripods, and tetrapods formation, 411, 413–417  
  STM, 405  
  twin boundaries, 402, 404  
  ZnO, ABF technique, 406–407
- Polyketone/polyamid (PK/PA) polymer alloy  
  <sup>13</sup>C CP MAS NMR spectra, 184, 185  
  DSC curves, 178, 179  
  EELS, 181–182  
  grass transition phenomenon, 179–181  
  load-displacement curve, 184, 185  
  mass fraction, 187  
  maximum stress and displacement, 186  
  moisture absorption rates, 177, 178  
  phase inversion, 183  
  SAXS, 183–184  
  TEM images, 181–182  
  weight ratio, 176, 177  
  wet test specimens, 177
- Polymeric nano-composites  
  carbon black network structure, 145–151  
  carbon black/rubber interaction layer visualization, 161–167  
  3D-TEM, 143–144  
  polyketone/polyamid alloy, 176–187  
  silica-filled cured NR, optical properties, 168–172, 174–176  
  Zn removal from rubber vulcanizates, 144–145

- Polymer matrix nanocomposites (PMNC), 336.  
*See also* Polymer matrix nanocomposites  
 applications, 356–357  
 inorganic nanofiller, 356  
 synthesis, 357–358  
 ZrO<sub>2</sub> dispersion, 358–363
- Porosity  
 characterization, 634  
 mesoporous zeolite, 635  
 quantitative measurement, 634
- Positive staining, 4–5
- Protein cages, 13–15
- Pt@Pd core-shell nanoparticles, 270, 272
- Q**
- Quantitative 3D-TEM  
 faceted nanoparticles, 639–643  
 long-range ordering, 643–646  
 NPs, 3D localization, 635–639  
 porosity, 634–635  
 reconstructions, combined analysis, 647
- Quantum dots (QDs), 19, 90, 268, 545, 658, 682
- Quantum wires, InAs<sub>x</sub>P<sub>1-x</sub> on InP, MBE  
 nucleation and evolution, 683–689  
 spatial distribution and size  
 homogeneity, 683  
 Stranski-Krastanov (SK) mode, 683  
 stress field, 682
- Quasi-neutrality level, 67
- R**
- Radiation spectrum, 45, 47
- Recombination velocity  
 cathodoluminescence, 72–75  
 electron-beam-induced current, 72
- Reconstruction algorithms  
 algebraic reconstruction technique, 627  
 Fourier transform, 626  
 quality, 627  
 simultaneous iterative reconstruction techniques, 627
- S**
- SALT, TE nanomaterials  
 Ag-free system, 512  
 disperse precipitates, 515–517  
 electrical transport properties, 517, 520–521, 523  
 lamellar structure and precipitates, 520–523, 525  
 nanocrystal domains, 514, 515  
 nanoscale lamellar features, 514, 515  
 temperature dependence, 512, 514  
 TE nanomaterials, 512, 514
- Sample preparation, semiconductor nanomaterials  
 complexity, 96–97  
 FIB, 95  
 thickness, 95
- Scanning transmission electron microscopy (STEM). *See also* TEM/STEM methods  
 metallic nanocatalysts elemental distribution, 594–600, 602, 603  
 schematic diagram, 382, 383  
 semiconductor nanowires, 382, 384, 386, 389–392, 623
- Sea urchin (SU) spine, 10–11
- Second generation photovoltaics, 48
- Sectioning, 4
- Selected area electron diffraction (SAED), 205
- Self-assembled hierarchically structured biotemplates, 21–23
- Semiconductor nanomaterials  
 clusters, 119–125  
 electron diffraction, 92–93, 100, 116–118  
 imaging experiments, 91, 92, 97–99  
 sample preparation, 95–97  
 spatial resolution, 91  
 spectroscopic experiments, 93–94, 100–103  
 strain effect, 114–116  
 TEM result simulation, 103–107  
 TEM/STEM, heterostructures, 107–114
- Semiconductor nanowires  
 aberration-corrected STEM, 380–381, 383  
 Au distribution in Si and GaAs, 399–401  
 cross-sectional STM, 377  
 dumbbell identification, 402–419  
 EELS, 393–399  
 elemental mapping, core-multishell, 274–275  
 Ga in AlN barriers, core-shell nanowires, 402, 403  
 low-and high-magnification, 377–378  
 STEM special modes, 382, 384–392  
 STM image, 377–379  
 twin boundary crossing and high-resolution XSTM image, 378

- III-V semiconductors
  - HAADF-STEM image, ZnO nanowires, 663
  - InAsP1-x/InP interface, HAADF, 661–662
  - integrated intensities, 662–663
  - limitations, 660
  - MBE, 661
  - segregation and interdiffusion, 660
  - Z-contrast imaging, 661
- Shockley partial dislocations (SPDs), 586
- Shockley-Read-Hall (SRH) recombination, 68
- Silica-coated core-shell nanomaterials
  - advantages, 248
  - Au@SiO<sub>2</sub> nanoparticles, 248–249
  - CoFe<sub>2</sub>O<sub>4</sub>-SiO<sub>2</sub> core-shell nanoparticles, 249–250
  - Fe<sub>3</sub>O<sub>4</sub>/SiO<sub>2</sub>/Au/porous-SiO<sub>2</sub> composite colloids, 251
  - porous silica protected Fe<sub>3</sub>O<sub>4</sub>/SiO<sub>2</sub>/Au composite structures, 249, 251
  - Si nanowire lithiation on stainless steel substrate, 252, 253
- Silica-filled cured NR, optical properties
  - chain density × chain length vs. silica loading, 175
  - diffuse transmittance, 168, 170, 174
  - diffusion transmittance and haze vs. chain density × chain length, 175, 176
  - 3D-TEM images, 170, 171
  - haze, 168, 170
  - optical transparency, 168, 169
- Silica-filled cured NR, rearrangement and destruction, network
  - curing, 154–161
  - heat-treatment, 151–154
  - recipes of, 168, 169
  - shield effect, 168, 170
  - visualization of network structures, 172–174
  - volume resistivity, 172
- Silica, in plants and microorganisms, 11–12
- Silica-pili bio-inorganic nanocomposites, 23
- Silicon nanowires
  - HAADF-STEM images, 212
  - internal structure, 209, 211
- Simultaneous iterative reconstruction techniques (SIRT), 627
- Small-angle X-ray scattering (SAXS), 183–184
- Soft-X-ray emission spectroscopy (SXES)
  - advantage and disadvantage, 290
  - anisotropic emission, 317–321
  - extension for higher-energy region, 324–327
  - multichannel plate with CCD detector, 294
  - schematic representation of optics, 292
  - ver.1, 292–293
  - ver.6, 292–293
- Special transmission electron microscope, techniques
  - atom probe tomography, 431–433
  - geometric phase analysis, 428–431
- Spectroscopic experiments, 93–94
  - EELS, 101–103
  - energy-dispersive X-rays, 100–101
- Spontaneous phase separation, nanocomposite oxide thin films
  - microstructural evolution tracking, 547–550
  - microstructure and nucleation control, 545–546
  - misfit strain relaxation, film thickness effect, 557, 558, 560–563
  - nanocomposite components identification, 550–556
  - spatial distribution dependence, 556
  - strain measurements, 563–564
- Stacking faults (SFs), 107–109
- Strain effect, in semiconductor nanomaterials, 114–116
- STEM. See Scanning Transmission Electron Microscopy
- STEM special modes
  - ABF, 386–389
  - HAADF, 382, 384–386
  - image simulation, 390–392
  - MABF, 389–391
  - schematic diagram, 382, 383
- STEM technique, elemental distributions
  - core-shell noble catalysts, 594–595, 598
  - Fe distribution, 596–597, 600
  - Pt3Co electrocatalyst, 599, 602
  - signal-to-noise ratio, 595
  - STEM-EELS, 600, 603
- Surface rendering, 143, 632
- Synthetic inorganic nanomaterials
  - bacterial flagella templates, 19, 21
  - 1D filamentous biological templates, 14–20
  - DNA-based biotemplates, 23–27
  - protein cages, 13–15
  - self-assembled structure, 21–23

**T**

## TAGS

TE nanomaterials, 497–501

XRD patterns, 501–503

TEM. *see also* Transmission Electron

Microscopy

analysis, 543–545

sample preparation, 543

strain mapping, GPA and HRTEM,

543–545

TEM in scanning (STEM) mode. *See* Scanning

transmission electron microscopy

(STEM)

## TEM/STEM methods

analytical 3D-TEM, 624, 629, 630, 632,

647–653

diffraction mode, 338–339

energy-filtered TEM, 623–624

imaging mode, 338

nonrelativistic and relativistic

wavelength, 337

scanning mode, 339

schematic diagram of, 336–337

tomographic mode, 342–346

## TEM technique

amplitude contrast, 247

elemental mapping, 247–248

HRTEM image, 247

Z-contrast image, 247

## Ternary III-N grown by catalyst-free

PAMBE

core-shell Al<sub>x</sub>Ga<sub>1-x</sub>N/GaN nanowires,

677–682

MOCVD, pulse laser

deposition, 676

reflection high-energy electron diffraction

pattern, 677

## Thermoelectric (TE) nanomaterials

definition, 428

description, 431

detector measurement, 432

dual-beam focused ion beam,

432–434

energy crisis and energy conversion

efficiency, 433–436

experimental and instrumental

methodology, 443–445

LAST(T), 501, 504–513

local-electrode atom-probe, 432, 433

nanostructures comparison, 431

PbTe, doped, 445, 446, 448–450

PbTe + PbX, 18, 468–471, 473–487

PbTe-Sb<sub>2</sub>Te<sub>3</sub>TE Compounds, 523,

525–530

PbTe + X, 487–497

PbTe + XTe, 448–458, 460–467

SALT, 512, 514

sample preparation, 432

special transmission electron microscope

techniques, 428–433

TAGS, 497

TE materials, 436–439

ZT, 439–443

## Thermomechanical analysis (TMA),

179–180

## Thin-film photovoltaics, 44–45

## III-V semiconductors, column-to-column

compositional quantification

HAADF-STEM image, ZnO

nanowires, 663

InAs<sub>c</sub>P<sub>1-x</sub>/InP interface, HAADF, 661–662

integrated intensities, 662–663

limitations, 660

MBE, 661

segregation and interdiffusion, 660

Z-contrast imaging, 661

## TiN-Ag nanocomposites

bright-field TEM images, 352

dc arc-plasma method, schematic

diagram, 351

formation mechanism, schematic diagram,

353, 355

HRTEM images, 352

semitransparent reconstructed volume,

353–354

STEM-HAADF images, 353

tilt series of STEM-HAADF images,

353–354

## Titanium nitride (TiN)

application of, 349

fabrication of, 349–351

properties, 348–349

TiN-Ag nanocomposites, 351–355

## Tobacco mosaic virus (TMV) templates, 14,

16–17

## Tomographic mode, TEM/STEM

absence of images and missing wedge,

schematic diagram, 344

angular range-image quality relation,

344–345

3D-ET method, 342–343

3D reconstructed volume of Al

alloys, 346

elongation factor, 344

- number of projections-image quality relation, 344–345
  - relative specimen thickness
    - increases, 345–346
  - resolution, 343
  - schematic diagram, overlapped structure, 343
  - Total electronic structure analysis
    - Al-Ni-Co, 322, 323
    - DOS of bands, 320
    - EELS and SXES spectrum, 321–324
  - Trans-activating transcriptional activator (TAT) peptide, 31
- U**
- Ultramicrotome, 3–4
  - Ultrasoft-X-ray emission spectra
    - Be K-emission spectrum, 295–296
    - Cu M<sub>2,3</sub>-emission spectrum, 298
    - Li K-emission spectrum, 294–296
    - Mg and Al L-emission spectra, 296–297
    - M<sub>2,3</sub>-emission spectrum of Cu, 298
- V**
- Valence electron spectroscopy
    - boron K-emission spectra, 301–306
    - carbon K-emission spectra, 306–310
    - EELS, 288–291
    - L-emission spectra, 311–312
    - M-emission intensity, 314–318
    - total electronic structure analysis, 320–324
    - ultrasoft-X-ray emission spectra (*see also* Soft-X-ray emission spectroscopy (SXES)), 294–298
  - Van Roosbroeck model, 73
  - Vapor–liquid–solid (VLS) mechanism, 199
    - GaN, 221
    - Ge nanowires, 216–218
  - Vapor–solid–solid (VSS) mechanism
    - Ge nanowires, 216–218
    - Si-Ge heterojunction nanowire, 220
  - Video imaging, 197, 217
  - Viscoelasticity, 141, 188
- W**
- Water-gas shift (WGS) reaction, 582–583
  - Whole pattern (WP), CBED diffraction, 117–118
- X**
- X-ray absorption near edge structure (XANES), 129
  - X-ray magnetic circular dichroism (XMCD), 128–129, 131
- Y**
- Young's modulus, 229
- Z**
- Z-contrast tomography. *See also* High-angle annular dark-field (HAADF) imaging
    - BF-STEM vs. ADF-STEM, 629
    - pixel size, 628
    - Saxton scheme, 628
    - tilt increment, 628
    - visualization and quantitative analysis, 629
  - Zero Loss tilt series, 631
  - ZnO growth, CdTe (111)
    - applications, 664
    - catalytic effect, substrate elements, 667–669
    - thermal oxidation, metallic zinc films, 665–667
  - ZnO growth on Si (111)
    - CBD rods, 674–676
    - cross-sectional TEM image, 671
    - EEL spectra, 671–672
    - HAADF-STEM image, 670
    - HRTEM mode, 670
    - ZnO seed layers, 673–674
  - ZnO nanorods growth, Si (111)
    - CBD methods, 669
    - three-step catalyst-free method, 673–676
    - using three step method, 670–673
  - ZnO nanowires growth, CdTe (111)
    - applications, 664
    - catalytic effect, substrate elements, 667–669
    - thermal oxidation of metallic zinc films, 665–667
  - ZnSe/GaAs heterostructure
    - HAADF images, 109–112
    - HRTEM image, 109
    - staking faults, 107, 108
  - ZnS nanowires, 17–19
  - Zn/ZnO core-shell nanobelts, 269–271

- ZrO<sub>2</sub> dispersed PMNC
  - advantages, 358
  - 3D reconstructed volume, 360–361
  - fabrication, 358
  - grain diameters, histograms of, 361
  - interparticle distances, histograms of, 362
  - light scattering, 362–363
  - refractive indexes, 363
  - sample comparison, 358
  - schematic diagram, 359–360
  - STEM-HAADF images, pillar-shaped specimens, 359–360
  - transmittance and transparencies, 358–359
- ZT
  - enhancement methods, 441–443
  - TE nanomaterials, 439–441