

Index

A

- Additional wire stresses
 - in straight spiral ropes, 70–73
 - in straight stranded ropes, 73–78
 - in running ropes, 185
- Aging, artificial, 2, 22
- Alternate strength, 21
- Alternate stress, 9, 10
- Angular frequency, 96
- Artificial aging, 2, 22

B

- Bearing ropes, redundant, 275, 276
- Bending wires, 9, 11
 - reverse, 9, 10
 - rotary, 9, 15
 - simple, 10
- Bending cycles, wire ropes
 - breaking number of, 220, 224
 - discarding number of, 220, 224
 - influence of deflection angle on, 243
 - reverse, 215, 292
- Bending-fatigue-machines rope, 213–216
- Bending length(s), 17, 215, 228, 229
 - reference, 269
- Bending line, 190, 191
- Bending machine, rotary, 12
- Bending strength amplitude, 19
- Bending strength, rotary, 15, 20, 22–24
- Bending stress in ropes
 - fluctuating, 185
 - global, 179
 - secondary, 193, 194
 - tertiary, 194
- Bending test
 - reverse, 8
 - rotary, 8, 11
 - simple, 8, 11, 214
- Bent strand, 181

- Bent stranded rope, 182
- Beta-function, 267
- Birth-distribution, 267
- Bottom sheave, rotation, 115
- Boundary angle, 50, 197
- Braided rope, 38
- Breaking force, 43
 - measured, 139, 140
 - minimum, 42
 - residual, 162, 256, 257
- Breaking force factor, 139, 140

C

- Cable-laid ropes, 36
- Carbon content, 2
- Classes of mechanism, 278
- Clearance, 40, 50, 184, 189
- Clearance angle, 50
- Coating
 - metallic, 4
 - zinc, 4, 5, 17, 149, 233, 234
- Cold drawing, 3
- Combined loading, 252
- Compacted strand, 27
- Compacting grade, 27
- Compound lay strand, 26
- Contact angle, 50
- Contact bow, 192
- Contact force, length related, 196
- Contact force, 196
- Contact radius, 50
- Contour, wire, 50
- Corrosion resistant wires, 5
- Corrosion resisting steel, 5
- Corrosion times, 22
- Cranes, 276
- Cross lay ropes, 153
- Cross lay strands, 25
- Cross-section, 40, 41

Cumulative damage hypothesis. *See* Palmgren–Miner rule
 Curvature of space curve, 71
 Curvature radius, 71

D

Damage accumulation hypothesis. *See* Palmgren–Miner rule
 Damage sums, 161, 253
 Damping, 96, 98
 Decay coefficient, 99
 Decay tests, 96, 99
 Deflection angle, 199
 influence, on bending cycles, 243
 Discard criteria, 161, 272
 Discard limiting force, 254
 Discarding limit, 296
 Discarding number
 of bending cycles, 220, 223, 287
 of wire breaks, 269, 297, 298
 Donandt force, 221, 253, 272, 295, 296

E

Efficiency factor, 285
 Elasticity module(s), 6, 8, 79–94
 Empty hook block, rotating, 115
 lowering, 320
 Endurance, of wire ropes
 course of calculation, 279
 equations for, 143, 221, 287
 factors, 290
 formula, 143, 144
 Equivalent diameter ratio, 252
 Equivalent force factor, 252
 Equivalent force hypothesis, 142
 Equivalent tensile force, 250, 285
 Extension of rope, by twisting, 125
 Extreme forces, 167–169, 273, 274

F

Failure probability, 276
 Fatigue strength amplitude, wires, 20
 Fatigue-machines, bending wires, 10–14
 wire ropes, 213–220
 Fibre core(s), 29, 52, 231, 233
 Fibre core mass, 52
 Fill factor, 41
 Finite wire endurance, 17
 Flat rope, 38
 Flattened wire arcs, 212
 Fluctuating bending stress, 184

Fluctuating forces, 141, 172
 Fluctuating tension and bending, 241–252, 286
 Fluctuating twist, 136, 137
 Force factors, 285, 286
 Form grooves, 238–239

G

Galfan, 4
 Geometry calculation, 50
 Global
 wire bending stress, 179
 rope pressure, 205
 rope tensile stress, 59, 179
 Goodman line, 142, 143
 Groove(s)
 form, of traction sheave, 239, 285
 round, 186, 239, 243
 sheave, 290, 291
 of plastic, 242, 290
 of polyamide, 241
 of steel, 241
 Guidance factor, 285, 286
 Gumbel distribution, 147
 Groove contact angle, 209
 opening angle, 245
 Groove material, 241–242, 290
 Groove radius, 191, 209, 237, 290

H

Haigh diagram, 10, 11, 143
 Hanging sheave, 318
 Hoisting cycle, loading sequence during, 280
 Hook block, rotating, 115
 lowering, 320

I

Impact factor, 273
 Impact force, 275
 Infinite wire endurance, 18–23

L

Lang lay rope, 36
 Lay
 angle, 23
 direction, 23
 length, 23, 40
 ordinary, 35
 Lay strands
 compound, 26
 cross, 25

parallel, 25

Length-related

- contact force, 196–199
- mass, 42, 43
- radial force, 63

Lifting appliances, 276

Line pressure, 196, 199, 200

- peaks, 203

Load cycles, number of, 144, 162

Loading, combined, 251, 286

Loading elements, 279, 281

- symbols for, 281
- standard elements, 214, 280

Loading sequence, 279, 281

Logarithm normal distribution, 14, 146

Logarithmic decrement, 99

Longitudinal stress, amplitude of, 251

Longitudinal vibrations, 96, 97

Longitudinal waves, 98

Loss of stiffness, 162

Loss of strength, 162

Low-rotating ropes, 36

Lubricant, 31

- consumption, 32

Lubrication, 31, 153, 234, 290

- continuous, 32
- re-lubrication, 234–237

M

Magnetic devices, for detecting wire breaks, 270, 275

Magnetic inspection, 275

Mass, length-related, 41, 42

Metal sockets, 151–157

Metallic coating, 4

Metallic cross-section, 41, 42

Mining shaft hoists, inspection of, 262

Multi-strand ropes, 36

M

Magnetic devices, for detecting wire breaks, 270, 275

Magnetic inspection, 275

Mass, length-related, 41, 42

Metal sockets, 151–157

Metallic coating, 4

Metallic cross-section, 41, 42

Mining shaft hoists, inspection of, 262

Multi-strand ropes, 36

M

Magnetic devices, for detecting wire breaks, 270, 275

Magnetic inspection, 275

Mass, length-related, 41, 42

Metal sockets, 151–157

Metallic coating, 4

Metallic cross-section, 41, 42

Mining shaft hoists, inspection of, 262

Multi-strand ropes, 36

M

Magnetic devices, for detecting wire breaks, 270, 275

Magnetic inspection, 275

Mass, length-related, 41, 42

Metal sockets, 151–157

Metallic coating, 4

Metallic cross-section, 41, 42

Mining shaft hoists, inspection of, 262

Multi-strand ropes, 36

N

Nominal strengths, 3, 150, 244

Non-rotating ropes, 36, 114, 278

- definition, 114

O

OIPEEC recommendations, 214, 218

Open spiral wire ropes, load cycles of, 148, 149

Optimal rope diameter, 254, 255, 273, 314, 315

Ordinary lay, 35

Oval strand ropes, 27, 36

Overlapping ropes, 117

P

Palmgren–Miner rule, 161, 162, 250, 253, 292

Parallel lay strands, 25

Passenger lifting installations

- general/technical regulation requirements for, 274
- safety methods for prevention of car plunge in, 274

Patenting, 3

Plastic grooves, 242

Poisson distribution, 263, 264
 Poisson ratio, 68
 Profile wires, 2, 3

P

Palmgren–Miner rule, 161, 162, 250, 253, 292
 Parallel lay strands, 25
 Passenger lifting installations
 general/technical regulation requirements
 for, 274
 safety methods for prevention of car plunge
 in, 274
 Patenting, 3
 Plastic grooves, 242
 Poisson distribution, 263, 264
 Poisson ratio, 68
 Profile wires, 2, 3

P

Palmgren–Miner rule, 161, 162, 250, 253, 292
 Parallel lay strands, 25
 Passenger lifting installations
 general/technical regulation requirements
 for, 274
 safety methods for prevention of car plunge
 in, 274
 Patenting, 3
 Plastic grooves, 242
 Poisson distribution, 263, 264
 Poisson ratio, 68
 Profile wires, 2, 3

R

Radial force, length-related, 63, 196
 Redundant bearing ropes, 275, 276
 Reference rope lengths, 262, 264
 bending, 269
 Re-lubrication, 234–237
 Repetitive stress, 10
 Residual extension, 83–85
 Residual rope breaking force, 162, 256–258
 Resin sockets, 151, 152
 Reverse bending, 8, 247–249, 291
 Reverse bending cycles, 291
 Reverse bending test, of wires, 8, 11
 Rope(s)
 extension by twisting of, 125
 geometry, 45
 low-rotating, 36
 multi-strand, 36
 non-rotating, 36, 114, 278

 oval strand, 26, 36
 ovalisation, 192, 193
 overlapping, 117
 rope bending fatigue machines, 216, 217
 test conditions, 218–220
 test principles, 213–216
 ropes during bendings
 residual breaking force, 256, 257
 rope diameter reduction, 258
 wire rope elongation, 256
 side deflection of, 138, 245–247
 usage classification, 34
 Rope breaking force, 43, 45
 residual, 162, 256–258
 Rope cores, 28–30, 231
 Rope deflection, 244, 245
 side deflection of, 245–247, 289
 Rope diameter, 104
 reduction, 258
 size effect, 157, 163, 219
 Rope drive requirements, 271–274
 Rope drives
 calculation of, 278

S

Safety factor, 168, 271
 Safety requirements, 145, 270, 272, 274, 295
 Seale ropes, 14
 Secondary bending stress, 193, 194
 Secondary tensile stress, 194, 237, 251
 Sequence loading, 305, 309
 Shaped strands, 26
 Shear module, 112
 Sheave grooves, 242, 274
 of plastic, 242
 of polyamide, 241
 of steel, 270
 Side deflection angle, 245
 Side deflection of rope, 138, 245–247
 Simple bending test, 8, 11, 216
 Size effect, 161–164
 rope diameter, 20, 160, 227
 bending length, stressed length, 17,
 161–165, 229, 230
 Smith diagram, 148, 150
 Sorbite, 3
 Space curve of wires, 71, 182
 Specific minimum breaking force, 44
 Specific pressure, 207–209
 Specific tensile force, 44, 55, 181
 Spiral ropes, 34, 150–154
 Spring constant of rope piece, 99
 Standard loading elements, 214, 280, 293

- per working cycle, 280
 - Standing waves, 102
 - Steel cores, 30, 233
 - Steel grooves, radius, 238
 - Step length, 264
 - Stiffness, loss of, 162
 - Strand(s)
 - compacted, 27
 - geometry, 45
 - compound, 26
 - cross, 25
 - shaped, 26
 - Strand elongation, 64
 - Strand forming grade, 44
 - Strand lay direction, 36
 - Strand mass factor, 27, 29
 - Strand ropes, 31, 33, 35, 38, 42, 44, 46, 87, 89–91, 94
 - Strength(s), 150, 151, 223–225
 - alternate, 22
 - bending, 20
 - tensile, 18
 - Stress(es)
 - rotary, 14
 - secondary tensile, 189
 - secondary bending, 193
 - tertiary bending, 194
 - total, 194, 263
 - repetitive, 10
 - self-contained, 60
 - torsion stress, 72
 - Stress-extension curves, 6, 82, 85
 - Stress gradient effect, 19
 - Stress range, 141, 172, 194
 - Survival probability, 17, 230
 - Symbols for rope curves, 29
 - Symbols for standard loading elements, 215
 - Symbols for loading elements, 281
- T**
- Tackle block, 317, 318
 - Technical regulation requirements, for rope drives, 273, 274
 - Tensile fatigue strength, 10
 - Tensile fatigue tests, 9, 11, 160
 - Tensile force wave, 94
 - Tensile stress, 10, 11, 17, 19, 25, 32, 33, 45, 59, 60, 63, 68–70, 72, 73, 77, 79–81, 83, 84–86, 90, 91–94, 96, 99, 100, 104, 110, 129, 132, 135, 137, 153, 179, 186–190, 194, 195, 213, 222, 237, 250, 255, 260
 - Tension and bending
 - independent, 249
 - combined, 250
 - Tension-tension tests, 141–143
 - Terminations, 140, 167
 - Tertiary bending stress, 194
 - Torque measurements, 108, 111
 - Torque constant, 107
 - Torque meter, 108
 - Torsion stress, 77, 184
 - Torsional stiffness, 105, 111
 - Traction sheave, form groove of, 239
 - Transverse contraction ratio,
 - see Poisson ratio
 - Transverse vibrations, 102, 103, 172
 - Transverse waves, 100–102
 - Triangular strands, 26, 36
 - Twist, fluctuating, 136, 137
 - Twist angle, 112, 119
- U**
- Undercut grooves, 207–209, 240, 271, 292
- V**
- Variance factor, birth distribution, 268
 - V-grooves, 239
- W**
- Warrington ropes, 25, 33
 - Warrington-Seale ropes, 26, 33
 - Wave velocity
 - longitudinal, 94
 - transverse, 100
 - Window method, for counting wire breaks, 266
 - Wire(s)
 - corrosion resistant, 5
 - displacement of, 186–189
 - profile(d), 2, 47
 - round, contour of, 49, 50
 - space curve of, 180
 - Wire arcs, flattened, 212
 - Wire arc force, 210
 - Wire breaks, 161, 265
 - discarding number of, 284, 300, 301
 - distribution of, 264–269
 - growth of number of, 260–263
 - magnetic detection of, 270
 - maximum number of, 263, 264
 - increase in, 262
 - mean number of, 262
 - number of, 259, 264

- in running ropes, inspection methods to detect, 271
 - window method for counting of, 264
 - Wire clearance, 40, 50
 - Wire diameters, of ropes, 20
 - Wire displacement, 187
 - Wire elongation, 64
 - Wire endurance, 8, 9
 - finite, 16
 - infinite, 18
 - Wire forming grade, 44
 - Wire lay angle, 23
 - Wire rope(s), 38
 - breaking force, 43–44, 140
 - constructions, 34
 - non-rotating, 37, 114, 278
 - round, designation of, 39
 - round strand, 23, 143–157
 - spiral, 34
 - Wire rope core, 29, 54
 - Wire rope elongation, 258
 - Wire tensile test, 5
 - Wire terminations, 5, 139
 - Wöhler diagram, 14, 15, 145, 146
 - Working cycle, loading sequence during, 280
- Y**
- Yield strength, 5
- Z**
- Zinc coating, 4, 151, 233, 234