

Index

A

Accumulation, 69
Acronyms, list of, xiii
Active load, 13
Amplification, 171
Analog MOS switch, 20
Analog voltage buffer, 201, 205, 209
Analog-to-digital converter (ADC), 1, 239
Analog-to-timing converter, 56
Attenuation, 196

B

Back-gate effect, 30, 57, 65, 223
BER analyzer, 99, 127
Bias voltage, 169, 193, 195, 201, 202, 208
Bit error rate (BER), 33, 99, 127, 134, 158, 168, 169, 180, 188, 193, 199, 202, 207, 225, 234
Bit error ratio, 34
Bit pattern generator, 132
Bit pattern receiver, 134, 158, 165
Block capacitor, 69
Body effect, 217
Bond wire, 111, 157, 178, 205, 221, 233
Bondpads, 71
Buffer, 105, 201

C

Carrier mobility, 71
Channel-length modulation, 67
Charge compensation, 56
Charge injection, 15, 21
Clock driver, 115, 126, 220
Clock feedthrough, 21

Clock frequency, 31, 49, 56, 108, 155, 158, 162, 168, 170, 180, 185, 188, 193, 196, 198, 202, 207, 215, 222, 225, 226, 234
Clock period, 217
Clock signal, 230
Clocking comparator, 3, 7
Clocking regenerative comparator, 2, 8, 11, 28, 31, 33, 62, 79, 239
CML-latched comparator, 18
65 nm CMOS, 70
CMOS logic, 3, 99
Co salicide, 65
Common-mode voltage, 176
4-stage comparator, 49
Comparison phase, 198, 217
Compensation, 5
Complementary static latch, 13
Contacts, 71
Continuous-time current comparator, 6
Current consumption, 159
Current switch comparator, 6
Current-mode logic (CML), 17

D

Damping factor, 80
Decision, 31, 33, 165, 173, 180, 193, 198, 202, 207
Decision time, 57
Delay line, 115, 122, 132, 158, 164, 174
Delay time, 69, 101, 103, 105, 109, 110, 115, 118, 124, 127, 165, 181, 199, 208, 210, 217, 226, 227, 237
Delay time difference, 153, 164, 199
Demultiplexer, 49
Dielectric constant, 65
Differential amplifier, 184, 188

Digital Signal Processor (DSP), 1
 Digital-to-analog converters (DAC), 1
 Distortion, 76, 201
 Double tail sense amplifier, 55
 Drift velocity, 67
 Duty cycle, 186, 198, 205, 220
 Dynamic CMOS latch, 7
 Dynamic comparator, 7
 Dynamic latched comparator, 16
 Dynamic offset, 30
 Dynamic offset cancellation, 28
 Dynamic power consumption, 170
 Dynamic range, 75

E

Early voltage, 67, 72, 73
 Error voltage, 21

F

Failure rate, 31
 Falling ramp, 201
 Feedback amplifier, 49
 Fill structures, 177, 190, 203
 Flash ADC, 31, 54
 Flicker (1/f) noise, 24, 75, 76
 Flip-flop, 31, 49
 Frequency divider, 118
 Fringing-field effect, 72

G

Gain peak, 82
 Gate capacitance, 210
 Gate leakage current, 76
 Gate oxide, 66, 69
 Gate oxide capacitance, 76
 Ground bounce, 222

H

Headroom, 75, 76
 High-impedance input, 227
 High-k dielectrics, 76
 Hot carrier injection, 30
 Hysteresis, 3, 23, 30, 201

I

Impedance, 201
 Inductive behavior, 82
 Inductor, 49
 Input amplitude, 208

Input capacitance, 80, 82
 Input common-mode level, 31, 210
 Input common-mode voltage, 53, 101, 155, 158, 168, 176, 180, 185
 Input differential amplifier, 184
 Input offset storage, 28
 Input referred offset, 29
 Input resistance, 108
 Input resolution, 31
 Input voltage, 158, 217
 Input voltage difference, 27
 Interlevel dielectrics, 65
 Intrinsic gain, 75
 Inversion, 70
 Inverter, 5, 54, 56, 69, 107, 120, 122, 152, 186, 202, 209, 227

K

Kickback noise, 24, 54, 176, 186, 201

L

Laplace transformation, 83
 Latch, 49, 54, 120, 155, 160, 173, 194, 198, 210, 215
 Latched comparator, 14
 Layout plot, 85, 93, 115, 166, 177, 190, 203, 221, 232
 Leakage current, 70, 208
 Least significant bit, 31
 Level shifter, 79
 Linearity, 69, 76, 86, 93
 Load capacitance, 159
 Load transistor, 184, 194
 Long-channel transistor, 66
 Low-power CMOS, 221, 232
 Low-power comparator, 240
 Low-threshold transistor, 174
 Low-voltage operation, 227, 230

M

Matching, 69, 76, 201
 Maximum oscillation frequency, 75
 Measurement setup, 234
 Measurement system, 201
 Mechanical stress, 71
 Metastability, 34, 57, 162, 198, 202
 Metastability detector, 58
 Metastability error, 31, 33, 34, 162, 180, 198, 202
 Metastable point, 12
 Metastable state, 152

Microchip line, 192, 205
 Microphotograph, 85, 221, 232
 Microstrip line, 87, 155, 166, 178, 222, 233
 Miller compensation, 5
 Minimal input resolution, 31
 Mismatch, 27, 45, 50, 110, 161, 172, 198, 201, 210, 227
 Mixed-signal applications, 70
 Moderate inversion, 75
 Monte Carlo simulation, 154, 165, 176, 189, 201, 212, 220, 230
 MOS current-mode logic (MCML), 17
 MOS switch, 20
 Multi-stage voltage buffer, 80
 Multilevel current comparator, 6
 Multiplexer, 120, 174, 186, 199

N

Negative feedback, 49
 Network analyzer, 131
 NFET-in-nwell capacitor, 69
 Noise, 24, 31, 33, 34, 157, 159, 161, 171, 172, 180, 193, 198, 202, 207, 210, 222, 227
 Non-return-to-zero (NRZ), 99

O

Offset, 23, 27, 106, 154, 166, 170, 181, 190, 201, 205, 207, 212, 220, 227, 232, 234
 Offset cancellation, 28, 29
 Offset compensation, 50, 56
 On-chip temperature, 207
 On-resistance, 20, 153, 158
 Operational amplifier, 4
 Oscilloscope, 104, 110, 134, 157
 Output characteristics, 71, 73
 Output common-mode voltage, 158
 Output conductance, 72
 Output driver, 220
 Output nodes, 217
 Output offset storage, 28
 Output resistance, 67, 75, 80, 182, 194
 Output voltage difference, 160, 194, 198
 Oxide thickness, 76

P

Packing density, 75
 Parallel-current noise, 26
 Parasitic capacitance, 159, 196, 227
 Passivation, 65
 Passivation layer, 85, 177, 190, 203

Pattern generator, 132, 234
 Planarisation, 85, 177, 190, 203
 Pnp transistor, 97
 Polyimide passivation layer, 71
 Polysilicon resistor, 69
 Positive feedback, 7, 11, 152, 171, 185, 194, 198, 217, 227
 Post-layout simulation, 202
 Power consumption, 75, 159, 170, 181, 193, 196, 208, 226, 237
 Power dissipation, 88
 Power supply pad, 205, 222, 233
 Pre-amplifier, 14, 29, 153, 158
 Probability density function, 33
 Pseudo-random-bit-sequence, 34
 Pull-down network, 3
 Pull-up network, 3

R

Rail-to-rail input, 80
 Rail-to-rail output, 227
 Ramp, 201, 210
 Random offset, 28
 Random switching, 202
 Reference output, 115
 Reference voltage, 31, 105, 157, 167, 190, 201, 205, 217, 222, 225, 234
 Regeneration, 153, 169, 198, 210
 Regeneration phase, 53
 Regenerative comparator, 57
 Regenerative latch, 56
 Replica, 89, 93, 186
 Replica circuits, 75
 Reset phase, 198, 217
 Reset switch, 152, 196
 Reset transistor, 217
 Rising ramp, 201
 Robustness, 198, 210, 227

S

Salicidation, 69
 Salicide, 71
 Sampling frequency, 205
 Sandwich capacitor, 69
 Saturation, 66
 Saturation current, 76
 Saw-tooth, 205
 Scaling, 71, 75
 Second harmonic, 87
 Self-aligned silicide, 71
 Sense amplifier, 54, 172

Sensitivity, 31, 168, 180, 193, 196, 202, 207, 217, 222, 225
 Sensitivity tuning, 181, 209, 221, 226
 Series inductance, 205, 222, 233
 Series resistance, 76
 Series-voltage noise, 26
 Shallow trench isolation (STI), 65, 71
 Short-channel effect, 72
 Short-channel transistor, 66
 Shot noise, 76
 Signal headroom, 75
 Signal-to-noise ratio, 75
 Silicon oxide, 65
 Single-tone measurement, 86
 Software Defined Radio (SDR), 1
 Spectrum analyzer, 87
 SRAM, 26, 52
 Static complementary latch, 11
 Static current, 217
 Static latch, 26, 31
 Static noise, 26
 Static noise margin (SNM), 26
 Static offset cancellation, 28
 Static power consumption, 76, 170, 227
 Stress engineered devices, 71
 Subthreshold current, 68, 75, 174, 185, 198
 Subthreshold regime, 57
 Successive-approximation-register(SAR) ADC, 57, 62
 Supply line, 205, 222, 233
 Supply rail, 215, 227
 Supply voltage, 31, 66, 68, 70, 75, 87, 93, 112, 151, 159, 178, 183, 192, 199, 205, 215, 217, 221, 230, 233
 Surface channel transistor, 66
 Switch, 93, 158, 169
 Switching threshold, 202
 System on a Chip (SoC), 2
 Systematic offset, 28

T

Tail current, 169
 Tail transistor, 196, 198, 201
 Temperature, 207
 Temperature sensor, 94, 186, 199
 Termination, 157
 Test board, 131, 155, 178, 221, 233

Test chip, 85, 110, 115, 126, 131, 165, 166, 177, 186, 190, 199, 203, 218, 221, 232
 Thermal noise, 24
 Third harmonic, 87
 Threshold voltage, 57, 66, 72, 75, 82, 159, 171, 174, 184, 195, 198, 215, 217, 221, 227, 228, 232
 Threshold-voltage roll-off, 72
 Transconductance, 73, 160, 174, 182, 194
 Transconductance parameter, 171, 198
 Transconductance stage, 56
 Transfer characteristics, 93
 Transfer stage, 186, 220
 Transistor parameters, 71
 Transit frequency, 75
 Transmission gate, 93, 110, 112, 120, 126, 127, 152, 163, 174, 196, 198, 199, 208, 215, 230
 Tri-level comparator, 57
 Trigger voltage, 120
 Trimming, 28
 Triple well process, 71, 217
 Tunneling, 30

U

Ultra-WideBand (UWB), 1
 Unity-gain buffer, 80

V

Varactor, 69, 122
 Vector network analyzer, 86, 131
 Velocity saturation, 67, 76
 Voltage buffer, 79, 89, 183, 186, 195, 201, 205, 239
 Voltage difference, 198
 Voltage follower, 80
 Voltage-controlled capacitor, 69, 122
 Voltage-controlled delay line, 69, 115, 174, 186

W

Weak inversion, 66
 Wirebonding, 71
 Wireless Personal Area Network (WPAN), 1
 Wiring, 71