

Index

A

Abrasive tools, 9–16
Al modified, 206, 208–210
Al₂O₃ ceramic coatings, 78
Al₂O₃ ceramic cores, 1–7
Analysis model, 133
Antifungal properties, 123
Anti-solvent, 25–31
Atom Transfer Radical Polymerization (ATRP), 213–215, 224

B

Bending strength, 9, 12–16
Bifunctional effects, 18

C

Carbon fiber braided, 165–168
Carbon Nanotube (CNT) film, 187, 188, 191, 192
CaS:Eu²⁺ phosphor, 113–117
cBN, 9–15
CCTO ceramics, 196, 198, 199, 202
Celery, 67–70, 73–75
CeO₂, 9–12
Chitosan, 17, 18
Colossal dielectric constant, 202
Composite membranes, 17, 18, 21, 22
Conduction mechanism, 187, 188, 190, 192, 193
Copolyamide, 33, 34, 45
Copolyester, 156, 158–163
Crystallization, 141–147, 149, 152
Crystal structure, 34, 36–38, 42, 57–59, 58, 61, 62, 65

D

DiAldehyde Cellulose NanoCrystal (DACNCs), 17–22
Diffusion bonding, 93, 94
Draft ratio, 33–35, 37, 38, 40, 41, 45
Drawing temperature, 33, 34, 41, 42, 44, 45
Dry-pressing, 1, 2

E

Electrical conductivity, 187–190, 192
Electrolytic plasma spraying, 165–167, 170
Electrospinning, 25–31
Electrospun nanofibrous membrane, 18, 19, 22

F

Ferroelectric hysteresis measurement, 47, 48, 54
Freeze-tape-casting, 85–90

G

Glass fiber-reinforced tape, 133–136, 138

H

Halloysite, 121–124, 127, 130
Hydrophilicity, 155
Hydroxyapatite, 85–91

I

Internal Barrier Layer Capacitor (IBLC), 195, 196, 198, 202

L

Liquid-phase, 77, 78, 84
Luminescence, 113, 114, 116
Lycium chinense fruits, 67–70, 73–75

M

Mechanical alloying, 105, 106
Mechanical property, 33, 35, 37, 40, 42, 45, 105–109, 111
Microstructure, 93, 95–101, 105
Molecular orientation, 144, 149–152

N

Nanofibers, 25–31, 213, 214, 216, 218–224
Nano-SiO₂, 155–159, 161
Network structure, 227–233, 235, 236
Nonlinearity, 47, 53, 54

O

Oxidation resistance, 165–167, 170

P

PA6/66, 33–38, 40–42, 44, 45, 57–65
Permeability, 85–87, 90, 91
Photochromism, 213, 214, 216, 217, 222–224
Photoluminescence, 213, 214
Photoluminescence properties, 113
PLA monofilaments, 141
Plasma electrolysis, 77–80, 84
PLZT, 205–210
Polyamide 6, 57, 65
Polyethylene glycol adipate, 155, 156
Polyethylene terephthalate, 155
Polypropylene, 67–75
Porous, 25–31
Porous ceramics substrates, 85, 86, 89
Precursor, 1, 2, 7

Q

Quartz fiber braid, 78, 79, 83, 84
Quaternary ammonium compounds, 121–123, 128, 130

R

Radial difference, 141, 142, 144, 147, 149, 150, 152
Reinforced thermoplastic pipe, 133, 134, 138
Relaxor ferroelectric, 47, 54

S

Short-term burst pressure test, 134
SiBCN ceramic, 105–107, 111
SiC ceramics, 94–100, 102, 103
SiC_f/SiC composite, 93, 94, 97, 100–103
Silicone resin, 1–5, 7
Sintering, 1–7
Sintering properties, 227
SiO₂/SiC coating, 165–168, 170
Sol-gel, 227, 228, 233
Spark plasma sintering, 105, 106, 107
Spiropyran, 213–215, 221, 222

T

Transparent ceramics, 205, 206, 210

V

Vitrified bonds, 9, 10, 13–15

W

Winding speed, 57, 58, 60–65